



kerakoll

DECLARATION OF PERFORMANCE No 0287

1. Unique identification code of the product-type: **H20**
2. Intended use/es:
Improved cementitious adhesive for ceramic tiling, all internal and external tiling
3. Manufacturer:
KERAKOLL Hellas E.P.E. - 1st km. Schimatari-Avlida Rd. - 32009 Schimatari-Viotia - Greece
4. System/s of AVCP: **System 3 and System 3 for reaction to fire**
5. Harmonised standard: **EN12004:2007 + A1:2012**
Notified body/ies: **Modena Centro Prove No. 1599**
Istituto Giordano No. 0407
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Bond strength as: initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
Durability for: Tensile adhesion strength after heat ageing Tensile adhesion strength after water immersion Tensile adhesion strength after freeze-thaw cycles	$\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Zissis Koulaxidis (General Manager)**

At Schimatari-Viotia, on 29/08/2026

kerakoll.com

KERAKOLL ΕΛΛΑΣ Ε.Π.Ε. – 1ο Χλμ. Σχηματαρίου – Αυλίδας, Θέση Ρουθούνια – 32009 Σχηματάρι Βοιωτίας, Ελλάδα

Tel. +30 22620 49700 – Fax +30 22620 58788 – e-mail: info@kerakollhellas.gr

Α.Φ.Μ.: 099224696, Γενικό Εμπορικό Μητρώο (Γ.Ε.ΜΗ.): 013412517000, Μετοχικό Κεφάλαιο: 5.001.270 €