

kerakoll

DECLARATION OF PERFORMANCE No. 0079

1. Unique identification code of the product-type: FLEX PAINT

2. Intended use/es:

Products for the protection of concrete structures, Ingress protection (1.3), moisture control (2.2) and increasing resistivity (8.2)

3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia

4. System/s of AVCP: System 2+ and System 3 for reaction to fire

Harmonised standard: EN 1504-2: 2004
 Notified body/ies: LRQA Iberia No.0094

INSTYTUT CERAMIKI I MATERIALOW BUDOWLANYCH No. 1487

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class B-s1,d0
Permeability to CO ₂ Permeability to water vapour (S _D) Capillary absorption and permeability to water Adhesion strength by pull-off test	S _D > 50 m Classe I; S _D < 5 m w ≤ 0,1 Kg/m ² h ^{0,5} ≥ 0,8 N/mm ²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Romano Sghedoni (legal representative)

At Sassuolo, on 28/10/2025

Myledei