



kerakoll

DECLARATION OF PERFORMANCE No 0614

1. Unique identification code of the product-type: **EPOFILL**
2. Intended use/ies: **Concrete injection product U (F1) W (2) (1/2) (5/30) (1)**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 2+
5. Harmonised standard: **EN 1504-5:2005 + A1:2013**
6. Notified body/ies: **LRQA Inspection Iberia - 0094**
7. Declared performance/s:

Essential characteristics	Performance
Adhesion by tensile bond strength	Cohesive failure in the substrate
Adhesion by slant shear strength	Breaking monolithic
No volatile substances:	> 95%
Glass transition temperature	> 40°C
Workability	Crack width from 0,2 mm Moisture state of the crack : dry and wet
Durability	Pass
Corrosion behavior	Deemed to have no corrosive effect
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**
At Sassuolo, on 06/10/2025

kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.



kerakoll

DECLARATION OF PERFORMANCE No 0614

1. Unique identification code of the product-type: **EPOFILL**
2. Intended use/ies: **Anchoring product**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:

System 2+

System 3 for reaction to fire

5. Harmonised standard: **EN 1504-6:2007**

Notified body/ies: **LRQA Inspection Iberia - 0094**

Ist. Giordano - 0407

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class E
Pull-out	≤ 0,6 mm
Creep under tensile load	≤ 0,6 mm
Glass transition temperature	≥ 45°C
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**
At Sassuolo, on 06/10/2025

kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.