

## DECLARATION OF PERFORMANCE No 0416

1. Unique identification code of the product-type: **H40 REVOLUTION**
2. Intended use/es:  
**Improved fast setting cementitious adhesive for all internal and external tiling**
3. Manufacturer: **Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów**
4. System/s of AVCP:  
**System 3**  
**System 3 for reaction to fire**
5. Harmonised standard: **EN 12004:2007 + A1:2012**  
Notified body/ies: **Modena Centro Prove No. 1599**  
**Istituto Giordano No. 0407**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Bond strength expressed as: early tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$
Bond strength expressed as: initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
Durability of bond strength against climate/heat ageing action expressed as: tensile adhesion strength after heat ageing	$\geq 1,0 \text{ N/mm}^2$
Durability of bond strength against water/humidity action expressed as: tensile adhesion strength after water immersion	$\geq 1,0 \text{ N/mm}^2$
Durability of bond strength against freeze-thaw cycles expressed as: tensile adhesion strength after freeze-thaw cycles	$\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Michał Wróblewski (legal representative)**

At Rzgów, on 05/09/2025

