

DECLARATION OF PERFORMANCE No 0663

1. Unique identification code of the product-type: **H40 GEL**
2. Intended use/es:
Improved cementitious adhesive for all internal and external tiling.
3. Manufacturer: **Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów**
4. System/s of AVCP:
System 3
System 3 for reaction to fire
5. Harmonised standard: **EN 12004:2007 + A1:2012**
Notified body/ies:
SIEĆ BADAWCZA ŁUKASIEWICZ - INSTYTUT CERAMIKI I MATERIAŁOW BUDOWLANYCH No. 1487
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A2-s1, d0/A2fl-s1
Bond strength expressed as: initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
Durability of bond strength against climate/heat ageing action expressed as: tensile adhesion strength after heat ageing	$\geq 1,0 \text{ N/mm}^2$
Durability of bond strength against water/humidity action expressed as: tensile adhesion strength after water immersion	$\geq 1,0 \text{ N/mm}^2$
Durability of bond strength against freeze-thaw cycles expressed as: tensile adhesion strength after freeze-thaw cycles	$\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Michał Wróblewski (legal representative)**

At Rzgów, on 05/09/2025

