

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

AQUASTOP NANOGUM (A)

Date of first edition: 3/7/2022

Safety Data Sheet dated 12/05/2025

version 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: AQUASTOP NANOGUM (A)

Trade code: S100B0007 30

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Waterproofing product

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112


Ireland Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Members of the public Number (8 am-10 pm): +353 (0)1 809 2166

Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

Malta In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2 Causes serious eye irritation.

Skin Sens. 1A May cause an allergic skin reaction.

Aquatic Chronic 2 Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Warning

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

- P280 Wear protective gloves and eye protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P501 Dispose of contents/container in accordance with applicable regulations.

Contains

Cashew, nutshell liq.
bis-[4-(2,3-epoxipropoxy)phenyl]propane
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: Crystalline silica in breathable fraction present in the product does not contribute to the hazard classification according to the criteria laid down by the EC Regulation 1272/2008 (CLP) by virtue of the physical state of the product itself (liquid/solid paste) as it is marketed and reasonably be expected to be used. (Position IMA-Europe, Classification of mixtures in liquid form containing crystalline silica (May 2020)). The liquid/solid paste mixture, due to hardening or exposure to heat, can lose its liquid content (water and other liquid components) and appear in a solid state; in case of handling of the solid mixture for disposal (non-compliant product) in so doing, comply with the local and national regulations currently in force.

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: AQUASTOP NANOGUM (A)

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥20-<50 %	bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS:1675-54-3 EC:216-823-5 Index:603-073-00-2	Eye Irrit. 2, H319; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 2, H411, M-Chronic:1	01-2119456619-26
			Specific Concentration Limits: C ≥ 5%: Eye Irrit. 2 H319 C ≥ 5%: Skin Irrit. 2 H315	
≥10-<20 %	p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	CAS:3101-60-8 EC:221-453-2	Skin Sens. 1, H317; Aquatic Chronic 2, H411, M-Chronic:1	
≥5-<10 %	Quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372	
≥0.5-<1 %	Titanium dioxide	CAS:13463-67-7 EC:236-675-5	Not classified as hazardous	
≥0.5-<1 %	Cashew, nutshell liq.	CAS:8007-24-7 EC:232-355-4	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1A, H317	01-2119502450-57
<0.036 %	xylene	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Acute Tox. 4, H332; Acute Tox. 4, H312; Skin Irrit. 2, H315; STOT SE 3, H335; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 3, H412; Eye Irrit. 2, H319, M-Chronic:1	01-2119488216-32
<0.01 %	ethyl acrylate	CAS:140-88-5 EC:205-438-8 Index:607-032-00-X	Flam. Liq. 2, H225; Acute Tox. 3, H331; Acute Tox. 4, H312; Acute Tox. 4, H302; STOT SE 3, H335; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	01-2119459301-46
			Specific Concentration Limits: C ≥ 5%: STOT SE 3 H335 C ≥ 5%: Skin Irrit. 2 H315 C ≥ 5%: Eye Irrit. 2 H319	

<0.0015 % methanol

CAS:67-56-1

EC:200-659-6

Index:603-001-00-X

Flam. Liq. 2, H225; STOT SE 1,

H370; Acute Tox. 3, H301; Acute

Tox. 3, H311; Acute Tox. 3, H331

01-2119433307-44

Specific Concentration Limits:

C ≥ 10%: STOT SE 1 H370

3% ≤ C < 10%: STOT SE 2 H371

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
Quartz CAS: 14808-60-7	ACGIH		Long Term: 0.025 mg/m ³ (8h) R, A2 - Pulm fibrosis, lung cancer
	NATIONAL	HUNGARY	Long Term: 0.1 mg/m ³ Source: 5/2020. (II. 6.) ITM rendelet
	NATIONAL	IRELAND	Long Term: 0.1 mg/m ³ Respirable fraction Source: 2021 Code of Practice
	NATIONAL	ITALY	Long Term: 0.1 mg/m ³ Polvere di silice cristallina respirabile (frazione inalabile). Rif:D.Lgs 81/2008 Source: D.lgs. 81/2008, Allegato XLIII
	NATIONAL	SPAIN	Long Term: 0.3 mg/m ³ Respirable fraction Source: LEP 2022
	NATIONAL	BELGIUM	Long Term: 0.1 mg/m ³ C Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	DENMARK	Long Term: 0.3 mg/m ³ alveolijae, liite 3 Source: BEK nr 2203 af 29/11/2021
	NATIONAL	DENMARK	Long Term: 0.1 mg/m ³ EK Source: BEK nr 2203 af 29/11/2021
	NATIONAL	ESTONIA	Long Term: 0.1 mg/m ³ 1, C Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	FINLAND	Long Term: 0.05 mg/m ³ alveolijae, liite 3 Source: HTP-ARVOT 2020
	NATIONAL	FRANCE	Long Term: 0.1 mg/m ³ La VLEP s'applique à la fraction alvéolaire. Forme de silice cristalline. Source: INRS outil65, article R. 4412-149 du Code du travail

NATIONAL	LITHUANIA	Long Term: 0.1 mg/m ³ Žiūrėti 1 priedo 3 punktą. Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	NETHERLANDS	Long Term: 0.075 mg/m ³ (2) Source: Arbeidsomstandighedenregeling - Lijst B1
NATIONAL	NORWAY	Long Term: 0.3 mg/m ³ K 7 Source: FOR-2021-06-28-2248
NATIONAL	NORWAY	Long Term: 0.05 mg/m ³ K G 7 21 Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 0.1 mg/m ³ 6) Source: Dz.U. 2018 poz. 1286
NATIONAL	SWEDEN	Long Term: 0.1 mg/m ³ C, M, 3 Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 0.15 mg/m ³ TWA mg/m ³ : (a), C1A, SSC, P, Cancpulm Silicose / Lugenkrebs Silikose, HSE NIOSH OSHA Source: suva.ch/valeurs-limites
Quartz CAS: 14808-60-7	EU	Long Term: 0.1 mg/m ³ Polvere di silice cristallina respirabile, frazione inalabile. (R), A2 - Pulm fibrosis, lung cancer. Directive 2017/2398
	ACGIH	Long Term: 0.025 mg/m ³ (8h) R, A2 - Pulm fibrosis, lung cancer
	NATIONAL HUNGARY	Long Term: 0.1 mg/m ³ (8h) Respirable aerosol Source: 5/2020. (II. 6.) ITM rendelet
	NATIONAL IRELAND	Long Term: 0.1 mg/m ³ (8h) Respirable fraction Source: 2021 Code of Practice
	NATIONAL ITALY	Long Term: 0.1 mg/m ³ (8h) Polvere di silice cristallina respirabile (frazione inalabile). D.Lgs 81/2008 Source: D.lgs. 81/2008, Allegato XLIII
	NATIONAL SPAIN	Long Term: 0.05 mg/m ³ (8h) Respirable fraction Source: LEP 2022
	NATIONAL CROATIA	Long Term: 0.1 mg/m ³ Source: NN 1/2021
	NATIONAL AUSTRIA	Long Term: 0.05 mg/m ³ MAK, III C, A Source: BGBl. II Nr. 156/2021
	NATIONAL BELGIUM	Long Term: 0.1 mg/m ³ C Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL DENMARK	Long Term: 0.3 mg/m ³ Source: BEK nr 2203 af 29/11/2021
	NATIONAL DENMARK	Long Term: 0.1 mg/m ³ EK Source: BEK nr 2203 af 29/11/2021
	NATIONAL ESTONIA	Long Term: 0.1 mg/m ³ 1, C Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL FINLAND	Long Term: 0.05 mg/m ³ alveolijae, liite 3 Source: HTP-ARVOT 2020
	NATIONAL FRANCE	Long Term: 0.1 mg/m ³ La VLEP s'applique à la fraction alvéolaire. Forme de silice cristalline.

Titanium dioxide CAS: 13463-67-7	NATIONAL	LITHUANIA	Long Term: 0.1 mg/m ³ Žiūrėti 1 priedo 3 punktą. Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
	NATIONAL	NETHERLANDS	Long Term: 0.075 mg/m ³ (2) Source: Arbeidsomstandighedenregeling - Lijst B1
	NATIONAL	NORWAY	Long Term: 0.3 mg/m ³ K 7 Source: FOR-2021-06-28-2248
	NATIONAL	NORWAY	Long Term: 0.05 mg/m ³ K G 7 21 Source: FOR-2021-06-28-2248
	NATIONAL	POLAND	Long Term: 0.1 mg/m ³ 6) Source: Dz.U. 2018 poz. 1286
	NATIONAL	SWEDEN	Long Term: 0.1 mg/m ³ C, M, 3 Source: AFS 2021:3
	SUVA	SWITZERLAND	Long Term: 0.15 mg/m ³ TWA mg/m ³ : (a), C1A, SSC, P, Cancpulm Silicose / Lugenkrebs Silikose, HSE NIOSH OSHA Source: suva.ch/valeurs-limites
	ACGIH		Long Term: 2.5 mg/m ³ (8h) Finescale particles; R ; A3 - LRT irr, pneumoconiosis
	NATIONAL	GERMANY	Long Term: 0.3 mg/m ³ ; Short Term: 2.4 mg/m ³ DFG; Long term and short term: excluding ultrafine particles; respirable fraction; multiplied by the material density; Source: TRGS900
	NATIONAL	BELGIUM	Long Term: 10 mg/m ³ Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	CROATIA	Long Term: 10 mg/m ³ U Source: NN 1/2021
	NATIONAL	CROATIA	Long Term: 4 mg/m ³ R Source: NN 1/2021
	NATIONAL	IRELAND	Long Term: 10 mg/m ³ Source: 2021 Code of Practice
	NATIONAL	IRELAND	Long Term: 4 mg/m ³ Source: 2021 Code of Practice
	NATIONAL	ROMANIA	Long Term: 10 mg/m ³ ; Short Term: 15 mg/m ³ Source: Republicarea 1 - nr. 743 din 29 iulie 2021
	NATIONAL	SPAIN	Long Term: 10 mg/m ³ Source: LEP 2022
	NATIONAL	AUSTRIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ 60(Miw), 2x, MAK, A Source: BGBl. II Nr. 156/2021
	NATIONAL	BULGARIA	Long Term: 10 mg/m ³ Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATIONAL	DENMARK	Long Term: 6 mg/m ³ K Source: BEK nr 2203 af 29/11/2021
	NATIONAL	ESTONIA	Long Term: 5 mg/m ³ Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	FRANCE	Long Term: 10 mg/m ³ Cancérogène de catégorie 2 Source: INRS outil65

	NATIONAL	GREECE	Long Term: 10 mg/m ³ εισπν. Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL	GREECE	Long Term: 5 mg/m ³ αvapv. Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL	LATVIA	Long Term: 10 mg/m ³ Source: KN325P1
	NATIONAL	LITHUANIA	Long Term: 5 mg/m ³ Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
	NATIONAL	NORWAY	Long Term: 5 mg/m ³ Source: FOR-2021-06-28-2248
	NATIONAL	POLAND	Long Term: 10 mg/m ³ 4), 7) Source: Dz.U. 2018 poz. 1286
	NATIONAL	SLOVAKIA	Long Term: 5 mg/m ³ Source: 355 NARIADENIE VLÁDY z 10. mája 2006
	NATIONAL	SWEDEN	Long Term: 5 mg/m ³ 3 Source: AFS 2021:3
	SUVA	SWITZERLAND	Long Term: 3 mg/m ³ TWA mg/m ³ : (a), SSC, Formel / Formal, NIOSH Source: suva.ch/valeurs-limites
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
Triiron tetraoxide CAS: 1317-61-9	NATIONAL	POLAND	Long Term: 2.5 mg/m ³ ; Short Term: 5 mg/m ³ 6) Source: Dz.U. 2018 poz. 1286
xylene CAS: 1330-20-7	ACGIH		Long Term: 20 ppm (8h) A4, BEI - URT and eye irr; hematologic eff; CNS impair
	NATIONAL	AUSTRIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm 15(Miw), 4x, MAK Source: BGBl. II Nr. 156/2021
	NATIONAL	BULGARIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Кожа Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATIONAL	CZECHIA	Long Term: 200 mg/m ³ ; Short Term: Ceiling - 400 mg/m ³ B, D, I Source: Nařízení vlády č. 361-2007 Sb
	NATIONAL	DENMARK	Long Term: 109 mg/m ³ - 25 ppm EH Source: BEK nr 2203 af 29/11/2021
	NATIONAL	ESTONIA	Long Term: 200 mg/m ³ - 50 ppm; Short Term: 450 mg/m ³ - 100 ppm A Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	FINLAND	Long Term: 220 mg/m ³ - 50 ppm; Short Term: 440 mg/m ³ - 100 ppm iho Source: HTP-ARVOT 2020
	NATIONAL	FRANCE	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Risque de pénétration percutanée Source: INRS outil65, article R. 4412-149 du Code du travail
	NATIONAL	GREECE	Long Term: 435 mg/m ³ - 100 ppm; Short Term: 650 mg/m ³ - 150 ppm Δ Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL	HUNGARY	Long Term: 221 mg/m ³ ; Short Term: 442 mg/m ³ b, BEM, EU1, R

NATIONAL	LITHUANIA	Long Term: 200 mg/m ³ - 50 ppm; Short Term: 450 mg/m ³ - 100 ppm O Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	NETHERLANDS	Long Term: 210 mg/m ³ ; Short Term: 442 mg/m ³ H Source: Arbeidsomstandighedenregeling - Lijst A
NATIONAL	NORWAY	Long Term: 108 mg/m ³ - 25 ppm H E Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 100 mg/m ³ ; Short Term: 200 mg/m ³ skóra Source: Dz.U. 2018 poz. 1286
NATIONAL	SLOVAKIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm K, 7) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATIONAL	SWEDEN	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm H Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 220 mg/m ³ - 50 ppm; Short Term: 440 mg/m ³ - 100 ppm R/H, B, SNC / ZNS, NIOSH INRS Source: suva.ch/valeurs-limites
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 220 mg/m ³ - 50 ppm; Short Term: 441 mg/m ³ - 100 ppm Sk, BMGV Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
NATIONAL	BELGIUM	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm D Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATIONAL	CROATIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm koža Source: 2000/39/EZ
NATIONAL	CYPRUS	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm δέρμα Source: Οι περί Ασφάλειας και Υγείας στην Εργασία (Χημικοί Παράγοντες) Κανονισμοί του 2001 έως 2021
NATIONAL	GERMANY	Long Term: 220 mg/m ³ - 50 ppm DFG, EU, H, 2(II) Source: TRGS 900
NATIONAL	IRELAND	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Sk, IOELV Source: 2021 Code of Practice
NATIONAL	ITALY	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Cute Source: D.lgs. 81/2008, Allegato XXXVIII
NATIONAL	LATVIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Āda Source: KN325P1
NATIONAL	LUXEMBOURG	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Peau Source: Mémorial A n.226 du 22 mars 2021
NATIONAL	MALTA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm skin Source: S.L.424.24
NATIONAL	PORTUGAL	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Cutânea Source: Decreto-Lei n.º 1/2021
NATIONAL	ROMANIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm P, Dir. 2000/39

			Source: Republicarea 1 - nr. 743 din 29 iulie 2021
silicon dioxide, chemically prepared CAS: 7631-86-9	NATIONAL	SLOVENIA	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm K, BAT, EU1 Source: UL št. 72, 11. 5. 2021
	NATIONAL	SPAIN	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm vía dérmica, VLB®, VLI Source: LEP 2022
	EU		Long Term: 221 mg/m ³ - 50 ppm (8h); Short Term: 442 mg/m ³ - 100 ppm Skin
	NATIONAL	BELGIUM	Long Term: 10 mg/m ³ Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	IRELAND	Long Term: 6 mg/m ³ Inhalable fraction Source: 2021 Code of Practice
	NATIONAL	IRELAND	Long Term: 2.4 mg/m ³ Respirable fraction Source: 2021 Code of Practice
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 6 mg/m ³ Inhalable aerosol Source: EH40/2005 Workplace exposure limits
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 2.4 mg/m ³ Respirable aerosol Source: EH40/2005 Workplace exposure limits
	NATIONAL	GERMANY	Long Term: 4 mg/m ³ DFG, 2, Y, E Source: TRGS 900
	NATIONAL	SLOVENIA	Long Term: 4 mg/m ³ Y, (I) Source: UL št. 72, 11. 5. 2021
Aluminium oxide CAS: 1344-28-1	NATIONAL	AUSTRIA	MAK Source: BGBl. II Nr. 156/2021
	NATIONAL	ESTONIA	Long Term: 2 mg/m ³ 1 Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	LATVIA	Long Term: 1 mg/m ³ Source: KN325P1
	SUVA	SWITZERLAND	SSC, Fibpulm / Lungenfibrose, Des VMEs se trouvent sous les substances associées / MAK-Werte finden sich unter den zugeordneten Stoffen Source: suva.ch/valeurs-limites
	SUVA	SWITZERLAND	Long Term: 4 mg/m ³ TWA mg/m ³ : (i), SSC, Fibpulm / Lungenfibrose Source: suva.ch/valeurs-limites
	NATIONAL	BELGIUM	Long Term: 1 mg/m ³ Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	CROATIA	Long Term: 10 mg/m ³ U Source: NN 1/2021
	NATIONAL	CROATIA	Long Term: 4 mg/m ³ R Source: NN 1/2021
	NATIONAL	ROMANIA	Long Term: 2 mg/m ³ ; Short Term: 5 mg/m ³ (Aerosoli) Source: Republicarea 1 - nr. 743 din 29 iulie 2021

NATIONAL	SPAIN	Long Term: 10 mg/m ³ véase Capítulo 9 Source: LEP 2022
NATIONAL	AUSTRIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ 60(Miw), 2x, A Source: GKV, BGBl. II Nr. 156/2021
NATIONAL	AUSTRIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ 60(Miw), 2x, MAK, A Source: GKV, BGBl. II Nr. 156/2021
NATIONAL	DENMARK	Long Term: 5 mg/m ³ Source: BEK nr 2203 af 29/11/2021
NATIONAL	ESTONIA	Long Term: 4 mg/m ³ 1 Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	FRANCE	Long Term: 10 mg/m ³ Source: INRS outil65
NATIONAL	GREECE	Long Term: 10 mg/m ³ εισπν Source: ΦΕΚ 94/A` 13.5.1999
NATIONAL	GREECE	Long Term: 5 mg/m ³ αvapn Source: ΦΕΚ 94/A` 13.5.1999
NATIONAL	HUNGARY	Long Term: 5 mg/m ³ N Source: 5/2020. (II. 6.) ITM rendelet
NATIONAL	HUNGARY	Long Term: 2 mg/m ³ resp, N Source: 5/2020. (II. 6.) ITM rendelet
NATIONAL	LATVIA	Long Term: 6 mg/m ³ Source: KN325P1
NATIONAL	LATVIA	Long Term: 4 mg/m ³ Source: KN325P1
NATIONAL	NORWAY	Long Term: 10 mg/m ³ 1 Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 2.5 mg/m ³ 4) Source: Dz.U. 2018 poz. 1286
NATIONAL	POLAND	Long Term: 1.2 mg/m ³ 6) Source: Dz.U. 2018 poz. 1286
NATIONAL	SLOVAKIA	Long Term: 4 mg/m ³ 10) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
SUVA	SWITZERLAND	Long Term: 3 mg/m ³ D TWA mg/m ³ : (a), B, Formel / Formal, NIOSH Source: suva.ch/valeurs-limites
SUVA	SWITZERLAND	Long Term: 3 mg/m ³ ; Short Term: 24 mg/m ³ D TWA mg/m ³ : (a), Fimétal / Metallrauch, NIOSH Source: suva.ch/valeurs-limites
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)

IRELAND

ethyl acrylate
CAS: 140-88-5

ACGIH		Long Term: 5 ppm (8h); Short Term: 15 ppm A4 - URT, eye, and GI irr, CNS impair, skin sens
NATIONAL	AUSTRIA	Long Term: 20 mg/m ³ - 5 ppm; Short Term: Ceiling - 40 mg/m ³ - 10 ppm 5(Mow), 8x, MAK, H, Sh Source: BGBl. II Nr. 156/2021
NATIONAL	BULGARIA	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
NATIONAL	CYPRUS	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm Source: Οι περί Ασφάλειας και Υγείας στην Εργασία (Χημικοί Παράγοντες) Κανονισμοί του 2001 έως 2021
NATIONAL	CZECHIA	Long Term: 20 mg/m ³ ; Short Term: Ceiling - 40 mg/m ³ I, S Source: Nařízení vlády č. 361-2007 Sb
NATIONAL	DENMARK	Long Term: 21 mg/m ³ - 5 ppm EHK Source: BEK nr 2203 af 29/11/2021
NATIONAL	ESTONIA	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm S Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	FINLAND	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm iho Source: HTP-ARVOT 2020
NATIONAL	FRANCE	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm Source: INRS outil65, article R. 4412-149 du Code du travail
NATIONAL	GREECE	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm Source: ΦΕΚ 19/Α` 9.2.2012
NATIONAL	HUNGARY	Long Term: 21 mg/m ³ ; Short Term: 42 mg/m ³ b, i, sz, EU4, N Source: 5/2020. (II. 6.) ITM rendelet
NATIONAL	LATVIA	Long Term: 10 mg/m ³ Source: KN325P1
NATIONAL	LITHUANIA	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm J Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	NETHERLAND S	Long Term: 21 mg/m ³ ; Short Term: 42 mg/m ³ Source: Arbeidsomstandighedenregeling - Lijst A
NATIONAL	NORWAY	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm H A K E S Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 20 mg/m ³ ; Short Term: 40 mg/m ³ skóra Source: Dz.U. 2018 poz. 1286
NATIONAL	PORTUGAL	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm Source: Decreto-Lei n.º 1/2021
NATIONAL	SLOVAKIA	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm S Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATIONAL	SWEDEN	Long Term: 20 mg/m ³ - 5 ppm; Short Term: 40 mg/m ³ - 10 ppm M, S Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 10 mg/m ³ - 2.5 ppm; Short Term: 42 mg/m ³ - 10 ppm S, SSC, VRS Yeux / OAW Auge, INRS NIOSH Source: suva.ch/valeurs-limites
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)

methanol
CAS: 67-56-1

	IRELAND	
NATIONAL	BELGIUM	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATIONAL	CROATIA	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm koža, alergen koža Source: 2009/161/EU
NATIONAL	GERMANY	Long Term: 8.3 mg/m ³ - 2 ppm DFG, EU, H, Y, Sh, 2(I) Source: TRGS 900
NATIONAL	IRELAND	Long Term: 20 mg/m ³ - 5 ppm; Short Term: 41 mg/m ³ - 10 ppm IOELV, Sk, Sens Source: 2021 Code of Practice
NATIONAL	ITALY	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm Source: D.lgs. 81/2008, Allegato XXXVIII
NATIONAL	LUXEMBOUR G	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm Source: Mémorial A n.226 du 22 mars 2021
NATIONAL	MALTA	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm Source: S.L.424.24
NATIONAL	ROMANIA	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm Dir. 2009/161 Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATIONAL	SLOVENIA	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm K, Y, EU3 Source: UL št. 72, 11. 5. 2021
NATIONAL	SPAIN	Long Term: 21 mg/m ³ - 5 ppm; Short Term: 42 mg/m ³ - 10 ppm VLI, Sen Source: LEP 2022
EU		Long Term: 21 mg/m ³ - 5 ppm (8h); Short Term: 42 mg/m ³ - 10 ppm
ACGIH		Long Term: 200 ppm (8h); Short Term: 250 ppm Skin, BEI - Headache, eye dam, dizziness, nausea
NATIONAL	AUSTRIA	Long Term: 260 mg/m ³ - 200 ppm; Short Term: 1040 mg/m ³ - 800 ppm 15(Miw), 4x, MAK, H Source: BGBl. II Nr. 156/2021
NATIONAL	BULGARIA	Long Term: 260 mg/m ³ - 200 ppm Кожа Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
NATIONAL	CZECHIA	Long Term: 250 mg/m ³ ; Short Term: Ceiling - 1000 mg/m ³ D, B Source: Nařízení vlády č. 361-2007 Sb
NATIONAL	DENMARK	Long Term: 260 mg/m ³ - 200 ppm EH Source: BEK nr 2203 af 29/11/2021
NATIONAL	ESTONIA	Long Term: 250 mg/m ³ - 200 ppm; Short Term: 350 mg/m ³ - 250 ppm A Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	FINLAND	Long Term: 270 mg/m ³ - 200 ppm; Short Term: 330 mg/m ³ - 250 ppm iho Source: HTP-ARVOT 2020
NATIONAL	FRANCE	Long Term: 260 mg/m ³ - 200 ppm; Short Term: 1300 mg/m ³ - 1000 ppm Risque de pénétration percutanée Source: INRS outil65, article R. 4412-149 du Code du travail
NATIONAL	GREECE	Long Term: 260 mg/m ³ - 200 ppm; Short Term: 325 mg/m ³ - 250 ppm Δ Source: ΦΕΚ 94/Α` 13.5.1999
NATIONAL	HUNGARY	Long Term: 260 mg/m ³ b, i, BEM, EU2, R+T Source: 5/2020. (II. 6.) ITM rendelet
NATIONAL	LITHUANIA	Long Term: 260 mg/m ³ - 200 ppm O

NATIONAL	NETHERLANDS	Long Term: 133 mg/m ³ H Source: Arbeidsomstandighedenregeling - Lijst A
NATIONAL	NORWAY	Long Term: 130 mg/m ³ - 100 ppm H E Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 100 mg/m ³ ; Short Term: 300 mg/m ³ skóra Source: Dz.U. 2018 poz. 1286
NATIONAL	SLOVAKIA	Long Term: 260 mg/m ³ - 200 ppm K, 7) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATIONAL	SWEDEN	Long Term: 250 mg/m ³ - 200 ppm; Short Term: 350 mg/m ³ - 250 ppm H, V Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 260 mg/m ³ - 200 ppm; Short Term: 520 mg/m ³ - 400 ppm R/H, SSC, B, SNC / ZNS, INRS NIOSH Source: suva.ch/valeurs-limites
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 266 mg/m ³ - 200 ppm; Short Term: 333 mg/m ³ - 250 ppm Sk Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
NATIONAL	BELGIUM	Long Term: 266 mg/m ³ - 200 ppm; Short Term: 333 mg/m ³ - 250 ppm D Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATIONAL	CROATIA	Long Term: 260 mg/m ³ - 200 ppm koža Source: 2006/15/EZ
NATIONAL	CYPRUS	Long Term: 260 mg/m ³ - 200 ppm δέρμα Source: Οι περί Ασφάλειας και Υγείας στην Εργασία (Χημικοί Παράγοντες) Κανονισμοί του 2001 έως 2021
NATIONAL	GERMANY	Long Term: 130 mg/m ³ - 100 ppm DFG, EU, H, Y, 2(II) Source: TRGS 900
NATIONAL	IRELAND	Long Term: 260 mg/m ³ - 200 ppm Sk, IOELV Source: 2021 Code of Practice
NATIONAL	ITALY	Long Term: 260 mg/m ³ - 200 ppm Cute Source: D.lgs. 81/2008, Allegato XXXVIII
NATIONAL	LATVIA	Long Term: 260 mg/m ³ - 200 ppm Āda Source: KN325P1
NATIONAL	LUXEMBOURG	Long Term: 260 mg/m ³ - 200 ppm Peau Source: Mémorial A n.226 du 22 mars 2021
NATIONAL	MALTA	Long Term: 260 mg/m ³ - 200 ppm skin Source: S.L.424.24
NATIONAL	PORTUGAL	Long Term: 260 mg/m ³ - 200 ppm Cutânea Source: Decreto-Lei n.º 1/2021
NATIONAL	ROMANIA	Long Term: 260 mg/m ³ - 200 ppm P, Dir. 2006/15 Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATIONAL	SLOVENIA	Long Term: 260 mg/m ³ - 200 ppm; Short Term: 1040 mg/m ³ - 800 ppm K, Y, BAT, EU2

Source: UL št. 72, 11. 5. 2021

NATIONAL SPAIN

Long Term: 266 mg/m³ - 200 ppm
vía dérmica, VLB®, VLI, r
Source: LEP 2022

EU

Long Term: 260 mg/m³ - 200 ppm (8h)
Skin

Biological limit values

xylene
CAS: 1330-20-7

Biological Indicator: Methyl hippuric acid in urine; Sampling Period: End of turn
Value: 2000 mg/L; Medium: Urine

methanol
CAS: 67-56-1

Biological Indicator: Methyl alcohol; Sampling Period: End of turn; End of working week
Value: 30 mg/L; Medium: Urine

Predicted No Effect Concentration (PNEC) values

bis-[4-(2,3-epoxipropoxy)phenyl]
propane
CAS: 1675-54-3

Exposure Route: Fresh Water; PNEC Limit: 0.006 mg/l

Exposure Route: Marine water; PNEC Limit: 600 ng/L

Exposure Route: Freshwater sediments; PNEC Limit: 0.996 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0.099 mg/kg

Exposure Route: Soil; PNEC Limit: 0.196 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.018 mg/l

Titanium dioxide
CAS: 13463-67-7

Exposure Route: Fresh Water; PNEC Limit: 0.184 mg/l

Exposure Route: Marine water; PNEC Limit: 0.018 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 1 mg/kg

Exposure Route: Intermittent releases (marine water); PNEC Limit: 100 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/kg

Cashew, nutshell liq.
CAS: 8007-24-7

Exposure Route: Fresh Water; PNEC Limit: 0.003 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 0.088 mg/kg

Exposure Route: Freshwater sediments; PNEC Limit: 0.97 mg/kg

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.03 mg/l

Exposure Route: Soil; PNEC Limit: 6.71 mg/kg

xylene
CAS: 1330-20-7

Exposure Route: Fresh Water; PNEC Limit: 327 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 327 µg/l

Exposure Route: Marine water; PNEC Limit: 327 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 6.58 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 12.46 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 12.46 mg/kg

Exposure Route: Soil; PNEC Limit: 2.31 mg/kg

ethyl acrylate
CAS: 140-88-5

Exposure Route: Fresh Water; PNEC Limit: 2.72 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 11 µg/l

Exposure Route: Marine water; PNEC Limit: 270 ng/L

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 21.3 µg/kg

Exposure Route: Marine water sediments; PNEC Limit: 21.3 µg/kg

Exposure Route: Soil; PNEC Limit: 1 mg/kg

Exposure Route: Secondary poisoning; PNEC Limit: 10 mg/kg

methanol
CAS: 67-56-1

Exposure Route: Fresh Water; PNEC Limit: 20.8 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 1540 mg/l

Exposure Route: Marine water; PNEC Limit: 2.08 mg/l
 Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l
 Exposure Route: Freshwater sediments; PNEC Limit: 77 mg/kg
 Exposure Route: Marine water sediments; PNEC Limit: 7.7 mg/kg
 Exposure Route: Soil; PNEC Limit: 100 mg/kg

Derived No Effect Level (DNEL) values

bis-[4-(2,3-epoxipropoxy)phenyl]propane
 CAS: 1675-54-3

Exposure Route: Human Oral; Exposure Frequency: Long Term, local effects
 Worker Professional: 0.75 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 0.75 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 3.571 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects
 Worker Professional: 3.571 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 12.25 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
 Worker Professional: 12.25 mg/m³

Titanium dioxide
 CAS: 13463-67-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
 Worker Professional: 10 mg/m³

Cashew, nutshell liq.
 CAS: 8007-24-7

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects
 Worker Professional: 0.5 mg/kg; Consumer: 0.25 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
 Worker Professional: 0.88 mg/m³; Consumer: 0.2 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Long Term, local effects
 Consumer: 0.25 mg/kg

xylene
 CAS: 1330-20-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 221 mg/m³; Consumer: 65.3 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
 Worker Professional: 442 mg/m³; Consumer: 260 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
 Worker Professional: 221 mg/m³; Consumer: 65.3 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
 Worker Professional: 442 mg/m³; Consumer: 260 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 212 mg/kg; Consumer: 125 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
 Consumer: 12.5 mg/kg

ethyl acrylate
 CAS: 140-88-5

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
 Worker Professional: 21 mg/m³; Consumer: 2.5 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Short Term, local effects
 Worker Professional: 0.92 mg/cm²; Consumer: 0.92 mg/cm²

methanol
 CAS: 67-56-1

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 130 mg/m³; Consumer: 26 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
 Worker Professional: 130 mg/m³; Consumer: 26 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
 Worker Professional: 130 mg/m³; Consumer: 26 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
 Worker Professional: 130 mg/m³; Consumer: 26 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 20 mg/kg; Consumer: 4 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Professional: 20 mg/kg; Consumer: 4 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 4 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 4 mg/kg

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing. Safety shoes.

Protection for hands:

Protection for hands:

Suitable materials for safety gloves; EN 374:

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Solid

Colour: White

Odour: Characteristic

Odour threshold: N.A.

pH: N.A.

Kinematic viscosity: N.A.

Melting point/freezing point: N.A.

Boiling point or initial boiling point and boiling range: $> 300\text{ }^{\circ}\text{C}$ (572 $^{\circ}\text{F}$)

Flash point: $> 100\text{ }^{\circ}\text{C}$ (212 $^{\circ}\text{F}$)

Lower and upper explosion limit: N.A.

Relative vapour density: N.A.

Vapour pressure: N.A.

Density and/or relative density: 1.20 g/cm^3

Solubility in water: N.A.

Solubility in oil: N.A.

Partition coefficient n-octanol/water (log value): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: N.A.

Volatile Organic compounds - VOCs = $0.03\text{ }\%$; 0.39 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

bis-[4-(2,3-epoxipropoxy)phenyl]propane	a) acute toxicity	LD50 Oral Rabbit = 19800 mg/kg LD50 Skin Rabbit > 20 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive	epoxy resin with an average molecular mass <= 700 d irritate skin of rabbits
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	f) carcinogenicity	Genotoxicity Negative Carcinogenicity Oral Rat = 15 mg/kg Carcinogenicity Skin Rat = 1 mg/kg	Mouse, oral NOAEL NOAEL
	g) reproductive toxicity	No Observed Effect Level Oral Rat = 750 mg/kg	
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg LD50 Skin Rat > 2000 mg/kg 24h	
	c) serious eye damage/irritation	Eye Irritant Rabbit No	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	f) carcinogenicity	Genotoxicity Rat Negative	
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 100 mg/kg	
Quartz	a) acute toxicity	LD50 Oral > 2000 mg/kg	
Titanium dioxide	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg LC50 Inhalation > 6.82 mg/l	

		LD50 Skin Rat > 2000 mg/kg	
	c) serious eye damage/irritation	Eye Corrosive Negative	
		Eye Irritant No	
	d) respiratory or skin sensitisation	Skin Sensitization Negative	
	i) STOT-repeated exposure	No Observed Adverse Effect Level 1000	
Cashew, nutshell liq.	a) acute toxicity	LD50 Oral Rat = 2000 mg/kg LD50 Skin Rat > 2000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
xylene	a) acute toxicity	LD50 Oral Rat = 3523 ml/Kg LC50 Inhalation Vapour Rat = 29000 mg/m3 4h LD50 Skin Rabbit = 12126 mg/kg 24h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Negative 4h	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes 1h	
	f) carcinogenicity	Genotoxicity Negative	Mouse subcutaneous route
	g) reproductive toxicity	No Observed Adverse Effect Level Inhalation Rat = 2171 mg/kg	
ethyl acrylate	a) acute toxicity	LD50 Oral Rat = 1120 ml/Kg LC50 Inhalation Vapour Rat < 9.13 mg/l 4h LD50 Skin Rat = 3049 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes 72h	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	f) carcinogenicity	Genotoxicity Negative	Mouse intraperitoneal route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 110 mg/kg	
methanol	a) acute toxicity	LD50 Oral Rat >= 2528 mg/kg LC50 Inhalation = 43.68 mg/l 6h LD50 Skin Rabbit = 17100 mg/kg	Cat
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative	
	c) serious eye damage/irritation	Eye Irritant Rabbit No	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Negative	
	f) carcinogenicity	Genotoxicity Negative Carcinogenicity Rat Negative	Mouse intraperitoneal route
	g) reproductive toxicity	Lowest Observed Adverse Effect Level Oral = 1000 mg/kg	Mouse

11.2. Information on other hazards

Endocrine disrupting properties:

SECTION 12: Ecological information**12.1. Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Toxic to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 2(H411)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS: 1675-54-3 - EINECS: 216-823-5 - INDEX: 603-073-00-2	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 2 mg/L 96h a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 1.8 mg/L 48h a) Aquatic acute toxicity : EC50 Algae Scenedesmus capricornutum = 11 mg/L 72h EPA-660/3-75-009 c) Bacteria toxicity : EC50 Sludge activated sludge = 100 mg/L 3h
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	CAS: 3101-60-8 - EINECS: 221-453-2	a) Aquatic acute toxicity : LC50 Fish rainbow trout = 7.5 mg/L „OECD Guideline 203 (Fish, Acute Toxicity Test) a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 67.9 mg/L 48h OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 9 mg/L 72h „OECD Guideline 201 (Alga, Growth Inhibition Test) a) Aquatic acute toxicity : EC50 Sludge activated sludge > 1000 mg/L 3h „OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Titanium dioxide	CAS: 13463-67-7 - EINECS: 236-675-5	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas (Cavedano americano) > 1000 mg/L 96h a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata (alghe cloroficee) > 100 mg/L 72h a) Aquatic acute toxicity : NOEC Algae = 5600 mg/L a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna (Pulce d'acqua grande) > 100 mg/L 48h
Cashew, nutshell liq.	CAS: 8007-24-7 - EINECS: 232-355-4	a) Aquatic acute toxicity : LC50 Fish Cyprinodon variegatus = 1000 mg/L 96h „OECD Guideline 203 (Fish, Acute Toxicity Test) a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 40.46 mg/L 48h „EPA OPPTS 850.1010 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 1300 mg/L 72h „OECD Guideline 201 (Alga, Growth Inhibition Test) a) Aquatic acute toxicity : NOEC Sludge activated sludge = 100 mg/L
xylene	CAS: 1330-20-7 - EINECS: 215-535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : LC50 Fish freshwater fish = 2.6 mg/L 96h OECD 203 b) Aquatic chronic toxicity : NOEC Fish freshwater fish = 1.3 mg/L - 56days a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 1 mg/L 24h OECD 202 b) Aquatic chronic toxicity : NOEC Daphnia Ceriodaphnia dubia = 0.96 mg/L - 7days a) Aquatic acute toxicity : EC50 Algae freshwater algae = 1.3 mg/L 48h OECD 201 a) Aquatic acute toxicity : EC50 microorganisms = 96 mg/L OECD 301F

ethyl acrylate	CAS: 140-88-5 - EINECS: 205- 438-8 - INDEX: 607-032-00-X	d) Terrestrial toxicity : NOEC Worm earthworms = 16 mg/kg - 14days
		e) Plant toxicity : LC50 terrestrial plants = 1 mg/kg - 14days
methanol	CAS: 67-56-1 - EINECS: 200- 659-6 - INDEX: 603-001-00-X	a) Aquatic acute toxicity : LC50 Fish Salmo gairdneri = 4.6 mg/L 96h EPA OTS 797.1400
		a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 7.9 mg/L 48h EPA OTS 797.1300
		b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 0.19 mg/L EPA OTS 797.1330
		a) Aquatic acute toxicity : EC50 Algae Selenastrum capricornutum = 4.5 mg/L 72h OECD TG 201
		a) Aquatic acute toxicity : NOEC Sludge activated sludge = 100 mg/L
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 15400 mg/L 96h
		b) Aquatic chronic toxicity : NOEC Fish = 450 mg/L
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 22200 mg/L 48h
		b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 208 mg/L
		a) Aquatic acute toxicity : EC50 Algae Selenastrum capricornutum = 22000 mg/L 96h OECD 201 Guideline.
		d) Terrestrial toxicity : NOEC Worm Eisenia andrei = 10000 mg/kg
		d) Terrestrial toxicity : NOEC Folsomia candida = 1000 mg/kg OECD Guideline 232

12.2. Persistence and degradability

Component	Persistence/Degradability:	Test	Value	Notes:
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Non-readily biodegradable	Oxygen consumption		OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	Non-readily biodegradable	Oxygen consumption		28days
Cashew, nutshell liq.	Readily biodegradable	Oxygen consumption	83.800	%; EU Method C.4-D
xylene	Readily biodegradable			
ethyl acrylate	Readily biodegradable	Biochemical oxygen demand	100.000	
methanol	Readily biodegradable			

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value	Notes:
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Bioaccumulative	BCF - Bioconcentration factor	31.000	
xylene	Bioaccumulative	BCF - Bioconcentration factor	25.900	
ethyl acrylate	Bioaccumulative	BCF - Bioconcentration factor	2.000	
methanol	Not bioaccumulative	BCF - Bioconcentration factor	< 10	

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration $\geq 0.1\%$

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Recover if possible. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as hazardous waste

SECTION 14: Transport information**14.1. UN number or ID number**

3077

14.2. UN proper shipping name

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane - p-tert-butylphenyl 1-(2,3-epoxy)propyl ether)

IATA-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane - p-tert-butylphenyl 1-(2,3-epoxy)propyl ether)

IMDG-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane - p-tert-butylphenyl 1-(2,3-epoxy)propyl ether)

14.3. Transport hazard class(es)

ADR-Class: 9

IATA-Class: 9

IMDG-Class: 9

14.4. Packing group

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

14.5. Environmental hazards

Most important toxic component: bis-[4-(2,3-epoxipropoxi)phenyl]propane

Marine pollutant: Yes

Environmental Pollutant: Yes

IMDG-EMS: F-A, S-F

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 9

ADR - Hazard identification number: 90

ADR-Special Provisions: 274 335 375 601

ADR-Transport category (Tunnel restriction code): 3 (-)

ADR Limited Quantities: 5 kg

ADR Excepted Quantities: E1

Air (IATA):

IATA-Passenger Aircraft: 956

IATA-Cargo Aircraft: 956

IATA-Label: 9

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisions: A97 A158 A179 A197 A215

Sea (IMDG):

IMDG-Stowage and handling: Category A SW23

IMDG-Segregation: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 274 335 966 967 969

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)
Regulation (EU) n. 2021/849 (ATP 17 CLP)
Regulation (EU) n. 2022/692 (ATP 18 CLP)
Regulation (EU) n. 2023/707
Regulation (EU) n. 2023/1434 (ATP 19 CLP)
Regulation (EU) n. 2023/1435 (ATP 20 CLP)
Regulation (EU) n. 2024/197 (ATP 21 CLP)
Regulation (EU) n. 2020/878
Regulation (EC) nr 648/2004 (Detergents).
Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
Restrictions related to the product: None.
Restrictions related to the substances contained: 40, 69, 75
Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
Product belongs to category: E2	200	500

Explosives precursors – Regulation 2019/1148

No substances listed
Regulation (EU) No 649/2012 (PIC regulation)
No substances listed

German Water Hazard Class.
3: Severe hazard to waters
German Lagerklasse according to TRGS 510:
LGK 11

SVHC Substances:
No SVHC substances present in concentration >= 0.1%

15.2. Chemical safety assessment
No Chemical Safety Assessment has been carried out for the mixture.
Substances for which a Chemical Safety Assessment has been carried out:
bis-[4-(2,3-epoxipropoxy)phenyl]propane
Cashew, nutshell liq.

SECTION 16: Other information

Code	Description
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/3/Dermal	Acute Tox. 3	Acute toxicity (dermal), Category 3
3.1/3/Inhal	Acute Tox. 3	Acute toxicity (inhalation), Category 3
3.1/3/Oral	Acute Tox. 3	Acute toxicity (oral), Category 3
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.8/1	STOT SE 1	Specific target organ toxicity — single exposure, Category 1
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1
3.9/2	STOT RE 2	Specific target organ toxicity — repeated exposure, Category 2
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
---	--------------------------

Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1A, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index
 BOD: Biochemical Oxygen Demand
 CAS: Chemical Abstracts Service (division of the American Chemical Society).
 CAV: Poison Center
 CE: European Community
 CLP: Classification, Labeling, Packaging.
 CMR: Carcinogenic, Mutagenic and Reprotoxic
 COD: Chemical Oxygen Demand
 COV: Volatile Organic Compound
 CSA: Chemical Safety Assessment
 CSR: Chemical Safety Report
 DMEL: Derived Minimal Effect Level
 DNEL: Derived No Effect Level.
 DPD: Dangerous Preparations Directive
 DSD: Dangerous Substances Directive
 EC50: Half Maximal Effective Concentration
 ECHA: European Chemicals Agency
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 ES: Exposure Scenario
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 IC50: half maximal inhibitory concentration
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 IMDG: International Maritime Code for Dangerous Goods.
 INCI: International Nomenclature of Cosmetic Ingredients.
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care
 KAFH: Keep Away From Heat
 KSt: Explosion coefficient.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 LDLo: Leathal Dose Low
 N.A.: Not Applicable
 N/A: Not Applicable
 N/D: Not defined/ Not available
 NA: Not available
 NIOSH: National Institute for Occupational Safety and Health
 NOAEL: No Observed Adverse Effect Level
 OSHA: Occupational Safety and Health Administration
 PBT: Persistent, Bioaccumulative and Toxic
 PGK: Packaging Instruction
 PNEC: Predicted No Effect Concentration.
 PSG: Passengers
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 vPvB: Very Persistent, Very Bioaccumulative.
 WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information

- SECTION 13: Disposal considerations
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Exposure Scenario

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Exposure Scenario, 07/06/2021

Substance identity	
	bis-[4-(2,3-epoxipropoxy)phenyl]propane
CAS No.	1675-54-3
INDEX No.	603-073-00-2
EINECS No.	216-823-5
Registration number	01-2119456619-26

Table of contents

1. **ES 1** Widespread use by professional workers; ESC2_0000001

1. ES 1 Widespread use by professional workers; ESC2_0000001	
1.1 TITLE SECTION	
Exposure Scenario name	Professional application of coatings and inks - Etching agent - Resins (prepolymers) - Adhesion promotor
Date - Version	27/05/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	ESC2_0000001
Article Category(ies)	Other articles made of stone, plaster, cement, glass or ceramic (AC4g)
Environment Contributing Scenario	
CS1	ERC8c - ERC8f
Worker Contributing Scenario	
CS2 Material transfers	PROC8a
CS3 Rolling, Brushing	PROC10
CS4 Roller, spreader, flow application	PROC11
CS5 Mixing operations - Manual	PROC19
1.2 Conditions of use affecting exposure	
1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)	
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use (or from service life)</i>	
Amounts used: Daily amount per site = 175 kg/day	
Release type: Continuous release	
Emission days: 365 days per year	
<i>Technical and organisational conditions and measures</i>	
Control measures to prevent releases Provide onsite wastewater removal efficiency of ³ (%):	
<i>Conditions and measures related to sewage treatment plant</i>	
STP type: Municipal Sewage Treatment Plant	
STP effluent (m³/day): 2	
<i>Conditions and measures related to treatment of waste (including article waste)</i>	
Waste treatment Dispose of waste cans and containers according to local regulations.	
<i>Other conditions affecting environmental exposure</i>	

Local marine water dilution factor: 100
Local freshwater dilution factor: 10
Receiving surface water flow: 18000 m³/day
Covers indoor and outdoor use

1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories	Roller application or brushing (PROC10)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
---------------------------	----------------------------------

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Wear suitable face shield.

Wear an impervious suit.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)**Process Categories**

Manual activities involving hand contact (PROC19)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 1 hour per day.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source**1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)**

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	= 0.0022 mg/L	EUSES	= 0.00022
marine sediment	= 0.00127 mg/L	EUSES	= 0.0128
freshwater sediment	= 0.012 mg/L	EUSES	= 0.0369
marine water	= 2.34E-05 mg/L	EUSES	= 0.029
soil	= 0.00142 mg/kg dry weight	EUSES	= 0.00722

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 0.84 mg/m ³	ECETOC TRA worker v2.0	0.07
dermal, systemic, long-term	= 0.2742 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.03

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 5E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 2.743 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.33

1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 0.36 mg/m ³	ECETOC TRA worker v2.0	0.03
dermal, systemic, long-term	= 2.68 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.32


1.3. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 2E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 1.414 mg/kg bw/day	ECETOC TRA worker v3	< 0.42
combined routes, systemic, long-term	N/A	ECETOC TRA worker v3	= 0.42

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

Cashew, nutshell liq.

Exposure Scenario, 08/06/2021

Substance identity	
	Cashew, nutshell liq.
CAS No.	8007-24-7
EINECS No.	232-355-4
Registration number	01-2119502450-57

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9b, PC9a, PC1)

1. ES 1		Widespread use by professional workers; Various products (PC9b, PC9a, PC1)	
1.1 TITLE SECTION			
Exposure Scenario name	Dye - Professional application of coatings and inks by brush or roller - Use in rigid foams, coatings, adhesives and sealants		
Date - Version	21/05/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Fillers, putties, plasters, modelling clay (PC9b) - Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1)		
Article Category(ies)	Stone, plaster, cement, glass and ceramic articles: Large surface area articles (AC4a) - Other articles made of stone, plaster, cement, glass or ceramic (AC4g)		
Environment Contributing Scenario			
CS1	ERC8c - ERC8f		
Worker Contributing Scenario			
CS2 Mixing operations	PROC19		
CS3 Equipment cleaning and maintenance - (aqueous) - Material transfers	PROC8b		
CS4 Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous)	PROC10		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)			
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid			
Concentration of substance in product: Covers percentage substance in the product up to 1 %.			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Amounts used: < 50 t(onnes)/year < 167 kg/day			
Release type: Intermittent release			
Emission days: 365 days per year			
<i>Conditions and measures related to sewage treatment plant</i>			
STP type: Municipal Sewage Treatment Plant Water - minimum efficiency of: = 93.2 %			
<i>Conditions and measures related to treatment of waste (including article waste)</i>			
Waste treatment Residues which cannot be recycled are disposed off as chemical waste			
<i>Other conditions affecting environmental exposure</i>			
Local marine water dilution factor: 100 Local freshwater dilution factor: 10			

Receiving surface water flow: 18000 m ³ /day Covers indoor and outdoor use	
1.2. CS2: Worker Contributing Scenario: Mixing operations (PROC19)	
Process Categories	Manual activities involving hand contact (PROC19)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Concentration of substance in product: Covers percentage substance in the product up to 1 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Amounts used: < 50 t(tonnes)/year	
Duration: Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Ensure operatives are trained to minimise exposures. Avoid direct eye contact with product, also via contamination on hands.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374. Wear suitable coveralls to prevent exposure to the skin. Use eye protection according to EN 166. Wear a respirator conforming to EN140.	
<i>Other conditions affecting worker exposure</i>	
Covers indoor and outdoor use Professional use Temperature: Covers use at ambient temperatures.	
1.2. CS3: Worker Contributing Scenario: Equipment cleaning and maintenance - (aqueous) - Material transfers (PROC8b)	
Process Categories	Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP	
Concentration of substance in product: Covers percentage substance in the product up to 25 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
Frequency: Avoid using product more than = 4 h/event	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Ensure operatives are trained to minimise exposures. Avoid direct eye contact with product, also via contamination on hands.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374.	
<i>Other conditions affecting worker exposure</i>	

Indoor use

Professional use

Temperature: Covers use at ambient temperatures.

1.2. CS4: Worker Contributing Scenario: Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous) (PROC10)

Process Categories Roller application or brushing (PROC10)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Avoid using product more than = 4 h/event

Technical and organisational conditions and measures

Technical and organisational measures

Ensure operatives are trained to minimise exposures.

Provide extract ventilation to points where emissions occur.

Avoid direct eye contact with product, also via contamination on hands.

Use long handled brushes and rollers.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Covers use at ambient temperatures.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
N/A	N/A	N/A	< 1

1.3. CS2: Worker Contributing Scenario: Mixing operations (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative	N/A	ECETOC TRA worker v2.0	< 1
dermal	N/A	ECETOC TRA worker v2.0	< 1

1.3. CS3: Worker Contributing Scenario: Equipment cleaning and maintenance - (aqueous) - Material transfers (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 7.75 mg/m ³	ECETOC TRA worker v2.0	= 0.562

dermal, systemic, long-term	= 0.014 mg/m ³	ECETOC TRA worker v2.0	= 0.004
-----------------------------	---------------------------	------------------------	---------

1.3. CS4: Worker Contributing Scenario: Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous) (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, local, short-term	= 2.325 mg/m ³	ECETOC TRA worker v2.0	= 0.168
dermal, systemic, long-term	= 0.137 mg/m ³	ECETOC TRA worker v2.0	= 0.035

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.