

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

AQUASTOP NANOGUM (B)

Date of first edition: 3/7/2022

Safety Data Sheet dated 19/05/2025

version 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: AQUASTOP NANOGUM (B)

Trade code: S100B0009 60

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: hardener

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Ireland Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Members of the public Number (8 am-10 pm): +353 (0)1 809 2166

Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

Malta In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Acute Tox. 4 Harmful if swallowed.

Acute Tox. 4 Harmful if inhaled.

Skin Corr. 1B Causes severe skin burns and eye damage.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1A May cause an allergic skin reaction.

Aquatic Chronic 2 Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Danger

Hazard statements

H302+H332 Harmful if swallowed or if inhaled

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P260 Do not breathe vapours.
- P280 Wear protective gloves and eye protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER if you feel unwell.

Contains

Cashew, nutshell liq.
M-phenylenebis(methylamine)
Polyoxpropylenediamine
amines, polyethylenepoly-; HEPA

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: AQUASTOP NANOGUM (B)

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥ 20 -<50 %	M-phenylenebis(methylamine)	CAS:1477-55-0 EC:216-032-5	Acute Tox. 4, H302; Acute Tox. 4, H332; Aquatic Chronic 3, H412; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1B, H314, EUH071	01-2119480150-50
≥ 20 -<50 %	Cashew, nutshell liq.	CAS:8007-24-7 EC:700-991-6	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1A, H317	01-2119502450-57
≥ 20 -<50 %	Polyoxpropylenediamine	CAS:9046-10-0 EC:618-561-0	Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 3, H412	01-2119557899-12
≥ 5 -<10 %	amines, polyethylenepoly-; HEPA	CAS:68131-73-7 EC:268-626-9 Index:612-121-00-1	Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Acute Tox. 4, H312, M-Chronic:1	01-2119485823-28

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Remove contaminated clothing immediately and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Give nothing to eat or drink.

In case of Inhalation:

- If breathing is irregular or stopped, administer artificial respiration.
- In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.
Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Use appropriate respiratory protection.
See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:
None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
M-phenylenebis(methylamine) CAS: 1477-55-0	ACGIH		Short Term: Ceiling - 0.018 ppm Skin - Eye, skin, and GI irr
	NATIONAL	BELGIUM	Short Term: 0.1 mg/m3 D, M Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	IRELAND	Long Term: 0.1 mg/m3 Source: 2021 Code of Practice
	NATIONAL	AUSTRIA	Long Term: 0.1 mg/m3; Short Term: Ceiling - 0.1 mg/m3 Mow, MAK Source: GKV, BGBl. II Nr. 156/2021
	NATIONAL	DENMARK	Short Term: Ceiling - 0.1 mg/m3 - 0.02 ppm LH Source: BEK nr 2203 af 29/11/2021
	NATIONAL	FINLAND	Short Term: Ceiling - 0.1 mg/m3 kattoarvo, iho Source: HTP-ARVOT 2020
	NATIONAL	FRANCE	Short Term: 0.1 mg/m3 Source: INRS outil65
	NATIONAL	NORWAY	Short Term: Ceiling - 0.1 mg/m3 T Source: FOR-2021-06-28-2248
	SUVA	SWITZERLAND	Long Term: 0.1 mg/m3 R/H, S, TGI Peau Yeux / GIT Haut Auge Source: suva.ch/valeurs-limites

Predicted No Effect Concentration (PNEC) values

M-phenylenebis(methylamine) CAS: 1477-55-0	Exposure Route: Fresh Water; PNEC Limit: 94 µg/l
	Exposure Route: Intermittent releases (fresh water); PNEC Limit: 152 µg/l
	Exposure Route: Marine water; PNEC Limit: 9.4 µg/l
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l
	Exposure Route: Freshwater sediments; PNEC Limit: 430 µg/kg
	Exposure Route: Marine water sediments; PNEC Limit: 43 µg/kg
	Exposure Route: Soil; PNEC Limit: 45 µg/kg
Cashew, nutshell liq. CAS: 8007-24-7	Exposure Route: Fresh Water; PNEC Limit: 0.003 mg/l
	Exposure Route: Marine water sediments; PNEC Limit: 0.088 mg/kg
	Exposure Route: Freshwater sediments; PNEC Limit: 0.97 mg/kg
	Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.03 mg/l
	Exposure Route: Soil; PNEC Limit: 6.71 mg/kg
Polyoxpropylenediamine CAS: 9046-10-0	Exposure Route: Fresh Water; PNEC Limit: 15 µg/l
	Exposure Route: Intermittent releases (fresh water); PNEC Limit: 150 µg/l
	Exposure Route: Marine water; PNEC Limit: 14.2 µg/l
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 7.5 mg/l
	Exposure Route: Freshwater sediments; PNEC Limit: 132 µg/kg
	Exposure Route: Marine water sediments; PNEC Limit: 125 µg/kg

Exposure Route: Soil; PNEC Limit: 17.6 µg/kg
Exposure Route: Secondary poisoning; PNEC Limit: 6.93 mg/kg
Exposure Route: Fresh Water; PNEC Limit: 1.6 µg/l

amines,
polyethylenepoly-; HEPA
CAS: 68131-73-7

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 16 µg/l
Exposure Route: Marine water; PNEC Limit: 1.6 µg/l
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 3.19 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 0.14 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 0.14 mg/kg
Exposure Route: Soil; PNEC Limit: 10 mg/kg

Derived No Effect Level (DNEL) values

M-
phenylenebis
(methylamine)
CAS: 1477-55-0

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 1.2 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 200 µg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 330 µg/kg

Cashew, nutshell liq.
CAS: 8007-24-7

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects
Worker Professional: 0.5 mg/kg; Consumer: 0.25 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 0.88 mg/m³; Consumer: 0.2 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Long Term, local effects
Consumer: 0.25 mg/kg

Polyoxpropylenediamine
CAS: 9046-10-0

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 1.36 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 2.5 mg/kg

amines,
polyethylenepoly-; HEPA
CAS: 68131-73-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 1.59 mg/m³; Consumer: 0.46 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 8550 mg/m³; Consumer: 2542 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 0.65 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 32 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 0.91 mg/m³; Consumer: 0.4 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects
Worker Professional: 0.044 mg/cm²; Consumer: 0.68 mg/cm²

Exposure Route: Human Dermal; Exposure Frequency: Short Term (acute)
Consumer: 1.59 mg/cm²

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing.

Protection for hands:

Protection for hands:

Suitable materials for safety gloves; EN 374:

Nitrile rubber - NBR: thickness ≥0,35mm; breakthrough time ≥480min.

Respiratory protection:

Particle filter P2 .

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: Light yellow

Odour: Like: Amines

Odour threshold: N.A.

pH: Not Relevant

Kinematic viscosity: N.A.

Melting point/freezing point: N.A.

Boiling point or initial boiling point and boiling range: 247 °C (477 °F)

Flash point: 66 °C (151 °F)

Lower and upper explosion limit: N.A.

Relative vapour density: N.A.

Vapour pressure: N.A.

Density and/or relative density: 0.93 g/cm³

Solubility in water: Miscible

Solubility in oil: N.A.

Partition coefficient n-octanol/water (log value): N.A.

Auto-ignition temperature: 435.00 °C

Decomposition temperature: N.A.

Flammability: N.A.

Volatile Organic compounds - VOCs = 0 % ; 0 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	The product is classified: Acute Tox. 4(H302), Acute Tox. 4(H332)
b) skin corrosion/irritation	The product is classified: Skin Corr. 1B(H314)
c) serious eye damage/irritation	The product is classified: Eye Dam. 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met

h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

M-phenylenebis (methyamine)	a) acute toxicity	LD50 Oral Rat = 1001 mg/kg	
		LC50 Inhalation Mist Rat = 1.34 mg/l 4h	
		LD50 Skin Rat > 3100 mg/kg	
	b) skin corrosion/irritation	Skin Irritant Rat Positive 4h	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	f) carcinogenicity	Genotoxicity Negative	Mouse
	g) reproductive toxicity	No Observed Effect Level Oral Rat = 450 mg/kg	
Cashew, nutshell liq.	a) acute toxicity	LD50 Oral Rat = 2000 mg/kg	
		LD50 Skin Rat > 2000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
Polyoxpropylenediamine	a) acute toxicity	LD50 Oral Rat = 2885 mg/kg	
		LC50 Inhalation Vapour Rat > 0.74 mg/l 8h	
		LD50 Skin Rabbit = 2980 mg/kg 24h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive 4h	
	c) serious eye damage/irritation	Eye Corrosive Rabbit Positive	
	f) carcinogenicity	Genotoxicity Negative	Mouse oral route
	g) reproductive toxicity	No Observed Adverse Effect Level Skin Rat = 30 mg/kg	
amines, polyethylenepoly-; HEPA	a) acute toxicity	LD50 Oral Rat = 1716.2 mg/kg	
		LD50 Skin Rabbit = 1465.4 mg/kg 24h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Positive	
	f) carcinogenicity	Genotoxicity Negative	Mouse intraperitoneal route

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Toxic to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 2(H411)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
M-phenylenebis(methylamine)	CAS: 1477-55-0 - EINECS: 216-032-5	a) Aquatic acute toxicity : LC50 Fish <i>Oryzias latipes</i> = 87.6 mg/L 96h OECD 203 a) Aquatic acute toxicity : EC50 <i>Daphnia magna</i> = 15.2 mg/L 48h OECD 202 b) Aquatic chronic toxicity : NOEC <i>Daphnia magna</i> = 4.7 mg/L OECD 211 - 21days a) Aquatic acute toxicity : EC50 <i>Selenastrum capricornutum</i> = 32.1 mg/L 72h OECD 201 a) Aquatic acute toxicity : EC50 Sludge activated sludge > 1000 mg/L OECD 209
Cashew, nutshell liq.	CAS: 8007-24-7 - EINECS: 700-991-6	a) Aquatic acute toxicity : LC50 Fish <i>Cyprinodon variegatus</i> = 1000 mg/L 96h „OECD Guideline 203 (Fish, Acute Toxicity Test) a) Aquatic acute toxicity : LC50 <i>Daphnia magna</i> = 40.46 mg/L 48h „EPA OPPTS 850.1010 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) a) Aquatic acute toxicity : EC50 <i>Pseudokirchneriella subcapitata</i> = 1300 mg/L 72h „OECD Guideline 201 (Alga, Growth Inhibition Test) a) Aquatic acute toxicity : NOEC Sludge activated sludge = 100 mg/L
Polyoxpropylenediamine	CAS: 9046-10-0 - EINECS: 618-561-0	a) Aquatic acute toxicity : LC50 Fish <i>Oncorhynchus mykiss</i> > 15 mg/L 96h OECD Guideline 203 a) Aquatic acute toxicity : LC50 <i>Daphnia magna</i> = 80 mg/L 48h OECD Guideline 202 a) Aquatic acute toxicity : EC50 <i>Pseudokirchneriella subcapitata</i> = 15 mg/L 72h OECD Guideline 201 a) Aquatic acute toxicity : NOEC <i>Pseudokirchneriella subcapitata</i> = 1.4 mg/L 72h OECD Guideline 201 a) Aquatic acute toxicity : EC50 Sludge Activated Sludge = 750 mg/L 3h OECD Guideline 209 a) Aquatic acute toxicity : NOEC Sludge Activated Sludge = 310 mg/L 3h OECD Guideline 209
amines, polyethylenepoly-; HEPA	CAS: 68131-73-7 - EINECS: 268-626-9 - INDEX: 612-121-00-1	a) Aquatic acute toxicity : LC50 Fish <i>Poecilia reticulata</i> = 100 mg/L 96h EU Method C.1 (Acute Toxicity for Fish) a) Aquatic acute toxicity : EC50 <i>Daphnia magna</i> = 2.2 mg/L 48h EU Method C.2 (Acute Toxicity for Daphnia) a) Aquatic acute toxicity : EC50 <i>Selenastrum capricornutum</i> = 0.23 mg/L 72h OECD TG 201 c) Bacteria toxicity : EC50 nitrifying bacteria = 319.3 mg/L - 2h d) Terrestrial toxicity : NOEC Worm <i>Eisenia fetida</i> = 1000 mg/kg OECD Guideline 222 (Earthworm Reproduction Test (<i>Eisenia fetida</i> / <i>Eisenia andrei</i>)) - 56days

12.2. Persistence and degradability

Component	Persitence/Degradability:	Test	Value	Notes:
M-phenylenebis(methylamine)	Non-readily biodegradable	Oxygen consumption		OECD 301B
Cashew, nutshell liq.	Readily biodegradable	Oxygen consumption	83.800	%; EU Method C.4-D
Polyoxpropylenediamine	Non-readily biodegradable	CO2 production	9.800	%; OECD Guideline 301B

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Notes:
M-phenylenebis(methylamine)	Not bioaccumulative	BCF - Bioconcentration factor	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessmentNo PBT or vPvB substances present in concentration $\geq 0.1\%$ **12.6. Endocrine disrupting properties**No endocrine disruptor substances present in concentration $\geq 0.1\%$ **12.7. Other adverse effects**

N.A.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as hazardous waste

SECTION 14: Transport information**14.1. UN number or ID number**

2735

14.2. UN proper shipping name

ADR-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (M-phenylenebis(methylamine) - Polyoxpropylenediamine)

IATA-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (M-phenylenebis(methylamine) - Polyoxpropylenediamine)

IMDG-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (M-phenylenebis(methylamine) - Polyoxpropylenediamine)

14.3. Transport hazard class(es)

ADR-Class: 8

IATA-Class: 8

IMDG-Class: 8

14.4. Packing group

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

14.5. Environmental hazards

Most important toxic component: amines, polyethylenepoly-; HEPA

Marine pollutant: Yes

Environmental Pollutant: Yes

IMDG-EMS: F-A, S-B

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 8

ADR - Hazard identification number: 80

ADR-Special Provisions: 274

ADR-Transport category (Tunnel restriction code): 3 (E)

ADR Limited Quantities: 5 L

ADR Excepted Quantities: E1

Air (IATA):

IATA-Passenger Aircraft: 852

IATA-Cargo Aircraft: 856

IATA-Label: 8

IATA-Subsidiary hazards: -

IATA-Erg: 8L

IATA-Special Provisions: A3 A803

Sea (IMDG):

IMDG-Stowage and handling: Category A

IMDG-Segregation: SG35 SGG18

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 223 274

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2023/707

Regulation (EU) n. 2023/1434 (ATP 19 CLP)

Regulation (EU) n. 2023/1435 (ATP 20 CLP)

Regulation (EU) n. 2024/197 (ATP 21 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
--	-------------------------------	-------------------------------

Product belongs to category: E2	200	500
---------------------------------	-----	-----

Explosives precursors – Regulation 2019/1148

No substances listed

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

3: Severe hazard to waters

German Lagerklasse according to TRGS 510:

LGK 8A

SVHC Substances:

No SVHC substances present in concentration $\geq 0.1\%$

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

Cashew, nutshell liq.

Polyoxpropylenediamine

amines, polyethylenepoly-; HEPA

SECTION 16: Other information

Code	Description
EUH071	Corrosive to the respiratory tract.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/1C	Skin Corr. 1C	Skin corrosion, Category 1C
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
---	--------------------------

Acute Tox. 4, H302	Calculation method
Acute Tox. 4, H332	Calculation method
Skin Corr. 1B, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1A, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community
 CLP: Classification, Labeling, Packaging.
 CMR: Carcinogenic, Mutagenic and Reprotoxic
 COD: Chemical Oxygen Demand
 COV: Volatile Organic Compound
 CSA: Chemical Safety Assessment
 CSR: Chemical Safety Report
 DMEL: Derived Minimal Effect Level
 DNEL: Derived No Effect Level.
 DPD: Dangerous Preparations Directive
 DSD: Dangerous Substances Directive
 EC50: Half Maximal Effective Concentration
 ECHA: European Chemicals Agency
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 ES: Exposure Scenario
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 IC50: half maximal inhibitory concentration
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 IMDG: International Maritime Code for Dangerous Goods.
 INCI: International Nomenclature of Cosmetic Ingredients.
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care
 KAFH: Keep Away From Heat
 KSt: Explosion coefficient.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 LDLo: Leathal Dose Low
 N.A.: Not Applicable
 N/A: Not Applicable
 N/D: Not defined/ Not available
 NA: Not available
 NIOSH: National Institute for Occupational Safety and Health
 NOAEL: No Observed Adverse Effect Level
 OSHA: Occupational Safety and Health Administration
 PBT: Persistent, Bioaccumulative and Toxic
 PGK: Packaging Instruction
 PNEC: Predicted No Effect Concentration.
 PSG: Passengers
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 vPvB: Very Persistent, Very Bioaccumulative.
 WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 4: First aid measures
- SECTION 6: Accidental release measures
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 13: Disposal considerations
- SECTION 14: Transport information

- SECTION 15: Regulatory information
- SECTION 16: Other information



Exposure Scenario

Amines, polyethylenepoly-; hepa

Exposure Scenario, 10/08/2021

Substance identity	
	Amines, polyethylenepoly-; hepa
CAS No.	68131-73-7
INDEX No.	612-121-00-1
EINECS No.	268-626-9
Registration number	01-2119485823-28

Table of contents

1. **ES 1** Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)
2. **ES 2** Widespread use by professional workers; Adhesives, sealants (PC1)

1. ES 1		Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)	
1.1 TITLE SECTION			
Exposure Scenario name	Professional application of coatings and inks		
Date - Version	10/08/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Coatings and paints, thinners, paint removers (PC9a)		
Environment Contributing Scenario			
CS1	ERC8c - ERC8f		
Worker Contributing Scenario			
CS2 Material transfers	PROC8a		
CS3 Rolling, Brushing	PROC10		
CS4 Roller, spreader, flow application	PROC11		
CS5 Handling and dilution of concentrates	PROC19		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)			
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP			
Concentration of substance in product: Covers concentrations up to 25 %			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Amounts used: Daily amount per site = 2114 kg/day			
Release type: Continuous release			
Emission days: 220 days per year			
<i>Other conditions affecting environmental exposure</i>			
Local freshwater dilution factor: 10			
1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)			
Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP			
Concentration of substance in product: Covers concentrations up to 25 %			
<i>Amount used, frequency and duration of use/exposure</i>			

Duration:

Covers use up to > 15 min

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable respiratory protection.
Wear suitable gloves tested to EN374.

Inhalation - minimum efficiency of: 95 %

1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)**Process Categories**

Roller application or brushing (PROC10)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 15 %

Amount used, frequency and duration of use/exposure**Duration:**

Covers use up to 60 min

Technical and organisational conditions and measures**Technical and organisational measures**

Provide extract ventilation to points where emissions occur.

Inhalation - minimum efficiency of: 90 %

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)**Process Categories**

Non industrial spraying (PROC11)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 15 %

Amount used, frequency and duration of use/exposure**Duration:**

Covers use up to 60 min

Technical and organisational conditions and measures**Technical and organisational measures**

Provide extract ventilation to points where emissions occur.

Inhalation - minimum efficiency of: 90 %

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

1.2. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Process Categories	Manual activities involving hand contact (PROC19)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP	
Concentration of substance in product: Covers concentrations up to 5 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers use up to 8 h	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374.	

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	7.92E-05 mg/L	EUSES	0.05
marine water	7.9E-06 mg/L	EUSES	0.005
freshwater sediment	0.0795 mg/kg dry weight	EUSES	0.568
marine sediment	0.00792 mg/kg dry weight	EUSES	0.057
soil	0.0118 mg/kg dry weight	EUSES	0.001

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.068 mg/kg bw/day	ECETOC TRA worker v2.0	0.12
inhalative, systemic, long-term	0.456 mg/m ³	ECETOC TRA worker v2.0	0.457
combined routes	N/A	N/A	0.577
inhalative, local, short-term	0.913 mg/m ³	ECETOC TRA worker v2.0	< 0.001

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.082 mg/kg bw/day	ECETOC TRA worker v2.0	0.144
inhalative, systemic, long-term	0.457 mg/m ³	ECETOC TRA worker v2.0	0.229
combined routes	N/A	N/A	0.373
inhalative, local, short-term	0.914 mg/m ³	ECETOC TRA worker v2.0	< 0.001

1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.214 mg/kg bw/day	ECETOC TRA worker v2.0	0.376
inhalative, systemic, long-term	0.121 mg/m ³	ECETOC TRA worker v2.0	0.122
combined routes	N/A	N/A	0.498
inhalative, local, short-term	0.243 mg/m ³	ECETOC TRA worker v2.0	< 0.001

1.3. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.14 mg/kg bw/day	ECETOC TRA worker v2.0	0.248
inhalative, systemic, long-term	0.76 mg/m ³	ECETOC TRA worker v2.0	0.076
combined routes	N/A	N/A	0.324
inhalative, local, short-term	1.52 mg/m ³	ECETOC TRA worker v2.0	< 0.001

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2

Widespread use by professional workers; Adhesives, sealants (PC1)

2.1 TITLE SECTION

Exposure Scenario name	Use in rigid foams, coatings, adhesives and sealants
Date - Version	10/08/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Adhesives, sealants (PC1)

Environment Contributing Scenario

CS1	ERC8a - ERC8d
-----	---------------

Worker Contributing Scenario

CS2 Material transfers	PROC8a
CS3 Rolling, Brushing	PROC10
CS4 Roller, spreader, flow application	PROC11
CS5 Handling and dilution of concentrates	PROC19

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	--

*Product (article) characteristics***Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 25 %

*Amount used, frequency and duration of use (or from service life)***Amounts used:**

Daily amount per site = 15500 kg/day

Release type: Continuous release**Emission days:** 300 days per year*Technical and organisational conditions and measures***Control measures to prevent releases**

Pre-treatment of waste water by neutralization	Water - minimum efficiency of: 53.1 %
--	---------------------------------------

*Conditions and measures related to sewage treatment plant***STP type:**

Municipal Sewage Treatment Plant

STP effluent (m³/day): 2000

Other conditions affecting environmental exposure

Local freshwater dilution factor: 1000

2.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 25 %

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to > 15 min

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable respiratory protection. Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 95 %
--	--------------------------------------

2.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories	Roller application or brushing (PROC10)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 15 %

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to 60 min

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 95 %
---------------------------------------	--------------------------------------

2.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
---------------------------	----------------------------------

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 15 %

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to 60 min

Technical and organisational conditions and measures

Technical and organisational measures

Provide extract ventilation to points where emissions occur.	Inhalation - minimum efficiency of: 90 %
--	--

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

2.2. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Process Categories	Manual activities involving hand contact (PROC19)
--------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 5 %

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to 8 h

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

2.3 Exposure estimation and reference to its source

2.3. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	6.74E-05 mg/L	Other measured data	0.042
marine water	6.7E-06 mg/L	Other measured data	0.004
freshwater sediment	0.0677 mg/kg dry weight	Other measured data	0.483
marine sediment	0.00674 mg/kg dry weight	Other measured data	0.048
soil	0.0118 mg/kg dry weight	Other measured data	0.001

2.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.068 mg/kg bw/day	ECETOC TRA worker v2.0	0.12
inhalative, systemic, long-term	0.456 mg/m ³	ECETOC TRA worker v2.0	0.457
combined routes	N/A	N/A	0.577
inhalative, local, short-term	0.913 mg/m ³	ECETOC TRA worker v2.0	< 0.001

2.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.082 mg/kg bw/day	ECETOC TRA worker v2.0	0.144
inhalative, systemic, long-term	0.457 mg/m ³	ECETOC TRA worker v2.0	0.229
combined routes	N/A	N/A	0.373
inhalative, local, short-term	0.914 mg/m ³	ECETOC TRA worker v2.0	< 0.001

2.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.214 mg/kg bw/day	ECETOC TRA worker v2.0	0.376
inhalative, systemic, long-term	0.121 mg/m ³	ECETOC TRA worker v2.0	0.122
combined routes	N/A	N/A	0.498
inhalative, local, short-term	0.243 mg/m ³	ECETOC TRA worker v2.0	< 0.001

2.3. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.14 mg/kg bw/day	ECETOC TRA worker v2.0	0.248
inhalative, systemic, long-term	0.76 mg/m ³	ECETOC TRA worker v2.0	0.076
combined routes	N/A	N/A	0.324
inhalative, local, short-term	1.52 mg/m ³	ECETOC TRA worker v2.0	< 0.001

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

Cashew, nutshell liq.

Exposure Scenario, 08/06/2021

Substance identity	
	Cashew, nutshell liq.
CAS No.	8007-24-7
EINECS No.	232-355-4
Registration number	01-2119502450-57

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9b, PC9a, PC1)

1. ES 1		Widespread use by professional workers; Various products (PC9b, PC9a, PC1)	
1.1 TITLE SECTION			
Exposure Scenario name	Dye - Professional application of coatings and inks by brush or roller - Use in rigid foams, coatings, adhesives and sealants		
Date - Version	21/05/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Fillers, putties, plasters, modelling clay (PC9b) - Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1)		
Article Category(ies)	Stone, plaster, cement, glass and ceramic articles: Large surface area articles (AC4a) - Other articles made of stone, plaster, cement, glass or ceramic (AC4g)		
Environment Contributing Scenario			
CS1	ERC8c - ERC8f		
Worker Contributing Scenario			
CS2 Mixing operations	PROC19		
CS3 Equipment cleaning and maintenance - (aqueous) - Material transfers	PROC8b		
CS4 Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous)	PROC10		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)			
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid			
Concentration of substance in product: Covers percentage substance in the product up to 1 %.			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Amounts used: < 50 t(tonnes)/year < 167 kg/day			
Release type: Intermittent release			
Emission days: 365 days per year			
<i>Conditions and measures related to sewage treatment plant</i>			
STP type: Municipal Sewage Treatment Plant Water - minimum efficiency of: = 93.2 %			
<i>Conditions and measures related to treatment of waste (including article waste)</i>			
Waste treatment Residues which cannot be recycled are disposed off as chemical waste			
<i>Other conditions affecting environmental exposure</i>			
Local marine water dilution factor: 100 Local freshwater dilution factor: 10			

Receiving surface water flow: 18000 m ³ /day Covers indoor and outdoor use	
1.2. CS2: Worker Contributing Scenario: Mixing operations (PROC19)	
Process Categories	Manual activities involving hand contact (PROC19)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Concentration of substance in product: Covers percentage substance in the product up to 1 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Amounts used: < 50 t(tonnes)/year	
Duration: Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Ensure operatives are trained to minimise exposures. Avoid direct eye contact with product, also via contamination on hands.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374. Wear suitable coveralls to prevent exposure to the skin. Use eye protection according to EN 166. Wear a respirator conforming to EN140.	
<i>Other conditions affecting worker exposure</i>	
Covers indoor and outdoor use Professional use Temperature: Covers use at ambient temperatures.	
1.2. CS3: Worker Contributing Scenario: Equipment cleaning and maintenance - (aqueous) - Material transfers (PROC8b)	
Process Categories	Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP	
Concentration of substance in product: Covers percentage substance in the product up to 25 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
Frequency: Avoid using product more than = 4 h/event	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Ensure operatives are trained to minimise exposures. Avoid direct eye contact with product, also via contamination on hands.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374.	
<i>Other conditions affecting worker exposure</i>	

Indoor use

Professional use

Temperature: Covers use at ambient temperatures.

1.2. CS4: Worker Contributing Scenario: Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous) (PROC10)

Process Categories Roller application or brushing (PROC10)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Avoid using product more than = 4 h/event

Technical and organisational conditions and measures

Technical and organisational measures

Ensure operatives are trained to minimise exposures.

Provide extract ventilation to points where emissions occur.

Avoid direct eye contact with product, also via contamination on hands.

Use long handled brushes and rollers.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Covers use at ambient temperatures.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
N/A	N/A	N/A	< 1

1.3. CS2: Worker Contributing Scenario: Mixing operations (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative	N/A	ECETOC TRA worker v2.0	< 1
dermal	N/A	ECETOC TRA worker v2.0	< 1

1.3. CS3: Worker Contributing Scenario: Equipment cleaning and maintenance - (aqueous) - Material transfers (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 7.75 mg/m ³	ECETOC TRA worker v2.0	= 0.562

dermal, systemic, long-term	= 0.014 mg/m ³	ECETOC TRA worker v2.0	= 0.004
-----------------------------	---------------------------	------------------------	---------

1.3. CS4: Worker Contributing Scenario: Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous) (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, local, short-term	= 2.325 mg/m ³	ECETOC TRA worker v2.0	= 0.168
dermal, systemic, long-term	= 0.137 mg/m ³	ECETOC TRA worker v2.0	= 0.035

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

Polyoxpropylenediamine

Exposure Scenario, 17/06/2021

Substance identity	
	Polyoxpropylenediamine
CAS No.	9046-10-0
EINECS No.	618-561-0
Registration number	01-2119557899-12

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9b, PC32)

1. ES 1		Widespread use by professional workers; Various products (PC9b, PC32)	
1.1 TITLE SECTION			
Exposure Scenario name	Use in coatings - Use in rigid foams, coatings, adhesives and sealants - Waterproofing agent		
Date - Version	17/06/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Fillers, putties, plasters, modelling clay (PC9b) - Polymer preparations and compounds (PC32)		
Environment Contributing Scenario			
CS1	ERC8c		
Worker Contributing Scenario			
CS2 Rolling, Brushing	PROC10		
CS3 Mixing operations - Manual	PROC19		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8c)			
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) (ERC8c)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid			
Vapour pressure: = 90 Pa			
Concentration of substance in product: Covers percentage substance in the product up to 25 %.			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Emission days: 365 days per year			
<i>Technical and organisational conditions and measures</i>			
Control measures to prevent releases			
Municipal sewage treatment plant is assumed.		Water - minimum efficiency of: = 1.5 %	
<i>Conditions and measures related to sewage treatment plant</i>			
STP type: Municipal Sewage Treatment Plant			
STP effluent (m³/day): 2000			
<i>Other conditions affecting environmental exposure</i>			
Local marine water dilution factor: 100 Local freshwater dilution factor: 10 Receiving surface water flow: 18000 m³/day Indoor use			
1.2. CS2: Worker Contributing Scenario: Rolling, Brushing (PROC10)			

Process Categories	Roller application or brushing (PROC10)	
<i>Product (article) characteristics</i>		
Physical form of product: Liquid		
Vapour pressure: = 90 Pa		
Concentration of substance in product: Covers percentage substance in the product up to 25 %.		
<i>Amount used, frequency and duration of use/exposure</i>		
Duration: Covers use up to = 480 min		
Frequency: Covers use up to = 5 days per week		
<i>Technical and organisational conditions and measures</i>		
Technical and organisational measures Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed. Avoid direct eye contact with product, also via contamination on hands.		
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>		
Personal protection		
Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. Wear respiratory protection when its use is identified for certain contributing scenarios. Wear suitable respiratory protection. Wear suitable face shield.		Dermal - minimum efficiency of: = 90 %
<i>Other conditions affecting worker exposure</i>		
Indoor use Professional use Temperature: Assumes use at not more than 20 °C above ambient temperature.		
1.2. CS3: Worker Contributing Scenario: Mixing operations - Manual (PROC19)		
Process Categories	Manual activities involving hand contact (PROC19)	
<i>Product (article) characteristics</i>		
Physical form of product: Liquid		
Vapour pressure: = 90 Pa		
Concentration of substance in product: Covers percentage substance in the product up to 25 %.		
<i>Amount used, frequency and duration of use/exposure</i>		
Duration: Covers use up to = 240 min		
Frequency: Covers use up to = 5 days per week		
<i>Technical and organisational conditions and measures</i>		
Technical and organisational measures Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed. Avoid direct eye contact with product, also via contamination on hands.		
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>		

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.
Wear respiratory protection when its use is identified for certain contributing scenarios.
Wear suitable respiratory protection.
Wear suitable face shield.

Dermal - minimum efficiency of: = 95 %

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

1.3. CS2: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 0.6857 mg/kg bw/day	ECETOC TRA worker v3	= 0.274286

1.3. CS3: Worker Contributing Scenario: Mixing operations - Manual (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 1.7697 mg/kg bw/day	ECETOC TRA worker v3	= 0.707143

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

Polyoxpropylenediamine

Exposure Scenario, 17/06/2021

Substance identity	
	Polyoxpropylenediamine
CAS No.	9046-10-0
EINECS No.	618-561-0
Registration number	01-2119557899-12

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9b, PC32)

1. ES 1		Widespread use by professional workers; Various products (PC9b, PC32)	
1.1 TITLE SECTION			
Exposure Scenario name	Use in coatings - Use in rigid foams, coatings, adhesives and sealants - Waterproofing agent		
Date - Version	17/06/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Fillers, putties, plasters, modelling clay (PC9b) - Polymer preparations and compounds (PC32)		
Environment Contributing Scenario			
CS1	ERC8c		
Worker Contributing Scenario			
CS2 Rolling, Brushing	PROC10		
CS3 Mixing operations - Manual	PROC19		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8c)			
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) (ERC8c)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid			
Vapour pressure: = 90 Pa			
Concentration of substance in product: Covers percentage substance in the product up to 25 %.			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Emission days: 365 days per year			
<i>Technical and organisational conditions and measures</i>			
Control measures to prevent releases			
Municipal sewage treatment plant is assumed.		Water - minimum efficiency of: = 1.5 %	
<i>Conditions and measures related to sewage treatment plant</i>			
STP type: Municipal Sewage Treatment Plant			
STP effluent (m³/day): 2000			
<i>Other conditions affecting environmental exposure</i>			
Local marine water dilution factor: 100 Local freshwater dilution factor: 10 Receiving surface water flow: 18000 m³/day Indoor use			
1.2. CS2: Worker Contributing Scenario: Rolling, Brushing (PROC10)			

Process Categories	Roller application or brushing (PROC10)	
<i>Product (article) characteristics</i>		
Physical form of product: Liquid		
Vapour pressure: = 90 Pa		
Concentration of substance in product: Covers percentage substance in the product up to 25 %.		
<i>Amount used, frequency and duration of use/exposure</i>		
Duration: Covers use up to = 480 min		
Frequency: Covers use up to = 5 days per week		
<i>Technical and organisational conditions and measures</i>		
Technical and organisational measures Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed. Avoid direct eye contact with product, also via contamination on hands.		
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>		
Personal protection		
Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. Wear respiratory protection when its use is identified for certain contributing scenarios. Wear suitable respiratory protection. Wear suitable face shield.		Dermal - minimum efficiency of: = 90 %
<i>Other conditions affecting worker exposure</i>		
Indoor use Professional use Temperature: Assumes use at not more than 20 °C above ambient temperature.		
1.2. CS3: Worker Contributing Scenario: Mixing operations - Manual (PROC19)		
Process Categories	Manual activities involving hand contact (PROC19)	
<i>Product (article) characteristics</i>		
Physical form of product: Liquid		
Vapour pressure: = 90 Pa		
Concentration of substance in product: Covers percentage substance in the product up to 25 %.		
<i>Amount used, frequency and duration of use/exposure</i>		
Duration: Covers use up to = 240 min		
Frequency: Covers use up to = 5 days per week		
<i>Technical and organisational conditions and measures</i>		
Technical and organisational measures Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed. Avoid direct eye contact with product, also via contamination on hands.		
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>		

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.
Wear respiratory protection when its use is identified for certain contributing scenarios.
Wear suitable respiratory protection.
Wear suitable face shield.

Dermal - minimum efficiency of: = 95 %

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

1.3. CS2: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 0.6857 mg/kg bw/day	ECETOC TRA worker v3	= 0.274286

1.3. CS3: Worker Contributing Scenario: Mixing operations - Manual (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 1.7697 mg/kg bw/day	ECETOC TRA worker v3	= 0.707143

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.