

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

B3

Date of first edition: 1/4/2023

Safety Data Sheet dated 1/4/2023

version 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: B3

Trade code: K06628

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Adhesives, sealants

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Kerakoll Italy - +39-0536-816511

Ireland

Poison information centre: 01 809 2166 (Daily 8am-10pm)

In case of emergency call 999 or 112

Malta

In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

0 The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Special Provisions:

EUH208 Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: B3

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
2,5-4,9 %	propylene carbonate	CAS:108-32-7 EC:203-572-1 Index:607-194-00-1	Eye Irrit. 2, H319	01-2119537232-48
< 0,0015 %	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS:55965-84-9 Index:613-167-00-5	Acute Tox. 2, H330 Acute Tox. 2, H310 Acute Tox. 3, H301 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410, M-Chronic:100, M-Acute:100, EUH071 Specific Concentration Limits: C ≥ 0.6%: Skin Corr. 1C H314 0.06% ≤ C < 0.6%: Skin Irrit. 2 H315 C ≥ 0.6%: Eye Dam. 1 H318 0.06% ≤ C < 0.6%: Eye Irrit. 2 H319 C ≥ 0.0015%: Skin Sens. 1A H317	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

N.A.

4.3. Indication of any immediate medical attention and special treatment needed

N.A.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Notes
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	NATIONAL	AUSTRIA		0.050				
	NATIONAL	GERMANY		0.200		0.400		DFG; Long term and short term: inhalable fraction
	NATIONAL	SWITZERLAND		0.200		0.400		Inhalable fraction
	NATIONAL	KOREA, REPUBLIC OF		0.100				
	NATIONAL	NETHERLANDS		0.200				

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC Limit	Exposure Route	Exposure Frequency
propylene carbonate	108-32-7	900.000 µg/l	Freshwater	
		9.000 mg/l	Intermittent releases (freshwater)	
		90.000 µg/l	Marine water	
		900.000 µg/l	Intermittent releases (marine water)	
		7400.000 mg/l	Microorganisms in sewage treatments	
		810.000 µg/kg	Soil	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-	55965-84-9	3.390 µg/l	Freshwater	

methyl-2H-isothiazol-3-one (3:1)

3.390 µg/l	Intermittent releases (freshwater)
3.390 µg/l	Marine water
3.390 µg/l	Intermittent releases (marine water)
230.000 µg/l	Microorganisms in sewage treatments
27.000 µg/l	Freshwater sediments
27.000 µg/l	Marine water sediments
10.000 µg/l	Soil

Derived No Effect Level (DNEL) values

Component	CAS-No.	Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency
propylene carbonate	108-32-7		70.530 mg/m³	17.400 mg/m³	Human Inhalation	Long Term, systemic effects
			20.000 mg/m³	10.000 mg/m³	Human Inhalation	Long Term, local effects
			20.000 mg/kg	10.000 mg/kg	Human Dermal	Long Term, local effects
				10.000 mg/kg	Human Oral	Long Term, systemic effects
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9		20.000 µg/m³	20.000 µg/m³	Human Inhalation	Long Term, local effects
			40.000 µg/m³	20.000 µg/m³	Human Inhalation	Short Term, local effects
				90.000 µg/kg	Human Oral	Long Term, systemic effects
				110.000 µg/kg	Human Oral	Short Term, systemic effects

8.2. Exposure controls

- Eye protection:
- Not needed for normal use. Anyway, operate according good working practices.
- Protection for skin:
- No special precaution must be adopted for normal use.
- Protection for hands:
- Not needed for normal use.
- Respiratory protection:
- N.A.
- Thermal Hazards:
- N.A.
- Environmental exposure controls:
- N.A.
- Hygienic and Technical measures
- N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical State Liquid
- Color: White
- Odour: Light
- Odour threshold: N.A.
- pH: =3.00
- Kinematic viscosity: N.A.

Melting point / freezing point: 100 °C (212 °F) Notes @ 101.325 kPa
Initial boiling point and boiling range: 0 °C (32 °F) Notes @ 101.325 kPa
Flash point: Not Applicable
Upper/lower flammability or explosive limits: N.A.
Vapour density: N.A.
Vapour pressure: N.A.
Relative density: 1.09 g/cm³ (ISO 2811)
Solubility in water: N.A.
Solubility in oil: N.A.
Partition coefficient (n-octanol/water): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Flammability: N.A.
Volatile Organic compounds - VOCs = 4.9 % ; 53.41 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

Miscibility: N.A.

Conductivity: N.A.

Evaporation rate: N.A. No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified Based on available data, the classification criteria are not met
c) serious eye damage/irritation	Not classified Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	Not classified Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

propylene carbonate	a) acute toxicity	LD50 Oral Rat > 5000.00000 mg/kg LC50 Inhalation Vapour Rat Negative 8h LD50 Skin Rabbit >= 2000.00000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative 24h	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Negative	
	f) carcinogenicity	Genotoxicity Negative Carcinogenicity Negative	Mouse intraperitoneal route Mouse
	g) reproductive toxicity	No Observed Adverse Effect Level Oral = 10100.00000 mg/kg	Mouse
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	a) acute toxicity	LD50 Oral Rat = 69.00 mg/kg LD50 Skin Rabbit = 141.00 mg/kg LC50 Inhalation Rat = 0.33 mg/l 4h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive	
	c) serious eye damage/irritation	Eye Corrosive Rabbit Positive	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	
	f) carcinogenicity	Genotoxicity Negative Carcinogenicity Skin Negative	
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 22.70000 mg/kg	

11.2 Information on other hazards**Endocrine disrupting properties:**

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information**12.1. Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
propylene carbonate	CAS: 108-32-7 - EINECS: 203-572-1 - INDEX: 607-194-00-1	a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio > 1000.00000 mg/L 96h EU Method C1
		a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna > 1000.00000 mg/L 48h EU Method C2
		a) Aquatic acute toxicity : EC50 Algae freshwater algae > 900.00000 mg/L 72h OECD guideline 201
		c) Bacteria toxicity : NOEC Pseudomonas putida = 7400.00000 mg/L
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS: 55965-84-9 - INDEX: 613-167-00-5	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 0.19000 mg/L 96h EPA OPP 72-1 (Fish Acute Toxicity Test)

b) Aquatic chronic toxicity : NOEC Fish Danio rerio = 0.02000 mg/L „OECD Guideline 210 (Fish, Early-Life Stage Toxicity Test) - 35days

a) Aquatic acute toxicity : LC50 Daphnia magna = 0.16000 mg/L 48h EPA OPP 72-2 (Aquatic Invertebrate Acute Toxicity Test)

b) Aquatic chronic toxicity : NOEC Daphnia magna = 0.10000 mg/L EPA OPP 72-4 (Fish Early Life-Stage and Aquatic Invertebrate Life-Cycle Studies) - 21days

a) Aquatic acute toxicity : EC50 Algae Skeletonema costatum = 0.00 mg/L 96h „OECD Guideline 201 (Alga, Growth Inhibition Test)

a) Aquatic acute toxicity : EC50 Sludge activated sludge = 4.50000 mg/L 3h „OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

d) Terrestrial toxicity : LC50 Worm Eisenia fetida = 613.00000 mg/kg „OECD Guideline 207 (Earthworm, Acute Toxicity Tests) - 14days

e) Plant toxicity : NOEC Trifolium pratense, Oryza sativa, Brassica napus = 1000.00000 mg/L OECD Guideline 208 (Terrestrial Plants Test: Seedling Emergence and Seedling Growth Test) - 21days

12.2. Persistence and degradability

Component	Persistence/Degradability:	Test	Notes
propylene carbonate	Readily biodegradable	CO2 production	OECD guideline 301 B
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Non-readily biodegradable		

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value	Notes
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Bioaccumulative	BCF - Bioconcentration factor	54.000	≤ 54

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7 Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

A waste code according to European waste catalogue (EWC) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

N.A.

SECTION 14: Transport information

14.1. UN number or ID number

N/A

14.2. UN proper shipping name

ADR-Shipping Name: N/A

IATA-Technical name: N/A

IMDG-Technical name: N/A

14.3. Transport hazard class(es)

ADR-Class: N/A

IATA-Class: N/A

IMDG-Class: N/A

14.4. Packing group

ADR-Packing Group: N/A

IATA-Packing group: N/A

IMDG-Packing group: N/A

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: N/A

14.6. Special precautions for user

Road and Rail (ADR-RID) :

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code): N/A

ADR Limited Quantities: N/A

ADR Excepted Quantities: N/A

Air (IATA) :

IATA-Passenger Aircraft: N/A

IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A

IATA-Erg: N/A

IATA-Special Provisioning: N/A

Sea (IMDG) :

IMDG-Stowage Code: N/A

IMDG-Stowage Note: N/A

IMDG-Subsidiary hazards: N/A

IMDG-Special Provisioning: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: None

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

Regulation (EU) 649/2012 (PIC regulation):

No Substance Listed

German Water Hazard Class.

NWG: Not hazardous for water

SVHC Substances:

No data available

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
H319	Causes serious eye irritation.

Code	Hazard class and hazard category	Description
3.3/2	Eye Irrit. 2	Eye irritation, Category 2

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).


IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: Keep Away From Heat

KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration.
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.



Exposure Scenario

Propylene carbonate

Exposure Scenario, 07/06/2021

Substance identity	
	Propylene carbonate
CAS No.	108-32-7
INDEX No.	607-194-00-1
EINECS No.	203-572-1
Registration number	01-2119537232-48

Table of contents

1. **ES 1** Widespread use by professional workers; Adhesives, sealants (PC1)

1. ES 1		Widespread use by professional workers; Adhesives, sealants (PC1)	
1.1 TITLE SECTION			
Exposure Scenario name	Use in rigid foams, coatings, adhesives and sealants		
Date - Version	07/06/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Adhesives, sealants (PC1)		
Environment Contributing Scenario			
CS1	ERC8a		
Worker Contributing Scenario			
CS2 Hand application - finger paints, pastels, adhesives	PROC19		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8a)			
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid, vapour pressure < 10 Pa (Standard Temperature and Pressure)			
Vapour pressure: = 6 Pa			
Concentration of substance in product: Covers percentage substance in the product up to 100 %.			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Amounts used: Application rate = 35000 kg/ha			
Release type: Continuous release			
Emission days: 365 days per year			
<i>Technical and organisational conditions and measures</i>			
Control measures to prevent releases			
		Air - minimum efficiency of: = 100 % Water - minimum efficiency of: = 100 %	
<i>Other conditions affecting environmental exposure</i>			
Local marine water dilution factor: 100 Local freshwater dilution factor: 10 Receiving surface water flow: 18000 m ³ /day Indoor use			
1.2. CS2: Worker Contributing Scenario: Hand application - finger paints, pastels, adhesives (PROC19)			

Process Categories	Manual activities involving hand contact (PROC19)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid, vapour pressure < 10 Pa (Standard Temperature and Pressure)			
Vapour pressure: = 6 Pa			
Concentration of substance in product: Covers percentage substance in the product up to 100 %.			
<i>Amount used, frequency and duration of use/exposure</i>			
Duration: Covers use up to = 480 min/day			
Frequency: Covers frequency up to: = 5 days per week			
<i>Technical and organisational conditions and measures</i>			
Technical and organisational measures			
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).		Inhalation - minimum efficiency of: = 70 %	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>			
Personal protection			
Wear suitable face shield. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.		Dermal - minimum efficiency of: = 80 %	
<i>Other conditions affecting worker exposure</i>			
Indoor use Professional use Temperature: Covers use at ambient temperatures. 20°C			
1.3 Exposure estimation and reference to its source			
1.3. CS1: Environment Contributing Scenario (ERC8a)			
protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
Man via environment - Oral	N/A	ECETOC TRA environment v3	= 0.000933
1.3. CS2: Worker Contributing Scenario: Hand application - finger paints, pastels, adhesives (PROC19)			
Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 5.4857 mg/kg bw/day	ECETOC TRA worker v3	= 0.274286
inhalative, systemic, long-term	= 23.7781 mg/m ³	ECETOC TRA worker v3	= 0.336992
1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES			
Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least			

equivalent levels.