Safety Data Sheet

Skladno z Uredbo ES št. 1907/2006 (REACH), Člen 31, Priloga II, kot spremenjeno z Uredbo Komisije (EU) št. 2020/878

BIOCALCE MURATURA FINO

Date of first edition: 12. 10. 2020

Safety Data Sheet dated 24/07/2026 version 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: BIOCALCE MURATURA FINO

Trade code: S100K0267 43

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Malte

Uses advised against: Uporabe, ki niso priporočene

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

112 v primeru zastrupitve v sil/ in case of emergency poisoning

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Eye Dam. 1 Causes serious eye damage.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Danger

Hazard statements

H318 Causes serious eye damage.

Precautionary statements

P102 Keep out of reach of children.

P280 Wear protective gloves and eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with applicable regulations.

Contains

naravno hidravlično apno (NHL)

Special provisions according to Annex XVII of REACH and subsequent amendments:

Nobena

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: Dolgotrajna izpostavljenost in/ali intenzivno vdihavanje vdihljivega prostega kristalnega kremena la ko povzroči pljučno fibrozo splono znano kot silikozo.

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: BIOCALCE MURATURA FINO

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥5-<10 %	naravno hidravlično apno (NHL)	CAS:85117-09-5 EC:285-561-1	Skin Irrit. 2, H315; Eye Dam. 1, H318; STOT SE 3, H335	
≥0.15-<0.20 %	Quarz (SIO2)	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372	
<0.036 %	Calcium dihydroxide	CAS:1305-62-0 EC:215-137-3	Skin Irrit. 2, H315; Eye Dam. 1, H318; STOT SE 3, H335	01-2119475151-45

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediatley and dispose off safely.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

Calcium Carbonate

CAS: 471-34-1	NATION Francija AL	Long Term: 10 mg/m3 Source: INRS outil65
	NATION Hrvaška AL	Long Term: 10 mg/m3 Notes: U Source: NN 1/2021
		Long Term: 4 mg/m3 Notes: R Source: NN 1/2021
	NATION Madžarska AL	Long Term: 10 mg/m3 Notes: inhalable aerosol Source: 5/2020. (II. 6.) ITM
	NATION Irska AL	Long Term: 10 mg/m3 Notes: Inhalable fraction Source: 2021 Code of Practice
		Long Term: 4 mg/m3 Notes: Respirable fraction Source: 2021 Code of Practice
	NATION Latvija AL	Long Term: 6 mg/m3 Source: KN325P1
	NATION Poljska AL	Long Term: 10 mg/m3 Notes: 4) Source: Dz.U. 2018 poz. 1286

	SUVA	Švicar	Long Term: 3 mg/m3 Notes: TWA mg/m3: (a), Formel / Formal, NIOSH Source: suva.ch/valeurs-limites
Quartz (SiO2)			
CAS: 14808-60-7	ACGIH		Long Term: 0.025 mg/m3 (8h) Notes: R, A2 - Pulm fibrosis, lung cancer
	NATIONAL	Belgija	Long Term: 0.1 mg/m3 Notes: C Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	Danska	Long Term: 0.3 mg/m3 Notes: alveolijae, liite 3 Source: BEK nr 2203 af 29/11/2021 Long Term: 0.1 mg/m3 Notes: EK Source: BEK nr 2203 af 29/11/2021
	NATIONAL	Španija	Long Term: 0.3 mg/m3 Notes: Respirable fraction Source: LEP 2022
	NATIONAL	Estonija	Long Term: 0.1 mg/m3 Notes: 1, C Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	Finska	Long Term: 0.05 mg/m3 Notes: alveolijae, liite 3 Source: HTP-ARVOT 2020
	NATIONAL	Francija	Long Term: 0.1 mg/m3 Notes: La VLEP s'applique à la fraction alvéolaire. Forme de silice cristalline. Source: INRS outil65, article R. 4412-149 du Code du travail
	NATIONAL	Madžarska	Long Term: 0.1 mg/m3 Source: 5/2020. (II. 6.) ITM rendelet
	NATIONAL	Irska	Long Term: 0.1 mg/m3 Notes: Respirable fraction Source: 2021 Code of Practice
	NATIONAL	Italija	Long Term: 0.1 mg/m3 Notes: Polvere di silice cristallina respirabile (frazione inalabile). Rif:D.Lgs 81/2008 Source: D.lgs. 81/2008, Allegato XLIII
	NATIONAL	Litva	Long Term: 0.1 mg/m3 Notes: Žiūrėti 1 priedo 3 punktą. Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
	NATIONAL	Nizozemska	Long Term: 0.075 mg/m3 Notes: (2) Source: Arbeidsomstandighedenregeling - Lijst B1
	NATIONAL	Norveška	Long Term: 0.3 mg/m3 Notes: K 7 Source: FOR-2021-06-28-2248 Long Term: 0.05 mg/m3 Notes: K G 7 21 Source: FOR-2021-06-28-2248
	NATIONAL	Poljska	Long Term: 0.1 mg/m3 Notes: 6) Source: Dz.U. 2018 poz. 1286
	NATIONAL	Švedska	Long Term: 0.1 mg/m3 Notes: C, M, 3 Source: AFS 2021:3
	SUVA	Švicar	Long Term: 0.15 mg/m3 Notes: TWA mg/m3: (a), C1A, SSC, P, Cancpulm Silicose / Lugenkrebs Silikose, HSE NIOSH OSHA Source: suva.ch/valeurs-limites
Calcium sulfate			
CAS: 7778-18-9	ACGIH		Long Term: 10 mg/m3 (8h) Notes: I - Nasal symptoms

NATION AL	Avstrija	Long Term: 5 mg/m3; Short Term: 10 mg/m3 Notes: 60(Miw), 2x, MAK, A Source: GKV, BGBl. II Nr. 156/2021
NATION AL	Belgija	Long Term: 10 mg/m3 Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATION AL	Nemčija	Long Term: 6 mg/m3 Notes: DFG, A Source: TRGS 900
NATION AL	Španija	Long Term: 10 mg/m3 Notes: e Source: LEP 2022
NATION AL	Grčija	Long Term: 10 mg/m3 Source: ΦΕΚ 94/Α` 13.5.1999
		Long Term: 5 mg/m3 Notes: αναπν. Source: ΦΕΚ 94/Α` 13.5.1999
		Long Term: 10 mg/m3 Notes: εισπν. Source: ΦΕΚ 94/Α` 13.5.1999
NATION AL	Madžarska	Long Term: 4 mg/m3 Notes: N Source: 5/2020. (II. 6.) ITM rendelet
		Long Term: 1.5 mg/m3 Notes: resp, N Source: 5/2020. (II. 6.) ITM rendelet
NATION AL	Irska	Long Term: 10 mg/m3 Source: 2021 Code of Practice
NATION AL	Latvija	Long Term: 4 mg/m3 Source: KN325P1
NATION AL	Poljska	Long Term: 10 mg/m3 Notes: 4), 7) Source: Dz.U. 2018 poz. 1286
NATION AL	Slovaška	Long Term: 4 mg/m3 Notes: 10) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
		Long Term: 1.5 mg/m3 Notes: 11) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
		Long Term: 4 mg/m3 Notes: 10) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
		Long Term: 1.5 mg/m3 Notes: 11) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATION AL	Slovenija	Long Term: 6 mg/m3 Notes: (A) Source: UL št. 72, 11. 5. 2021
SUVA	Švicar	Long Term: 3 mg/m3 Notes: TWA mg/m3: (a), SSC, Formel / Formal Source: suva.ch/valeurs-limites

Potassium sulfate

CAS: 7778-80-5	NATION AL Bolgarija	Long Term: 10 mg/m3 Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATION AL Litva	Long Term: 10 mg/m3 Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
	NATION AL Latvija	Long Term: 10 mg/m3 Source: KN325P1

Quarz (SIO2)

CAS: 14808-60-7	ACGIH	Long Term: 0.025 mg/m3 (8h) Notes: R, A2 - Pulm fibrosis, lung cancer
	EU	Long Term: 0.1 mg/m3 Notes: Polvere di silice cristallina respirabile, frazione inalabile. (R), A2 - Pulm fibrosis, lung cancer. Directive 2017/2398
	NATION Avstrija AL	Long Term: 0.05 mg/m3 Notes: MAK, III C, A Source: BGBl. II Nr. 156/2021
	NATION Belgija AL	Long Term: 0.1 mg/m3 Notes: C Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATION Danska AL	Long Term: 0.3 mg/m3 Source: BEK nr 2203 af 29/11/2021
		Long Term: 0.1 mg/m3 Notes: EK Source: BEK nr 2203 af 29/11/2021
	NATION Španija AL	Long Term: 0.05 mg/m3 (8h) Notes: Respirable fraction Source: LEP 2022
	NATION Estonija AL	Long Term: 0.1 mg/m3 Notes: 1, C Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATION Finska AL	Long Term: 0.05 mg/m3 Notes: alveolijae, liite 3 Source: HTP-ARVOT 2020
	NATION Francija AL	Long Term: 0.1 mg/m3 Notes: La VLEP s'applique à la fraction alvéolaire. Forme de silice cristalline. Source: INRS outil65, article R. 4412-149 du Code du travail
	NATION Hrvaška AL	Long Term: 0.1 mg/m3 Source: NN 1/2021
	NATION Madžarska AL	Long Term: 0.1 mg/m3 (8h) Notes: Respirable aerosol Source: 5/2020. (II. 6.) ITM rendelet
	NATION Irska AL	Long Term: 0.1 mg/m3 (8h) Notes: Respirable fraction Source: 2021 Code of Practice
	NATION Italija AL	Long Term: 0.1 mg/m3 (8h) Notes: Polvere di silice cristallina respirabile (frazione inalabile). D.Lgs 81/2008 Source: D.lgs. 81/2008, Allegato XLIII
	NATION Litva AL	Long Term: 0.1 mg/m3 Notes: Žiūrėti 1 priedo 3 punktą. Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
	NATION Nizozemska AL	Long Term: 0.075 mg/m3 Notes: (2) Source: Arbeidsomstandighedenregeling - Lijst B1
	NATION Norveška AL	Long Term: 0.3 mg/m3 Notes: K 7 Source: FOR-2021-06-28-2248
		Long Term: 0.05 mg/m3 Notes: K G 7 21 Source: FOR-2021-06-28-2248
	NATION Poljska AL	Long Term: 0.1 mg/m3 Notes: 6) Source: Dz.U. 2018 poz. 1286
	NATION Švedska AL	Long Term: 0.1 mg/m3 Notes: C, M, 3 Source: AFS 2021:3
	SUVA Švicar	Long Term: 0.15 mg/m3 Notes: TWA mg/m3: (a), C1A, SSC, P, Cancpulm Silicose / Lugenkrebs Silikose, HSE NIOSH OSHA Source: suva.ch/valeurs-limites

Limestone

CAS: 1317-65-3	NATION Belgija AL	Long Term: 10 mg/m3 Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATION Bolgarija AL	Long Term: 10 mg/m3 Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATION Švicar AL	Long Term: 3 mg/m3 Notes: (1) respirable aerosol Source: suva.ch/valeurs-limites
	NATION Španija AL	Long Term: 10 mg/m3 Notes: (1) inhalable aerosol Source: LEP 2022
	NATION Estonija AL	Long Term: 10 mg/m3 Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
		Long Term: 5 mg/m3 Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATION Grčija AL	Long Term: 10 mg/m3 Notes: εισπν. Source: ΦΕΚ 94/Α` 13.5.1999
		Long Term: 5 mg/m3 Notes: αναπν. Source: ΦΕΚ 94/Α` 13.5.1999
	NATION Madžarska AL	Long Term: 10 mg/m3 Notes: N Source: 5/2020. (II. 6.) ITM rendelet
	NATION Irska AL	Long Term: 10 mg/m3 Source: 2021 Code of Practice
		Long Term: 4 mg/m3 Source: 2021 Code of Practice

Calcium dihydroxide

CAS: 1305-62-0	ACGIH	Long Term: 5 mg/m3 (8h) Notes: Eye, URT and skin irr
	EU	Long Term: 1 mg/m3 (8h); Short Term: 4 mg/m3 Notes: Respirable fraction
	NATION Avstrija AL	Long Term: 1 mg/m3; Short Term: Ceiling - 4 mg/m3 Notes: 5(Mow), 8x, MAK, E Source: GKV, BGBl. II Nr. 156/2021
	NATION Belgija AL	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATION Bolgarija AL	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: 5 Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATION Ciper AL	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: 9 (2019) Source: Οι περί Ασφάλειας και Υγείας στην Εργασία (Χημικοί Παράγοντες) Κανονισμοί του 2001 έως 2021
	NATION Češka AL	Long Term: 1 mg/m3; Short Term: Ceiling - 4 mg/m3 Notes: I, R Source: Nařízení vlády č. 361-2007 Sb
	NATION Nemčija AL	Long Term: 1 mg/m3 Notes: Y, EU, DFG, E, 2 (I) Source: TRGS 900
	NATION Danska AL	Long Term: 5 mg/m3 Notes: E Source: BEK nr 2203 af 29/11/2021
		Long Term: 1 mg/m3 Notes: E Source: BEK nr 2203 af 29/11/2021

NATIONAL	Španija	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: VLI, d Source: LEP 2022
NATIONAL	Estonija	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: 1 Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	Finska	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Source: HTP-ARVOT 2020
NATIONAL	Francija	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Source: INRS outil65, article R. 4412-149 du Code du travail
NATIONAL	Grčija	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: 9) Source: Π.Δ. 82/2018 (ΦΕΚ 152/Α` 21.8.2018)
NATIONAL	Hrvaška	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: R (14) Source: 2017/164/EU
NATIONAL	Madžarska	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: resp, EU4, N Source: 5/2020. (II. 6.) ITM rendelet
NATIONAL	Irska	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: IOELV, R Source: 2021 Code of Practice
NATIONAL	Italija	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: Frazione respirabile Source: D.lgs. 81/2008, Allegato XXXVIII
NATIONAL	Litva	Long Term: 5 mg/m3 Notes: O Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	Luksemburg	Long Term: 5 mg/m3 Notes: 11, 14 Source: Mémorial A n.226 du 22 mars 2021 Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: 9, 14 Source: Mémorial A n.226 du 22 mars 2021
NATIONAL	Latvija	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Source: KN325P1
NATIONAL	Malta	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: 10 Source: S.L.424.24
NATIONAL	Nizozemska	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: (2) Source: Arbeidsomstandighedenregeling - Lijst A
NATIONAL	Norveška	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: E S Source: FOR-2021-06-28-2248
NATIONAL	Poljska	Long Term: 2 mg/m3; Short Term: 6 mg/m3 Notes: 4) Source: Dz.U. 2018 poz. 1286 Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: 6) Source: Dz.U. 2018 poz. 1286
NATIONAL	Portugalska	Long Term: 1 mg/m3 Notes: (9) Source: Decreto-Lei n.º 1/2021
NATIONAL	Romunija	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: Fracțiune respirabilă, Dir. 2017/164 Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATIONAL	Slovaška	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: 11)

			Source: 355 NARIADENIE VLÁDY z 10. mája 2006
	NATIONAL	Slovenija	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: Y, EU4, (A) Source: UL št. 72, 11. 5. 2021
	NATIONAL	Švedska	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: 3 Source: AFS 2021:3
	SUVA	Švicar	Long Term: 1 mg/m3; Short Term: 4 mg/m3 Notes: TWA mg/m3: (i), SSC, VRS / OAW, NIOSH Source: suva.ch/valeurs-limites

Starch

CAS: 9005-25-8	ACGIH		Long Term: 10 mg/m3 (8h) Notes: A4 - Dermatitis
	NATIONAL	Belgija	Long Term: 10 mg/m3 Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	Španija	Long Term: 10 mg/m3 Source: LEP 2022
	NATIONAL	Grčija	Long Term: 10 mg/m3 Notes: εισπν Source: ΦΕΚ 94/Α` 13.5.1999
			Long Term: 5 mg/m3 Notes: αναπν Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL	Irska	Long Term: 10 mg/m3 Source: 2021 Code of Practice
			Long Term: 4 mg/m3 Source: 2021 Code of Practice
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m3 Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
			Long Term: 4 mg/m3 Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	SUVA	Švicar	Long Term: 3 mg/m3 Notes: TWA mg/m3: (a) Source: suva.ch/valeurs-limites

Predicted No Effect Concentration (PNEC) values

naravno hidravlično apno (NHL)

CAS: 85117-09-5	Exposure Route: Fresh Water; PNEC Limit: 574 mg/m3
	Exposure Route: Intermittent releases (fresh water); PNEC Limit: 574 mg/m3
	Exposure Route: Marine water; PNEC Limit: 374 mg/m3
	Exposure Route: Intermittent releases (marine water); PNEC Limit: 374 mg/m3
	Exposure Route: Mikroorganizmi v čiščenju odplak; PNEC Limit: 3.511 mg/l
	Exposure Route: Zemlja; PNEC Limit: 1262 mg/kg

Calcium dihydroxide

CAS: 1305-62-0	Exposure Route: Fresh Water; PNEC Limit: 490 mg/m3
	Exposure Route: Intermittent releases (fresh water); PNEC Limit: 490 mg/m3
	Exposure Route: Marine water; PNEC Limit: 320 mg/m3
	Exposure Route: Mikroorganizmi v čiščenju odplak; PNEC Limit: 3 mg/l
	Exposure Route: Zemlja; PNEC Limit: 1080 mg/kg

Derived No Effect Level (DNEL) values

naravno hidravlično apno (NHL)

CAS: 85117-09-5	Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects Worker Professional: 1 mg/kg/day; Consumer: 1 mg/kg/day

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Professional: 4 mg/kg/day; Consumer: 4 mg/kg/day

Calcium dihydroxide

CAS: 1305-62-0 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 1 mg/kg/day; Consumer: 1 mg/kg/day

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Professional: 4 mg/kg/day; Consumer: 4 mg/kg/day

8.2. Exposure controls

Eye protection:

Očala s stransko zaščito.(EN166)

Protection for skin:

Kemična zaščitna oblačila. Zaščitna obutev

Protection for hands:

Zaščita rok:

Materiali primerni za začitne rokavice; EN 374:

Nitril kavčuk NBR: debeline ≥ 0,35 mm; čas preboja ≥ 480 min.

Respiratory protection:

N.A.

Thermal Hazards:

Ni predvideno, če se uporablja, kot je predvideno

Environmental exposure controls:

Ne dovolite, da izdelek pride v kanalizacijo ali v površinske ali podzemne vode.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Solid
Colour:	beige
Odour:	odourless
Odour threshold:	Not Relevant Notes: Podatek ni na voljo
pH:	=11.00 Method: OECD 122
Kinematic viscosity:	Not Relevant Notes: Ni določeno, ker ni potrebno za CLP-razvrstitev
Melting point/freezing point:	N.A.
Boiling point or initial boiling point and boiling range:	N.A.
Flash point:	Not applicable
Lower and upper explosion limit:	Not Relevant Notes: Se ne uporablja, ker zmes ni tekoča
Relative vapour density:	Not Relevant Notes: Se ne uporablja, ker zmes ni tekoča
Vapour pressure:	Not Relevant Notes: Se ne uporablja, ker zmes ni tekoča
Density and/or relative density:	1.30 g/cm3 Method: EN 1097-03
Solubility in water:	Topno
Solubility in oil:	Not Relevant Notes: Ni določeno, ker ni potrebno za CLP-razvrstitev
Partition coefficient n-octanol/water (log value):	Not Relevant

Notes: Ni uporabljivo za zmesi

Auto-ignition temperature: Not Relevant
Notes: Se ne uporablja, ker zmes ni tekoča

Decomposition temperature: Not Relevant
Notes: Ni uporabljivo, ker zmes ni samoreaktivna

Flammability: N.A.

Volatile Organic compounds - VOCs = 0.00%; 0.00g/L

Particle characteristics:
Particle size: N.A.

9.2. Other information

Explosive properties: Not Relevant
Notes: Ni uporabljivo, zmes ne vsebuje eksplozivnih skupin

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified
	Based on available data, the classification criteria are not met
c) serious eye damage/irritation	The product is classified: Eye Dam. 1(H318)
d) respiratory or skin sensitisation	Not classified
	Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

naravno hidravlično apno (NHL)

CAS: 85117-09-5 a) acute toxicity LD50 Oral Rat > 2000 mg/kg

		LC50 Inhalation Dust Rat > 6.04 mg/l 4h
		LD50 Skin Rabbit > 2500 mg/kg 24h
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive 4h
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes
	d) respiratory or skin sensitisation	Skin Sensitization Negative
	g) reproductive toxicity	No Observed Adverse Effect Level Oral >= 400 mg/kg
Quarz (SIO2)		
CAS: 14808-60-7	Generic information:	Informazione tossicologia a livello di sostanza
	a) acute toxicity	LD50 Oral > 2000 mg/kg
Calcium dihydroxide		
CAS: 1305-62-0	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg
		LC50 Inhalation Dust Rat > 6.04 mg/l 4h
		LD50 Skin Rabbit > 2500 mg/kg
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes
	d) respiratory or skin sensitisation	Skin Sensitization Negative
	f) carcinogenicity	Carcinogenicity Oral Rat = 517 mg/kg

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

naravno hidravlično apno (NHL)

CAS: 85117-09-5	a) Aquatic acute toxicity: LC50 Fish rainbow trout = 50.6 mg/L 96h
	a) Aquatic acute toxicity: LC50 Daphnia Daphnia magna = 49.1 mg/L 48h
	b) Aquatic chronic toxicity: NOEC Crangon septemspinosa = 32 mg/L
	d) Terrestrial toxicity: NOEC Worm Eisenia fetida = 2000 mg/kg
	e) Plant toxicity: EC10 = 1080 mg/kg

Calcium dihydroxide

CAS: 1305-62-0	a) Aquatic acute toxicity: LC50 Fish rainbow trout = 50.6 mg/L 96h
	a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 49.1 mg/L 48h
	b) Aquatic chronic toxicity: NOEC Crangon septemspinosa = 32 mg/L 48h
	a) Aquatic acute toxicity: EC50 Algae Pseudokirchneriella subcapitata = 184.57 mg/L 72h
	a) Aquatic acute toxicity: EC50 Sludge activated sludge = 300.4 mg/L 3h
	d) Terrestrial toxicity: NOEC Worm Eisenia fetida = 2000 mg/kg
	d) Terrestrial toxicity: EC10 soil microorganisms = 4000 mg/kg

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

Ni sestavine PBT/vPvB.

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Če je mogoče, predelajte. Pošljite v usposobljena odlagališča ali v zažig pod kontroliranimi pogoji. Ravnajte se po lokalnih in državnih normah. Odstranjevanje z izpustom v odpadne vode ni dovoljeno

Odstranjeni izdelek mora biti v skladu z Uredbo (EU) 1357/2014 razvrščen kot nevaren odpadek

Šifre odpadkov v skladu z Evropski seznam odpadkov (ESO) ni mogoče določiti zaradi odvisnosti od uporabe. Obrnite se na pooblaščeno službo za odstranjevanje odpadkov.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

N.A.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

N/A

14.2. UN proper shipping name

ADR-Shipping Name: N/A
IATA-Shipping Name: N/A
IMDG-Shipping Name: N/A

14.3. Transport hazard class(es)

ADR-Class: N/A
IATA-Class: N/A
IMDG-Class: N/A

14.4. Packing group

ADR-Packing Group: N/A
IATA-Packing group: N/A
IMDG-Packing group: N/A

14.5. Environmental hazards

Marine pollutant: No
Environmental Pollutant: No
IMDG-EMS: N/A

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: N/A
ADR - Hazard identification number: N/A
ADR-Special Provisions: N/A
ADR-Transport category (Tunnel restriction code): N/A
ADR Limited Quantities: N/A
ADR Excepted Quantities: N/A

Air (IATA):

IATA-Passenger Aircraft: N/A
IATA-Cargo Aircraft: N/A
IATA-Label: N/A
IATA-Subsidiary hazards: N/A
IATA-Erg: N/A
IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage and handling: N/A
IMDG-Segregation: N/A
IMDG-Subsidiary hazards: N/A
IMDG-Special Provisions: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)	Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 286/2011 (ATP 2 CLP)	Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)	Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)	Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)	Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)	Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)	Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)	Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)	Regulation (EU) n. 2021/849 (ATP 17 CLP)
Regulation (EU) n. 2022/692 (ATP 18 CLP)	Regulation (EU) n. 2023/707
Regulation (EU) n. 2023/1434 (ATP 19 CLP)	Regulation (EU) n. 2023/1435 (ATP 20 CLP)
Regulation (EU) n. 2024/197 (ATP 21 CLP)	Regulation (EU) n. 2024/2564 (ATP 22 CLP)
Regulation (EU) n. 2024/2865	Regulation (EU) n. 2025/1222 (ATP 23 CLP)

Regulation (EC) nr 648/2004 (Detergents).
Omejitve, povezane z izdelkom ali vsebovanimi snovmi, v skladu s Prilogo XVII Uredbe (ES) 1907/2006 (REACH) in poznejše spremembe:
Restrictions related to the product: Nobena
Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

None

Explosives precursors – Regulation 2019/1148

No substances listed

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.
Razred 3: izjemno nevarna.

German Lagerklasse according to TRGS 510:
LGK 11

SVHC Substances:
No SVHC substances present in concentration >= 0.1%

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

naravno hidravlično apno (NHL)

Calcium dihydroxide

SECTION 16: Other information

Code	Description
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.

Code	Hazard class and hazard category	Description
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Eye Dam. 1, H318	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: Keep Away From Heat

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration

PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- Safety Data Sheet
- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 4: First aid measures
- SECTION 6: Accidental release measures
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Scenarij izpostavljenosti
Calcium dihydroxide

Scenarij izpostavljenosti, 24/06/2021

Identiteta snovi	
	Calcium dihydroxide
št.CAS	1305-62-0
št.EINECS	215-137-3
Registracijska številka	01-2119475151-45

Kazalo

1. **ES 1** Široko razširjena uporaba, ki jo izvajajo poklicni delavci; Razni produkti (PC9a, PC9b, PC15)

1. ES 1 Široko razširjena uporaba, ki jo izvajajo poklicni delavci; Razni produkti (PC9a, PC9b, PC15)

1.1 NASLOVNI ODSTAVEK

Ime scenarija izpostavljenosti	Gospodarska uporaba premazov in barv - Uporaba za trde penaste mase, premaze, lepila in tesnila
Datum - revizija	24/06/2021 - 1.0
Stopnja življenjskega cikla	Široko razširjena uporaba, ki jo izvajajo poklicni delavci
Glavna uporabniška skupina	Poklicne uporabe
Sektor(-ji) uporabe	Poklicne uporabe (SU22)
Kategorije izdelkov	Premazi in barve, razredčila, sredstva za odstranjevanje barv (PC9a) - Polnila, kiti, mavci, modelirna glina (PC9b) - Izdelki za obdelavo nekovinskih površin (PC15)

Scenarij, ki prispeva Okolje

CS1	ERC8c - ERC8f

Scenarij, ki prispeva Delojemalec

CS2 Prenosi materiala	PROC8a
CS3 Ročna uporaba - Prstne barve, krede, lepila - Nanašanje z valjem in čopičem	PROC10
CS4 Dejavnosti mešanja - Ročno	PROC19

1.2 Pogoji uporabe z vplivom na izpostavitev

1.2. CS1: Scenarij, ki prispeva Okolje (ERC8c, ERC8f)

Kategorije sproščanja v okolje	Široko razširjena uporaba, rezultat katere je vključitev v ali na izdelek (notranja) - Široko razširjena uporaba, rezultat katere je vključitev v ali na izdelek (zunanja) (ERC8c, ERC8f)

Lastnosti izdelka (proizvoda)

Fizikalna oblika izdelka:

Trdna snov, srednje velika prašnost

Parni tlak:

< 1E-05 Pa

1.2. CS2: Scenarij, ki prispeva Delojemalec: Prenosi materiala (PROC8a)

Kategorije procesov	Prenos snovi ali zmesi (polnjenje in praznjenje) na nenamenskih napravah (PROC8a)

Lastnosti izdelka (proizvoda)

Fizikalna oblika izdelka:

Trdna snov, srednje velika prašnost

Uporabljena količina, pogostost in trajanje uporabe/izpostavljenost

Trajanje:

Trajanje izpostavljenosti <= 480 min

Tehnični in organizacijski pogoji in ukrepi

Tehnični in organizacijski ukrepi

Zagotovite, da so upravljavci usposobljeni za zmanjšanje izpostavljenosti na minimum. Preprečite neposreden stik z očmi, tudi z umazanimi rokami. Ne používati. Lokalno odsesavanje	Vdihavanje - najmanjša učinkovitost: 72 %

Pogoji in ukrepi glede na osebno zaščito, higieno in preverjanje zdravstvenega stanja

Osebna zaščitna oprema

Nosite primerne rokavice, preizkušene po EN374.
Uporabljajte primerno zaščito oči.
Uporabljajte ustrezno zaščito za obraz.

Drugi pogoji uporabe, ki vplivajo na izpostavljenost delojemalcev

Zajema notranjo in zunanjo uporabo
Gospodarska uporaba
Temperatura: Obsega uporabo pri temperaturi okolice.
Izpostavljeni deli telesa:
Predpostavlja se, da je morebiten stik s kožo omejen na zgornji del telesa.

Dodaten nasvet iz primerov dobre prakse. Obveznosti v skladu s 4. odstavkom 37. člena Uredbe REACH ne veljajo.

Dodaten nasvet iz primerov dobre prakse:
Zagotovite redno preverjanje in vzdrževanje nadzornih ukrepov. Odprta vrata in okna. Preprečite iztekanje in onesnaženje tal/vode zaradi iztekanja.

1.2. CS3: Scenarij, ki prispeva Delojemalec: Ročna uporaba - Prstne barve, krede, lepila - Nanašanje z valjem in čopičem (PROC10)

Kategorije procesov	Nanašanje z valjčkom ali čopičem (PROC10)

Lastnosti izdelka (proizvoda)

Fizikalna oblika izdelka:
Trdna snov, srednje velika prašnost

Uporabljena količina, pogostost in trajanje uporabe/izpostavljenost

Trajanje:
Trajanje izpostavljenosti <= 480 min

Tehnični in organizacijski pogoji in ukrepi

Tehnični in organizacijski ukrepi
Zagotovite, da so upravljavci usposobljeni za zmanjšanje izpostavljenosti na minimum.
Preprečite neposreden stik z očmi, tudi z umazanimi rokami.
Ne používati.

Pogoji in ukrepi glede na osebno zaščito, higieno in preverjanje zdravstvenega stanja

Osebna zaščitna oprema
Nosite primerne rokavice, preizkušene po EN374.
Uporabljajte primerno zaščito oči.
Uporabljajte ustrezno zaščito za obraz.

Drugi pogoji uporabe, ki vplivajo na izpostavljenost delojemalcev

Zajema notranjo in zunanjo uporabo
Gospodarska uporaba
Temperatura: Obsega uporabo pri temperaturi okolice.

Dodaten nasvet iz primerov dobre prakse. Obveznosti v skladu s 4. odstavkom 37. člena Uredbe REACH ne veljajo.

Dodaten nasvet iz primerov dobre prakse:
Zagotovite redno preverjanje in vzdrževanje nadzornih ukrepov. Preprečite iztekanje in onesnaženje tal/vode zaradi iztekanja.

1.2. CS4: Scenarij, ki prispeva Delojemalec: Dejavnosti mešanja - Ročno (PROC19)

Kategorije procesov	Ročne dejavnosti, ki vključujejo ročni stik (PROC19)

Lastnosti izdelka (proizvoda)

Fizikalna oblika izdelka:
Trdna snov, srednje velika prašnost

Uporabljena količina, pogostost in trajanje uporabe/izpostavljenost

Trajanje:
Trajanje izpostavljenosti <= 240 min

Tehnični in organizacijski pogoji in ukrepi

Tehnični in organizacijski ukrepi
Zagotovite, da so upravljavci usposobljeni za zmanjšanje izpostavljenosti na minimum.
Preprečite neposreden stik z očmi, tudi z umazanimi rokami.
Ne používati.

Lokalno odsesavanje
Zagotovite zadostno stopnjo splošnega prezračevanja (ne manj kot 3 do 5 izmenjav zraka na uro).

Pogoji in ukrepi glede na osebno zaščito, higieno in preverjanje zdravstvenega stanja

Osebna zaščitna oprema

Nosite primerne rokavice, preizkušene po EN374.
Uporabljajte primerno zaščito oči.
Uporabljajte ustrezno zaščito za obraz.

Drugi pogoji uporabe, ki vplivajo na izpostavljenost delojemalcev

Zunanja uporaba
Gospodarska uporaba
Temperatura: Obsega uporabo pri temperaturi okolice.
Izpostavljeni deli telesa:

Predpostavlja se, da je morebiten stik s kožo omejen na zgornji del telesa.

Dodaten nasvet iz primerov dobre prakse. Obveznosti v skladu s 4. odstavkom 37. člena Uredbe REACH ne veljajo.

Dodaten nasvet iz primerov dobre prakse:

Zagotovite redno preverjanje in vzdrževanje nadzornih ukrepov. Odprta vrata in okna. Preprečite iztekanje in onesnaženje tal/vode zaradi iztekanja.

1.3 Ocena izpostavljenosti in sklicevanje na njen vir

1.3. CS1: Scenarij, ki prispeva Okolje (ERC8c, ERC8f)

cilj zaščite	Stopnja izpostavljenosti	Metoda izračuna	Stopnja opredelitve tveganja (RCR)
tla	N/A	N/A	= 0.65

1.3. CS2: Scenarij, ki prispeva Delojemalec: Prenosi materiala (PROC8a)

Pot izpostavljenosti, Učinki na zdravje, Indikatorji izpostavljenosti	Stopnja izpostavljenosti	Metoda izračuna	Stopnja opredelitve tveganja (RCR)
inhalacijski	< 1 mg/m³	MEASE	N/A

1.3. CS3: Scenarij, ki prispeva Delojemalec: Ročna uporaba - Prstne barve, krede, lepila - Nanašanje z valjem in čopičem (PROC10)

Pot izpostavljenosti, Učinki na zdravje, Indikatorji izpostavljenosti	Stopnja izpostavljenosti	Metoda izračuna	Stopnja opredelitve tveganja (RCR)
inhalacijski	< 1 mg/m³	MEASE	N/A

Dodatne informacije glede ocene izpostavljenosti:

Če obstaja verjetnost večkratne ali daljše izpostavljenosti kože snovi, nosite primerne rokavice, skladne z EN374.

1.3. CS4: Scenarij, ki prispeva Delojemalec: Dejavnosti mešanja - Ročno (PROC19)

Pot izpostavljenosti, Učinki na zdravje, Indikatorji izpostavljenosti	Stopnja izpostavljenosti	Metoda izračuna	Stopnja opredelitve tveganja (RCR)
inhalacijski	< 1 mg/m³	MEASE	N/A

1.4 Smernica za uporabnika, za ugotavljanje, ali dela znotraj omejitev scenarija

izpostavitve

Vodilo za preverjanje skladnosti s scenarijem izpostavljenosti:

Če so bili sprejeti dodatni ukrepi za upravljanje s tveganji/pogoji za uporabo, morajo uporabniki zagotoviti vsaj enakovredno raven upravljanja s tveganji.

Scenarij izpostavljenosti

Lime (chemical), hydraulic

Scenarij izpostavljenosti, 08/06/2021

Identiteta snovi	
	Lime (chemical), hydraulic
št.CAS	85117-09-5
št.EINECS	285-561-1

Kazalo

1. **ES 1** Uporabna doba - delojemalci; Izdelki iz kamna, mavca, cementa, stekla in keramike: Izdelki, ki se uporabljajo na velikih površinah (AC4a)

1. ES 1 Uporabna doba - delojemalci; Izdelki iz kamna, mavca, cementa, stekla in keramike: Izdelki, ki se uporabljajo na velikih površinah (AC4a)

1.1 NASLOVNI ODSTAVEK

Ime scenarija izpostavljenosti	Uporaba v visokih in nizkih gradnjah - Gospodarska uporaba sredstev za nego tal - Lepljiva podlaga
Datum - revizija	20/05/2021 - 1.0
Stopnja življenjskega cikla	Uporabna doba - delojemalci
Glavna uporabniška skupina	Poklicne uporabe
Sektor(-ji) uporabe	Poklicne uporabe (SU22)
Kategorije izdelkov	Polnila, kiti, mavci, modelirna glina (PC9b) - Premazi in barve, razredčila, sredstva za odstranjevanje barv (PC9a) - Lepila, tesnilna sredstva (PC1) - Izdelki za obdelavo nekovinskih površin (PC15)
Kategorije proizvodov	Izdelki iz kamna, mavca, cementa, stekla in keramike: Izdelki, ki se uporabljajo na velikih površinah (AC4a)

Scenarij, ki prispeva Okolje

CS1 Nizki izpusti v okolje	ERC2

Scenarij, ki prispeva Delojemalec

CS2 Dejavnosti mešanja - Površine - Polnjenje posod in izlivanje iz njih - Ročna uporaba - Prstne barve, krede, lepila - Polnjenje in priprava opreme iz sodov ali posod	PROC8b - PROC9 - PROC26

1.2 Pogoji uporabe z vplivom na izpostavitev

1.2. CS1: Scenarij, ki prispeva Okolje: Nizki izpusti v okolje (ERC2)

Kategorije sproščanja v okolje	Formuliranje v zmes (ERC2)

Lastnosti izdelka (proizvoda)

Fizikalna oblika izdelka:

Trdna snov, zelo visoka prašnost

Parni tlak:

< 1E-05 Pa

1.2. CS2: Scenarij, ki prispeva Delojemalec: Dejavnosti mešanja - Površine - Polnjenje posod in izlivanje iz njih - Ročna uporaba - Prstne barve, krede, lepila - Polnjenje in priprava opreme iz sodov ali posod (PROC8b, PROC9, PROC26)

Kategorije procesov	Prenos snovi ali zmesi (polnjenje in praznjenje) na namenskih napravah - Prenos snovi ali zmesi v majhne vsebnike (namenska polnilna linija, vključno s tehtanjem) - Rokovanje s trdnimi anorganskimi snovmi na sobni temperaturi (PROC8b, PROC9, PROC26)

Lastnosti izdelka (proizvoda)

Fizikalna oblika izdelka:

Trdna snov, zelo visoka prašnost

Uporabljena količina, pogostost in trajanje uporabe/izpostavljenost

Trajanje:

Trajanje izpostavljenosti <= 240 min

Frekvenca:

Pogostost uporabe = 8 h/dogodek

Tehnični in organizacijski pogoji in ukrepi

Tehnični in organizacijski ukrepi

Zagotovite osnovno stopnjo splošnega prezračevanja (1 do 3 izmenjav zraka na uro).
Ne používati.

Pogoji in ukrepi glede na osebno zaščito, higieno in preverjanje zdravstvenega stanja

Osebna zaščitna oprema
Nosite primerne rokavice, preizkušene po EN374.
Uporaba zaščite oči v skladu z EN 166.
Nosite respirator skladno z EN140.

Drugi pogoji uporabe, ki vplivajo na izpostavljenost delojemalcev

Notranja aplikacija
Gospodarska uporaba
Temperatura: Obsega uporabo pri temperaturi okolice. 23°C

1.3 Ocena izpostavljenosti in sklicevanje na njen vir

1.3. CS2: Scenarij, ki prispeva Delojemalec: Dejavnosti mešanja - Površine - Polnjenje posod in izlivanje iz njih - Ročna uporaba - Prstne barve, krede, lepila - Polnjenje in priprava opreme iz sodov ali posod (PROC8b, PROC9, PROC26)

Pot izpostavljenosti, Učinki na zdravje, Indikatorji izpostavljenosti	Stopnja izpostavljenosti	Metoda izračuna	Stopnja opredelitve tveganja (RCR)
inhalacijski, lokalno, kratkoročno	< 1 mg/m³	MEASE	N/A

Dodatne informacije glede ocene izpostavljenosti:
Razpoložljivi podatki o nevarnostih ne dovoljujejo odstopanja od DNEL za draženje na koži.

1.4 Smernica za uporabnika, za ugotavljanje, ali dela znotraj omejitev scenarija izpostavitve

Vodilo za preverjanje skladnosti s scenarijem izpostavljenosti:
Če so bili sprejeti dodatni ukrepi za upravljanje s tveganji/pogoji za uporabo, morajo uporabniki zagotoviti vsaj enakovredno raven upravljanja s tveganji.