

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

BIOSCUD DL

Date of first edition: 1/28/2021 Safety Data Sheet dated 1/9/2023

version 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Identification of the substance:

Trade name: BIOSCUD DL Trade code: 25062019-02 CAS number: 1330-20-7 EC number: 215-535-7

Index number: 601-022-00-9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Diluent

Uses advised against: Data not available.

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Kerakoll Italy - +39-0536-816511

Ireland

Poison information centre: 01 809 2166 (Daily 8am-10pm)

In case of emergency call 999 or 112

Malta

In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification







2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 3 Flammable liquid and vapour.

Acute Tox. 4 Harmful in contact with skin.

Acute Tox. 4 Harmful if inhaled.
Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2 Causes serious eye irritation.

STOT SE 3 May cause respiratory irritation.

STOT RE 2 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 May be fatal if swallowed and enters airways.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Pictograms and Signal Words

Date 1/9/2023 Production Name BIOSCUD DL Page n. 1 of 10



Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P280 Wear protective gloves and eye protection.
P301+P310 IF SWALLOWED: Immediately call a doctor.

P331 Do NOT induce vomiting.

Contains

xylene

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

This substance has no PBT, vPvB or endocrine disrupting properties

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance Identifications: xylene

CAS number: 1330-20-7

EC number: 215-535-7

Index number: 601-022-00-9

Registration Number 01-2119488216-32

3.2. Mixtures

N.A.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediatley and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

Date 1/9/2023 Production Name BIOSCUD DL Page n. 2 of 10

Eye irritation Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhaltion of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Store away from heat.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

Date 1/9/2023 Production Name BIOSCUD DL Page n. 3 of 10

SECTION 8: Exposure controls/personal protection 8.1. Control parameters

OEL Type	Country C	eiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term	Notes
ACGIH	NNN		mg/ms	100.000	ilig/ili3	ppm 150.000	A4, BEI - URT and eye irr, CNS impair
EU	NNN		221.000	50.000	442.000	100.000	Skin
NATIONAL	AUSTRIA		221.000	50.000	442.000	100.000	
NATIONAL	BELGIUM		221.000	50.000	442.000	100.000	
NATIONAL	CANADA			100.000		150.000	Ontario
NATIONAL	CANADA		434.000	100.000	651.000	150.000	Québec
NATIONAL	DENMARK		109.000	25.000	442.000	100.000	
NATIONAL	FINLAND		220.000	50.000	440.000	100.000	
NATIONAL	FRANCE		221.000	50.000	442.000	100.000	
NATIONAL	GERMANY		440.000	100.000	880.000	200.000	AGS
NATIONAL	GERMANY		440.000	100.000	880.000	200.000	DFG
NATIONAL	HUNGARY		221.000		442.000		
NATIONAL	IRELAND		221.000	50.000	442.000	100.000	
NATIONAL	ISRAEL		434.000	100.000	442.000	100.000	
NATIONAL	ITALY		221.000	50.000	442.000	100.000	Cute
NATIONAL	LATVIA		221.000	50.000	442.000	100.000	
NATIONAL	NEW ZEALAND		217.000	50.000			
NATIONAL	CHINA			50.000		100.000	
NATIONAL	POLAND			100.000			
NATIONAL	ROMANIA		221.000	50.000	442.000	100.000	
NATIONAL	SINGAPORE		434.000	100.000	651.000	150.000	
NATIONAL	KOREA, REPUBLIC OF		435.000	100.000	655.000	150.000	
NATIONAL	SPAIN		221.000	50.000	442.000	100.000	
NATIONAL	SWEDEN		221.000	50.000	442.000	100.000	
NATIONAL	SWITZERLA ND		435.000	100.000	870.000	200.000	
NATIONAL	NETHERLA NDS		210.000		442.000		
NATIONAL	TURKEY		221.000	50.000	442.000	100.000	
NATIONAL	UNITED STATES OF AMERICA		435.000	100.000	655.000	150.000	NIOSH
NATIONAL	UNITED STATES OF AMERICA		435.000	100.000			OSHA
NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND		220.000	50.000	441.000	100.000	
NATIONAL	ARGENTINA			100.000		150.000	
NATIONAL	BULGARIA		221.000	50.000	445.000	100.000	
NATIONAL	CZECHIA		200.000		400.000		
NATIONAL	CHILE		380.000	87.000	621.000	150.000	

Date 1/9/2023 Production Name BIOSCUD DL Page n. 4 of 10

NATIONAL	CROATIA	221.000	50.000	442.000	100.000
NATIONAL	ESTONIA	200.000	50.000	450.000	100.000
NATIONAL	GREECE	435.000	100.000	650.000	150.000
NATIONAL	INDONESIA	434.000	100.000	651.000	150.000
NATIONAL	ICELAND	109.000	25.000	442.000	100.000
NATIONAL	LITHUANIA	221.000	50.000	442.000	100.000
NATIONAL	NORWAY	108.000	25.000		
NATIONAL	PORTUGAL		100.000		150.000
NATIONAL	RUSSIAN FEDERATIO N	50.000		150.000	
NATIONAL	SLOVAKIA	221.000	50.000	442.000	100.000
NATIONAL	SLOVENIA	221.000	50.000	442.000	100.000
NATIONAL	SOUTH AFRICA	218.000	50.000	435.000	100.000
NATIONAL	TAIWAN, PROVINCE OF CHINA	434.000	100.000		

Predicted No Effect Concentration (PNEC) values

PNEC Limit	Exposure Route	Exposure Frequency
327.000 µg/l	Freshwater	
327.000 μg/l	Intermittent releases (freshwater)	
327.000 µg/l	Marine water	
6.580 mg/l	Microorganisms in sewage treatments	
12.460 mg/kg	Freshwater sediments	
12.460 mg/kg	Marine water sediments	
2.310 mg/kg	Soil	

Derived No Effect Level (DNEL) values

Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency
	289.000 mg/m³	174.000 mg/m ³	Human Inhalation	Short Term, systemic effects
	289.000 mg/m³	174.000 mg/m ³	Human Inhalation	Short Term, local effects
	180.000 mg/kg	108.000 mg/kg	Human Dermal	Long Term, systemic effects
		1.600 mg/kg	Human Oral	Long Term, systemic effects
	77.000 mg/kg	14.800 mg/kg	Human Inhalation	Long Term, systemic effects

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A

Hygienic and Technical measures

Date 1/9/2023 Production Name BIOSCUD DL Page n. 5 of 10

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid Color: Transparent Odour: N.A.

Odour threshold: N.A.

pH: N.A.

Kinematic viscosity: N.A.

Melting point / freezing point: < -13 °C (9 °F) Notes @ 101 325 Pa

Initial boiling point and boiling range: > 130 °C (266 °F) Notes @ 101 325 Pa

Flash point: 30 °C (86 °F) Notes @ 101 325 Pa

Upper/lower flammability or explosive limits: 7.00 % (UEL). 1.10 % (LEL).

Vapour density: N.A. Vapour pressure: 2.50 kPa

Relative density: 0.87 kg/l Notes @ 20°C

Solubility in water: Insoluble 165.8 mg/L @ 25 °C

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): 3.16

Auto-ignition temperature: 450.00 °C Notes @ 101 325 Pa

Decomposition temperature: N.A.

Flammability: The product is classified Flam. Liq. 3 H226 Volatile Organic compounds - VOCs = 100 %; 870 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

Miscibility: N.A.
Conductivity: N.A.
Evaporation rate: N.A.
Viscosity: 0.74 cPo

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Data not available.

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

Vapors may form explosive mixture with air

10.4. Conditions to avoid

Data not available.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

Data not available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Substance

a) acute toxicity The product is classified: Acute Tox. 4(H312), Acute Tox. 4(H332)

LD50 Oral Rat = 3523.00 ml/Kg

LC50 Inhalation Vapour Rabbit = 26.00 mg/l 4h

LD50 Skin Rat = 4350.00 mg/kg

b) skin corrosion/irritation The product is classified: Skin Irrit. 2(H315) c) serious eye damage/irritation The product is classified: Eye Irrit. 2(H319)

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Date 1/9/2023 Production Name BIOSCUD DL Page n. 6 of 10

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure
The product is classified: STOT SE 3(H335)
i) STOT-repeated exposure
The product is classified: STOT RE 2(H373)
j) aspiration hazard
The product is classified: Asp. Tox. 1(H304)

11.2 Information on other hazards

Endocrine disrupting properties:

This substance has no endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6 Endocrine disrupting properties

This substance has no endocrine disrupting properties

12.7 Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

A waste code according to European waste catalogue (EWC) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

HP 3: Flammable; HP 4: Irritant — skin irritation and eye damage; HP 5: Specific Target Organ Toxicity (STOT)/Aspiration Toxicity; HP 6: Acute Toxicity

SECTION 14: Transport information

14.1. UN number or ID number

1307

14.2. UN proper shipping name

ADR-Shipping Name: XYLENES IATA-Technical name: XYLENES IMDG-Technical name: XYLENES

14.3. Transport hazard class(es)

ADR-Class: 3
IATA-Class: 3
IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: III

Date 1/9/2023 Production Name BIOSCUD DL Page n. 7 of 10

IATA-Packing group: III
IMDG-Packing group: III

14.5. Environmental hazards
Marine pollutant: No
Environmental Pollutant: No
IMDG-EMS: F-E, S-D

14.6. Special precautions for user

Road and Rail (ADR-RID) :

ADR-Label: 3

ADR - Hazard identification number: 30

ADR-Special Provisions: -

ADR-Transport category (Tunnel restriction code): 3 (D/E)

ADR Limited Quantities: 5 L ADR Excepted Quantities: E1

Air (IATA):

IATA-Passenger Aircraft: 355 IATA-Cargo Aircraft: 366

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisioning: A3

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 223

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

Date 1/9/2023 Production Name BIOSCUD DL Page n. 8 of 10

Seveso III category according Lower-tier threshold (tonnes) Upper-tier threshold (tonnes) to Annex 1, part 1

Product belongs to category: P5c 5000 50000

Regulation (EU) 649/2012 (PIC regulation):

No Substance Listed

German Water Hazard Class.

Class 2: hazardous for water.

SVHC Substances:

No data available

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for the substance.

SECTION 16: Other information

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

 $\hbox{GHS: Globally Harmonized System of Classification and Labeling of Chemicals.}$

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: Keep Away From Heat KSt: Explosion coefficient.

Date 1/9/2023 Production Name BIOSCUD DL Page n. 9 of 10

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 4. FIRST AID MEASURES
- 5. FIRE-FIGHTING MEASURES
- 6. ACCIDENTAL RELEASE MEASURES
- 7. HANDLING AND STORAGE
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 10. STABILITY AND REACTIVITY
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 13. DISPOSAL CONSIDERATIONS
- 14. TRANSPORT INFORMATION

- 15. REGULATORY INFORMATION

Date 1/9/2023 Production Name BIOSCUD DL Page n. 10 of 10



Exposure Scenario, 14/10/2022

Substance identity	
	Xylene, Mixed Isomers
CAS No.	1330-20-7
INDEX No.	601-022-00-9
EINECS No.	215-535-7
Registration number	01-2119488216-32

Table of contents

1. **ES 1** Widespread use by professional workers

1. ES 1 Widespread use by professional workers

1.1 TITLE SECTION

Exposure Scenario name	Professional application of coatings and inks	
Date - Version	14/10/2022 - 1.0	
Life Cycle Stage Widespread use by professional workers		
Main user group	Professional uses	
Sector(s) of use	Professional uses (SU22)	

Environment Contributing Scenario

CS1	ERC8a - ERC8d			
Worker Contributing Scenario				
CS2 Material transfers	PROC8a			
CS3 Rolling, Brushing	PROC10			
CS4 Roller, spreader, flow application	PROC11			

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

Environmental release	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) -
categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
	(FRC8a FRC8d)

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use (or from service life)

Emission days: 300 days per year

Conditions and measures related to sewage treatment plant

STP type:

Onsite Sewage Treatment Plant STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100 Local freshwater dilution factor: 10

1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities		
	(PROC8a)		

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

= 500 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Use in closed process

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories Roller application or brushing (PROC10)

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

= 500 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories Non industrial spraying (PROC11)

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

= 500 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Carry out in a vented booth provided with laminar airflow.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	= 0.0015 mg/L	N/A	= 0.005
marine water	= 0.000145 mg/L	N/A	< 0.001
freshwater sediment	= 0.016 mg/kg wet weight	N/A	= 0.006
marine sediment	= 0.0156 mg/kg wet weight	N/A	< 0.001
soil	= 0.0117 mg/kg wet weight	N/A	= 0.006
Sewage treatment plant	= 0.00866 mg/L	N/A	= 0.001

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure level	Calculation method	Risk Characterization Ratio (RCR)
= 14 ppm	N/A	= 0.79
= 13.71 mg/kg bw/day	N/A	= 0.08
N/A	N/A	= 0.87
	= 14 ppm = 13.71 mg/kg bw/day	= 14 ppm N/A = 13.71 mg/kg bw/day N/A

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 3 ppm	N/A	= 0.17
dermal, systemic, long-term	= 27.43 mg/kg bw/day	N/A	= 0.15
combined routes	N/A	N/A	= 0.32

1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)

inhalative, systemic, long-term	= 5 ppm	N/A	= 0.28
dermal, systemic, long-term	= 13.71 mg/kg bw/day	N/A	= 0.08
combined routes	N/A	N/A	= 0.29

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.