

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/1000

KERADECOR WOOD WHITE

Date of first edition: 7/23/2021

Safety Data Sheet dated 05/05/2025

version 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: KERADECOR WOOD WHITE

Trade code: 19022021_WHITE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Other paints and coating materials

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Ireland Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Members of the public Number (8 am-10 pm): +353 (0)1 809 2166

Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

Malta In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 3 Flammable liquid and vapour.

STOT SE 3 May cause drowsiness or dizziness.

DECL10 This titanium dioxide-containing product is not classified as carcinogen by inhalation because it does not meet the criteria stated in Note 10, Annex VI of Regulation (EC) 1272/2008.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Warning

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours.
P280	Wear protective gloves/clothing and eye/face protection.
P370+P378	In case of fire, use a CO2 fire extinguisher to extinguish.
P501	Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

EUH208	Contains Hydroxyphenyl benzotriazole derivatives. May produce an allergic reaction.
EUH208	Contains maleic anhydride. May produce an allergic reaction.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Naphtha (petroleum), hydrotreated heavy

Dir. 2004/42/EC (VOC directive)

Interior and exterior minimal build woodstains
EU limit value for this product (cat. A/f): 700 g/l
This product contains max 546.48 g/l VOC.

Special provisions according to Annex XVII of REACH and subsequent amendments:

Restricted to professional users.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: KERADECOR WOOD WHITE

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥20-<50 %	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC:919-857-5	Asp. Tox. 1, H304; Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	01-2119463258-33
≥20-<50 %	Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2	Carc. 2, H351	
≥10-<20 %	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC:918-481-9	Asp. Tox. 1, H304, EUH066	01-2119457273-39
≥1-<3 %	Naphtha (petroleum), hydrotreated heavy	CAS:64742-48-9 EC:265-150-3 Index:649-327-00-6	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066, DECLP(*)	
≥0.3-<0.5 %	Hydroxyphenyl benzotriazole derivatives	EC:400-830-7 Index:607-176-00-3	Aquatic Chronic 2, H411; Skin Sens. 1, H317	01-0000015075-76
<0.0015 %	maleic anhydride	CAS:108-31-6 EC:203-571-6 Index:607-096-00-9	Acute Tox. 4, H302 STOT RE 1, H372 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317, EUH071	
Specific Concentration Limits: C ≥ 0.001%: Skin Sens. 1A H317				

(*)DECLP Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008.

The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance

contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

This mixture contains >= 1% titanium dioxide (CAS 13463-67-7). The Annex VI classification of titanium dioxide does not apply to this mixture according to its Note 10.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediatley and dispose off safely.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

N.A.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a CO2 fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Store the product at a temperature between +5°C and +35°C.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

OEL Type	Country	Occupational Exposure Limit
Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] CAS: 13463-67-7	ACGIH	Long Term: 2.5 mg/m ³ (8h) Finescale particles; R ; A3 - LRT irr, pneumoconiosis
NATIONAL	BELGIUM	Long Term: 10 mg/m ³ Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATIONAL	CROATIA	Long Term: 10 mg/m ³ U Source: NN 1/2021
NATIONAL	CROATIA	Long Term: 4 mg/m ³ R Source: NN 1/2021
NATIONAL	IRELAND	Long Term: 10 mg/m ³ Source: 2021 Code of Practice
NATIONAL	IRELAND	Long Term: 4 mg/m ³ Source: 2021 Code of Practice
NATIONAL	ROMANIA	Long Term: 10 mg/m ³ ; Short Term: 15 mg/m ³ Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATIONAL	SPAIN	Long Term: 10 mg/m ³ Source: LEP 2022
NATIONAL	AUSTRIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ 60(Miw), 2x, MAK, A Source: BGBI. II Nr. 156/2021
NATIONAL	BULGARIA	Long Term: 10 mg/m ³ Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
NATIONAL	DENMARK	Long Term: 6 mg/m ³ K Source: BEK nr 2203 af 29/11/2021
NATIONAL	ESTONIA	Long Term: 5 mg/m ³ Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	FRANCE	Long Term: 10 mg/m ³ Cancérogène de catégorie 2 Source: INRS outil65
NATIONAL	GREECE	Long Term: 10 mg/m ³ εισπν. Source: ΦΕΚ 94/A` 13.5.1999

NATIONAL	GREECE	Long Term: 5 mg/m ³ αναν. Source: ΦΕΚ 94/A` 13.5.1999
NATIONAL	LATVIA	Long Term: 10 mg/m ³ Source: KN325P1
NATIONAL	LITHUANIA	Long Term: 5 mg/m ³ Source: 2011 m. rugėjo 1 d. Nr. V-824/A1-389
NATIONAL	NORWAY	Long Term: 5 mg/m ³ Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 10 mg/m ³ 4), 7) Source: Dz.U. 2018 poz. 1286
NATIONAL	SLOVAKIA	Long Term: 5 mg/m ³ Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATIONAL	SWEDEN	Long Term: 5 mg/m ³ 3 Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 3 mg/m ³ TWA mg/m ³ : (a), SSC, Formel / Formal, NIOSH Source: suva.ch/valeurs-limites
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
Naphtha (petroleum), hydrotreated heavy CAS: 64742-48-9	NATIONAL POLAND	Long Term: 300 mg/m ³ ; Short Term: 900 mg/m ³ Source: Dz.U. 2018 poz. 1286
maleic anhydride CAS: 108-31-6	SUVA	Long Term: 300 mg/m ³ - 50 ppm; Short Term: 600 mg/m ³ - 100 ppm SNC / ZNS Source: suva.ch/valeurs-limites
	ACGIH	Long Term: 0.01 mg/m ³ (8h) IFV, DSEN, RSEN, A4 - Resp sens
	NATIONAL AUSTRIA	Long Term: 0.4 mg/m ³ - 0.1 ppm; Short Term: Ceiling - 0.8 mg/m ³ - 0.2 ppm 5(Mow), 8x, MAK, Sah Source: BGBl. II Nr. 156/2021
	NATIONAL BULGARIA	Long Term: 1 mg/m ³ Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATIONAL CZECHIA	Long Term: 1 mg/m ³ ; Short Term: Ceiling - 2 mg/m ³ I, S Source: Nařízení vlády č. 361-2007 Sb
	NATIONAL DENMARK	Long Term: 0.4 mg/m ³ - 0.1 ppm Source: BEK nr 2203 af 29/11/2021
	NATIONAL ESTONIA	Long Term: 1.2 mg/m ³ - 0.3 ppm; Short Term: 2.5 mg/m ³ - 0.6 ppm S Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL FINLAND	Long Term: 0.41 mg/m ³ - 0.1 ppm; Short Term: Ceiling - 0.81 mg/m ³ - 0.2 ppm kattoarvo Source: HTP-ARVOT 2020
	NATIONAL FRANCE	Short Term: 1 mg/m ³ Risque d'allergie Source: INRS outil65
	NATIONAL GREECE	Long Term: 1 mg/m ³ - 0.25 ppm Source: ΦΕΚ 94/A` 13.5.1999
	NATIONAL HUNGARY	Long Term: 0.08 mg/m ³ ; Short Term: 0.08 mg/m ³ m, sz, R+T Source: 5/2020. (II. 6.) ITM rendelet
	NATIONAL LATVIA	Long Term: 1 mg/m ³

Source: KN325P1

NATIONAL	LITHUANIA	Long Term: 1.2 mg/m ³ - 0.3 ppm; Short Term: 2.5 mg/m ³ - 0.6 ppm J Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	NORWAY	Long Term: 0.8 mg/m ³ - 0.2 ppm A Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 0.5 mg/m ³ ; Short Term: 1 mg/m ³ skóra Source: Dz.U. 2018 poz. 1286
NATIONAL	SLOVAKIA	Long Term: 0.41 mg/m ³ - 0.1 ppm S Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATIONAL	SWEDEN	Long Term: 0.2 mg/m ³ - 0.05 ppm; Short Term: 0.4 mg/m ³ - 0.1 ppm M, S Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 0.4 mg/m ³ - 0.1 ppm; Short Term: 0.4 mg/m ³ - 0.1 ppm S, SSC, VR / AW, NIOSH OSHA, La substance peut être présente sous forme de vapeur et d'aérosol en même temps / Der Stoff kann gleichzeitig als Dampf und Aerosol vorliegen Source: suva.ch/valeurs-limites
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 1 mg/m ³ ; Short Term: 3 mg/m ³ Sen Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
NATIONAL	BELGIUM	Long Term: 0.01 mg/m ³ - 0.003 ppm Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATIONAL	CROATIA	Long Term: 0.41 mg/m ³ - 0.1 ppm; Short Term: 0.8 mg/m ³ - 0.2 ppm alergen (koža i udisanje) Source: NN 1/2021
NATIONAL	GERMANY	Long Term: 0.081 mg/m ³ - 0.02 ppm DFG, Sah, Y, 11, 1;=2, 5=(I) Source: TRGS 900
NATIONAL	IRELAND	Long Term: 0.01 ppm Sens., IFV Source: 2021 Code of Practice
NATIONAL	ROMANIA	Long Term: 1 mg/m ³ - 0.25 ppm; Short Term: 3 mg/m ³ - 0.75 ppm Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATIONAL	SLOVENIA	Long Term: 0.41 mg/m ³ - 0.1 ppm; Short Term: 0.41 mg/m ³ - 0.1 ppm Y Source: UL št. 72, 11. 5. 2021
NATIONAL	SPAIN	Long Term: 0.4 mg/m ³ - 0.1 ppm FIV, Sen Source: LEP 2022

Predicted No Effect Concentration (PNEC) values

maleic anhydride Exposure Route: Fresh Water; PNEC Limit: 87.5 µg/l
CAS: 108-31-6

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 589.5 µg/l
Exposure Route: Marine water; PNEC Limit: 8.75 µg/l
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 24.53 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 197 µg/kg
Exposure Route: Marine water sediments; PNEC Limit: 19.7 µg/kg
Exposure Route: Soil; PNEC Limit: 25.75 µg/kg
Exposure Route: Secondary poisoning; PNEC Limit: 6.67 mg/kg

Derived No Effect Level (DNEL) values

Hydroxyphenyl benzotriazole derivatives Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 350 µg/m³; Consumer: 85 µg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 250 µg/kg; Consumer: 25 µg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 25 µg/kg

maleic anhydride
CAS: 108-31-6

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 190 µg/m³; Consumer: 50 µg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 800 µg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 320 µg/m³; Consumer: 80 µg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 200 µg/kg; Consumer: 100 µg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Professional: 200 µg/kg; Consumer: 100 µg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 60 µg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 100 µg/kg

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing. Safety shoes.

Protection for hands:

Neoprene, Nitrile rubber.

Respiratory protection:

Gas filter type A .

Thermal Hazards:

Not expected if used as intended

Environmental exposure controls:

Prevent the product from entering sewers or surface and underground water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: White

Odour: Like: Hydrocarbons, aliphatic

Odour threshold: N.A.

pH: Not Relevant

Kinematic viscosity: > 20,5 mm²/sec (40 °C)

Melting point/freezing point: N.A.

Boiling point or initial boiling point and boiling range: 120 °C (248 °F)

Flash point: 41 °C (106 °F)

Lower and upper explosion limit: N.A.

Relative vapour density: N.A.

Vapour pressure: 3.00 hPa

Density and/or relative density: 0.92 g/cm³

Solubility in water: Insoluble

Solubility in oil: N.A.

Partition coefficient n-octanol/water (log value): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: The product is classified Flam. Liq. 3 H226

Volatile Organic compounds - VOCs = 59.4 % ; 546.48 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

Vapors may form explosive mixture with air

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified
	Based on available data, the classification criteria are not met
c) serious eye damage/irritation	Not classified
	Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	Not classified
	Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	The product is classified: STOT SE 3(H336)
i) STOT-repeated exposure	Not classified
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

Hydrocarbons, C9-C11, n- a) acute toxicity	LD50 Oral Rat > 5000 mg/kg	
alkanes, isoalkanes, cyclics, <2% aromatics		
	LC50 Inhalation Vapour Rat > 5000 mg/m ³ 8h	
	LD50 Skin Rabbit > 2000 mg/kg 24h	
b) skin corrosion/irritation	Skin Irritant Rabbit Negative 4h	
c) serious eye damage/irritation	Eye Irritant Rabbit No	
d) respiratory or skin sensitisation	Skin Sensitization Guineapig Negative	
f) carcinogenicity	Genotoxicity Rat Negative	Inhalation route
	Carcinogenicity Inhalation Rat Positive	
g) reproductive toxicity	No Observed Adverse Effect Level Rat > 20000 mg/m ³	

Hydrocarbons, C10-C13, a) acute toxicity	LD50 Oral Rat > 5000 mg/kg
n-alkanes, isoalkanes, cyclics, < 2% aromatics	

LC50 Inhalation Vapour Rat > 5000 mg/m³ 8h

		LD50 Skin Rat > 2000 mg/kg 24h	
b) skin corrosion/irritation		Skin Irritant Rabbit Positive 24h	
c) serious eye damage/irritation		Eye Irritant Rabbit No 24-72 h	
d) respiratory or skin sensitisation		Skin Sensitization Guineapig Negative	
f) carcinogenicity		Genotoxicity Rat Negative	Inhalation route
g) reproductive toxicity		No Observed Adverse Effect Level Inhalation Rat >= ppm 400	
Naphtha (petroleum), hydrotreated heavy	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg	
		LC50 Inhalation Vapour Rat > 5610 mg/m ³ 4h	
		LD50 Skin Rabbit > 2000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive 4h	
	c) serious eye damage/irritation	Eye Irritant Rabbit No	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Negative	
	f) carcinogenicity	Genotoxicity Rat Negative	Inhalation route
Hydroxyphenyl benzotriazole derivatives		Carcinogenicity Inhalation Rat Positive	
	g) reproductive toxicity	No Observed Adverse Effect Level Rat > 20000 mg/m ³	
	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg	
		LC50 Inhalation Rat > 5.8 mg/l 96h	
		LD50 Skin Rat > 2000 mg/kg	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative 4h	
	c) serious eye damage/irritation	Eye Irritant Rabbit No	
maleic anhydride	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Positive	
	f) carcinogenicity	Genotoxicity Negative	Hamster oral route
	g) reproductive toxicity	No Observed Effect Level Oral Rat < 2 mg/kg	
	a) acute toxicity	LD50 Oral Rat = 1090 mg/kg	
		LC50 Inhalation Rat > 4.35 mg/l 1h	
		LD50 Skin Rabbit = 2620 mg/kg	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive 4h	
	c) serious eye damage/irritation	Eye Corrosive Rabbit Positive	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
		Respiratory Sensitization Rat Positive	
	f) carcinogenicity	Genotoxicity Rat Negative 6h	Inhalation route
		Carcinogenicity Negative	
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 55 mg/kg	

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numbr.	Ecotox Data
Hydrocarbons, C9-C11, n-alkanes, EINECS: 919-isoalkanes, cyclics, <2% aromatics 857-5		a) Aquatic acute toxicity : LL50 Fish Oncorhynchus mykiss = 10 mg/L 96h a) Aquatic acute toxicity : EL50 Daphnia Daphnia magna = 4.5 mg/L 48h b) Aquatic chronic toxicity : NOELR Daphnia Daphnia magna = 2.6 mg/L - 21days a) Aquatic acute toxicity : NOELR Algae Pseudokirchneriella subcapitata = 0.5 mg/L 72h
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EINECS: 918-481-9	a) Aquatic acute toxicity : LL50 Fish Oncorhynchus mykiss > 1000 mg/L 96h „OECD Guideline 203 (Fish, Acute Toxicity Test) b) Aquatic chronic toxicity : LOELR Fish = 0.1 mg/L - 28days a) Aquatic acute toxicity : LL50 Daphnia Daphnia magna > 1000 mg/L 48h b) Aquatic chronic toxicity : NOELR freshwater invertebrate = 0.17 mg/L - 21days a) Aquatic acute toxicity : NOELR Algae 72h a) Aquatic acute toxicity : EL50 Tetrahymena pyriformis > 1000 mg/L 48h
Naphtha (petroleum), hydrotreated heavy	CAS: 64742-48-9 - EINECS: 265-150-3 - INDEX: 649-327-00-6	a) Aquatic acute toxicity : LL50 Fish Oncorhynchus mykiss = 10 mg/L 96h a) Aquatic acute toxicity : EL50 Daphnia Daphnia magna = 4.5 mg/L 48h b) Aquatic chronic toxicity : NOELR Daphnia Daphnia magna = 2.6 mg/L - 21days a) Aquatic acute toxicity : NOELR Algae Pseudokirchneriella subcapitata = 0.5 mg/L 72h
Hydroxyphenyl benzotriazole derivatives	EINECS: 400-830-7 - INDEX: 607-176-00-3	a) Aquatic acute toxicity : LC50 Fish freshwater fish = 2.8 mg/L 96h a) Aquatic acute toxicity : LC50 freshwater invertebrates = 4 mg/L b) Aquatic chronic toxicity : EC50 Daphnia Daphnia magna = 780 µg/L OECD Guideline 211 (Daphnia magna Reproduction Test) - 21days a) Aquatic acute toxicity : EC50 Algae freshwater algae = 9 mg/L 72h d) Terrestrial toxicity : LC50 Worm Eisenia foetida > 1000 mg/kg „OECD Guideline 207 (Earthworm, Acute Toxicity Tests - 14days
maleic anhydride	CAS: 108-31-6 - EINECS: 203-571-6 - INDEX: 607-096-00-9	a) Aquatic acute toxicity : LC50 Fish rainbow trout = 75 mg/L 96h a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 42.81 mg/L 48h b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 10 mg/L - 21days a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 74.32 mg/L a) Aquatic acute toxicity : NOEC Sludge activated sludge = 44.6 mg/L - 18h

12.2. Persistence and degradability

Component	Persistence/Degradability:	Value	Notes:
-----------	----------------------------	-------	--------

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Readily biodegradable	
Hydroxyphenyl benzotriazole derivatives	Non-readily biodegradable	12.000 %; OECD 301B
maleic anhydride	Readily biodegradable	90.000 28days

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value	Notes:
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Bioaccumulative	BCF - Bioconcentration factor	962.000 L/kg	

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration >= 0.1%

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT
IATA-Shipping Name: PAINT
IMDG-Shipping Name: PAINT

14.3. Transport hazard class(es)

ADR-Class: 3
IATA-Class: 3
IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: III
IATA-Packing group: III
IMDG-Packing group: III

14.5. Environmental hazards

Marine pollutant: No
Environmental Pollutant: No
IMDG-EMS: F-E, S-E

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 3
ADR - Hazard identification number: -
ADR-Special Provisions: 163 367 650
ADR-Transport category (Tunnel restriction code): 3 (E)
ADR Limited Quantities: 5 L
ADR Excepted Quantities: E1

Air (IATA):

IATA-Passenger Aircraft: 355
IATA-Cargo Aircraft: 366

IATA-Label: 3
IATA-Subsidiary hazards: -
IATA-Erg: 3L
IATA-Special Provisions: A3 A72 A192

Sea (IMDG):

IMDG-Stowage and handling: Category A
IMDG-Segregation: -
IMDG-Subsidiary hazards: -
IMDG-Special Provisions: 163 223 367 955

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)
Regulation (EU) n. 2021/849 (ATP 17 CLP)
Regulation (EU) n. 2022/692 (ATP 18 CLP)
Regulation (EU) n. 2020/878
Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40

Restrictions related to the substances contained: 28, 29, 75

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
Product belongs to category: P5c	5000	50000

Explosives precursors – Regulation 2019/1148

No substances listed

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

3: Severe hazard to waters

German Lagerklasse according to TRGS 510:

LGK 3

SVHC Substances:

No SVHC substances present in concentration >= 0.1%

Dir. 2004/42/EC (VOC directive)

(ready to use)

Volatile Organic compounds - VOCs = 59.40 %

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

Naphtha (petroleum), hydrotreated heavy

SECTION 16: Other information

Code	Description
EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.6/2	Carc. 2	Carcinogenicity, Category 2
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:**Classification according to Regulation (EC) Nr. 1272/2008**

Flam. Liq. 3, H226	On basis of test data
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive
EC50: Half Maximal Effective Concentration
ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances.
ES: Exposure Scenario
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KAFH: Keep Away From Heat
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 10: Stability and reactivity
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 13: Disposal considerations
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Exposure Scenario

Naphtha (petroleum), hydrotreated heavy

Exposure Scenario, 08/06/2021

Substance identity	Naphtha (petroleum), hydrotreated heavy
CAS No.	64742-48-9
INDEX No.	649-327-00-6
EINECS No.	265-150-3

Table of contents

1. **ES 1** Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)

1. ES 1

Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)

1.1 TITLE SECTION

Exposure Scenario name	Professional application of coatings and inks
Date - Version	12/05/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Coatings and paints, thinners, paint removers (PC9a)

Environment Contributing Scenario

CS1	ERC8a - ERC8d
-----	---------------

Worker Contributing Scenario

CS2 Equipment cleaning and maintenance - Rolling, Brushing - Material transfers	PROC8a - PROC10 - PROC11
---	--------------------------

1.2 Conditions of use affecting exposure**1.2. CS1: Environment Contributing Scenario (ERC8a, ERC8d)**

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Product (article) characteristics**Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

1.2. CS2: Worker Contributing Scenario: Equipment cleaning and maintenance - Rolling, Brushing - Material transfers (PROC8a, PROC10, PROC11)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Roller application or brushing - Non industrial spraying (PROC8a, PROC10, PROC11)
--------------------	---

Product (article) characteristics**Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Do not ingest.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Wear suitable face shield.

Wear an impervious suit.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.