

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

L34 EVOLUTION (A)

Date of first edition: 11/22/2021

Safety Data Sheet dated 28/11/2023

version 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: L34 EVOLUTION (A)

Trade code: 001015023 -3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Adhesives, sealants

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel. +39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Ireland Poison information centre: 01 809 2166 (Daily 8am-10pm) In case of emergency call 999 or 112

Malta In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2 Causes serious eye irritation.

Skin Sens. 1 May cause an allergic skin reaction.

Aquatic Chronic 3 Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Warning

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P280 Wear protective gloves and eye protection.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with applicable regulations.

Contains

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: L34 EVOLUTION (A)

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
7-10 %	bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS:1675-54-3 EC:216-823-5 Index:603-073-00-2	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411, M-Chronic:1 Specific Concentration Limits: C $\geq 5\%$: Eye Irrit. 2 H319 C $\geq 5\%$: Skin Irrit. 2 H315	01-2119456619-26
2.5-3 %	propylene carbonate	CAS:108-32-7 EC:203-572-1 Index:607-194-00-1	Eye Irrit. 2, H319	01-2119537232-48

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
Limestone CAS: 1317-65-3	NATIONAL	BELGIUM	Long Term: 10 mg/m3 Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	BULGARIA	Long Term: 10 mg/m3 Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. НАРЕДБА № 10 ОТ 26 СЕПТЕМВРИ 2003
	NATIONAL	ESTONIA	Long Term: 10 mg/m3 Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105

Calcium carbonate
CAS: 471-34-1

NATIONAL	ESTONIA	Long Term: 5 mg/m3 Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	GREECE	Long Term: 10 mg/m3 e?sp? Source: ΦEK 94/A` 13.5.1999;
NATIONAL	GREECE	Long Term: 5 mg/m3 a?ap? Source: ΦEK 94/A` 13.5.1999;
NATIONAL	GREECE	Long Term: 10 mg/m3 e?sp?. Source: ΦEK 94/A` 13.5.1999;
NATIONAL	GREECE	Long Term: 5 mg/m3 a?ap?. Source: ΦEK 94/A` 13.5.1999;
NATIONAL	HUNGARY	Long Term: 10 mg/m3 N Source: 5/2020. (II. 6.) ITM rendelet
NATIONAL	IRELAND	Long Term: 10 mg/m3 Source: 2021 Code of Practice
NATIONAL	IRELAND	Long Term: 4 mg/m3 Source: 2021 Code of Practice
NATIONAL	AUSTRALIA	Long Term: 10 mg/m3 This value is for inhalable dust containing no asbestos and <1 % crystalline silica.
NATIONAL	CROATIA	Long Term: 10 mg/m3 U Source: NN 1/2021
NATIONAL	CROATIA	Long Term: 4 mg/m3 R Source: NN 1/2021
NATIONAL	FRANCE	Long Term: 10 mg/m3 Source: INRS outil65
NATIONAL	HUNGARY	Long Term: 10 mg/m3 inhalable aerosol Source: 5/2020. (II. 6.) ITM
NATIONAL	IRELAND	Long Term: 10 mg/m3 Inhalable fraction Source: 2021 Code of Practice
NATIONAL	IRELAND	Long Term: 4 mg/m3 Respirable fraction Source: 2021 Code of Practice
NATIONAL	LATVIA	Long Term: 6 mg/m3 Source: KN325P1
NATIONAL	POLAND	Long Term: 10 mg/m3 4) Source: Dz.U. 2018 poz. 1286
NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m3 inhalable aerosol Source: EH40/2005 Workplace exposure limits
NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m3 respirable aerosol Source: EH40/2005 Workplace exposure limits

propylene carbonate
CAS: 108-32-7

NATIONAL	LATVIA	Long Term: 2 mg/m3 Source: KN325P1
NATIONAL	LITHUANIA	Long Term: 7 mg/m3

NATIONAL GERMANY

Long Term: 8.5 mg/m³ - 2 ppm
 DFG, Y, 11, 1 (I)
 Source: TRGS 900

Predicted No Effect Concentration (PNEC) values

bis-[4-(2,3-epoxipropoxy)phenyl]
 propane
 CAS: 1675-54-3

Exposure Route: Fresh Water; PNEC Limit: 0.006 mg/l

Exposure Route: Marine water; PNEC Limit: 600 ng/L

Exposure Route: Freshwater sediments; PNEC Limit: 0.996 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0.099 mg/kg

Exposure Route: Soil; PNEC Limit: 0.196 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.018 mg/l

propylene carbonate
 CAS: 108-32-7

Exposure Route: Fresh Water; PNEC Limit: 900 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 9 mg/l

Exposure Route: Marine water; PNEC Limit: 90 µg/l

Exposure Route: Intermittent releases (marine water); PNEC Limit: 900 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 7400 mg/l

Exposure Route: Soil; PNEC Limit: 810 µg/kg

Derived No Effect Level (DNEL) values

bis-[4-(2,3-epoxipropoxy)phenyl]
 propane
 CAS: 1675-54-3

Exposure Route: Human Oral; Exposure Frequency: Long Term, local effects
 Worker Professional: 0.75 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 0.75 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 3.571 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects
 Worker Professional: 3.571 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 12.25 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
 Worker Professional: 12.25 mg/m³

propylene carbonate
 CAS: 108-32-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 70.53 mg/m³; Consumer: 17.4 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
 Worker Professional: 20 mg/m³; Consumer: 10 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects
 Worker Professional: 20 mg/kg; Consumer: 10 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
 Consumer: 10 mg/kg

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.

Protection for skin:

Chemical protection clothing.

Protection for hands:

Neoprene, Nitrile rubber.

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State: Liquid

Colour: Beige

Odour: Light

Odour threshold: N.A.

pH: Not Relevant

Kinematic viscosity: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: > 320 °C (608 °F)

Flash point: > 100°C / 212°F

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 1.72 g/cm³

Solubility in water: N.A.

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: N.A.

Volatile Organic compounds - VOCs = 2.65 % ; 45.58 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified

	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

bis-[4-(2,3-epoxipropoxy)phenyl]propane	a) acute toxicity	LD50 Oral Rabbit = 19800 mg/kg	
		LD50 Skin Rabbit > 20 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive	epoxy resin with an average molecular mass <= 700 d irritate skin of rabbits
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	f) carcinogenicity	Genotoxicity Negative Carcinogenicity Oral Rat = 15 mg/kg Carcinogenicity Skin Rat = 1 mg/kg	Mouse, oral NOAEL NOAEL
	g) reproductive toxicity	No Observed Effect Level Oral Rat = 750 mg/kg	
propylene carbonate	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg LC50 Inhalation Vapour Rat Negative 8h LD50 Skin Rabbit >= 2000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative 24h	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Negative	
	f) carcinogenicity	Genotoxicity Negative Carcinogenicity Negative	Mouse intraperitoneal route Mouse
	g) reproductive toxicity	No Observed Adverse Effect Level Oral = 10100 mg/kg	Mouse

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS: 1675-54-3 - EINECS: 216-823-5 - INDEX: 603-073-00-2	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 2 mg/L 96h a) Aquatic acute toxicity : LC50 Daphnia magna = 1.8 mg/L 48h

a) Aquatic acute toxicity : EC50 Algae Scenedesmus capricornutum = 11 mg/L 72h EPA-660/3-75-009

c) Bacteria toxicity : EC50 Sludge activated sludge = 100 mg/L 3h

propylene carbonate

CAS: 108-32-7 -
EINECS: 203-
572-1 - INDEX:
607-194-00-1

a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio > 1000 mg/L 96h EU Method C1

a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna > 1000 mg/L 48h EU Method C2

a) Aquatic acute toxicity : EC50 Algae freshwater algae > 900 mg/L 72h OECD guideline 201

c) Bacteria toxicity : NOEC Pseudomonas putida = 7400 mg/L

12.2. Persistence and degradability

Component	Persistence/Degradability:	Test	Notes:
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Non-readily biodegradable	Oxygen consumption	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
propylene carbonate	Readily biodegradable	CO2 production	OECD guideline 301 B

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Bioaccumulative	BCF - Bioconcentration factor	31.000

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration $\geq 0.1\%$

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

N.A.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

N/A

14.2. UN proper shipping name

ADR-Shipping Name: N/A

IATA-Technical name: N/A

IMDG-Technical name: N/A

14.3. Transport hazard class(es)

ADR-Class: N/A

IATA-Class: N/A

IMDG-Class: N/A

14.4. Packing group

ADR-Packing Group: N/A

IATA-Packing group: N/A

IMDG-Packing group: N/A

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: N/A

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code): N/A

ADR Limited Quantities: N/A

ADR Excepted Quantities: N/A

Air (IATA):

IATA-Passenger Aircraft: N/A

IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A

IATA-Erg: N/A

IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage Code: N/A

IMDG-Stowage Note: N/A

IMDG-Subsidiary hazards: N/A

IMDG-Special Provisions: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

Class 2: hazardous for water.

SVHC Substances:

No SVHC substances present in concentration $\geq 0.1\%$

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

bis-[4-(2,3-epoxipropoxy)phenyl]propane

propylene carbonate

SECTION 16: Other information

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand


COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report
 DMEL: Derived Minimal Effect Level
 DNEL: Derived No Effect Level.
 DPD: Dangerous Preparations Directive
 DSD: Dangerous Substances Directive
 EC50: Half Maximal Effective Concentration
 ECHA: European Chemicals Agency
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 ES: Exposure Scenario
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 IC50: half maximal inhibitory concentration
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 IMDG: International Maritime Code for Dangerous Goods.
 INCI: International Nomenclature of Cosmetic Ingredients.
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care
 KAFH: Keep Away From Heat
 KSt: Explosion coefficient.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 LDLo: Leathal Dose Low
 N.A.: Not Applicable
 N/A: Not Applicable
 N/D: Not defined/ Not available
 NA: Not available
 NIOSH: National Institute for Occupational Safety and Health
 NOAEL: No Observed Adverse Effect Level
 OSHA: Occupational Safety and Health Administration
 PBT: Persistent, Bioaccumulative and Toxic
 PGK: Packaging Instruction
 PNEC: Predicted No Effect Concentration.
 PSG: Passengers
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 vPvB: Very Persistent, Very Bioaccumulative.
 WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 13: Disposal considerations
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information



Exposure Scenario

Propylene carbonate

Exposure Scenario, 07/06/2021

Substance identity	
	Propylene carbonate
CAS No.	108-32-7
INDEX No.	607-194-00-1
EINECS No.	203-572-1
Registration number	01-2119537232-48

Table of contents

1. **ES 1** Widespread use by professional workers; Adhesives, sealants (PC1)

1. ES 1		Widespread use by professional workers; Adhesives, sealants (PC1)	
1.1 TITLE SECTION			
Exposure Scenario name	Use in rigid foams, coatings, adhesives and sealants		
Date - Version	07/06/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Adhesives, sealants (PC1)		
Environment Contributing Scenario			
CS1	ERC8a		
Worker Contributing Scenario			
CS2 Hand application - finger paints, pastels, adhesives	PROC19		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8a)			
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid, vapour pressure < 10 Pa (Standard Temperature and Pressure)			
Vapour pressure: = 6 Pa			
Concentration of substance in product: Covers percentage substance in the product up to 100 %.			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Amounts used: Application rate = 35000 kg/ha			
Release type: Continuous release			
Emission days: 365 days per year			
<i>Technical and organisational conditions and measures</i>			
Control measures to prevent releases			
		Air - minimum efficiency of: = 100 % Water - minimum efficiency of: = 100 %	
<i>Other conditions affecting environmental exposure</i>			
Local marine water dilution factor: 100 Local freshwater dilution factor: 10 Receiving surface water flow: 18000 m ³ /day Indoor use			
1.2. CS2: Worker Contributing Scenario: Hand application - finger paints, pastels, adhesives (PROC19)			

Process Categories	Manual activities involving hand contact (PROC19)		
Product (article) characteristics			
Physical form of product: Liquid, vapour pressure < 10 Pa (Standard Temperature and Pressure)			
Vapour pressure: = 6 Pa			
Concentration of substance in product: Covers percentage substance in the product up to 100 %.			
Amount used, frequency and duration of use/exposure			
Duration: Covers use up to = 480 min/day			
Frequency: Covers frequency up to: = 5 days per week			
Technical and organisational conditions and measures			
Technical and organisational measures			
Provide a good standard of controlled ventilation (5 to 10 air changes per hour).		Inhalation - minimum efficiency of: = 70 %	
Conditions and measures related to personal protection, hygiene and health evaluation			
Personal protection			
Wear suitable face shield. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.		Dermal - minimum efficiency of: = 80 %	
Other conditions affecting worker exposure			
Indoor use Professional use Temperature: Covers use at ambient temperatures. 20°C			
1.3 Exposure estimation and reference to its source			
1.3. CS1: Environment Contributing Scenario (ERC8a)			
protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
Man via environment - Oral	N/A	ECETOC TRA environment v3	= 0.000933
1.3. CS2: Worker Contributing Scenario: Hand application - finger paints, pastels, adhesives (PROC19)			
Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 5.4857 mg/kg bw/day	ECETOC TRA worker v3	= 0.274286
inhalative, systemic, long-term	= 23.7781 mg/m ³	ECETOC TRA worker v3	= 0.336992
1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES			
Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least			

equivalent levels.

Exposure Scenario

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Exposure Scenario, 07/06/2021

Substance identity	
	bis-[4-(2,3-epoxipropoxy)phenyl]propane
CAS No.	1675-54-3
INDEX No.	603-073-00-2
EINECS No.	216-823-5
Registration number	01-2119456619-26

Table of contents

1. **ES 1** Widespread use by professional workers; ESC2_0000001

1. ES 1		Widespread use by professional workers; ESC2_0000001	
1.1 TITLE SECTION			
Exposure Scenario name	Professional application of coatings and inks - Etching agent - Resins (prepolymers) - Adhesion promotor		
Date - Version	27/05/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	ESC2_0000001		
Article Category(ies)	Other articles made of stone, plaster, cement, glass or ceramic (AC4g)		
Environment Contributing Scenario			
CS1	ERC8c - ERC8f		
Worker Contributing Scenario			
CS2 Material transfers	PROC8a		
CS3 Rolling, Brushing	PROC10		
CS4 Roller, spreader, flow application	PROC11		
CS5 Mixing operations - Manual	PROC19		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)			
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP			
Concentration of substance in product: Covers percentage substance in the product up to 100 %.			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Amounts used: Daily amount per site = 175 kg/day			
Release type: Continuous release			
Emission days: 365 days per year			
<i>Technical and organisational conditions and measures</i>			
Control measures to prevent releases Provide onsite wastewater removal efficiency of ³ (%):			
<i>Conditions and measures related to sewage treatment plant</i>			
STP type: Municipal Sewage Treatment Plant			
STP effluent (m³/day): 2			
<i>Conditions and measures related to treatment of waste (including article waste)</i>			
Waste treatment Dispose of waste cans and containers according to local regulations.			
<i>Other conditions affecting environmental exposure</i>			

Local marine water dilution factor: 100
Local freshwater dilution factor: 10
Receiving surface water flow: 18000 m³/day
Covers indoor and outdoor use

1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories	Roller application or brushing (PROC10)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
---------------------------	----------------------------------

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Wear suitable face shield.

Wear an impervious suit.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)**Process Categories**

Manual activities involving hand contact (PROC19)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 1 hour per day.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source**1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)**

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	= 0.0022 mg/L	EUSES	= 0.00022
marine sediment	= 0.00127 mg/L	EUSES	= 0.0128
freshwater sediment	= 0.012 mg/L	EUSES	= 0.0369
marine water	= 2.34E-05 mg/L	EUSES	= 0.029
soil	= 0.00142 mg/kg dry weight	EUSES	= 0.00722

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 0.84 mg/m ³	ECETOC TRA worker v2.0	0.07
dermal, systemic, long-term	= 0.2742 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.03

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 5E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 2.743 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.33

1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 0.36 mg/m ³	ECETOC TRA worker v2.0	0.03
dermal, systemic, long-term	= 2.68 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.32

1.3. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 2E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 1.414 mg/kg bw/day	ECETOC TRA worker v3	< 0.42
combined routes, systemic, long-term	N/A	ECETOC TRA worker v3	= 0.42

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

L34 EVOLUTION (B)

Date of first edition: 11/22/2021

Safety Data Sheet dated 01/08/2025

version 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: L34 EVOLUTION (B)

Trade code: S100B0289 31

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: hardener

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Ireland Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Members of the public Number (8 am-10 pm): +353 (0)1 809 2166

Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

Malta In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2 Causes skin irritation.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1A May cause an allergic skin reaction.

Aquatic Chronic 3 Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Danger

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264	Wash ... Thoroughly after handling.
P272	Contaminated work clothing must not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/...
P321	Specific treatment (see ... On this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with applicable regulations.

Contains

Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

2,4,6-tris(dimethylaminomethyl)phenol

Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

benzyl alcohol

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: L34 EVOLUTION (B)

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥ 10 -<20 %	Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	CAS:68082-29-1 EC:500-191-5	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Sens. 1A, H317, M-Chronic:1	01-2119972320-44
≥ 5 -<10 %	Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	CAS:68082-29-1 EC:500-191-5	Skin Irrit. 2, H315; Skin Sens. 1A, H317; Eye Irrit. 2, H319	01-2119972320-44
≥ 5 -<10 %	benzyl alcohol	CAS:100-51-6 EC:202-859-9 Index:603-057-00-5	Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin Sens. 1B, H317 Acute Toxicity Estimate : ATE - Oral : 1200 mg/kg bw	01-2119492630-38
≥ 3 -<5 %	2,4,6-tris(dimethylaminomethyl)phenol	CAS:90-72-2 EC:202-013-9 Index:603-069-00-0	Acute Tox. 4, H302; Skin Corr. 1C, H314; Eye Dam. 1, H318	01-2119560597-27

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:**7.2. Conditions for safe storage, including any incompatibilities**

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Community Occupational Exposure Limits (OEL)**

	OEL Type	Country	Occupational Exposure Limit
Calcium carbonate CAS: 471-34-1	NATIONAL	HUNGARY	Long Term: 10 mg/m ³ inhalable aerosol Source: 5/2020. (II. 6.) ITM
	NATIONAL	IRELAND	Long Term: 10 mg/m ³ Inhalable fraction Source: 2021 Code of Practice
	NATIONAL	IRELAND	Long Term: 4 mg/m ³ Respirable fraction Source: 2021 Code of Practice
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m ³ inhalable aerosol Source: EH40/2005 Workplace exposure limits
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m ³ respirable aerosol Source: EH40/2005 Workplace exposure limits
	NATIONAL	CROATIA	Long Term: 10 mg/m ³ U Source: NN 1/2021
	NATIONAL	CROATIA	Long Term: 4 mg/m ³ R Source: NN 1/2021
	NATIONAL	FRANCE	Long Term: 10 mg/m ³ Source: INRS outil65
	NATIONAL	LATVIA	Long Term: 6 mg/m ³ Source: KN325P1
	NATIONAL	POLAND	Long Term: 10 mg/m ³ 4) Source: Dz.U. 2018 poz. 1286
benzyl alcohol CAS: 100-51-6	SUVA	SWITZERLAND	Long Term: 3 mg/m ³ TWA mg/m ³ : (a), Formel / Formal, NIOSH Source: suva.ch/valeurs-limites
	NATIONAL	BULGARIA	Long Term: 5 mg/m ³ Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATIONAL	CZECHIA	Long Term: 40 mg/m ³ ; Short Term: Ceiling - 80 mg/m ³ Source: Nařízení vlády č. 361-2007 Sb
	NATIONAL	FINLAND	Long Term: 45 mg/m ³ - 10 ppm Source: HTP-ARVOT 2020
	NATIONAL	LATVIA	Long Term: 5 mg/m ³

Source: KN325P1

NATIONAL	LITHUANIA	Long Term: 5 mg/m3 O ₃ Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	POLAND	Long Term: 240 mg/m3 Source: Dz.U. 2018 poz. 1286
SUVA	SWITZERLAND	Long Term: 22 mg/m3 - 5 ppm R/H, SSC, VR / AW, NIOSH, La substance peut être présente sous forme de vapeur et d'aérosol en même temps / Der Stoff kann gleichzeitig als Dampf und Aerosol vorliegen Source: suva.ch/valeurs-limites
NATIONAL	GERMANY	Long Term: 22 mg/m3 DFG, H, Y, 11, 2 (I) Source: TRGS 900
NATIONAL	SLOVENIA	Long Term: 22 mg/m3 - 5 ppm; Short Term: 44 mg/m3 - 10 ppm K, Y Source: UL št. 72, 11. 5. 2021
Octanoic acid CAS: 124-02-7	NATIONAL LITHUANIA	Long Term: 1 mg/m3 O ₃ Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389

Predicted No Effect Concentration (PNEC) values

Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine
CAS: 68082-29-1

Exposure Route: Fresh Water; PNEC Limit: 4.34 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 43.4 µg/l
Exposure Route: Marine water; PNEC Limit: 434 ng/L
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 3.84 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 434.02 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 43.4 mg/kg
Exposure Route: Soil; PNEC Limit: 86.78 mg/kg

Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine
CAS: 68082-29-1

Exposure Route: Fresh Water; PNEC Limit: 4.34 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 43.4 µg/l
Exposure Route: Marine water; PNEC Limit: 434 ng/L
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 3.84 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 434.02 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 43.4 mg/kg
Exposure Route: Soil; PNEC Limit: 86.78 mg/kg

benzyl alcohol
CAS: 100-51-6

Exposure Route: Fresh Water; PNEC Limit: 1 mg/l

Exposure Route: Marine water; PNEC Limit: 0.1 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 5.27 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 0.527 mg/kg
Exposure Route: Intermittent releases (fresh water); PNEC Limit: 2.3 mg/l
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 39 mg/l
Exposure Route: Soil; PNEC Limit: 0.456 mg/kg
Exposure Route: Fresh Water; PNEC Limit: 84 µg/l

2,4,6-tris
(dimethylaminomethyl)
phenol
CAS: 90-72-2

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 840 µg/l
Exposure Route: Marine water; PNEC Limit: 8.4 µg/l

Derived No Effect Level (DNEL) values

Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine
CAS: 68082-29-1

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 3.9 mg/m³; Consumer: 970 µg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 1.1 mg/kg; Consumer: 560 µg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 560 µg/kg

Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine
CAS: 68082-29-1

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 3.9 mg/m³; Consumer: 970 µg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 1.1 mg/kg; Consumer: 560 µg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 560 µg/kg

benzyl alcohol
CAS: 100-51-6

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 22 mg/m³; Consumer: 8.1 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 450 mg/m³; Consumer: 40.5 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 9.5 mg/kg; Consumer: 5.7 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Professional: 47 mg/kg; Consumer: 28.5 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 5 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 25 mg/kg

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.

Protection for skin:

Chemical protection clothing.

Protection for hands:

Nitrile rubber .

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: Yellow

Odour: Like: Ammonia

Odour threshold: N.A.

pH: Not Relevant

Kinematic viscosity: <= 20,5 mm²/sec (40 °C)

Melting point/freezing point: N.A.

Boiling point or initial boiling point and boiling range: > 140 °C (284 °F)

Flash point: > 100°C / 212°F

Lower and upper explosion limit: N.A.
Relative vapour density: N.A.
Vapour pressure: N.A.
Density and/or relative density: 1.49 g/cm³
Solubility in water: N.A.
Solubility in oil: N.A.
Partition coefficient n-octanol/water (log value): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Flammability: N.A.
Volatile Organic compounds - VOCs = 8.68 % ; 129.27 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Dam. 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	a) acute toxicity LD50 Oral Rat > 2000 mg/kg
	LD50 Skin Rat > 2000 mg/kg 24h
c) serious eye damage/irritation	Eye Irritant Yes 1h

		Eye Corrosive Rabbit Positive	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 1000 mg/kg	
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg	
		LD50 Skin Rat > 2000 mg/kg 24h	
	c) serious eye damage/irritation	Eye Irritant Yes 1h	
	d) respiratory or skin sensitisation	Eye Corrosive Rabbit Positive Skin Sensitization Positive	Mouse
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 1000 mg/kg	
benzyl alcohol	a) acute toxicity	ATE - Oral : 1200 mg/kg bw LD50 Oral Rat = 1620 mg/kg LC50 Inhalation of aerosol Rat > 4178 mg/m ³ 4h LD50 Skin Rabbit > 2000 mg/kg 24h LC50 Inhalation Mist Rat = 4.18 mg/l 4h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes 24h	
	d) respiratory or skin sensitisation	Skin Sensitization Negative	Mouse
	f) carcinogenicity	Genotoxicity Negative Carcinogenicity Oral Rat Negative	Mouse
	g) reproductive toxicity	No Observed Adverse Effect Level Oral = 200 mg/kg	Mouse
	a) acute toxicity	LD50 Oral Rat = 2169 mg/kg	
		LD50 Skin Rat > 1 ml/Kg 6h	
2,4,6-tris(dimethylaminomethyl) phenol	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive 4h	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Negative	
	g) reproductive toxicity	No Observed Effect Level Oral Rat = 15 mg/kg	

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	CAS: 68082-29-1 - EINECS: 500-191-5	a) Aquatic acute toxicity : LC50 Fish = 10 mg/L 96h a) Aquatic acute toxicity : EC100 Daphnia = 10 mg/L 24h a) Aquatic acute toxicity : EC50 Algae = 4.34 mL/L 72h
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	CAS: 68082-29-1 - EINECS: 500-191-5	a) Aquatic acute toxicity : LC50 Fish = 10 mg/L 96h a) Aquatic acute toxicity : EC100 Daphnia = 10 mg/L 24h a) Aquatic acute toxicity : EC50 Algae = 4.34 mL/L 72h
benzyl alcohol	CAS: 100-51-6 - EINECS: 202-859-9 - INDEX: 603-057-00-5	a) Aquatic acute toxicity : LC50 Fish Oryzias latipes = 460 mg/L 96h OECD SIDS (2001) b) Aquatic chronic toxicity : NOEC Fish = 48.897 mg/L ECOSAR QSAR a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 230 mg/L 48h OECD SIDS (2001) b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 51 mg/L OECD Guideline 211 a) Aquatic acute toxicity : EC50 Algae Pseudokirchnerella subcapitata = 770 mg/L 72h OECD SIDS on Benzoates (2001) c) Bacteria toxicity : EC50 Nitrosomonas = 390 mg/L
2,4,6-tris(dimethylaminomethyl)phenol	CAS: 90-72-2 - EINECS: 202-013-9 - INDEX: 603-069-00-0	a) Aquatic acute toxicity : LC50 Fish Cyorinus carpio = 175 mg/L 96h a) Aquatic acute toxicity : LC50 Salmo gairdneri < 240 mg/L 96h a) Aquatic acute toxicity : LC50 Daphnia Palemonetes vulgaris = 718 mg/L 96h a) Aquatic acute toxicity : EC50 Algae freshwater algae = 84 mg/L

12.2. Persistence and degradability

Component	Persistence/Degradability:	Test	Value	Notes:
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Non-readily biodegradable			OECD 301 D
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Non-readily biodegradable			OECD 301 D
benzyl alcohol	Readily biodegradable	Dissolved organic carbon	96.000	%; OECD Guideline 301A
2,4,6-tris(dimethylaminomethyl)phenol	Non-readily biodegradable			

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value	Notes:
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Bioaccumulative	BCF - Bioconcentration factor	77.400	L/kg ww; QSAR
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Bioaccumulative	BCF - Bioconcentration factor	77.400	L/kg ww; QSAR

benzyl alcohol Bioaccumulative BCF - Bioconcentration factor 1.000 L/kg ww

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration $\geq 0.1\%$

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as hazardous waste

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

N.A.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

14.2. UN proper shipping name

ADR-Shipping Name: N/A

IATA-Shipping Name: N/A

IMDG-Shipping Name: N/A

14.3. Transport hazard class(es)

ADR-Class:

IATA-Class: N/A

IMDG-Class: N/A

14.4. Packing group

ADR-Packing Group:

IATA-Packing group: N/A

IMDG-Packing group: N/A

14.5. Environmental hazards

N.A.

IMDG-EMS: N/A

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code): N/A

ADR Limited Quantities: N/A

ADR Excepted Quantities: N/A

Air (IATA):

IATA-Passenger Aircraft: N/A

IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A

IATA-Erg: N/A

IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage and handling: N/A

IMDG-Segregation: N/A

IMDG-Subsidiary hazards: N/A

IMDG-Special Provisions: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2023/707

Regulation (EU) n. 2023/1434 (ATP 19 CLP)

Regulation (EU) n. 2023/1435 (ATP 20 CLP)

Regulation (EU) n. 2024/197 (ATP 21 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

None

Explosives precursors – Regulation 2019/1148

No substances listed

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

Class 2: hazardous for water.

German Lagerklasse according to TRGS 510:

LGK 10

SVHC Substances:

No SVHC substances present in concentration $\geq 0.1\%$

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

benzyl alcohol

2,4,6-tris(dimethylaminomethyl)phenol

SECTION 16: Other information

Code	Description
------	-------------

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1C	Skin Corr. 1C	Skin corrosion, Category 1C
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008 Classification procedure

Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1A, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.
 ES: Exposure Scenario
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 IC50: half maximal inhibitory concentration
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 IMDG: International Maritime Code for Dangerous Goods.
 INCI: International Nomenclature of Cosmetic Ingredients.
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care
 KAFH: Keep Away From Heat
 KSt: Explosion coefficient.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 LDLo: Leathal Dose Low
 N.A.: Not Applicable
 N/A: Not Applicable
 N/D: Not defined/ Not available
 NA: Not available
 NIOSH: National Institute for Occupational Safety and Health
 NOAEL: No Observed Adverse Effect Level
 OSHA: Occupational Safety and Health Administration
 PBT: Persistent, Bioaccumulative and Toxic
 PGK: Packaging Instruction
 PNEC: Predicted No Effect Concentration.
 PSG: Passengers
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 vPvB: Very Persistent, Very Bioaccumulative.
 WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 13: Disposal considerations
- SECTION 15: Regulatory information
- SECTION 16: Other information



Exposure Scenario

Benzyl alcohol

Exposure Scenario, 30/06/2021

Substance identity	
	Benzyl alcohol
CAS No.	100-51-6
INDEX No.	603-057-00-5
EINECS No.	202-859-9
Registration number	01-2119492630-38

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9b, PC9a, PC1, PC15); Building and construction work (SU19)

1. ES 1		Widespread use by professional workers; Various products (PC9b, PC9a, PC1, PC15); Building and construction work (SU19)	
1.1 TITLE SECTION			
Exposure Scenario name	Professional application of coatings and inks - Use in rigid foams, coatings, adhesives and sealants		
Date - Version	30/06/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22) - Building and construction work (SU19)		
Product Categories	Fillers, putties, plasters, modelling clay (PC9b) - Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1) - Non-metal surface treatment products (PC15)		
Environment Contributing Scenario			
CS1	ERC8a - ERC8d		
Worker Contributing Scenario			
CS2	PROC8a - PROC10		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8a, ERC8d)			
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid, vapour pressure < 10 Pa (Standard Temperature and Pressure)			
Vapour pressure: = 7 Pa			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Amounts used: Annual site tonnage = 1000 t(tonnes)/year			
Release type: Continuous release			
Emission days: 365 days per year			
<i>Conditions and measures related to sewage treatment plant</i>			
STP type: Municipal Sewage Treatment Plant Water - minimum efficiency of: = 87.36 %			
STP effluent (m³/day): 2000			
<i>Conditions and measures related to treatment of waste (including article waste)</i>			
Waste treatment Product residual disposal complies with applicable regulations.			
1.2. CS2: Worker Contributing Scenario (PROC8a, PROC10)			
Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Roller application or brushing (PROC8a, PROC10)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid			

Vapour pressure:

< 7 Pa

Amount used, frequency and duration of use/exposure**Duration:**

Covers use up to = 8 h/day

Technical and organisational conditions and measures**Technical and organisational measures**

Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed.
Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: = 90 %
---------------------------------------	--

Other conditions affecting worker exposure

Covers indoor and outdoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.**Body parts exposed:**

Assumes that potential dermal contact is limited to hands.

1.3 Exposure estimation and reference to its source**1.3. CS1: Environment Contributing Scenario (ERC8a, ERC8d)**

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	N/A	EUSES v2.1	< 0.01
freshwater sediment	N/A	EUSES v2.1	< 0.01
marine water	N/A	EUSES v2.1	< 0.01
marine sediment	N/A	EUSES v2.1	< 0.01
soil	N/A	EUSES v2.1	= 0.019
Man via environment - Inhalation	N/A	EUSES v2.1	< 0.01
Man via environment - Oral	N/A	EUSES v2.1	< 0.01

1.3. CS2: Worker Contributing Scenario (PROC8a, PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
combined routes, systemic, long-term	N/A	ECETOC TRA worker v3	0.977

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

2,4,6-tris(dimethylaminomethyl)phenol

Exposure Scenario, 05/11/2021

Substance identity	
	2,4,6-tris(dimethylaminomethyl)phenol
CAS No.	90-72-2
INDEX No.	603-069-00-0
EINECS No.	202-013-9
Registration number	01-2119560597-27

Table of contents

1. **ES 1** Widespread use by professional workers; Fillers, putties, plasters, modelling clay (PC9b)

1. ES 1		Widespread use by professional workers; Fillers, putties, plasters, modelling clay (PC9b)	
1.1 TITLE SECTION			
Exposure Scenario name	Road and construction applications - Use in rigid foams, coatings, adhesives and sealants		
Date - Version	05/11/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Fillers, putties, plasters, modelling clay (PC9b)		
Environment Contributing Scenario			
CS1		ERC8b - ERC8e	
Worker Contributing Scenario			
CS2 Material transfers		PROC8a	
CS3 Rolling, Brushing		PROC10	
CS4 Rolling, Brushing		PROC10	
CS5 Roller, spreader, flow application		PROC11	
CS6 Roller, spreader, flow application		PROC11	
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8b, ERC8e)			
Environmental release categories	Widespread use of reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) (ERC8b, ERC8e)		
Product (article) characteristics			
Physical form of product: Liquid			
Vapour pressure: 0.197 Pa			
Concentration of substance in product: Covers percentage substance in the product up to 100 %.			
Amount used, frequency and duration of use (or from service life)			
Amounts used: Amount per use <= 0.0014 tonnes/day			
Release type: Continuous release			
Conditions and measures related to sewage treatment plant			
STP type: No specific measures identified. Water - minimum efficiency of: = 0.059 %			
Conditions and measures related to treatment of waste (including article waste)			
Waste treatment This material and its container must be disposed of as hazardous.			
1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)			
Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities		

(PROC8a)	
Product (article) characteristics	
Physical form of product: Liquid	
Vapour pressure: = 0.197 Pa	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration: Duration of contact < 30 min	
Technical and organisational conditions and measures	
Technical and organisational measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	Inhalation - minimum efficiency of: 30 %
Local exhaust ventilation	Inhalation - minimum efficiency of: 80 %
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection	
Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. Wear a full face respirator conforming to EN136.	Dermal - minimum efficiency of: 90 % Inhalation - minimum efficiency of: 95 %
Use suitable eye protection.	
Other conditions affecting worker exposure	
Body parts exposed: Assumes that potential dermal contact is limited to hands.	
1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)	
Process Categories	Roller application or brushing (PROC10)
Product (article) characteristics	
Physical form of product: Liquid	
Vapour pressure: = 0.197 Pa	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration: Duration of contact < 440 min	
Technical and organisational conditions and measures	
Technical and organisational measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	Inhalation - minimum efficiency of: 44 %

Ensure that direction of application is only horizontal or downward.
Open doors and windows.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. Wear a full face respirator conforming to EN136. Wear suitable respiratory protection. Wear an impervious suit.	Dermal - minimum efficiency of: 90 % Inhalation - minimum efficiency of: 99 %
Use suitable eye protection.	

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

Body parts exposed:

Assumes that potential dermal contact is limited to hands.

1.2. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories	Roller application or brushing (PROC10)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

= 0.197 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Duration of contact < 440 min

Technical and organisational conditions and measures

Technical and organisational measures

Mechanical ventilation giving at least [ACH]:	Inhalation - minimum efficiency of: 44 %
Ensure that direction of application is only horizontal or downward.	
Open doors and windows.	

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. Wear a full face respirator conforming to EN136. Wear suitable respiratory protection. Wear an impervious suit.	Dermal - minimum efficiency of: 90 % Inhalation - minimum efficiency of: 99 %
--	--

Use suitable eye protection.

Other conditions affecting worker exposure

Outdoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

Body parts exposed:

Assumes that potential dermal contact is limited to hands.

1.2. CS5: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
---------------------------	----------------------------------

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

= 0.197 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Duration of contact < 4 h

Technical and organisational conditions and measures

Technical and organisational measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).	Inhalation - minimum efficiency of: 44 %
Ensure that direction of application is only horizontal or downward.	
Open doors and windows.	

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.	Dermal - minimum efficiency of: 90 % Inhalation - minimum efficiency of: 99 %
Wear a full face respirator conforming to EN136.	
Wear suitable respiratory protection.	
Wear an impervious suit.	
Use suitable eye protection.	

Other conditions affecting worker exposure

Indoor use

Professional use

Body parts exposed:

Assumes that potential dermal contact is limited to hands.

1.2. CS6: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
---------------------------	----------------------------------

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

= 0.197 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Duration of contact < 4 h

Technical and organisational conditions and measures

Technical and organisational measures

Mechanical ventilation giving at least [ACH]:	Inhalation - minimum efficiency of: 44 %
Ensure that direction of application is only horizontal or downward.	
Open doors and windows.	

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. Wear a full face respirator conforming to EN136. Wear suitable respiratory protection. Wear an impervious suit.	Dermal - minimum efficiency of: 90 % Inhalation - minimum efficiency of: 99 %
Use suitable eye protection.	

Other conditions affecting worker exposure

Outdoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

Body parts exposed:

Assumes that potential dermal contact is limited to hands.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8b, ERC8e)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.00172 mg/L	EUSES v2.1	0.037
freshwater sediment	0.00701 mg/kg dry weight	EUSES v2.1	0.027
marine water	0.00017 mg/L	EUSES v2.1	0.037
marine sediment	0.0007 mg/kg dry weight	EUSES v2.1	0.027
Sewage treatment plant	0.014 mg/L	EUSES v2.1	0.069
Agricultural soil	8E-05 mg/kg dry weight	EUSES v2.1	< 0.01
Man via environment - Inhalation	< 0.0001 mg/m ³	EUSES v2.1	< 0.01

Man via environment - Oral	< 0.0001 mg/kg bw/day	EUSES v2.1	< 0.01
----------------------------	-----------------------	------------	--------

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.023 mg/m ³	EASY TRA v3.6	0.004
inhalative, systemic, short-term	0.464 mg/m ³	EASY TRA v3.6	0.211
combined routes, systemic, long-term	N/A	N/A	0.247
dermal, systemic, long-term	0.03 mg/kg bw/day	RISKOFDERM v2.1	0.203

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.31 mg/m ³	ECETOC TRA worker v3	0.584
inhalative, systemic, short-term	0.4641238 mg/m ³	EASY TRA v3.6	0.59
combined routes, systemic, long-term	N/A	N/A	0.854
dermal, systemic, long-term	0.041 mg/kg bw/day	RISKOFDERM v2.1	0.27

1.3. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.039 mg/m ³	ECETOC TRA worker v3	0.073
inhalative, systemic, short-term	0.867 mg/m ³	EASY TRA v3.6	0.413
combined routes, systemic, long-term	N/A	N/A	0.343
dermal, systemic, long-term	0.041 mg/kg bw/day	RISKOFDERM v2.1	0.27

1.3. CS5: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.367 mg/m ³	ART v1.5	0.022
inhalative, systemic, short-term	0.023 mg/m ³	ART v1.5	0.011
combined routes, systemic, long-term	N/A	N/A	0.827
dermal, systemic, long-term	0.121 mg/kg bw/day	RISKOFDERM v2.1	0.805

1.3. CS6: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.019 mg/m ³	ART v1.5	0.037
inhalative, systemic, short-term	0.039 mg/m ³	ART v1.5	0.019
combined routes, systemic, long-term	N/A	N/A	0.101
dermal, systemic, long-term	0.05 mg/kg bw/day	RISKOFDERM v2.1	0.33

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.