

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

L34 FLEX

Date of first edition: 8/7/2020

Safety Data Sheet dated 10/03/2025

version 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: L34 FLEX

Trade code: S100B0022 41

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Adhesives/sealants for hardwood floors

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Ireland Poison information centre: 01 809 2166 (Daily 8am-10pm) In case of emergency call 999 or 112

Malta In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Special Provisions:

EUH208 Contains 3-aminopropyltriethoxysilane. May produce an allergic reaction.

EUH208 Contains Trimethoxyvinilsilane. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: L34 FLEX

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥0.5-<1 %	3-aminopropyltriethoxysilane	CAS:919-30-2 EC:213-048-4 Index:612-108-00-0	Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317	01-2119480479-24
≥0.5-<1 %	Trimethoxyvinilsilane	CAS:2768-02-7 EC:220-449-8 Index:014-049-00-0	Skin Sens. 1B, H317; Flam. Liq. 2, H225; Acute Tox. 4, H332	01-2119513215-52

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

N.A.

4.3. Indication of any immediate medical attention and special treatment needed

N.A.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
Limestone CAS: 1317-65-3	NATIONAL	BULGARIA	Long Term: 10 mg/m ³ Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATIONAL	ESTONIA	Long Term: 10 mg/m ³ Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	ESTONIA	Long Term: 5 mg/m ³ Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	GREECE	Long Term: 10 mg/m ³ εισπν Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL	GREECE	Long Term: 5 mg/m ³ αvapn Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL	GREECE	Long Term: 10 mg/m ³ εισπν. Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL	GREECE	Long Term: 5 mg/m ³ αvapn. Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL	HUNGARY	Long Term: 10 mg/m ³ N Source: 5/2020. (II. 6.) ITM rendelet
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)

	NORTHERN IRELAND	
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
NATIONAL	BELGIUM	Long Term: 10 mg/m ³ Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATIONAL	IRELAND	Long Term: 10 mg/m ³ Source: 2021 Code of Practice
NATIONAL	IRELAND	Long Term: 4 mg/m ³ Source: 2021 Code of Practice
Calcium carbonate CAS: 471-34-1	NATIONAL AUSTRALIA	Long Term: 10 mg/m ³ This value is for inhalable dust containing no asbestos and <1 % crystalline silica.
	NATIONAL HUNGARY	Long Term: 10 mg/m ³ inhalable aerosol Source: 5/2020. (II. 6.) ITM
	NATIONAL IRELAND	Long Term: 10 mg/m ³ Inhalable fraction Source: 2021 Code of Practice
	NATIONAL IRELAND	Long Term: 4 mg/m ³ Respirable fraction Source: 2021 Code of Practice
	NATIONAL UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m ³ inhalable aerosol Source: EH40/2005 Workplace exposure limits
	NATIONAL UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m ³ respirable aerosol Source: EH40/2005 Workplace exposure limits
	NATIONAL CROATIA	Long Term: 10 mg/m ³ U Source: NN 1/2021
	NATIONAL CROATIA	Long Term: 4 mg/m ³ R Source: NN 1/2021
	NATIONAL FRANCE	Long Term: 10 mg/m ³ Source: INRS outil65
	NATIONAL LATVIA	Long Term: 6 mg/m ³ Source: KN325P1
	NATIONAL POLAND	Long Term: 10 mg/m ³ 4) Source: Dz.U. 2018 poz. 1286
	SUVA SWITZERLAND	Long Term: 3 mg/m ³ TWA mg/m ³ : (a), Formel / Formal, NIOSH Source: suva.ch/valeurs-limites
3-aminopropyltriethoxysilane CAS: 919-30-2	NATIONAL FINLAND	Long Term: 28 mg/m ³ - 3 ppm; Short Term: 55 mg/m ³ - 6 ppm Source: HTP-ARVOT 2020

Triiron tetraoxide CAS: 1317-61-9	NATIONAL	POLAND	Long Term: 2.5 mg/m ³ ; Short Term: 5 mg/m ³ 6) Source: Dz.U. 2018 poz. 1286
	ACGIH		Long Term: 5 mg/m ³ (8h) R, A4 - Pneumoconiosis
Diiron trioxide CAS: 1309-37-1	NATIONAL	AUSTRALIA	Long Term: 5 mg/m ³ (8h)
	NATIONAL	BELGIUM	Long Term: 5 mg/m ³ Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	CROATIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ Source: NN 1/2021
	NATIONAL	CROATIA	Long Term: 10 mg/m ³ U Source: NN 1/2021
	NATIONAL	CROATIA	Long Term: 4 mg/m ³ R Source: NN 1/2021
	NATIONAL	IRELAND	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ Source: 2021 Code of Practice
	NATIONAL	IRELAND	Long Term: 10 mg/m ³ Source: 2021 Code of Practice
	NATIONAL	IRELAND	Long Term: 4 mg/m ³ Source: 2021 Code of Practice
	NATIONAL	ROMANIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ (Fumuri, pulberi) Source: Republicarea 1 - nr. 743 din 29 iulie 2021
	NATIONAL	SPAIN	Long Term: 5 mg/m ³ Source: LEP 2022
	NATIONAL	AUSTRIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ 60(Miw), 2x, MAK, A Source: GKV, BGBl. II Nr. 156/2021
	NATIONAL	BULGARIA	Long Term: 5 mg/m ³ Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATIONAL	DENMARK	Long Term: 3.5 mg/m ³ Source: BEK nr 2203 af 29/11/2021
	NATIONAL	ESTONIA	Long Term: 3.5 mg/m ³ 1 Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	FINLAND	Long Term: 5 mg/m ³ Fe Source: HTP-ARVOT 2020
	NATIONAL	FRANCE	Long Term: 5 mg/m ³ Source: INRS outil65
	NATIONAL	GREECE	Long Term: 10 mg/m ³ ; Short Term: 10 mg/m ³ Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL	HUNGARY	Long Term: 4 mg/m ³ resp, T Source: 5/2020. (II. 6.) ITM rendelet
	NATIONAL	LITHUANIA	Long Term: 3.5 mg/m ³ Žiūrėti 1 priedo 3 punktą. Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
	NATIONAL	NORWAY	Long Term: 3 mg/m ³ Source: FOR-2021-06-28-2248
	NATIONAL	POLAND	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ 4) Source: Dz.U. 2018 poz. 1286
	NATIONAL	POLAND	Long Term: 2.5 mg/m ³ ; Short Term: 5 mg/m ³ 6) Source: Dz.U. 2018 poz. 1286

methanol CAS: 67-56-1	NATIONAL	SLOVAKIA	Long Term: 1.5 mg/m ³ 11) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
	NATIONAL	SLOVAKIA	Long Term: 4 mg/m ³ 10) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
	NATIONAL	SWEDEN	Long Term: 3.5 mg/m ³ 3 Source: AFS 2021:3
	SUVA	SWITZERLAND	Long Term: 3 mg/m ³ TWA mg/m ³ : (a), Formel / Formal, NIOSH Source: suva.ch/valeurs-limites
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	ACGIH		Long Term: 200 ppm (8h); Short Term: 250 ppm Skin, BEI - Headache, eye dam, dizziness, nausea
	EU		Long Term: 260 mg/m ³ - 200 ppm (8h) Skin
	NATIONAL	AUSTRIA	Long Term: 260 mg/m ³ - 200 ppm; Short Term: 1040 mg/m ³ - 800 ppm 15(Miw), 4x, MAK, H Source: BGBl. II Nr. 156/2021
	NATIONAL	BULGARIA	Long Term: 260 mg/m ³ - 200 ppm Кожа Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATIONAL	CZECHIA	Long Term: 250 mg/m ³ ; Short Term: Ceiling - 1000 mg/m ³ D, B Source: Nařízení vlády č. 361-2007 Sb
	NATIONAL	DENMARK	Long Term: 260 mg/m ³ - 200 ppm EH Source: BEK nr 2203 af 29/11/2021
	NATIONAL	ESTONIA	Long Term: 250 mg/m ³ - 200 ppm; Short Term: 350 mg/m ³ - 250 ppm A Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	FINLAND	Long Term: 270 mg/m ³ - 200 ppm; Short Term: 330 mg/m ³ - 250 ppm iho Source: HTP-ARVOT 2020

NATIONAL	FRANCE	Long Term: 260 mg/m ³ - 200 ppm; Short Term: 1300 mg/m ³ - 1000 ppm Risque de pénétration percutanée Source: INRS outil65, article R. 4412-149 du Code du travail
NATIONAL	GREECE	Long Term: 260 mg/m ³ - 200 ppm; Short Term: 325 mg/m ³ - 250 ppm Δ Source: ΦΕΚ 94/Α` 13.5.1999
NATIONAL	HUNGARY	Long Term: 260 mg/m ³ b, i, BEM, EU2, R+T Source: 5/2020. (II. 6.) ITM rendelet
NATIONAL	LITHUANIA	Long Term: 260 mg/m ³ - 200 ppm

		O Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	NETHERLANDS	Long Term: 133 mg/m ³ H Source: Arbeidsomstandighedenregeling - Lijst A
NATIONAL	NORWAY	Long Term: 130 mg/m ³ - 100 ppm H E Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 100 mg/m ³ ; Short Term: 300 mg/m ³ skóra Source: Dz.U. 2018 poz. 1286
NATIONAL	SLOVAKIA	Long Term: 260 mg/m ³ - 200 ppm K, 7) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATIONAL	SWEDEN	Long Term: 250 mg/m ³ - 200 ppm; Short Term: 350 mg/m ³ - 250 ppm H, V Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 260 mg/m ³ - 200 ppm; Short Term: 520 mg/m ³ - 400 ppm R/H, SSC, B, SNC / ZNS, INRS NIOSH Source: suva.ch/valeurs-limites
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 266 mg/m ³ - 200 ppm; Short Term: 333 mg/m ³ - 250 ppm Sk Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
NATIONAL	BELGIUM	Long Term: 266 mg/m ³ - 200 ppm; Short Term: 333 mg/m ³ - 250 ppm D Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATIONAL	CROATIA	Long Term: 260 mg/m ³ - 200 ppm koža Source: 2006/15/EZ
NATIONAL	CYPRUS	Long Term: 260 mg/m ³ - 200 ppm δέρμα Source: Οι περί Ασφάλειας και Υγείας στην Εργασία (Χημικοί Παράγοντες) Κανονισμοί του 2001 έως 2021
NATIONAL	GERMANY	Long Term: 130 mg/m ³ - 100 ppm DFG, EU, H, Y, 2(II) Source: TRGS 900
NATIONAL	IRELAND	Long Term: 260 mg/m ³ - 200 ppm Sk, IOELV Source: 2021 Code of Practice
NATIONAL	ITALY	Long Term: 260 mg/m ³ - 200 ppm Cute Source: D.lgs. 81/2008, Allegato XXXVIII
NATIONAL	LATVIA	Long Term: 260 mg/m ³ - 200 ppm Āda Source: KN325P1
NATIONAL	LUXEMBOURG	Long Term: 260 mg/m ³ - 200 ppm Peau Source: Mémorial A n.226 du 22 mars 2021
NATIONAL	MALTA	Long Term: 260 mg/m ³ - 200 ppm skin Source: S.L.424.24
NATIONAL	PORTUGAL	Long Term: 260 mg/m ³ - 200 ppm Cutânea Source: Decreto-Lei n.º 1/2021
NATIONAL	ROMANIA	Long Term: 260 mg/m ³ - 200 ppm P, Dir. 2006/15 Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATIONAL	SLOVENIA	Long Term: 260 mg/m ³ - 200 ppm; Short Term: 1040 mg/m ³ - 800 ppm

Predicted No Effect Concentration (PNEC) values

3-aminopropyltriethoxysilane
CAS: 919-30-2
Exposure Route: Fresh Water; PNEC Limit: 330 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 3.3 mg/l
Exposure Route: Marine water; PNEC Limit: 33 µg/l
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 13 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 1.2 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 120 µg/kg
Exposure Route: Soil; PNEC Limit: 50 µg/kg

Trimethoxyvinilsilane
CAS: 2768-02-7
Exposure Route: Fresh Water; PNEC Limit: 400 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 2.4 mg/l
Exposure Route: Marine water; PNEC Limit: 40 µg/l
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 6.6 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 1.5 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 150 µg/kg
Exposure Route: Soil; PNEC Limit: 60 µg/kg

Derived No Effect Level (DNEL) values

3-aminopropyltriethoxysilane
CAS: 919-30-2
Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 59 mg/m³; Consumer: 17.4 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 59 mg/m³; Consumer: 17.4 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 8.3 mg/kg; Consumer: 5 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Professional: 8.3 mg/kg; Consumer: 5 mg/kg

Trimethoxyvinilsilane
CAS: 2768-02-7
Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 27.6 mg/m³; Consumer: 6.7 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 260 mg/m³; Consumer: 50 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Professional: 3.9 mg/kg; Consumer: 7.8 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 300 µg/kg

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing.

Protection for hands:

Nitrile rubber .

Respiratory protection:

N.A.

Thermal Hazards:

Not expected if used as intended

Environmental exposure controls:

Prevent the product from entering sewers or surface and underground water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Brown
Odour: Light
Odour threshold: N.A.
pH: N.A.
Kinematic viscosity: N.A.
Melting point/freezing point: N.A.
Boiling point or initial boiling point and boiling range: N.A.
Flash point: > 93°C
Lower and upper explosion limit: N.A.
Relative vapour density: N.A.
Vapour pressure: N.A.
Density and/or relative density: 1.64 g/cm³
Solubility in water: Insoluble
Solubility in oil: N.A.
Partition coefficient n-octanol/water (log value): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Flammability: N.A.
Volatile Organic compounds - VOCs = 0.00 % ; 0.02 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified Based on available data, the classification criteria are not met
c) serious eye damage/irritation	Not classified Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	Not classified Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met

h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

3-aminopropyltriethoxysilane	a) acute toxicity	LD50 Oral Rat = 1460 mg/kg	
		LC50 Inhalation Vapour Rat Negative 6h	
		LD50 Skin Rabbit = 4076 mg/kg 24h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Positive	
	f) carcinogenicity	Genotoxicity Negative	Mouse intraperitoneal route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 600 mg/kg	
Trimethoxyvinylsilane	a) acute toxicity	LD50 Oral Rat = 7.34 ml/Kg	
		LC50 Inhalation Vapour Rat = 2773 Ppm 4h	
		LD50 Skin Rabbit = 3.36 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative 24h	
	c) serious eye damage/irritation	Eye Irritant Rabbit No 24h	
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Positive	
	f) carcinogenicity	Genotoxicity Rat Negative	Inhalation route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 250 mg/kg	

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
3-aminopropyltriethoxysilane	CAS: 919-30-2 - EINECS: 213-048-4 - INDEX: 612-108-00-0	a) Aquatic acute toxicity : LC50 Fish Brachydanio rerio > 934 mg/L 96h
		a) Aquatic acute toxicity : EC50 Daphnia magna = 331 mg/L 48h
		a) Aquatic acute toxicity : EC50 Algae Scenedesmus subspicatus > 1000 mg/L 72h
		c) Bacteria toxicity : EC50 Pseudomonas putida = 43 mg/L
Trimethoxyvinylsilane	CAS: 2768-02-7	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 137 mg/L 96h

- EINECS: 220-449-8 - INDEX: 014-049-00-0

- a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 121 mg/L 48h
b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 20 mg/L - 21days
a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata > 89 mg/L 72h
a) Aquatic acute toxicity : EC10 microorganisms > 100 mg/L 3h OECD 209

12.2. Persistence and degradability

Component	Persitence/Degradability:	Test	Value	Notes:
3-aminopropyltriethoxysilane	Non-readily biodegradable	Dissolved organic carbon	67.000	%; EU method C4-A; 28days
Trimethoxyvinilsilane	Readily biodegradable			

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value	Notes:
3-aminopropyltriethoxysilane	Bioaccumulative	BCF - Bioconcentration factor	3.400	OECD 305

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration $\geq 0.1\%$

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as non-hazardous waste

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

N/A

14.2. UN proper shipping name

ADR-Shipping Name: N/A

IATA-Technical name: N/A

IMDG-Technical name: N/A

14.3. Transport hazard class(es)

ADR-Class: N/A

IATA-Class: N/A

IMDG-Class: N/A

14.4. Packing group

ADR-Packing Group: N/A

IATA-Packing group: N/A

IMDG-Packing group: N/A

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: N/A

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: N/A
ADR - Hazard identification number: N/A
ADR-Special Provisions: N/A
ADR-Transport category (Tunnel restriction code): N/A
ADR Limited Quantities: N/A
ADR Excepted Quantities: N/A

Air (IATA):

IATA-Passenger Aircraft: N/A
IATA-Cargo Aircraft: N/A
IATA-Label: N/A
IATA-Subsidiary hazards: N/A
IATA-Erg: N/A
IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage Code: N/A
IMDG-Stowage Note: N/A
IMDG-Subsidiary hazards: N/A
IMDG-Special Provisions: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: None.

Restrictions related to the substances contained: 40, 69, 75

Provisions related to directive EU 2012/18 (Seveso III):

None

Explosives precursors – Regulation 2019/1148

No substances listed

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

NWG: Not hazardous for water

German Lagerklasse according to TRGS 510:

LGK 10

SVHC Substances:

No SVHC substances present in concentration $\geq 0.1\%$

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

3-aminopropyltriethoxysilane

Trimethoxyvinylsilane

SECTION 16: Other information

Code	Description
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.

Code	Hazard class and hazard category	Description
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 IC50: half maximal inhibitory concentration
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 IMDG: International Maritime Code for Dangerous Goods.
 INCI: International Nomenclature of Cosmetic Ingredients.
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care
 KAFH: Keep Away From Heat
 KSt: Explosion coefficient.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 LDLo: Leathal Dose Low
 N.A.: Not Applicable
 N/A: Not Applicable
 N/D: Not defined/ Not available
 NA: Not available
 NIOSH: National Institute for Occupational Safety and Health
 NOAEL: No Observed Adverse Effect Level
 OSHA: Occupational Safety and Health Administration
 PBT: Persistent, Bioaccumulative and Toxic
 PGK: Packaging Instruction
 PNEC: Predicted No Effect Concentration.
 PSG: Passengers
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 vPvB: Very Persistent, Very Bioaccumulative.
 WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 13: Disposal considerations
- SECTION 14: Transport information
- SECTION 15: Regulatory information



Exposure Scenario

Trimethoxyvinilsilane

Exposure Scenario, 08/06/2021

Substance identity	
	Trimethoxyvinilsilane
CAS No.	2768-02-7
INDEX No.	014-049-00-0
EINECS No.	220-449-8
Registration number	01-2119513215-52

Table of contents

1. ES 1

1. ES 1

1.1 TITLE SECTION

Exposure Scenario name	Use in rigid foams, coatings, adhesives and sealants - Barrier (Sealant)
Date - Version	18/05/2021 - 1.0
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22) - Building and construction work (SU19)
Product Categories	Adhesives, sealants (PC1)

Environment Contributing Scenario

CS1 Low environmental release	ERC8c - ERC8f
-------------------------------	---------------

Worker Contributing Scenario

CS2 Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application	PROC0
CS3 Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application	PROC1

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Low environmental release (ERC8c, ERC8f)

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Concentration after dilution for use maximum [%]: 0.7 %

Amount used, frequency and duration of use (or from service life)

Amounts used:

Daily amount per site = 0.28 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

	Water - minimum efficiency of: 1.5 %
--	--------------------------------------

Conditions and measures related to sewage treatment plant

STP type:

Onsite Sewage Treatment Plant

Water - minimum efficiency of: = 0.013 %

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Dispose of waste product or used containers according to local regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 20000 m³/day

Covers indoor and outdoor use	
1.2. CS2: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC0)	
Process Categories	Other (PROC0)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Concentration of substance in product: Covers concentrations up to 0.7 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Exposure duration ≤ 6 h Frequency: Use frequency = 250 days per year	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). For further specification, refer to section 8 of the SDS.	
<i>Other conditions affecting worker exposure</i>	
Covers indoor and outdoor use Professional use Room size: Covers use in room size of = 20 m ³ Temperature: Covers use at ambient temperatures. 25°C	
1.2. CS3: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC1)	
Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Concentration of substance in product: Covers concentrations up to 2 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Exposure duration = 8 h Frequency: Use frequency = 1 days per year	
Duration: Covers use up to = 6 h Frequency: Use frequency = 1 days per year	
<i>Other conditions affecting worker exposure</i>	
Covers indoor and outdoor use Professional use Room size: Covers use in room size of = 20 m ³ Ventilation rate: = 0.6 ach (air changes per hour)	
1.3 Exposure estimation and reference to its source	
1.3. CS2: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC0)	

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, long-term	= 1.9 mg/m ³	N/A	= 0.069
dermal, long-term	= 4.53 mg/kg bw/day	ConsExpo	= 0.038
combined routes, long-term	N/A	N/A	0.107

1.3. CS3: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, long-term	= 4.57 mg/m ³	N/A	= 0.682
dermal, long-term	= 0.044 mg/kg bw/day	ConsExpo	< 0.01
combined routes, short-term	N/A	N/A	0.682

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

3-aminopropyltriethoxysilane

Exposure Scenario, 14/07/2021

Substance identity	
	3-aminopropyltriethoxysilane
CAS No.	919-30-2
INDEX No.	612-108-00-0
EINECS No.	213-048-4
Registration number	01-2119480479-24

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9a, PC1)

1. ES 1		Widespread use by professional workers; Various products (PC9a, PC1)
1.1 TITLE SECTION		
Exposure Scenario name	Professional application of coatings and inks by spraying - Use in rigid foams, coatings, adhesives and sealants	
Date - Version	14/07/2021 - 1.0	
Life Cycle Stage	Widespread use by professional workers	
Main user group	Professional uses	
Sector(s) of use	Professional uses (SU22)	
Product Categories	Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1)	
Worker Contributing Scenario		
CS1 Rolling, Brushing	PROC10	
CS2 Roller, spreader, flow application	PROC11	
1.2 Conditions of use affecting exposure		
1.2. CS1: Worker Contributing Scenario: Rolling, Brushing (PROC10)		
Process Categories	Roller application or brushing (PROC10)	
Product (article) characteristics		
Physical form of product: Liquid		
Concentration of substance in product: Covers concentrations up to 2 %		
Amount used, frequency and duration of use/exposure		
Amounts used: Annual site tonnage = 0.2 t(tonnes)/year Daily amount per site = 0.5 kg/day		
Duration: Exposure duration = 4 h		
Frequency: Covers exposure up to = 365 days per year		
Technical and organisational conditions and measures		
Technical and organisational measures Provide a basic standard of general ventilation (1 to 3 air changes per hour). Use in contained systems For further specification, refer to section 8 of the SDS.		
Conditions and measures related to personal protection, hygiene and health evaluation		
Personal protection Wear suitable respiratory protection. For further specification, refer to section 8 of the SDS.		
1.2. CS2: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)		
Process Categories	Non industrial spraying (PROC11)	
Product (article) characteristics		
Physical form of product: Liquid		
Concentration of substance in product: Covers concentrations up to 2 %		

Amount used, frequency and duration of use/exposure

Amounts used:

Annual site tonnage = 0.2 t(tonnes)/year
Daily amount per site = 0.5 kg/day

Duration:

Exposure duration = 4 h

Frequency:

Covers exposure up to = 365 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).
Use in contained systems
For further specification, refer to section 8 of the SDS.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable respiratory protection.
For further specification, refer to section 8 of the SDS.

1.3 Exposure estimation and reference to its source

1.3. CS1: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal	= 0.055 mg/kg bw/day	ECETOC TRA worker v3	N/A
inhalative	= 1.8 mg/m ³	ECETOC TRA worker v3	N/A

1.3. CS2: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal	= 0.21 mg/kg bw/day	ECETOC TRA worker v3	N/A
inhalative	= 46 mg/m ³	ECETOC TRA worker v3	N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.