

#### **Safety Data Sheet**

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

#### SILICONE COLOR

Date of first edition: 2/26/2021 Safety Data Sheet dated 29/08/2025

version 5

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Mixture identification:

Trade name: SILICONE COLOR

Trade code: FBIFC702-

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Adhesives, sealants

Uses advised against: All uses other than recommended ones **1.3. Details of the supplier of the safety data sheet** 

Company: KERAKOLL France

25, avenue de l'Industrie - 69960 Corbas - France

Tel. +33 472 890 684 safety@kerakoll.com

#### 1.4. Emergency telephone number

European emergency phone number 112

Ireland Emergency medical information: (seven days) contact National Poisons Information Centre,

Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

Malta In case of emergency call: +356 2395 2000 (24h)

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) n. 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

DECL<sub>10</sub>

This titanium dioxide-containing product is not classified as carcinogen by inhalation because it does not meet the criteria stated in Note 10, Annex VI of Regulation (EC) 1272/2008.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu$ m.

Adverse physicochemical, human health and environmental effects:

No other hazards

## 2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

#### **Special Provisions:**

EUH208 Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

## Special provisions according to Annex XVII of REACH and subsequent amendments:

Restricted to professional users.

#### 2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: No other hazards

## **SECTION 3: Composition/information on ingredients**

## 3.1. Substances

Date 29/08/2025 Production Name SILICONE COLOR Page n. 1 of 12

#### 3.2. Mixtures

Mixture identification: SILICONE COLOR

#### Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥5-<10 %	Distillates (petroleum), hydrotreated middle; Gasoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205oC to 400oC (401 oF to 752 oF).]	CAS:64742-46-7 EC:265-148-2 Index:649-221-00-X	Asp. Tox. 1, H304	
≥1-<3 %	Titanium dioxide	CAS:13463-67-7 EC:236-675-5	Not classified as hazardous	
<0.0015 %	4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)	EC:264-843-8	Acute Tox. 2, H330; Acute Tox. 4, H302; Skin Corr. 1, H314; Eye Dam. 1, H318; Skin Sens. 1A, H317; Aquatic Acute 1, H400; Aquatic Chronic 1, H410, M-Chronic:100, M-Acute:100, EUH071  Specific Concentration Limits: $0.025\% \le C < 5\%$ : Skin Irrit. 2 H315 $0.025\% \le C < 3\%$ : Eye Irrit. 2 H319 $C \ge 0.0015\%$ : Skin Sens. 1A H317 Acute Toxicity Estimate: ATE - Oral: 567mg/kg bw ATE - Inhalation (Dust/mist): $0.16$ mg/l	

This mixture contains >= 1% titanium dioxide (CAS 13463-67-7). The Annex VI classification of titanium dioxide does not apply to this mixture according to its Note 10.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

## 4.2. Most important symptoms and effects, both acute and delayed

N.A

#### 4.3. Indication of any immediate medical attention and special treatment needed

N.A.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

Date 29/08/2025 Production Name SILICONE COLOR Page n. 2 of 12

### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

#### 5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

#### For emergency responders:

Wear personal protection equipment.

## 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

#### 6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

#### 6.4. Reference to other sections

See also section 8 and 13

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

## Advice on general occupational hygiene:

#### 7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

## 7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Community Occupational Exposure Limits (OEL)			
	OEL Type	Country	Occupational Exposure Limit
Titanium dioxide CAS: 13463-67-7	ACGIH		Long Term: 2.5 mg/m3 (8h) Finescale particles; R; A3 - LRT irr, pneumoconiosis
	NATIONAL	GERMANY	Long Term: 0.3 mg/m3; Short Term: 2.4 mg/m3 DFG; Long term and short term: excluding ultrafine particles; respirable fraction; multiplied by the material density; Source: TRGS900
	NATIONAL	BELGIUM	Long Term: 10 mg/m3 Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	CROATIA	Long Term: 10 mg/m3 U Source: NN 1/2021

Date 29/08/2025 **Production Name** SILICONE COLOR Page n. 3 of 12 NATIONAL CROATIA Long Term: 4 mg/m3

Source: NN 1/2021

Long Term: 10 mg/m3 NATIONAL IRELAND

Source: 2021 Code of Practice

NATIONAL IRELAND Long Term: 4 mg/m3

Source: 2021 Code of Practice

Long Term: 10 mg/m3; Short Term: 15 mg/m3 NATIONAL ROMANIA

Source: Republicarea 1 - nr. 743 din 29 iulie 2021

NATIONAL SPAIN Long Term: 10 mg/m3

Source: LEP 2022

NATIONAL AUSTRIA Long Term: 5 mg/m3; Short Term: 10 mg/m3

60(Miw), 2x, MAK, A

Source: BGBl. II Nr. 156/2021

NATIONAL BULGARIA Long Term: 10 mg/m3

Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.

NATIONAL DENMARK Long Term: 6 mg/m3

Source: BEK nr 2203 af 29/11/2021

NATIONAL ESTONIA Long Term: 5 mg/m3

Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105

NATIONAL FRANCE Long Term: 10 mg/m3

Cancérogène de catégorie 2 Source: INRS outil65

NATIONAL GREECE Long Term: 10 mg/m3

εισπν.

Source: ΦΕΚ 94/A` 13.5.1999

NATIONAL GREECE Long Term: 5 mg/m3

Source: ΦΕΚ 94/A` 13.5.1999

NATIONAL LATVIA Long Term: 10 mg/m3

Source: KN325P1

Long Term: 5 mg/m3 NATIONAL LITHUANIA

Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389

NATIONAL NORWAY Long Term: 5 mg/m3

Source: FOR-2021-06-28-2248

NATIONAL POLAND Long Term: 10 mg/m3

4), 7)

Source: Dz.U. 2018 poz. 1286

NATIONAL SLOVAKIA Long Term: 5 mg/m3

Source: 355 NARIADENIE VLÁDY z 10. mája 2006

NATIONAL SWEDEN Long Term: 5 mg/m3

Source: AFS 2021:3

SUVA SWITZERLAN Long Term: 3 mg/m3

D TWA mg/m3: (a), SSC, Formel / Formal, NIOSH

Source: suva.ch/valeurs-limites

WEL-EH40 UNITED Long Term: 10 mg/m3

KINGDOM OF Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)

**GREAT BRITAIN AND NORTHERN IRELAND** 

Carbon black **ACGIH** Long Term: 3 mg/m3 (8h)

CAS: 1333-86-4

I, A3 - Bronchitis

NATIONAL SWEDEN Long Term: 3 mg/m3

Source: AFS 2021:3

NATIONAL BELGIUM Long Term: 3 mg/m3

29/08/2025 **Production Name** SILICONE COLOR Page n. 4 of Date

Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1

NATIONAL CROATIA Long Term: 3.5 mg/m3; Short Term: 7 mg/m3

Source: NN 1/2021

NATIONAL IRELAND Long Term: 3 mg/m3

Ι

Source: 2021 Code of Practice

NATIONAL SPAIN Long Term: 3.5 mg/m3

Source: LEP 2022

NATIONAL DENMARK Long Term: 3.5 mg/m3

Κ

Source: BEK nr 2203 af 29/11/2021

NATIONAL FINLAND Long Term: 3.5 mg/m3; Short Term: 7 mg/m3

Source: HTP-ARVOT 2020

NATIONAL FRANCE Long Term: 3.5 mg/m3

Source: INRS outil65

NATIONAL GREECE Long Term: 3.5 mg/m3; Short Term: 7 mg/m3

Source: ΦΕΚ 94/A` 13.5.1999

NATIONAL HUNGARY Long Term: 3 mg/m3

belélegezhető koncentráció

Source: 5/2020. (II. 6.) ITM rendelet

NATIONAL NORWAY Long Term: 3.5 mg/m3

Source: FOR-2021-06-28-2248

NATIONAL POLAND Long Term: 4 mg/m3

4)

Source: Dz.U. 2018 poz. 1286

WEL-EH40 UNITED Long Term: 3.5 mg/m3; Short Term: 7 mg/m3

KINGDOM OF Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)

GREAT BRITAIN AND NORTHERN IRELAND

## **Predicted No Effect Concentration (PNEC) values**

Distillates (petroleum), Exposure Route: Secondary poisoning; PNEC Limit: 17000 mg/kg hydrotreated middle; Gasoil - unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205oC to 400oC (401 oF to 752

oF).] CAS: 64742-46-7

Exposure Route: Secondary poisoning; PNEC Limit: 17000 mg/kg

Titanium dioxide CAS: 13463-67-7

Exposure Route: Fresh Water; PNEC Limit: 0.184 mg/l

Exposure Route: Marine water; PNEC Limit: 0.018 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 1 mg/kg
Exposure Route: Intermittent releases (marine water); PNEC Limit: 100 mg/kg
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/kg

## **Derived No Effect Level (DNEL) values**

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified; [A complex combination of Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Professional: 16.4 mg/m³; Consumer: 4.85 mg/m³

Date 29/08/2025 Production Name SILICONE COLOR Page n. 5 of 12

hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205oC to 400oC (401 oF to 752 oF).]

CÁS: 64742-46-7

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Worker Professional: 2.91 mg/kg; Consumer: 1.25 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 1.25 mg/kg

Titanium dioxide Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

CAS: 13463-67-7 Worker Professional: 10 mg/m<sup>3</sup>

#### 8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: In compliance with the product description

Odour: Pungent Odour threshold: N.A.

pH: N.A.

Kinematic viscosity: N.A.

Melting point/freezing point: N.A.

Boiling point or initial boiling point and boiling range: N.A.

Flash point: 400 °C (752 °F)

Lower and upper explosion limit: N.A.

Relative vapour density: N.A. Vapour pressure: N.A.

Density and/or relative density: 1.04 g/cm3

Solubility in water: N.A. Solubility in oil: N.A.

Partition coefficient n-octanol/water (log value): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Flammability: N.A.

Volatile Organic compounds - VOCs = 10.52 %; 109.85 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

Viscosity: 80,000.00 cPo No other relevant information

Date 29/08/2025 **Production Name** SILICONE COLOR Page n. 6 of 12

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

Stable under normal conditions

#### 10.2. Chemical stability

Data not available.

#### 10.3. Possibility of hazardous reactions

None.

#### 10.4. Conditions to avoid

Stable under normal conditions.

#### 10.5. Incompatible materials

None in particular.

## 10.6. Hazardous decomposition products

None.

#### **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological Information of the Preparation

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

c) serious eye damage/irritation Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

## Toxicological information on main components of the mixture:

Distillates (petroleum), hydrotreated middle; Gasoil - unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205oC to 400oC (401 oF to 752 oF).]

a) acute toxicity LD50 Oral Rat > 5000 mg/kg

LC50 Inhalation of aerosol Rat = 4.6 mg/l 4h LD50 Skin Rabbit > 2000 mg/kg 24h

b) skin corrosion/irritation Skin Irritant Rabbit Positive 24h

c) serious eye

Eye Irritant Rabbit No

damage/irritation

d) respiratory or skin Skin Sensitization Guineapig Negative

Date 29/08/2025 Production Name SILICONE COLOR Page n. 7 of 12

sei	1 CIT	102	ıtı	$\sim$	r

f) carcinogenicity Genotoxicity Rat Negative Carcinogenicity Positive g) reproductive toxicity No Observed Adverse Effect Level Skin Rat = 1 mg/kg Titanium dioxide a) acute toxicity LD50 Oral Rat > 5000 mg/kg LC50 Inhalation > 6.82 mg/l LD50 Skin Rat > 2000 mg/kg c) serious eye Eye Corrosive Negative damage/irritation Eye Irritant No d) respiratory or skin Skin Sensitization Negative sensitisation i) STOT-repeated No Observed Adverse Effect Level 1000 exposure 4,5-dichloro-2-octyl-2H- a) acute toxicity

isothiazol-3-one (DCOIT)

ATE - Oral: 567 mg/kg bw

ATE - Inhalation (Dust/mist): 0.16 mg/l

#### 11.2. Information on other hazards

## **Endocrine disrupting properties:**

No endocrine disruptor substances present in concentration >= 0.1%

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Component

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

Ident. Numb.

## List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

## List of Eco-Toxicological properties of the components

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205oC to 400oC (401 oF to 752 oF).]	7 - EINECS: 265-148-2 - INDEX: 649-	a) Aquatic acute toxicity: LL50 Fish freshwater fish = 21 mg/L 96h
		b) Aquatic chronic toxicity: NOEC Fish freshwater fish = $0.069 \text{ mg/L}$
		a) Aquatic acute toxicity: EL50 Daphnia = 68 mg/L 48h
		b) Aquatic chronic toxicity: NOEC Daphnia = 0.163 mg/L - 21days
		a) Aquatic acute toxicity: EL50 Algae = 22 mg/L 72h
		c) Bacteria toxicity: EL50 Tetrahymena pyriformis > 1000 mg/L - 40hr
Titanium dioxide	CAS: 13463-67- 7 - EINECS: 236-675-5	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas (Cavedano americano) > 1000 mg/L 96h

**Ecotox Data** 

Date 29/08/2025 **Production Name** SILICONE COLOR Page n. 8 of 12

cloroficee) > 100 mg/L 72h

a) Aquatic acute toxicity: NOEC Algae = 5600 mg/L

a) Aquatic acute toxicity: EC50 Algae Pseudokirchneriella subcapitata (alghe

#### 12.2. Persistence and degradability

## Component

#### Persitence/Degradability:

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of

Readily biodegradable

## 12.3. Bioaccumulative potential

approximately 205oC to 400oC

N.A

(401 oF to 752 oF).]

#### 12.4. Mobility in soil

N.A

## 12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration >= 0.1%

#### 12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

#### 12.7. Other adverse effects

N.A.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as non-hazardous waste

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

#### Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

N.A.

## **SECTION 14: Transport information**

Not classified as dangerous in the meaning of transport regulations.

#### 14.1. UN number or ID number

N/A

#### 14.2. UN proper shipping name

ADR-Shipping Name: N/A IATA-Shipping Name: N/A IMDG-Shipping Name: N/A

#### 14.3. Transport hazard class(es)

ADR-Class: N/A IATA-Class: N/A IMDG-Class: N/A

## 14.4. Packing group

ADR-Packing Group: N/A IATA-Packing group: N/A IMDG-Packing group: N/A

## 14.5. Environmental hazards

Marine pollutant: No Environmental Pollutant: No

IMDG-EMS: N/A

## 14.6. Special precautions for user

Road and Rail (ADR-RID):

Date 29/08/2025 Production Name SILICONE COLOR Page n. 9 of 12

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code): N/A

ADR Limited Quantities: N/A ADR Excepted Quantities: N/A

Air (IATA):

IATA-Passenger Aircraft: N/A IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A

IATA-Erg: N/A

IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage and handling: N/A

IMDG-Segregation: N/A
IMDG-Subsidiary hazards: N/A
IMDG-Special Provisions: N/A

#### 14.7. Maritime transport in bulk according to IMO instruments

N.A

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2023/707

Regulation (EU) n. 2023/1434 (ATP 19 CLP)

Regulation (EU) n. 2023/1435 (ATP 20 CLP)

Regulation (EU) n. 2024/197 (ATP 21 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: None.

Restrictions related to the substances contained: 28, 52, 75

Provisions related to directive EU 2012/18 (Seveso III):

None

## Explosives precursors - Regulation 2019/1148

No substances listed

## Regulation (EU) No 649/2012 (PIC regulation)

Date 29/08/2025 Production Name SILICONE COLOR Page n. 10 of 12

No substances listed

#### German Water Hazard Class.

3: Severe hazard to waters

#### German Lagerklasse according to TRGS 510:

**LGK 10** 

SVHC Substances:

No SVHC substances present in concentration >= 0.1%

#### REGULATION (EU) No 528/2012

The product is identified as an article treated pursuant to art. 58 of Regulation (EU) no. 528/2012 and subsequent amendments.

Substances included in Regulation (EU) n. 528/2012 (concerning the making available on the market and use of biocidal products):

Nomenclature IUPAC: 4,5-dichloro-2-octyl-2H-isothiazol-3-one

Nomenclature BPR: DCOIT CAS number: 64359-81-5

Product-type 7: Film preservatives

Assessment status: Initial application for approval in progress.

Product-type 8: Film preservatives Assessment status: Approved

Commission Implementing Regulation (EU) 2011/66

## 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

#### **SECTION 16: Other information**

Code Description

H304 May be fatal if swallowed and enters airways.

Code Hazard class and hazard category Description

3.10/1 Asp. Tox. 1 Aspiration hazard, Category 1

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)
BCF: Biological Concentration Factor

BEI: Biological Exposure Index BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center CE: European Community

CLP: Classification, Labeling, Packaging. CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand COV: Volatile Organic Compound CSA: Chemical Safety Assessment CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive DSD: Dangerous Substances Directive EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

Date 29/08/2025 Production Name SILICONE COLOR Page n. 11 of 12

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: Keep Away From Heat KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

 $v P v B \colon Very \ Persistent, \ Very \ Bioaccumulative.$ 

WGK: German Water Hazard Class.

## Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Date 29/08/2025 Production Name SILICONE COLOR Page n. 12 of 12