

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

TETRA FIX

Date of first edition: 4/14/2023

Safety Data Sheet dated 4/14/2023

version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: TETRA FIX

Trade code: K50463

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Adhesives, sealants

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL France

25, avenue de l'Industrie - 69960 Corbas - France

Tel. +33 472 890 684

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Kerakoll Italy (+39) 0536 816511

Ireland

Poison information centre: (+353) 809 2166 (Daily 8am-10pm)

In case of emergency call 999 or 112

Malta

In case of emergency call: 112 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

0 The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Special Provisions:

EUH208 Contains Trimethoxyvinilsilane. May produce an allergic reaction.

EUH208 Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.

EUH208 Contains 1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: TETRA FIX

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
1-2,4 %	Fatty acids, C16-18	CAS:67701-03-5 EC:266-928-5	Skin Irrit. 2, H315; Eye Irrit. 2, H319	
< 1 %	Trimethoxyvinilsilane	CAS:2768-02-7 EC:220-449-8 Index:014-049-00-0	Skin Sens. 1B, H317; Flam. Liq. 2, H225; Acute Tox. 4, H332	01-2119513215-52
< 1 %	N-(3-(trimethoxysilyl)propyl)ethylenediamine	CAS:1760-24-3 EC:217-164-6	Eye Dam. 1, H318; Skin Sens. 1, H317; Acute Tox. 4, H332	
< 0,1 %	1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	CAS:1065336-91-5 EC:915-687-0	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Repr. 2, H361; Skin Sens. 1A, H317, M-Chronic:1, M-Acute:1	01-2119491304-40-XXXX

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

N.A.

4.3. Indication of any immediate medical attention and special treatment needed

N.A.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

- 6.3. Methods and material for containment and cleaning up**

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.
- 6.4. Reference to other sections**

See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling**

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities**

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

- Recommendation(s)

None in particular
- Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Notes
Calcium carbonate	NATIONAL	AUSTRALIA		10.000				This value is for inhalable dust containing no asbestos and <1 % crystalline silica.
	NATIONAL	FRANCE		10.000				inhalable aerosol
	NATIONAL	HUNGARY		10.000				inhalable aerosol
	NATIONAL	IRELAND		10.000				Inhalable fraction
	NATIONAL	IRELAND		4.000				Respirable fraction
	NATIONAL	LATVIA		6.000				
	NATIONAL	POLAND		10.000				
	NATIONAL	SWITZERLAND		3.000				respirable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND		10.000				inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND		4.000				respirable aerosol
	NATIONAL	BELGIUM		10.000				
	NATIONAL	CROATIA		10.000				
	NATIONAL	NETHERLANDS		10.000				
	NATIONAL	PORTUGAL		10.000				
	NATIONAL	SPAIN		10.000				
di isononylphthalate	NATIONAL	DENMARK		3.000		6.000		

Aluminium oxide	NATIONAL	IRELAND	5.000					
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	5.000					
	NATIONAL	FRANCE	10.000					Respirable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	10.000					Inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	4.000					Respirable aerosol
	NATIONAL	AUSTRALIA	10.000					Inhalable dust containing no asbestos and < 1% crystalline silica
	NATIONAL	AUSTRIA	10.000		20.000			Long term: inhalable fraction; Short term: inhalable fraction, 60 minutes average value
	NATIONAL	AUSTRIA	5.000		10.000			Long term: respirable fraction; Short term: respirable fraction, 60 minutes average value
	NATIONAL	DENMARK	5.000		10.000			Calculated as AI; Long term and Short term: inhalable aerosol
	NATIONAL	DENMARK	2.000		4.000			Calculated as AI; Long term and Short term: respirable aerosol
	NATIONAL	GERMANY	4.000					Inhalable aerosol
	NATIONAL	GERMANY	1.500					Respirable aerosol
	NATIONAL	HUNGARY	6.000					Respirable aerosol
	NATIONAL	IRELAND	10.000					Inhalable fraction
	NATIONAL	IRELAND	4.000					Respirable fraction
	NATIONAL	LATVIA	6.000					
	NATIONAL	POLAND	2.500		16.000			Dz. U. 2018 poz. 1286 wraz z późn. zm
	NATIONAL	POLAND	1.200					Aluminium trioxide as AI fume; Long term: respirable dust
	NATIONAL	ROMANIA	2.000	0.500	5.000	1.200		Long term and short term: aerosol
	NATIONAL	SPAIN	10.000					Inhalable aerosol
	NATIONAL	SPAIN	5.000					Respirable aerosol
	NATIONAL	SWEDEN	5.000					Inhalable aerosol
	NATIONAL	SWEDEN	2.000					Respirable aerosol
	NATIONAL	SWITZERLAND	3.000					Respirable aerosol
propan-2-ol; isopropyl alcohol; isopropanol	NATIONAL	AUSTRALIA	983.000	400.000	1230.000	500.000		
	NATIONAL	AUSTRIA	500.000	200.000	2000.000	800.000		
	NATIONAL	BELGIUM	500.000	200.000	1000.000	400.000		

2,2',2''-nitrilotriethanol methanol	NATIONAL	DENMARK	490.000	200.000	980.000	400.000	
	NATIONAL	FINLAND	500.000	200.000	620.000	250.000	
	NATIONAL	FRANCE			980.000	400.000	
	NATIONAL	GERMANY	500.000	200.000	1000.000	400.000	AGS
	NATIONAL	GERMANY	500.000	200.000	1000.000	400.000	DFG
	NATIONAL	HUNGARY	500.000		2000.000		
	NATIONAL	IRELAND		200.000		400.000	
	NATIONAL	LATVIA	350.000		600.000		
	NATIONAL	POLAND	900.000		1200.000		
	NATIONAL	ROMANIA	200.000	81.000	500.000	203.000	
	NATIONAL	SPAIN	500.000	200.000	1000.000	400.000	
	NATIONAL	SWEDEN	350.000	150.000	600.000	250.000	
	NATIONAL	SWITZERLAND	500.000	200.000	1000.000	400.000	
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	999.000	400.000	1250.000	500.000	
	NATIONAL	BULGARIA	980.000		1225.000		
	NATIONAL	CZECHIA	500.000		1000.000		
	NATIONAL	CROATIA	999.000	400.000	1250.000	500.000	
	NATIONAL	ESTONIA	350.000	150.000	600.000	250.000	
	NATIONAL	GREECE	980.000	400.000	1225.000	500.000	
	NATIONAL	LITHUANIA	350.000	150.000	600.000	250.000	
	NATIONAL	NETHERLANDS	650.000	250.000			
	NATIONAL	PORTUGAL		200.000		400.000	
	NATIONAL	SLOVAKIA	500.000	200.000	1000.000	400.000	
	NATIONAL	SLOVENIA	500.000	200.000	1000.000	400.000	
	ACGIH	NNN		200.000		400.000	A4, BEI - Eye and URT irr, CNS impair
	ACGIH	NNN	5				Eye and skin irr
	EU	NNN	260	200			Skin
	NATIONAL	AUSTRIA	260.000	200.000	1040.000	800.000	
	NATIONAL	BELGIUM	266.000	200.000	333.000	250.000	Additional indication "D" means that the absorption of the agent through the skin, mucous membranes or eyes is an important part of the total exposure. It can be the result of both direct contact and its presence in the air
	NATIONAL	DENMARK	260.000	200.000	328.000	250.000	
	NATIONAL	FINLAND	270.000	200.000	330.000	250.000	
	NATIONAL	FRANCE	260.000	200.000			Bold type: Restrictive statutory limit values Skin
	NATIONAL	GERMANY	270.000	200.000	1080.000	800.000	AGS
	NATIONAL	GERMANY	130.000	100.000	260.000	200.000	DFG
	NATIONAL	HUNGARY	260.000				
	NATIONAL	IRELAND	260.000	200.000			
	NATIONAL	ITALY	260.000	200.000			Cute
	NATIONAL	LATVIA	260.000	200.000			
	NATIONAL	POLAND	100.000		300.000		

NATIONAL	ROMANIA	260.000	200.000			
NATIONAL	SPAIN	266.000	200.000	333.000	250.000	
NATIONAL	SWEDEN	250.000	200.000	350.000	250.000	
NATIONAL	SWITZERLAND	260.000	200.000	1040.000	800.000	
NATIONAL	NETHERLANDS	133.000				
NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	266.000	200.000	333.000	250.000	
NATIONAL	ITALY	262.000	200.000	328.000	250.000	TWA
NATIONAL	ITALY	260.000	200.000	1040.000	800.000	TLV
NATIONAL	BULGARIA	260.000	200.000			
NATIONAL	CZECHIA	250.000		1000.000		
NATIONAL	CROATIA	260.000	200.000			
NATIONAL	ESTONIA	250.000	200.000	350.000	250.000	
NATIONAL	GREECE	260.000	200.000	325.000	250.000	
NATIONAL	IRELAND	260.000	200.000			
NATIONAL	LITHUANIA	260.000	200.000			
NATIONAL	PORTUGAL		200.000		250.000	
ACGIH	NNN		200.000		250.000	Skin, BEI - Headache, eye dam, dizziness, nausea
EU	NNN	260.000	200.000			Skin

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC Limit	Exposure Route	Exposure Frequency
Trimethoxyvinilsilane	2768-02-7	400.000 µg/l	Freshwater	
		2.400 mg/l	Intermittent releases (freshwater)	
		40.000 µg/l	Marine water	
		6.600 mg/l	Microorganisms in sewage treatments	
		1.500 mg/kg	Freshwater sediments	
		150.000 µg/kg	Marine water sediments	
		60.000 µg/kg	Soil	
N-(3-(trimethoxysilyl)propyl) ethylenediamine	1760-24-3	62.000 µg/l	Freshwater	
		620.000 µg/l	Intermittent releases (freshwater)	
		6.200 µg/l	Marine water	
		25.000 mg/l	Microorganisms in sewage treatments	
		220.000 µg/kg	Freshwater sediments	
		22.000 µg/kg	Marine water sediments	
		8.500 µg/kg	Soil	
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	1065336-91-5	2.200 µg/l	Freshwater	
		9.000 µg/l	Intermittent releases (freshwater)	

220.000 ng/L	Marine water
1.000 mg/l	Microorganisms in sewage treatments
1.050 mg/kg	Freshwater sediments
110.000 µg/kg	Marine water sediments
210.000 µg/kg	Soil

Derived No Effect Level (DNEL) values

Component	CAS-No.	Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency
Trimethoxyvinilsilane	2768-02-7		27.600 mg/m ³	6.700 mg/m ³	Human Inhalation	Long Term, systemic effects
			260.000 mg/m ³	50.000 mg/m ³	Human Inhalation	Short Term, systemic effects
			3.900 mg/kg	7.800 mg/kg	Human Dermal	Short Term, systemic effects
				300.000 µg/kg	Human Oral	Long Term, systemic effects
N-(3-(trimethoxysilyl)propyl) ethylenediamine	1760-24-3		260.000 mg/m ³	50.000 mg/m ³	Human Inhalation	Long Term, systemic effects
			260.000 mg/m ³	50.000 mg/m ³	Human Inhalation	Short Term, systemic effects
			600.000 µg/m ³	100.000 µg/m ³	Human Inhalation	Long Term, local effects
			5.360 mg/m ³	4.000 mg/m ³	Human Inhalation	Short Term, local effects
				8.000 mg/kg	Human Oral	Long Term, systemic effects
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	1065336-91-5		680.000 µg/m ³	170.000 µg/m ³	Human Inhalation	Long Term, systemic effects
			500.000 µg/kg	250.000 µg/kg	Human Dermal	Long Term, systemic effects
				50.000 µg/kg	Human Oral	Long Term, systemic effects

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid

Color: In compliance with the product description

Odour: Light
Odour threshold: N.A.
pH: N.A.
Kinematic viscosity: N.A.
Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.
Flash point: > 60°C / 93°C
Upper/lower flammability or explosive limits: N.A.
Vapour density: N.A.
Vapour pressure: N.A.
Relative density: 1.50 g/cm³
Solubility in water: Miscible
Solubility in oil: N.A.
Partition coefficient (n-octanol/water): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Flammability: N.A.
Volatile Organic compounds - VOCs = 0.25 % ; 2.53 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

Miscibility: N.A.
Conductivity: N.A.
Evaporation rate: N.A. No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified Based on available data, the classification criteria are not met
c) serious eye damage/irritation	Not classified Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	Not classified Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met

i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

Trimethoxyvinilsilane	a) acute toxicity	LD50 Oral Rat = 7.34000 ml/Kg LC50 Inhalation Vapour Rat = 2773.00000 Ppm 4h LD50 Skin Rabbit = 3.36000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative 24h	
	c) serious eye damage/irritation	Eye Irritant Rabbit No 24h	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Positive	
	f) carcinogenicity	Genotoxicity Rat Negative	Inhalation route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 250.00000 mg/kg	
N-(3-(trimethoxysilyl)propyl) ethylenediamine	a) acute toxicity	LD50 Oral Rat = 2295.00 mg/kg LC50 Inhalation of aerosol Rat > 1.49 mg/l 4h LD50 Skin Rabbit > 2000.00 mg/kg 24h	<2.44 mg/l
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Positive	
	f) carcinogenicity	Genotoxicity Negative	Mouse intraperitoneal route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 500.00 mg/kg	
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	a) acute toxicity	LD50 Oral Rat = 3230.00 mg/kg LD50 Skin Rat > 3170.00 mg/kg	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative 24h	
	c) serious eye damage/irritation	Eye Irritant Rabbit No	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Positive	
	f) carcinogenicity	Genotoxicity Negative	Mouse oral route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 30.00 mg/kg	

11.2 Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
Trimethoxyvinilsilane	CAS: 2768-02-7 - EINECS: 220-449-8 - INDEX: 014-049-00-0	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 137.00000 mg/L 96h a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 121.00000 mg/L 48h b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 20.00000 mg/L - 21days a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata > 89.00000 mg/L 72h a) Aquatic acute toxicity : EC10 microorganisms > 100.00000 mg/L 3h OECD 209
N-(3-(trimethoxysilyl)propyl)ethylenediamine	CAS: 1760-24-3 - EINECS: 217-164-6	a) Aquatic acute toxicity : LC50 Fish Danio rerio = 597.00 mg/L 96h a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 81.00 mg/L 48h b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna >= 1.00 ppm - 21days a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 8.80 mg/L 72h c) Bacteria toxicity : EC50 Pseudomonas putida = 67.00 mg/L d) Terrestrial toxicity : LC50 Worm Eisenia foetida > 1000.00 mg/kg - 14days
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	CAS: 1065336-91-5 - EINECS: 915-687-0	a) Aquatic acute toxicity : LC50 Fish Danio rerio = 0.90 mg/L 96h OECD Guideline 203 b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 1.00 mg/L OECD guideline 211 a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 1.68 mg/L 72h OECD Guideline 201 a) Aquatic acute toxicity : EC20 Sludge activated sludge >= 100.00 mg/L 3h OECD guideline 209

12.2. Persistence and degradability

Component	Persistence/Degradability:	Test	Value	Notes
Trimethoxyvinilsilane	Readily biodegradable			
N-(3-(trimethoxysilyl)propyl)ethylenediamine	Non-readily biodegradable	Dissolved organic carbon	39.000	28days
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	Non-readily biodegradable		38.000	28days

12.3. Bioaccumulative potential

Component	Bioaccumulation
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	Not bioaccumulative

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7 Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

A waste code according to European waste catalogue (EWC) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

N.A.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

N.A.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

N.A.

14.6. Special precautions for user

N.A.

Road and Rail (ADR-RID) :

N.A.

Air (IATA) :

N.A.

Sea (IMDG) :

N.A.

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: None

Restrictions related to the substances contained: 30, 40, 52, 69, 75

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

Regulation (EU) 649/2012 (PIC regulation):

No Substance Listed

German Water Hazard Class.

Class 3: extremely hazardous.

SVHC Substances:

No data available

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B
3.7/2	Repr. 2	Reproductive toxicity, Category 2
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor
 BEI: Biological Exposure Index
 BOD: Biochemical Oxygen Demand
 CAS: Chemical Abstracts Service (division of the American Chemical Society).
 CAV: Poison Center
 CE: European Community
 CLP: Classification, Labeling, Packaging.
 CMR: Carcinogenic, Mutagenic and Reprotoxic
 COD: Chemical Oxygen Demand
 COV: Volatile Organic Compound
 CSA: Chemical Safety Assessment
 CSR: Chemical Safety Report
 DMEL: Derived Minimal Effect Level
 DNEL: Derived No Effect Level.
 DPD: Dangerous Preparations Directive
 DSD: Dangerous Substances Directive
 EC50: Half Maximal Effective Concentration
 ECHA: European Chemicals Agency
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 ES: Exposure Scenario
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 IC50: half maximal inhibitory concentration
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 IMDG: International Maritime Code for Dangerous Goods.
 INCI: International Nomenclature of Cosmetic Ingredients.
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care
 KAFH: Keep Away From Heat
 KSt: Explosion coefficient.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 LDLo: Leathal Dose Low
 N.A.: Not Applicable
 N/A: Not Applicable
 N/D: Not defined/ Not available
 NA: Not available
 NIOSH: National Institute for Occupational Safety and Health
 NOAEL: No Observed Adverse Effect Level
 OSHA: Occupational Safety and Health Administration.
 PBT: Persistent, Bioaccumulative and Toxic
 PGK: Packaging Instruction
 PNEC: Predicted No Effect Concentration.
 PSG: Passengers
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 vPvB: Very Persistent, Very Bioaccumulative.
 WGK: German Water Hazard Class.

Exposure Scenario

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate
bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate

Exposure Scenario, 20/04/2022

Substance identity	
	1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate
CAS No.	1065336-91-5
EINECS No.	915-687-0

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9a, PC9b)

1. ES 1		Widespread use by professional workers; Various products (PC9a, PC9b)	
1.1 TITLE SECTION			
Exposure Scenario name	Professional application of coatings and inks - Use in rigid foams, coatings, adhesives and sealants		
Date - Version	20/04/2022 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Coatings and paints, thinners, paint removers (PC9a) - Fillers, putties, plasters, modelling clay (PC9b)		
Environment Contributing Scenario			
CS1	ERC8c		
Worker Contributing Scenario			
CS2 Material transfers	PROC8a		
CS3 Rolling, Brushing	PROC10		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8c)			
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) (ERC8c)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid			
Vapour pressure: Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Emission days: 365 days per year			
<i>Technical and organisational conditions and measures</i>			
Control measures to prevent releases			
		Air - minimum efficiency of: 15 % Water - minimum efficiency of: 1 %	
<i>Conditions and measures related to sewage treatment plant</i>			
STP type: Municipal Sewage Treatment Plant Water - minimum efficiency of: = 88.9 %			
STP effluent (m³/day): 2000			
<i>Other conditions affecting environmental exposure</i>			
Local marine water dilution factor: 100 Local freshwater dilution factor: 10 Receiving surface water flow: 18000 m³/day Indoor use			
1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)			

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)	
<i>Product (article) characteristics</i>		
Physical form of product: Liquid		
Vapour pressure: Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa		
Concentration of substance in product: Covers percentage substance in the product up to 5 %.		
<i>Amount used, frequency and duration of use/exposure</i>		
Duration: Covers use up to 480 min		
Frequency: Covers use up to 5 days per week		
<i>Technical and organisational conditions and measures</i>		
Technical and organisational measures Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed. Ensure operatives are trained to minimise exposures.		
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>		
Personal protection		
Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.		Dermal - minimum efficiency of: = 90 %
Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin.		
<i>Other conditions affecting worker exposure</i>		
Indoor use Professional use		
<i>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.</i>		
Additional Good Practice Advice: Ensure no splashing occurs during transfer.		
1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)		
Process Categories	Roller application or brushing (PROC10)	
<i>Product (article) characteristics</i>		
Physical form of product: Liquid		
Vapour pressure: Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa		
Concentration of substance in product: Covers percentage substance in the product up to 5 %.		
<i>Amount used, frequency and duration of use/exposure</i>		
Duration: Covers use up to 480 min		
Frequency: Covers use up to 5 days per week		
<i>Technical and organisational conditions and measures</i>		
Technical and organisational measures		

Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed.
Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.	Dermal - minimum efficiency of: = 90 %
Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin.	

Other conditions affecting worker exposure

Indoor use
Professional use

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Ensure no splashing occurs during transfer.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8c)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
soil	N/A	ECETOC TRA environment v2.0	0.0579

Additional information on exposure estimation:

Risk from environmental exposure is driven by soil.

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 0.2743 mg/kg bw/day	ECETOC TRA worker v3	= 0.137143
inhalative, systemic, long-term	= 0.4233 mg/m ³	ECETOC TRA worker v3	= 0.119924

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 0.5486 mg/kg bw/day	ECETOC TRA worker v3	= 0.274286
inhalative, systemic, long-term	= 0.274286 mg/m ³	ECETOC TRA worker v3	= 0.097

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario

N-(3-(trimethoxysilyl)propyl)ethylenediamine

Exposure Scenario, 12/01/2022

Substance identity	
	N-(3-(trimethoxysilyl)propyl)ethylenediamine
CAS No.	1760-24-3
EINECS No.	217-164-6

Table of contents

1. **ES 1** Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)

1. ES 1		Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)	
1.1 TITLE SECTION			
Exposure Scenario name	Professional application of coatings and inks		
Date - Version	12/01/2022 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Coatings and paints, thinners, paint removers (PC9a)		
Environment Contributing Scenario			
CS1	ERC8c - ERC8f		
Worker Contributing Scenario			
CS2 Rolling, Brushing - Roller, spreader, flow application - Manual	PROC10 - PROC11 - PROC19		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)			
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid			
Concentration of substance in product: Covers percentage substance in the product up to 5 %.			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Amounts used: Daily amount per site <= 1.37 kg/day Annual site tonnage <= 0.5 tonnes/day			
Emission days: 365 days per year			
<i>Technical and organisational conditions and measures</i>			
Control measures to prevent releases Prevent discharge of undissolved substance to or recover from onsite wastewater.			
<i>Conditions and measures related to treatment of waste (including article waste)</i>			
Waste treatment Dispose of solid residue according to applicable regulations.			
1.2. CS2: Worker Contributing Scenario: Rolling, Brushing - Roller, spreader, flow application - Manual (PROC10, PROC11, PROC19)			
Process Categories	Roller application or brushing - Non industrial spraying - Manual activities involving hand contact (PROC10, PROC11, PROC19)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid			
Concentration of substance in product: Covers percentage substance in the product up to 5 %.			
<i>Amount used, frequency and duration of use/exposure</i>			

Amounts used:

Annual site tonnage ≤ 0.5 t(tonnes)/year
Daily amount per site ≤ 1.37 kg/day

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers use up to ≤ 5 days per week

Technical and organisational conditions and measures**Technical and organisational measures**

Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Wear suitable coveralls to prevent exposure to the skin.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

Release route	Release rate	Release estimation method
Air	0.17 kg/day	N/A
Water	0.011 kg/day	N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

Trimethoxyvinilsilane

Exposure Scenario, 08/06/2021

Substance identity	
	Trimethoxyvinilsilane
CAS No.	2768-02-7
INDEX No.	014-049-00-0
EINECS No.	220-449-8
Registration number	01-2119513215-52

Table of contents

1. ES 1

1. ES 1

1.1 TITLE SECTION

Exposure Scenario name	Use in rigid foams, coatings, adhesives and sealants - Barrier (Sealant)
Date - Version	18/05/2021 - 1.0
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22) - Building and construction work (SU19)
Product Categories	Adhesives, sealants (PC1)

Environment Contributing Scenario

CS1 Low environmental release	ERC8c - ERC8f
-------------------------------	---------------

Worker Contributing Scenario

CS2 Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application	PROC0
CS3 Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application	PROC1

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Low environmental release (ERC8c, ERC8f)

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Concentration after dilution for use maximum [%]: 0.7 %

Amount used, frequency and duration of use (or from service life)

Amounts used:

Daily amount per site = 0.28 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

	Water - minimum efficiency of: 1.5 %
--	--------------------------------------

Conditions and measures related to sewage treatment plant

STP type:

Onsite Sewage Treatment Plant

Water - minimum efficiency of: = 0.013 %

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Dispose of waste product or used containers according to local regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 20000 m³/day

Covers indoor and outdoor use	
1.2. CS2: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC0)	
Process Categories	Other (PROC0)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Concentration of substance in product: Covers concentrations up to 0.7 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Exposure duration ≤ 6 h Frequency: Use frequency = 250 days per year	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). For further specification, refer to section 8 of the SDS.	
<i>Other conditions affecting worker exposure</i>	
Covers indoor and outdoor use Professional use Room size: Covers use in room size of = 20 m ³ Temperature: Covers use at ambient temperatures. 25°C	
1.2. CS3: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC1)	
Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Concentration of substance in product: Covers concentrations up to 2 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Exposure duration = 8 h Frequency: Use frequency = 1 days per year	
Duration: Covers use up to = 6 h Frequency: Use frequency = 1 days per year	
<i>Other conditions affecting worker exposure</i>	
Covers indoor and outdoor use Professional use Room size: Covers use in room size of = 20 m ³ Ventilation rate: = 0.6 ach (air changes per hour)	
1.3 Exposure estimation and reference to its source	
1.3. CS2: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC0)	

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, long-term	= 1.9 mg/m ³	N/A	= 0.069
dermal, long-term	= 4.53 mg/kg bw/day	ConsExpo	= 0.038
combined routes, long-term	N/A	N/A	0.107

1.3. CS3: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, long-term	= 4.57 mg/m ³	N/A	= 0.682
dermal, long-term	= 0.044 mg/kg bw/day	ConsExpo	< 0.01
combined routes, short-term	N/A	N/A	0.682

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.