

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

TETRA TACK CRYSTAL

Date of first edition: 3/12/2024

Safety Data Sheet dated 12/03/2024

version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: TETRA TACK CRYSTAL

Trade code: K50461

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Adhesives, sealants

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL HELLAS E.P.E

1st km Schimatari-Avlida Rd., Routhounia Area – 32009 Schimatari-Viotia, Greece

Tel. +30 2262049724 – Fax +30 2262058788

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112 Kerakoll Italy - +39-0536-816511 Ireland Poison information centre: 01 809 2166 (Daily 8am-10pm) In case of emergency call 999 or 112 Malta In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Eye Irrit. 2 Causes serious eye irritation.

Skin Sens. 1A May cause an allergic skin reaction.

Aquatic Chronic 3 Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Warning

Hazard statements

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P273 Avoid release to the environment.

P280 Wear protective gloves and eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Contains

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate

Trimethoxyvinilsilane

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: TETRA TACK CRYSTAL

Hazardous components within the meaning of the CLP regulation and related classification:

| Qty | Name | Ident. Numb. | Classification | Registration Number |
|---------|---|---|--|-----------------------|
| ≥3-<5 % | Trimethoxyvinilsilane | CAS:2768-02-7 EC:220-449-8 Index:014-049-00-0 | Skin Sens. 1B, H317; Flam. Liq. 2, H225; Acute Tox. 4, H332 | 01-2119513215-52 |
| ≥1-<3 % | 3-(trimethoxysilyl)propylamine | CAS:13822-56-5 EC:237-511-5 | Skin Irrit. 2, H315; Eye Dam. 1, H318 | 01-2119510159-45 |
| ≥1-<3 % | 1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate | CAS:1065336-91-5 EC:915-687-0 | Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Repr. 2, H361; Skin Sens. 1A, H317, M-Chronic:1, M-Acute:1 | 01-2119491304-40-XXXX |
| <0.05 % | methanol | CAS:67-56-1 EC:200-659-6 Index:603-001-00-X | Flam. Liq. 2, H225 STOT SE 1, H370 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Specific Concentration Limits: C ≥ 10%: STOT SE 1 H370 3% ≤ C < 10%: STOT SE 2 H371 | 01-2119433307-44 |

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediatley and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.

5.3. Advice for firefighters

- Use suitable breathing apparatus .
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

- Wear personal protection equipment.
- Remove persons to safety.
- See protective measures under point 7 and 8.

For emergency responders:

- Wear personal protection equipment.

6.2. Environmental precautions

- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Retain contaminated washing water and dispose it.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
- Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

- Suitable material for taking up: absorbing material, organic, sand
- Wash with plenty of water.

6.4. Reference to other sections

- See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.
- Don't use empty container before they have been cleaned.
- Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
- Contaminated clothing should be changed before entering eating areas.
- Do not eat or drink while working.
- See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

- None in particular.

Instructions as regards storage premises:

- Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

- None in particular

Industrial sector specific solutions:

- None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

| | OEL Type | Country | Occupational Exposure Limit |
|--------------------------|----------|---------|--|
| methanol CAS: 67-56-1 | ACGIH | | Long Term: 200 ppm (8h); Short Term: 250 ppm Skin, BEI - Headache, eye dam, dizziness, nausea |
| | EU | | Long Term: 260 mg/m3 - 200 ppm (8h) |

| | | |
|----------|-----------------|---|
| | | Skin |
| NATIONAL | AUSTRIA | Long Term: 260 mg/m ³ - 200 ppm; Short Term: 1040 mg/m ³ - 800 ppm 15(Miw), 4x, MAK, H Source: BGBl. II Nr. 156/2021 |
| NATIONAL | BULGARIA | Long Term: 260 mg/m ³ - 200 ppm ???? Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. НАРЕДБА № 10 ОТ 26 СЕПТЕМВРИ 2003 |
| NATIONAL | CZECHIA | Long Term: 250 mg/m ³ ; Short Term: Ceiling - 1000 mg/m ³ D, B Source: Nařízení vlády č. 361-2007 Sb |
| NATIONAL | DENMARK | Long Term: 260 mg/m ³ - 200 ppm EH Source: BEK nr 2203 af 29/11/2021 |
| NATIONAL | ESTONIA | Long Term: 250 mg/m ³ - 200 ppm; Short Term: 350 mg/m ³ - 250 ppm A Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105 |
| NATIONAL | FINLAND | Long Term: 270 mg/m ³ - 200 ppm; Short Term: 330 mg/m ³ - 250 ppm iho Source: HTP-ARVOT 2020 |
| NATIONAL | FRANCE | Long Term: 260 mg/m ³ - 200 ppm; Short Term: 1300 mg/m ³ - 1000 ppm Risque de pénétration percutanée Source: INRS outil65, article R. 4412-149 du Code du travail |
| NATIONAL | GREECE | Long Term: 260 mg/m ³ - 200 ppm; Short Term: 325 mg/m ³ - 250 ppm ? Source: ΦΕΚ 94/Α` 13.5.1999 |
| NATIONAL | HUNGARY | Long Term: 260 mg/m ³ b, i, BEM, EU2, R+T Source: 5/2020. (II. 6.) ITM rendelet |
| NATIONAL | LITHUANIA | Long Term: 260 mg/m ³ - 200 ppm O Source: 2011 m. rugsejo 1 d. Nr. V-824/A1-389 |
| NATIONAL | NETHERLAND S | Long Term: 133 mg/m ³ H Source: Arbeidsomstandighedenregeling - Lijst A |
| NATIONAL | NORWAY | Long Term: 130 mg/m ³ - 100 ppm H E Source: FOR-2021-06-28-2248 |
| NATIONAL | POLAND | Long Term: 100 mg/m ³ ; Short Term: 300 mg/m ³ skóra Source: Dz.U. 2018 poz. 1286 |
| NATIONAL | SLOVAKIA | Long Term: 260 mg/m ³ - 200 ppm K, 7) Source: 355 NARIADENIE VLÁDY z 10. mája 2006 |
| NATIONAL | SWEDEN | Long Term: 250 mg/m ³ - 200 ppm; Short Term: 350 mg/m ³ - 250 ppm H, V Source: AFS 2021:3 |
| NATIONAL | BELGIUM | Long Term: 266 mg/m ³ - 200 ppm; Short Term: 333 mg/m ³ - 250 ppm D Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1 |
| NATIONAL | CROATIA | Long Term: 260 mg/m ³ - 200 ppm koža Source: 2006/15/EZ |
| NATIONAL | CYPRUS | Long Term: 260 mg/m ³ - 200 ppm d??μα Source: Οι περί Ασφάλειας και Υγείας στην Εργασία (Χημικοί Παράγοντες) Κανονισμοί του 2001 έως 2021 |
| NATIONAL | GERMANY | Long Term: 130 mg/m ³ - 100 ppm DFG, EU, H, Y, 2(II) Source: TRGS 900 |

| | | |
|----------|------------|--|
| NATIONAL | IRELAND | Long Term: 260 mg/m3 - 200 ppm Sk, IOELV Source: 2021 Code of Practice |
| NATIONAL | ITALY | Long Term: 260 mg/m3 - 200 ppm Cute Source: D.lgs. 81/2008, Allegato XXXVIII |
| NATIONAL | LATVIA | Long Term: 260 mg/m3 - 200 ppm Ada Source: KN325P1 |
| NATIONAL | LUXEMBOURG | Long Term: 260 mg/m3 - 200 ppm Peau Source: Mémorial A n.226 du 22 mars 2021 |
| NATIONAL | MALTA | Long Term: 260 mg/m3 - 200 ppm skin Source: S.L.424.24 |
| NATIONAL | PORTUGAL | Long Term: 260 mg/m3 - 200 ppm Cutânea Source: Decreto-Lei n.º 1/2021 |
| NATIONAL | ROMANIA | Long Term: 260 mg/m3 - 200 ppm P, Dir. 2006/15 Source: Republicarea 1 - nr. 743 din 29 iulie 2021 |
| NATIONAL | SLOVENIA | Long Term: 260 mg/m3 - 200 ppm; Short Term: 1040 mg/m3 - 800 ppm K, Y, BAT, EU2 Source: UL št. 72, 11. 5. 2021 |
| NATIONAL | SPAIN | Long Term: 266 mg/m3 - 200 ppm vía dérmica, VLB®, VLI, r Source: LEP 2022 |

Biological limit values

methanol
CAS: 67-56-1

Biological Indicator: Methyl alcohol; Sampling Period: End of turn; End of working week
Value: 30 mg/L; Medium: Urine

Predicted No Effect Concentration (PNEC) values

Trimethoxyvinilsilane
CAS: 2768-02-7

Exposure Route: Fresh Water; PNEC Limit: 400 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 2.4 mg/l

Exposure Route: Marine water; PNEC Limit: 40 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 6.6 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 1.5 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 150 µg/kg

Exposure Route: Soil; PNEC Limit: 60 µg/kg

Exposure Route: Fresh Water; PNEC Limit: 500 µg/l

3-
(trimethoxysilyl)
propylamine
CAS: 13822-56-5

Exposure Route: Fresh Water; PNEC Limit: 2.05 mg/l

Exposure Route: Marine water; PNEC Limit: 50 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 810 µg/l

Exposure Route: Freshwater sediments; PNEC Limit: 1.8 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 180 µg/kg

Exposure Route: Soil; PNEC Limit: 69 µg/kg

Exposure Route: Secondary poisoning; PNEC Limit: 11.1 mg/kg

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate
bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate
CAS: 1065336-91-5

Exposure Route: Fresh Water; PNEC Limit: 2.2 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 9 µg/l

Exposure Route: Marine water; PNEC Limit: 220 ng/L
 Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 1 mg/l
 Exposure Route: Freshwater sediments; PNEC Limit: 1.05 mg/kg
 Exposure Route: Marine water sediments; PNEC Limit: 110 µg/kg
 Exposure Route: Soil; PNEC Limit: 210 µg/kg
 Exposure Route: Fresh Water; PNEC Limit: 20.8 mg/l

methanol
 CAS: 67-56-1

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 1540 mg/l
 Exposure Route: Marine water; PNEC Limit: 2.08 mg/l
 Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l
 Exposure Route: Freshwater sediments; PNEC Limit: 77 mg/kg
 Exposure Route: Marine water sediments; PNEC Limit: 7.7 mg/kg
 Exposure Route: Soil; PNEC Limit: 100 mg/kg

Derived No Effect Level (DNEL) values

Trimethoxyvinylsilane
 CAS: 2768-02-7
 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 27.6 mg/m³; Consumer: 6.7 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
 Worker Professional: 260 mg/m³; Consumer: 50 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
 Worker Professional: 3.9 mg/kg; Consumer: 7.8 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
 Consumer: 300 µg/kg

3-(trimethoxysilyl) propylamine
 CAS: 13822-56-5
 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 7.1 mg/m³; Consumer: 1.7 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
 Worker Professional: 260 mg/m³; Consumer: 50 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 1 mg/kg; Consumer: 500 µg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
 Consumer: 8 mg/kg

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate
 CAS: 1065336-91-5
 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 680 µg/m³; Consumer: 170 µg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 500 µg/kg; Consumer: 250 µg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
 Consumer: 50 µg/kg

methanol
 CAS: 67-56-1
 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 130 mg/m³; Consumer: 26 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
 Worker Professional: 130 mg/m³; Consumer: 26 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
 Worker Professional: 130 mg/m³; Consumer: 26 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
 Worker Professional: 130 mg/m³; Consumer: 26 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 20 mg/kg; Consumer: 4 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
 Worker Professional: 20 mg/kg; Consumer: 4 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 4 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 4 mg/kg

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State: Solid

Color: Colourless

Odour: Light

Odour threshold: N.A.

pH: Not Relevant

Kinematic viscosity: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: 227.1 °C (440.8 °F)

Flash point: > 93°C

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 1.08 g/cm³

Solubility in water: N.A.

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: N.A.

Volatile Organic compounds - VOCs = 0.04 % ; 0.39 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

| | |
|--------------------------------------|--|
| a) acute toxicity | Not classified Based on available data, the classification criteria are not met |
| b) skin corrosion/irritation | Not classified Based on available data, the classification criteria are not met |
| c) serious eye damage/irritation | The product is classified: Eye Irrit. 2(H319) |
| d) respiratory or skin sensitisation | The product is classified: Skin Sens. 1A(H317) |
| e) germ cell mutagenicity | Not classified Based on available data, the classification criteria are not met |
| f) carcinogenicity | Not classified Based on available data, the classification criteria are not met |
| g) reproductive toxicity | Not classified Based on available data, the classification criteria are not met |
| h) STOT-single exposure | Not classified Based on available data, the classification criteria are not met |
| i) STOT-repeated exposure | Not classified Based on available data, the classification criteria are not met |
| j) aspiration hazard | Not classified Based on available data, the classification criteria are not met |

Toxicological information on main components of the mixture:

| | | | |
|---|--------------------------------------|---|------------------|
| Trimethoxyvinilsilane | a) acute toxicity | LD50 Oral Rat = 7.34 ml/Kg LC50 Inhalation Vapour Rat = 2773 Ppm 4h LD50 Skin Rabbit = 3.36 mg/kg 24h | |
| | b) skin corrosion/irritation | Skin Irritant Rabbit Negative 24h | |
| | c) serious eye damage/irritation | Eye Irritant Rabbit No 24h | |
| | d) respiratory or skin sensitisation | Skin Sensitization Guineapig Positive | |
| | f) carcinogenicity | Genotoxicity Rat Negative | Inhalation route |
| | g) reproductive toxicity | No Observed Adverse Effect Level Oral Rat = 250 mg/kg | |
| 3-(trimethoxysilyl)propylamine | a) acute toxicity | LD50 Oral Rat = 2.97 ml/Kg LC50 Inhalation Vapour Rat Negative 6h LD50 Skin Rabbit = 11.3 ml/Kg 24h | No deaths |
| | b) skin corrosion/irritation | Skin Irritant Rabbit Positive 4h | |
| | c) serious eye damage/irritation | Eye Irritant Rabbit Yes | |
| | d) respiratory or skin sensitisation | Skin Sensitization Guineapig Negative | |
| | g) reproductive toxicity | No Observed Adverse Effect Level Oral Rat = 300 mg/kg | |
| | | | |
| 1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate | a) acute toxicity | LD50 Oral Rat = 3230 mg/kg LD50 Skin Rat > 3170 mg/kg | |
| | b) skin corrosion/irritation | Skin Irritant Rabbit Negative 24h | |

| | | | |
|----------|--------------------------------------|--|-----------------------------|
| | c) serious eye damage/irritation | Eye Irritant Rabbit No | |
| | d) respiratory or skin sensitisation | Skin Sensitization Guinea pig Positive | |
| | f) carcinogenicity | Genotoxicity Negative | Mouse oral route |
| | g) reproductive toxicity | No Observed Adverse Effect Level Oral Rat = 30 mg/kg | |
| methanol | a) acute toxicity | LD50 Oral Rat >= 2528 mg/kg LC50 Inhalation = 43.68 mg/l 6h LD50 Skin Rabbit = 17100 mg/kg | Cat |
| | b) skin corrosion/irritation | Skin Irritant Rabbit Negative | |
| | c) serious eye damage/irritation | Eye Irritant Rabbit No | |
| | d) respiratory or skin sensitisation | Skin Sensitization Guinea pig Negative | |
| | f) carcinogenicity | Genotoxicity Negative Carcinogenicity Rat Negative | Mouse intraperitoneal route |
| | g) reproductive toxicity | Lowest Observed Adverse Effect Level Oral = 1000 mg/kg | Mouse |
| | | | |
| | | | |

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of Eco-Toxicological properties of the components

| Component | Ident. Numb. | Ecotox Data |
|--------------------------------|---|---|
| Trimethoxyvinylsilane | CAS: 2768-02-7 - EINECS: 220-449-8 - INDEX: 014-049-00-0 | a) Aquatic acute toxicity : LC50 Fish <i>Oncorhynchus mykiss</i> = 137 mg/L 96h a) Aquatic acute toxicity : LC50 <i>Daphnia magna</i> = 121 mg/L 48h b) Aquatic chronic toxicity : NOEC <i>Daphnia magna</i> = 20 mg/L - 21days a) Aquatic acute toxicity : EC50 Algae <i>Pseudokirchneriella subcapitata</i> > 89 mg/L 72h a) Aquatic acute toxicity : EC10 microorganisms > 100 mg/L 3h OECD 209 |
| 3-(trimethoxysilyl)propylamine | CAS: 13822-56-5 - EINECS: 237-511-5 | a) Aquatic acute toxicity : LC50 Fish <i>Danio rerio</i> > 579 mg/L 96h „OECD Guideline 203 (Fish, Acute Toxicity Test) a) Aquatic acute toxicity : LC50 <i>Daphnia magna</i> = 205 mg/L 48h OECD Guideline 202 (<i>Daphnia</i> sp. Acute Immobilisation Test) b) Aquatic chronic toxicity : NOEC <i>Daphnia magna</i> = 1 ppm - 21days a) Aquatic acute toxicity : EC50 Algae <i>Scenedesmus subspicatus</i> = 620 mg/L 72h ISO 10253 c) Bacteria toxicity : EC50 <i>Pseudomonas putida</i> = 43 mg/L |

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate

CAS: 1065336-91-5 - EINECS: 915-687-0

a) Aquatic acute toxicity : LC50 Fish Danio rerio = 0.9 mg/L 96h OECD Guideline 203

b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 1 mg/L OECD guideline 211

a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 1.68 mg/L 72h OECD Guideline 201

a) Aquatic acute toxicity : EC20 Sludge activated sludge >= 100 mg/L 3h OECD guideline 209

methanol

CAS: 67-56-1 - EINECS: 200-659-6 - INDEX: 603-001-00-X

a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 15400 mg/L 96h

b) Aquatic chronic toxicity : NOEC Fish = 450 mg/L

a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 22200 mg/L 48h

b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 208 mg/L

a) Aquatic acute toxicity : EC50 Algae Selenastrum capricornutum = 22000 mg/L 96h OECD 201 Guideline.

d) Terrestrial toxicity : NOEC Worm Eisenia andrei = 10000 mg/kg

d) Terrestrial toxicity : NOEC Folsomia candida = 1000 mg/kg OECD Guideline 232

12.2. Persistence and degradability

| Component | Persistence/Degradability: | Value | Notes: |
|---|----------------------------|--------|--------|
| Trimethoxyvinylsilane | Readily biodegradable | | |
| 3-(trimethoxysilyl)propylamine | Non-readily biodegradable | | |
| 1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate | Non-readily biodegradable | 38.000 | 28days |
| methanol | Readily biodegradable | | |

12.3. Bioaccumulative potential

| Component | Bioaccumulation | Test | Notes: |
|---|---------------------|-------------------------------|--------|
| 1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate | Not bioaccumulative | | |
| methanol | Not bioaccumulative | BCF - Bioconcentration factor | < 10 |

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration >= 0.1%

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as hazardous waste

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

N/A

14.2. UN proper shipping name

ADR-Shipping Name: N/A

IATA-Technical name: N/A

IMDG-Technical name: N/A

14.3. Transport hazard class(es)

IATA-Class: N/A

IMDG-Class: N/A

14.4. Packing group

IATA-Packing group: N/A

IMDG-Packing group: N/A

14.5. Environmental hazards

N.A.

IMDG-EMS: N/A

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code): N/A

ADR Limited Quantities: N/A

ADR Excepted Quantities: N/A

Air (IATA):

IATA-Passenger Aircraft: N/A

IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A

IATA-Erg: N/A

IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage Code: N/A

IMDG-Stowage Note: N/A

IMDG-Subsidiary hazards: N/A

IMDG-Special Provisions: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)
Regulation (EU) n. 2021/849 (ATP 17 CLP)
Regulation (EU) n. 2022/692 (ATP 18 CLP)
Regulation (EU) n. 2020/878
Regulation (EC) nr 648/2004 (Detergents).
Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
Restrictions related to the product: None.
Restrictions related to the substances contained: 40, 69, 75
Provisions related to directive EU 2012/18 (Seveso III):
N.A.

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed
German Water Hazard Class.
Class 1: slightly hazardous for water.
SVHC Substances:
No SVHC substances present in concentration >= 0.1%

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for the mixture.
Substances for which a Chemical Safety Assessment has been carried out:
Trimethoxyvinilsilane
3-(trimethoxysilyl)propylamine
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate

SECTION 16: Other information

| Code | Description | |
|--------------|---|---|
| H225 | Highly flammable liquid and vapour. | |
| H301 | Toxic if swallowed. | |
| H311 | Toxic in contact with skin. | |
| H315 | Causes skin irritation. | |
| H317 | May cause an allergic skin reaction. | |
| H318 | Causes serious eye damage. | |
| H319 | Causes serious eye irritation. | |
| H331 | Toxic if inhaled. | |
| H332 | Harmful if inhaled. | |
| H361 | Suspected of damaging fertility or the unborn child. | |
| H370 | Causes damage to organs. | |
| H400 | Very toxic to aquatic life. | |
| H410 | Very toxic to aquatic life with long lasting effects. | |
| H412 | Harmful to aquatic life with long lasting effects. | |
| Code | Hazard class and hazard category | Description |
| 2.6/2 | Flam. Liq. 2 | Flammable liquid, Category 2 |
| 3.1/3/Dermal | Acute Tox. 3 | Acute toxicity (dermal), Category 3 |
| 3.1/3/Inhal | Acute Tox. 3 | Acute toxicity (inhalation), Category 3 |
| 3.1/3/Oral | Acute Tox. 3 | Acute toxicity (oral), Category 3 |
| 3.1/4/Inhal | Acute Tox. 4 | Acute toxicity (inhalation), Category 4 |
| 3.2/2 | Skin Irrit. 2 | Skin irritation, Category 2 |
| 3.3/1 | Eye Dam. 1 | Serious eye damage, Category 1 |
| 3.3/2 | Eye Irrit. 2 | Eye irritation, Category 2 |
| 3.4.2/1A | Skin Sens. 1A | Skin Sensitisation, Category 1A |
| 3.4.2/1B | Skin Sens. 1B | Skin Sensitisation, Category 1B |
| 3.7/2 | Repr. 2 | Reproductive toxicity, Category 2 |

| | | |
|--------|-------------------|--|
| 3.8/1 | STOT SE 1 | Specific target organ toxicity — single exposure, Category 1 |
| 4.1/A1 | Aquatic Acute 1 | Acute aquatic hazard, category 1 |
| 4.1/C1 | Aquatic Chronic 1 | Chronic (long term) aquatic hazard, category 1 |
| 4.1/C3 | Aquatic Chronic 3 | Chronic (long term) aquatic hazard, category 3 |

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008 Classification procedure

| | |
|-------------------------|--------------------|
| Eye Irrit. 2, H319 | Calculation method |
| Skin Sens. 1A, H317 | Calculation method |
| Aquatic Chronic 3, H412 | Calculation method |

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: Keep Away From Heat

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

Exposure Scenario

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate
bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate

Exposure Scenario, 20/04/2022

| Substance identity | |
|--------------------|---|
| | 1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate |
| CAS No. | 1065336-91-5 |
| EINECS No. | 915-687-0 |

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9a, PC9b)

| | | | |
|--|--|---|--|
| 1. ES 1 | | Widespread use by professional workers; Various products (PC9a, PC9b) | |
| 1.1 TITLE SECTION | | | |
| Exposure Scenario name | Professional application of coatings and inks - Use in rigid foams, coatings, adhesives and sealants | | |
| Date - Version | 20/04/2022 - 1.0 | | |
| Life Cycle Stage | Widespread use by professional workers | | |
| Main user group | Professional uses | | |
| Sector(s) of use | Professional uses (SU22) | | |
| Product Categories | Coatings and paints, thinners, paint removers (PC9a) - Fillers, putties, plasters, modelling clay (PC9b) | | |
| Environment Contributing Scenario | | | |
| CS1 | ERC8c | | |
| Worker Contributing Scenario | | | |
| CS2 Material transfers | PROC8a | | |
| CS3 Rolling, Brushing | PROC10 | | |
| 1.2 Conditions of use affecting exposure | | | |
| 1.2. CS1: Environment Contributing Scenario (ERC8c) | | | |
| Environmental release categories | Widespread use leading to inclusion into/onto article (indoor) (ERC8c) | | |
| <i>Product (article) characteristics</i> | | | |
| Physical form of product: Liquid | | | |
| Vapour pressure: Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa | | | |
| <i>Amount used, frequency and duration of use (or from service life)</i> | | | |
| Emission days: 365 days per year | | | |
| <i>Technical and organisational conditions and measures</i> | | | |
| Control measures to prevent releases | | | |
| | | Air - minimum efficiency of: 15 % Water - minimum efficiency of: 1 % | |
| <i>Conditions and measures related to sewage treatment plant</i> | | | |
| STP type: Municipal Sewage Treatment Plant Water - minimum efficiency of: = 88.9 % | | | |
| STP effluent (m³/day): 2000 | | | |
| <i>Other conditions affecting environmental exposure</i> | | | |
| Local marine water dilution factor: 100 Local freshwater dilution factor: 10 Receiving surface water flow: 18000 m³/day Indoor use | | | |
| 1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a) | | | |

| | | |
|--|--|--|
| Process Categories | Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a) | |
| <i>Product (article) characteristics</i> | | |
| Physical form of product: Liquid | | |
| Vapour pressure: Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa | | |
| Concentration of substance in product: Covers percentage substance in the product up to 5 %. | | |
| <i>Amount used, frequency and duration of use/exposure</i> | | |
| Duration: Covers use up to 480 min | | |
| Frequency: Covers use up to 5 days per week | | |
| <i>Technical and organisational conditions and measures</i> | | |
| Technical and organisational measures Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed. Ensure operatives are trained to minimise exposures. | | |
| <i>Conditions and measures related to personal protection, hygiene and health evaluation</i> | | |
| Personal protection | | |
| Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. | | Dermal - minimum efficiency of: = 90 % |
| Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin. | | |
| <i>Other conditions affecting worker exposure</i> | | |
| Indoor use Professional use | | |
| <i>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.</i> | | |
| Additional Good Practice Advice: Ensure no splashing occurs during transfer. | | |
| 1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10) | | |
| Process Categories | Roller application or brushing (PROC10) | |
| <i>Product (article) characteristics</i> | | |
| Physical form of product: Liquid | | |
| Vapour pressure: Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa | | |
| Concentration of substance in product: Covers percentage substance in the product up to 5 %. | | |
| <i>Amount used, frequency and duration of use/exposure</i> | | |
| Duration: Covers use up to 480 min | | |
| Frequency: Covers use up to 5 days per week | | |
| <i>Technical and organisational conditions and measures</i> | | |
| Technical and organisational measures | | |

Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed.
Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

| | |
|---|--|
| Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. | Dermal - minimum efficiency of: = 90 % |
| Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin. | |

Other conditions affecting worker exposure

Indoor use
Professional use

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Ensure no splashing occurs during transfer.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8c)

| protection target | Exposure level | Calculation method | Risk Characterization Ratio (RCR) |
|-------------------|----------------|-----------------------------|-----------------------------------|
| soil | N/A | ECETOC TRA environment v2.0 | 0.0579 |

Additional information on exposure estimation:

Risk from environmental exposure is driven by soil.

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

| Exposure route, Health effect, Exposure indicator | Exposure level | Calculation method | Risk Characterization Ratio (RCR) |
|---|----------------------------|----------------------|-----------------------------------|
| dermal, systemic, long-term | = 0.2743 mg/kg bw/day | ECETOC TRA worker v3 | = 0.137143 |
| inhalative, systemic, long-term | = 0.4233 mg/m ³ | ECETOC TRA worker v3 | = 0.119924 |

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

| Exposure route, Health effect, Exposure indicator | Exposure level | Calculation method | Risk Characterization Ratio (RCR) |
|---|------------------------------|----------------------|-----------------------------------|
| dermal, systemic, long-term | = 0.5486 mg/kg bw/day | ECETOC TRA worker v3 | = 0.274286 |
| inhalative, systemic, long-term | = 0.274286 mg/m ³ | ECETOC TRA worker v3 | = 0.097 |

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

3-(trimethoxysilyl)propylamine

Exposure Scenario, 25/08/2021

| Substance identity | |
|---------------------|--------------------------------|
| | 3-(trimethoxysilyl)propylamine |
| CAS No. | 13822-56-5 |
| EINECS No. | 237-511-5 |
| Registration number | 01-2119510159-45 |

Table of contents

1. **ES 1** Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)

1. ES 1

Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)

1.1 TITLE SECTION

| | |
|-------------------------------|--|
| Exposure Scenario name | Professional application of coatings and inks |
| Date - Version | 25/08/2021 - 1.0 |
| Life Cycle Stage | Widespread use by professional workers |
| Main user group | Professional uses |
| Sector(s) of use | Professional uses (SU22) |
| Product Categories | Coatings and paints, thinners, paint removers (PC9a) |

Environment Contributing Scenario

| | |
|------------|---------------|
| CS1 | ERC8c - ERC8f |
|------------|---------------|

Worker Contributing Scenario

| | |
|---|--------|
| CS2 Rolling, Brushing | PROC10 |
| CS3 Roller, spreader, flow application | PROC11 |

1.2 Conditions of use affecting exposure**1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)**

| | |
|---|---|
| Environmental release categories | Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f) |
|---|---|

*Product (article) characteristics***Physical form of product:**

Liquid

Concentration of substance in product:

Covers concentrations up to 2 %

*Amount used, frequency and duration of use (or from service life)***Amounts used:**

Annual site tonnage = 0.004 t(tonnes)/year

Release type: Continuous release**Emission days:** 365 days per year*Conditions and measures related to sewage treatment plant***STP type:**

Municipal Sewage Treatment Plant

STP effluent (m³/day): 2000*Other conditions affecting environmental exposure***Local marine water dilution factor:** 100**Local freshwater dilution factor:** 10**1.2. CS2: Worker Contributing Scenario: Rolling, Brushing (PROC10)**

| | |
|---------------------------|---|
| Process Categories | Roller application or brushing (PROC10) |
|---------------------------|---|

*Product (article) characteristics***Physical form of product:**

Liquid

Concentration of substance in product:

| | | | |
|---|-----------------------|--------------------------------------|--|
| Covers concentrations up to 2 % | | | |
| Amount used, frequency and duration of use/exposure | | | |
| Amounts used: Application rate = 0.011 kg/day Annual site tonnage = 0.004 t(onnes)/year | | | |
| Duration: Exposure duration > 4 h | | | |
| Conditions and measures related to personal protection, hygiene and health evaluation | | | |
| Personal protection | | | |
| Wear suitable gloves tested to EN374. | | Dermal - minimum efficiency of: 80 % | |
| Other conditions affecting worker exposure | | | |
| Covers indoor and outdoor use Professional use Room size: 20 m ³ Ventilation rate: 0.6 ach (air changes per hour) | | | |
| 1.2. CS3: Worker Contributing Scenario: Roller, spreader, flow application (PROC11) | | | |
| Process Categories | | Non industrial spraying (PROC11) | |
| Product (article) characteristics | | | |
| Physical form of product: Liquid | | | |
| Concentration of substance in product: Covers concentrations up to 2 % | | | |
| Amount used, frequency and duration of use/exposure | | | |
| Amounts used: Application rate = 0.011 kg/day Annual site tonnage = 0.004 t(onnes)/year | | | |
| Duration: Exposure duration > 4 h | | | |
| Conditions and measures related to personal protection, hygiene and health evaluation | | | |
| Personal protection | | | |
| Wear suitable gloves tested to EN374. | | Dermal - minimum efficiency of: 80 % | |
| Other conditions affecting worker exposure | | | |
| Covers indoor and outdoor use Professional use Room size: 20 m ³ Ventilation rate: 0.6 ach (air changes per hour) | | | |
| 1.3 Exposure estimation and reference to its source | | | |
| 1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f) | | | |
| protection target | Exposure level | Calculation method | Risk Characterization Ratio (RCR) |
| freshwater | = 0.00132 mg/L | EUSES v2.1 | N/A |

| | | | |
|------------------------|-----------------------------|------------|-----|
| soil | = 0.000325 mg/kg dry weight | EUSES v2.1 | N/A |
| freshwater sediment | = 0.00105 mg/kg dry weight | EUSES v2.1 | N/A |
| marine water | = 0.000129 mg/L | EUSES v2.1 | N/A |
| marine sediment | = 0.000102 mg/kg dry weight | EUSES v2.1 | N/A |
| Sewage treatment plant | = 5.51E-05 mg/L | EUSES v2.1 | N/A |

1.3. CS2: Worker Contributing Scenario: Rolling, Brushing (PROC10)

| Exposure route, Health effect, Exposure indicator | Exposure level | Calculation method | Risk Characterization Ratio (RCR) |
|---|---------------------------|------------------------|-----------------------------------|
| inhalative | = 37.35 mg/m ³ | ECETOC TRA worker v2.0 | N/A |

1.3. CS3: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

| Exposure route, Health effect, Exposure indicator | Exposure level | Calculation method | Risk Characterization Ratio (RCR) |
|---|---------------------|------------------------|-----------------------------------|
| dermal, long-term | = 0.21 mg/kg bw/day | ECETOC TRA worker v2.0 | N/A |

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

Trimethoxyvinilsilane

Exposure Scenario, 08/06/2021

| Substance identity | |
|---------------------|-----------------------|
| | Trimethoxyvinilsilane |
| CAS No. | 2768-02-7 |
| INDEX No. | 014-049-00-0 |
| EINECS No. | 220-449-8 |
| Registration number | 01-2119513215-52 |

Table of contents

1. ES 1

1. ES 1

1.1 TITLE SECTION

| | |
|------------------------|--|
| Exposure Scenario name | Use in rigid foams, coatings, adhesives and sealants - Barrier (Sealant) |
| Date - Version | 18/05/2021 - 1.0 |
| Main user group | Professional uses |
| Sector(s) of use | Professional uses (SU22) - Building and construction work (SU19) |
| Product Categories | Adhesives, sealants (PC1) |

Environment Contributing Scenario

| | |
|-------------------------------|---------------|
| CS1 Low environmental release | ERC8c - ERC8f |
|-------------------------------|---------------|

Worker Contributing Scenario

| | |
|---|-------|
| CS2 Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application | PROC0 |
| CS3 Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application | PROC1 |

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Low environmental release (ERC8c, ERC8f)

| | |
|----------------------------------|---|
| Environmental release categories | Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f) |
|----------------------------------|---|

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Concentration after dilution for use maximum [%]: 0.7 %

Amount used, frequency and duration of use (or from service life)

Amounts used:

Daily amount per site = 0.28 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

| | |
|--|--------------------------------------|
| | Water - minimum efficiency of: 1.5 % |
|--|--------------------------------------|

Conditions and measures related to sewage treatment plant

STP type:

Onsite Sewage Treatment Plant

Water - minimum efficiency of: = 0.013 %

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Dispose of waste product or used containers according to local regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 20000 m³/day

| | |
|---|--|
| Covers indoor and outdoor use | |
| 1.2. CS2: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC0) | |
| Process Categories | Other (PROC0) |
| <i>Product (article) characteristics</i> | |
| Physical form of product: Liquid | |
| Concentration of substance in product: Covers concentrations up to 0.7 % | |
| <i>Amount used, frequency and duration of use/exposure</i> | |
| Duration: Exposure duration <= 6 h | |
| Frequency: Use frequency = 250 days per year | |
| <i>Technical and organisational conditions and measures</i> | |
| Technical and organisational measures Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). For further specification, refer to section 8 of the SDS. | |
| <i>Other conditions affecting worker exposure</i> | |
| Covers indoor and outdoor use Professional use Room size: Covers use in room size of = 20 m ³ Temperature: Covers use at ambient temperatures. 25°C | |
| 1.2. CS3: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC1) | |
| Process Categories | Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) |
| <i>Product (article) characteristics</i> | |
| Physical form of product: Liquid | |
| Concentration of substance in product: Covers concentrations up to 2 % | |
| <i>Amount used, frequency and duration of use/exposure</i> | |
| Duration: Exposure duration = 8 h | |
| Frequency: Use frequency = 1 days per year | |
| Duration: Covers use up to = 6 h | |
| Frequency: Use frequency = 1 days per year | |
| <i>Other conditions affecting worker exposure</i> | |
| Covers indoor and outdoor use Professional use Room size: Covers use in room size of = 20 m ³ Ventilation rate: = 0.6 ach (air changes per hour) | |
| 1.3 Exposure estimation and reference to its source | |
| 1.3. CS2: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC0) | |

| Exposure route, Health effect, Exposure indicator | Exposure level | Calculation method | Risk Characterization Ratio (RCR) |
|---|-------------------------|--------------------|-----------------------------------|
| inhalative, long-term | = 1.9 mg/m ³ | N/A | = 0.069 |
| dermal, long-term | = 4.53 mg/kg bw/day | ConsExpo | = 0.038 |
| combined routes, long-term | N/A | N/A | 0.107 |

1.3. CS3: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC1)

| Exposure route, Health effect, Exposure indicator | Exposure level | Calculation method | Risk Characterization Ratio (RCR) |
|---|--------------------------|--------------------|-----------------------------------|
| inhalative, long-term | = 4.57 mg/m ³ | N/A | = 0.682 |
| dermal, long-term | = 0.044 mg/kg bw/day | ConsExpo | < 0.01 |
| combined routes, short-term | N/A | N/A | 0.682 |

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.