

Safety Data Sheet

Conforms to – Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II,
as amended by UK SI 2021/904

EP21 (B)

Date of first edition: 1/5/2026

Safety Data Sheet dated 05/01/2026 version 1

kerakoll

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: EP21 (B)

Trade code: S100B0172

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: hardener

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Kerakoll UK Ltd

Tomlinson Road, Leyland, Lancashire, PR25 2DY,

United Kingdom

Tel. 01772 456831

safety@kerakoll.co.uk

1.4. Emergency telephone number

UK National Poisons Information Service.

E-mail: npis.birmingham@nhs.net; Tel: +44 (0)344 892 0111

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

GB CLP regulation:

Skin Corr. 1B Causes severe skin burns and eye damage.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1A May cause an allergic skin reaction.

Aquatic Acute 1 Very toxic to aquatic life.

Aquatic Chronic 2 Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

GB CLP regulation:

Hazard pictograms and Signal Word



Danger

Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves and eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

Contains

Cashew, nutshell liq.

2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated

M-phenylenebis(methylamine)

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012 (UK implementation of Dir. 2004/42/EC)

Binding primers

Limit value for this product (cat. A/h): 750 g/l

This product contains max 0 g/l VOC.

Special provisions according to Annex XVII of UK REACH:

None.

2.3. Other hazards

When mixtures containing cement react with water, for instance when making concrete or mortar, or when the cement becomes wet, a strong alkaline solution is produced (high pH caused by the formation of calcium, sodium and potassium hydroxides).

Cement and mixtures containing cement may irritate the eyes, the mucous system, the throat and the respiratory system and cause coughing. Frequent inhalation of cement dust or mixtures containing cement over a long period of time increases the risk of developing lung diseases.

In case of prolonged contact with the skin, both cement and mixtures containing cement, including pastes, may cause skin sensitisation due to the presence of trace amounts of chromium VI salts. Where necessary, such an effect can be minimized by incorporating a special reducing agent to maintain the water-soluble chromium VI content to concentration rates below 0.0002% (2 ppm) on the total dry weight of cement.

No PBT or vPvB substances present in concentration >= 0.1%

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: EP21 (B)

Hazardous components within the meaning of GB CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥20-<50 %	2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated	CAS:1173092-74-4 EC:630-554-4	Skin Corr. 1, H314; Skin Sens. 1, H317	
≥10-<20 %	M-phenylenebis(methylamine)	CAS:1477-55-0 EC:216-032-5	Acute Tox. 4, H302; Acute Tox. 4, H332; Aquatic Chronic 3, H412; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1B, H314, EUH071	
≥10-<20 %	Cashew, nutshell liq.	CAS:8007-24-7 EC:700-991-6	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1A, H317	
≥10-<20 %	FATTY ACIDS, C18 UNSAT., REACTION PRODUCTS WITH TETRAETHYLENEPENTAMINE	CAS:1226892-45-0 EC:629-725-6	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317; Skin Corr. 1C, H314; Eye Dam. 1, H318, M-Chronic:1, M-Acute:10	
≥3-<5 %	1,3-benzenedimethanamine, n-(2-phenylethyl) derivs.	CAS:404362-22-7 EC:445-790-1	Acute Tox. 4, H302; Skin Corr. 1, H314; Skin Sens. 1, H317; STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410, M-Chronic:1, M-Acute:1	

≥1-<3 %	2,4,6-tris(dimethylaminomethyl)phenol	CAS:90-72-2 EC:202-013-9 Index:603-069-00-0	Acute Tox. 4, H302; Skin Corr. 1C, H314; Eye Dam. 1, H318
≥1-<3 %	3-aminopropyldiethylamine	CAS:104-78-9 EC:203-236-4 Index:612-062-00-1	Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 3, H311; Skin Corr. 1B, H314; Eye Dam. 1, H318; Skin Sens. 1, H317
≥1-<3 %	amines, polyethylenepoly-; HEPA	CAS:68131-73-7 EC:268-626-9 Index:612-121-00-1	Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Acute Tox. 4, H312, M-Chronic:1

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAINT IMMEDIATE MEDICAL ATTENTION.
- Remove contaminated clothing immediatley and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

- None in particular.

5.2. Special hazards arising from the substance or mixture

- Do not inhale explosion and combustion gases.

- Burning produces heavy smoke.

5.3. Advice for firefighters

- Use suitable breathing apparatus .

- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

- Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

- Wear personal protection equipment.

- Remove persons to safety.

- See protective measures under point 7 and 8.

For emergency responders:

- Wear personal protection equipment.

6.2. Environmental precautions

- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

- Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

The product must be stored in waterproof, dry, clean conditions and protected from contamination. Do not use aluminium containers due to incompatibility of the materials.

The product contains cement with an addition of a Chromium reducing agent (VI) and its effectiveness decreases with time. Consequently, packaging's of the material indicate information about the production date, storing conditions and the appropriate storage period for the maintaining of the activity of the reducing agent and for maintaining the soluble Chromium (VI) amount under 2ppm over the total dry weight referred to cement (BS EN 196-10).

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

OEL Type	Occupational Exposure Limit
----------	-----------------------------

M-phenylenebis(methylamine)	ACGIH	Short Term: Ceiling - 0.018 ppm
		Skin - Eye, skin, and GI irr
CAS: 1477-55-0		

Predicted No Effect Concentration (PNEC) values

M-phenylenebis(methylamine)	CAS: 1477-55-0	Exposure Route: Fresh Water; PNEC Limit: 94 µg/l
-----------------------------	----------------	--

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 152 µg/l

Exposure Route: Marine water; PNEC Limit: 9.4 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 430 µg/kg

Exposure Route: Marine water sediments; PNEC Limit: 43 µg/kg

Exposure Route: Soil; PNEC Limit: 45 µg/kg

Cashew, nutshell liq.	CAS: 8007-24-7	Exposure Route: Fresh Water; PNEC Limit: 0.003 mg/l
-----------------------	----------------	---

Exposure Route: Marine water sediments; PNEC Limit: 0.088 mg/kg

Exposure Route: Freshwater sediments; PNEC Limit: 0.97 mg/kg

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.03 mg/l

Exposure Route: Soil; PNEC Limit: 6.71 mg/kg

1,3-	Exposure Route: Fresh Water; PNEC Limit: 800 ng/L
------	---

benzedimethanamine,
n-(2-phenylethyl) derivs.
CAS: 404362-22-7

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 1.5 µg/l
Exposure Route: Marine water; PNEC Limit: 80 ng/L
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 1 ng/L
Exposure Route: Freshwater sediments; PNEC Limit: 140 µg/kg
Exposure Route: Marine water sediments; PNEC Limit: 14 µg/kg
Exposure Route: Soil; PNEC Limit: 28 µg/kg
Exposure Route: Secondary poisoning; PNEC Limit: 167 µg/kg

2,4,6-
tris
(dimethylaminomethyl)
phenol
CAS: 90-72-2

Exposure Route: Fresh Water; PNEC Limit: 84 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 840 µg/l
Exposure Route: Marine water; PNEC Limit: 8.4 µg/l
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 200 µg/l

3-
aminopropyldiethylamine
CAS: 104-78-9

Exposure Route: Fresh Water; PNEC Limit: 30 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 300 µg/l
Exposure Route: Marine water; PNEC Limit: 3 µg/l
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 418.2 µg/kg
Exposure Route: Marine water sediments; PNEC Limit: 41.8 µg/kg
Exposure Route: Soil; PNEC Limit: 66 µg/kg

amines,
polyethylenopoly-; HEPA
CAS: 68131-73-7

Exposure Route: Fresh Water; PNEC Limit: 1.6 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 16 µg/l
Exposure Route: Marine water; PNEC Limit: 1.6 µg/l
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 3.19 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 0.14 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 0.14 mg/kg
Exposure Route: Soil; PNEC Limit: 10 mg/kg

Derived No Effect Level (DNEL) values

M-
phenylenebis
(methylamine)
CAS: 1477-55-0

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 1.2 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 200 µg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 330 µg/kg

Cashew, nutshell liq.
CAS: 8007-24-7

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects
Worker Professional: 0.5 mg/kg; Consumer: 0.25 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 0.88 mg/m³; Consumer: 0.2 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Long Term, local effects
Consumer: 0.25 mg/kg

1,3-
benzedimethanamine,
n-(2-phenylethyl) derivs.
CAS: 404362-22-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 180 µg/m³; Consumer: 40 µg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 4 µg/m³; Consumer: 2 µg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 50 µg/kg; Consumer: 30 µg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 30 µg/kg

3-aminopropylidethylamine
CAS: 104-78-9
Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 24.7 mg/m³; Consumer: 1.8 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 3.5 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 500 µg/l

amines, polyethylenepoly-; HEPA
CAS: 68131-73-7
Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 1.59 mg/m³; Consumer: 0.46 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 8550 mg/m³; Consumer: 2542 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 0.65 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 32 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 0.91 mg/m³; Consumer: 0.4 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects
Worker Professional: 0.044 mg/cm²; Consumer: 0.68 mg/cm²

Exposure Route: Human Dermal; Exposure Frequency: Short Term (acute)
Consumer: 1.59 mg/cm²

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing. Safety shoes.

Protection for hands:

Protection for hands:

Suitable materials for safety gloves; EN 374:

Nitrile rubber - NBR: thickness ≥0,35mm; breakthrough time ≥480min.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

Not expected if used as intended

Environmental exposure controls:

Prevent the product from entering sewers or surface and underground water.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State: Liquid

Appearance and colour: Viscous Brown

Odour: Odourless

Odour threshold: N.A.

pH: Not Relevant Notes: non determinable

Melting point / freezing point: N.A. Notes: non determinable

Initial boiling point and boiling range: 200 °C (392 °F)

Flash point: 93 °C (199 °F)

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 1.00 g/cm3
Solubility in water: Insoluble
Solubility in oil: N.A.
Partition coefficient (n-octanol/water): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Viscosity: 0.46 PA-s
Explosive properties: N.A.
Oxidizing properties: N.A.
Solid/gas flammability: N.A.
Volatile Organic compounds - VOCs = 0 % ; 0 g/l

9.2. Other information

Substance Groups relevant properties N.A.
Miscibility: N.A.
Conductivity: N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Corr. 1B(H314)
c) serious eye damage/irritation	The product is classified: Eye Dam. 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated

LD50 Oral = 500 mg/kg

M-phenylenebis(methylamine)	a) acute toxicity	LD50 Oral Rat = 1001 mg/kg	
		LC50 Inhalation Mist Rat = 1.34 mg/l 4h	
		LD50 Skin Rat > 3100 mg/kg	
	b) skin corrosion/irritation	Skin Irritant Rat Positive 4h	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	f) carcinogenicity	Genotoxicity Negative	Mouse
	g) reproductive toxicity	No Observed Effect Level Oral Rat = 450 mg/kg	
Cashew, nutshell liq.	a) acute toxicity	LD50 Oral Rat = 2000 mg/kg	
		LD50 Skin Rat > 2000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
FATTY ACIDS, C18 UNSAT., REACTION PRODUCTS WITH TETRAETHYLENEPENTAMINE	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg bw	
1,3-benzenedimethanamine, n-(2-phenylethyl) derivs.	a) acute toxicity	LD50 Oral Rat > 500 mg/kg	500 and 2000 mg/kg
	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	g) reproductive toxicity	No Observed Effect Level Oral Rat = 15 mg/kg	
2,4,6-tris(dimethylaminomethyl)phenol	a) acute toxicity	LD50 Oral Rat = 2169 mg/kg	
		LD50 Skin Rat > 1 ml/Kg 6h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive 4h	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Negative	
	g) reproductive toxicity	No Observed Effect Level Oral Rat = 15 mg/kg	
3-aminopropyldiethylamine	a) acute toxicity	LD50 Oral Rat = 830 mg/kg	
		LC50 Inhalation Vapour Rat Negative 4h	No mortality
		LD50 Skin Rabbit = 524 mg/kg 24h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Negative	
amines, polyethylenepoly-; HEPA	a) acute toxicity	LD50 Oral Rat = 1716.2 mg/kg	

		LD50 Skin Rabbit = 1465.4 mg/kg 24h
b) skin corrosion/irritation	Skin Corrosive	Rabbit Positive
c) serious eye damage/irritation	Eye Irritant	Rabbit Yes
d) respiratory or skin sensitisation	Skin Sensitization	Guineapig Positive
f) carcinogenicity	Genotoxicity	Negative
		Mouse intraperitoneal route

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Very toxic to aquatic organisms.

Toxic to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Acute 1(H400), Aquatic Chronic 2(H411)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
M-phenylenebis(methylamine)	CAS: 1477-55-0 - EINECS: 216- 032-5	<p>a) Aquatic acute toxicity : LC50 Fish Oryzias latipes = 87.6 mg/L 96h OECD 202</p> <p>b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 4.7 mg/L 211 - 21days</p> <p>a) Aquatic acute toxicity : EC50 Algae Selenastrum capricornutum = 32.1 mg/L 72h OECD 201</p> <p>a) Aquatic acute toxicity : EC50 Sludge activated sludge > 1000 mg/L OECD 209</p>
Cashew, nutshell liq.	CAS: 8007-24-7 - EINECS: 700- 991-6	<p>a) Aquatic acute toxicity : LC50 Fish Cyprinodon variegatus = 1000 mg/L 96h „OECD Guideline 203 (Fish, Acute Toxicity Test)</p> <p>a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 40.46 mg/L 48h „EPA OPPTS 850.1010 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)</p> <p>a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 1300 mg/L 72h „OECD Guideline 201 (Alga, Growth Inhibition Test)</p> <p>a) Aquatic acute toxicity : NOEC Sludge activated sludge = 100 mg/L</p>
1,3-benzenedimethanamine, n-(2-phenylethyl) derivs.	CAS: 404362-22-7 - EINECS: 445-790-1	<p>a) Aquatic acute toxicity : LL50 Fish Oncorhynchus mykiss = 4 mg/L 96h OECD TG 203</p> <p>a) Aquatic acute toxicity : EL50 Daphnia Daphnia magna = 3.4 mg/L 48h OECD TG 202</p> <p>b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 0.14 mg/L 96h OECD TG 211 - 21days</p> <p>a) Aquatic acute toxicity : NOELR Algae Scenedesmus subspicatus = 0.04 mg/L 72h OECD TG 201</p> <p>a) Aquatic acute toxicity : NOEC Sludge activated sewage sludge = 10 mg/L 3h OECD TG 209</p>
2,4,6-tris(dimethylaminomethyl)phenol	CAS: 90-72-2 - EINECS: 202- 013-9 - INDEX: 603-069-00-0	<p>a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 175 mg/L 96h</p> <p>a) Aquatic acute toxicity : LC50 Salmo gairdneri < 240 mg/L 96h</p> <p>a) Aquatic acute toxicity : LC50 Daphnia Paleomonetes vulgaris = 718 mg/L 96h</p>

3-aminopropyldiethylamine	CAS: 104-78-9 - EINECS: 203-38412 part 15 236-4 - INDEX: 612-062-00-1	a) Aquatic acute toxicity : EC50 Algae freshwater algae = 84 mg/L a) Aquatic acute toxicity : LC50 Fish Leuciscus idus = 146.6 mg/L 96h DIN 38412 part 15
amines, polyethylenepoly-; HEPA	CAS: 68131-73-7 - EINECS: 268-626-9 - INDEX: 612-121-00-1	a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata = 100 mg/L 96h EU Method C.1 (Acute Toxicity for Fish) a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 2.2 mg/L 48h EU Method C.2 (Acute Toxicity for Daphnia)
		a) Aquatic acute toxicity : EC50 Algae Selenastrum capricornutum = 0.23 mg/L 72h OECD TG 201
		c) Bacteria toxicity : EC50 Pseudomonas putida = 100.5 mg/L ,DIN 38412, part 8
		d) Terrestrial toxicity : NOEC Worm Eisenia fetida = 1000 mg/kg OECD Guideline 222 (Earthworm Reproduction Test (Eisenia fetida/Eisenia andrei)) - 56days

12.2. Persistence and degradability

Component	Persistence/Degradability:	Test	Value	Notes:
M-phenylenebis(methylamine)	Non-readily biodegradable	Oxygen consumption		OECD 301B
Cashew, nutshell liq.	Readily biodegradable	Oxygen consumption	83.800	%; EU Method C.4-D
1,3-benzenedimethanamine, n-(2-phenylethyl) derivs.	Non-readily biodegradable	Oxygen consumption		OECD TG 301C
2,4,6-tris(dimethylaminomethyl)phenol	Non-readily biodegradable			
3-aminopropyldiethylamine	Readily biodegradable			OECD Guideline 301A
amines, polyethylenepoly-; HEPA	Non-readily biodegradable	Oxygen consumption		OECD 301D

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Notes:
M-phenylenebis(methylamine)	Not bioaccumulative	BCF - Bioconcentration factor	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration >= 0.1%

12.6. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

SECTION 14: Transport information

14.1. UN number

2735

14.2. UN proper shipping name

ADR-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated - M-phenylenebis(methylamine))

IATA-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated - M-phenylenebis(methylamine))

IMDG-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated - M-phenylenebis(methylamine))

14.3. Transport hazard class(es)

ADR-Class: 8

IATA-Class: 8

IMDG-Class: 8

14.4. Packing group

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

14.5. Environmental hazards

Most important toxic component: FATTY ACIDS, C18 UNSAT., REACTION PRODUCTS WITH TETRAETHYLENEPENTAMINE

Toxic ingredients quantity: 0.00

Very toxic ingredients quantity: 20.77

Marine pollutant: Yes

Environmental Pollutant: Yes

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 8

ADR - Hazard identification number: 80

ADR-Special Provisions: 274

ADR-Transport category (Tunnel restriction code): 2 (E)

Air (IATA):

IATA-Passenger Aircraft: 851

IATA-Cargo Aircraft: 855

IATA-Label: 8

IATA-Subsidiary hazards: -

IATA-Erg: 8L

IATA-Special Provisions: A3 A803

Sea (IMDG):

IMDG-Stowage and handling: Category A

IMDG-Segregation: SG35 SGG18

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 274

IMDG-EMS: F-A, S-B

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace exposure limit within the meaning of the Control of Substances Hazardous to Health Regulations 2002 (WEL-EH40)

REACH regulation as changed by the REACH etc. (Amendment etc.) (EU Exit) Regulations (UK REACH)

CLP regulation as changed by the Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations (GB CLP)

GB PIC legislation - (Regulation (EU) No 649/2012 as changed by the Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc) (EU Exit) Regulations

Restrictions related to the product or the substances contained according to Annex XVII of UK REACH:

Restrictions related to the product: 3

Restrictions related to the substances contained: 40

Additional Regulatory Information for Great Britain

No Additional Information

Provisions related to the Control of Major Accident Hazards Regulations 2015 (GB implementation of Seveso III):

Seveso III category according to Schedule I, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
--	--------------------------------------	--------------------------------------

Product belongs to category: E1	100	200
---------------------------------	-----	-----

GB PIC Legislation:

No substances listed

SVHC Substances:

No SVHC substances present in concentration >= 0.1%

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012 (UK implementation of Dir. 2004/42/EC)

(ready to use)

Volatile Organic compounds - VOCs = 0.00 %

Volatile Organic compounds - VOCs = 0.00 g/L

EP21 (B) (not ready to use)

Volatile Organic compounds - VOCs = 0.00 %

Volatile Organic compounds - VOCs = 0.00 g/L

UK regulations implementing Dir. 2010/75/EC (VOC directive)

Volatile Organic compounds - VOCs = 0.00 %

Volatile Organic compounds - VOCs = 0.00 g/L

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

Cashew, nutshell liq.

2,4,6-tris(dimethylaminomethyl)phenol

amines, polyethylenepoly-; HEPA

SECTION 16: Other information

Code	Description
EUH071	Corrosive to the respiratory tract.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/3/Dermal	Acute Tox. 3	Acute toxicity (dermal), Category 3
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1	Skin Corr. 1	Skin corrosion, Category 1
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/1C	Skin Corr. 1C	Skin corrosion, Category 1C
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.9/2	STOT RE 2	Specific target organ toxicity — repeated exposure, Category 2

4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to GB CLP regulation:

Classification according to GB CLP	Classification procedure
Skin Corr. 1B, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1A, H317	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: Keep Away From Heat

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

Exposure Scenario

Amines, polyethylenepoly-; hepa

Exposure Scenario, 10/08/2021

Substance identity	
	Amines, polyethylenepoly-; hepa
CAS No.	68131-73-7
INDEX No.	612-121-00-1
EINECS No.	268-626-9
Registration number	01-2119485823-28

Table of contents

1. **ES 1** Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)
2. **ES 2** Widespread use by professional workers; Adhesives, sealants (PC1)

1. ES 1

Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)

1.1 TITLE SECTION

Exposure Scenario name	Professional application of coatings and inks
Date - Version	10/08/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Coatings and paints, thinners, paint removers (PC9a)

Environment Contributing Scenario

CS1	ERC8c - ERC8f
-----	---------------

Worker Contributing Scenario

CS2 Material transfers	PROC8a
CS3 Rolling, Brushing	PROC10
CS4 Roller, spreader, flow application	PROC11
CS5 Handling and dilution of concentrates	PROC19

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 25 %

Amount used, frequency and duration of use (or from service life)

Amounts used:

Daily amount per site = 2114 kg/day

Release type:

Continuous release

Emission days:

220 days per year

Other conditions affecting environmental exposure

Local freshwater dilution factor:

1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 25 %

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to > 15 min

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable respiratory protection.

Wear suitable gloves tested to EN374.

Inhalation - minimum efficiency of: 95 %

1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories Roller application or brushing (PROC10)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 15 %

Amount used, frequency and duration of use/exposure**Duration:**

Covers use up to 60 min

Technical and organisational conditions and measures**Technical and organisational measures**

Provide extract ventilation to points where emissions occur.

Inhalation - minimum efficiency of: 90 %

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories Non industrial spraying (PROC11)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 15 %

Amount used, frequency and duration of use/exposure**Duration:**

Covers use up to 60 min

Technical and organisational conditions and measures**Technical and organisational measures**

Provide extract ventilation to points where emissions occur.

Inhalation - minimum efficiency of: 90 %

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

1.2. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Process Categories	Manual activities involving hand contact (PROC19)
--------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 5 %

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to 8 h

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	7.92E-05 mg/L	EUSES	0.05
marine water	7.9E-06 mg/L	EUSES	0.005
freshwater sediment	0.0795 mg/kg dry weight	EUSES	0.568
marine sediment	0.00792 mg/kg dry weight	EUSES	0.057
soil	0.0118 mg/kg dry weight	EUSES	0.001

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.068 mg/kg bw/day	ECETOC TRA worker v2.0	0.12
inhalative, systemic, long-term	0.456 mg/m ³	ECETOC TRA worker v2.0	0.457
combined routes	N/A	N/A	0.577
inhalative, local, short-term	0.913 mg/m ³	ECETOC TRA worker v2.0	< 0.001

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.082 mg/kg bw/day	ECETOC TRA worker v2.0	0.144
inhalative, systemic, long-term	0.457 mg/m ³	ECETOC TRA worker v2.0	0.229
combined routes	N/A	N/A	0.373
inhalative, local, short-term	0.914 mg/m ³	ECETOC TRA worker v2.0	< 0.001

1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.214 mg/kg bw/day	ECETOC TRA worker v2.0	0.376
inhalative, systemic, long-term	0.121 mg/m ³	ECETOC TRA worker v2.0	0.122
combined routes	N/A	N/A	0.498
inhalative, local, short-term	0.243 mg/m ³	ECETOC TRA worker v2.0	< 0.001

1.3. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.14 mg/kg bw/day	ECETOC TRA worker v2.0	0.248
inhalative, systemic, long-term	0.76 mg/m ³	ECETOC TRA worker v2.0	0.076
combined routes	N/A	N/A	0.324
inhalative, local, short-term	1.52 mg/m ³	ECETOC TRA worker v2.0	< 0.001

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2

Widespread use by professional workers; Adhesives, sealants (PC1)

2.1 TITLE SECTION

Exposure Scenario name	Use in rigid foams, coatings, adhesives and sealants
Date - Version	10/08/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Adhesives, sealants (PC1)

Environment Contributing Scenario

CS1	ERC8a - ERC8d
-----	---------------

Worker Contributing Scenario

CS2 Material transfers	PROC8a
CS3 Rolling, Brushing	PROC10
CS4 Roller, spreader, flow application	PROC11
CS5 Handling and dilution of concentrates	PROC19

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 25 %

Amount used, frequency and duration of use (or from service life)

Amounts used:

Daily amount per site = 15500 kg/day

Release type:

Continuous release

Emission days:

300 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Pre-treatment of waste water by neutralization	Water - minimum efficiency of: 53.1 %
--	---------------------------------------

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant

STP effluent (m³/day):

2000

Other conditions affecting environmental exposure

Local freshwater dilution factor: 1000

2.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 25 %

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to > 15 min

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable respiratory protection. Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 95 %
--	--------------------------------------

2.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories	Roller application or brushing (PROC10)
--------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 15 %

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to 60 min

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 95 %
---------------------------------------	--------------------------------------

2.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
--------------------	----------------------------------

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 15 %

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to 60 min

Technical and organisational conditions and measures

Technical and organisational measures

Provide extract ventilation to points where emissions occur.	Inhalation - minimum efficiency of: 90 %
--	--

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

2.2. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Process Categories	Manual activities involving hand contact (PROC19)
--------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers concentrations up to 5 %

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to 8 h

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

2.3 Exposure estimation and reference to its source

2.3. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	6.74E-05 mg/L	Other measured data	0.042
marine water	6.7E-06 mg/L	Other measured data	0.004
freshwater sediment	0.0677 mg/kg dry weight	Other measured data	0.483
marine sediment	0.00674 mg/kg dry weight	Other measured data	0.048
soil	0.0118 mg/kg dry weight	Other measured data	0.001

2.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.068 mg/kg bw/day	ECETOC TRA worker v2.0	0.12
inhalative, systemic, long-term	0.456 mg/m ³	ECETOC TRA worker v2.0	0.457
combined routes	N/A	N/A	0.577
inhalative, local, short-term	0.913 mg/m ³	ECETOC TRA worker v2.0	< 0.001

2.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.082 mg/kg bw/day	ECETOC TRA worker v2.0	0.144
inhalative, systemic, long-term	0.457 mg/m ³	ECETOC TRA worker v2.0	0.229
combined routes	N/A	N/A	0.373
inhalative, local, short-term	0.914 mg/m ³	ECETOC TRA worker v2.0	< 0.001

2.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.214 mg/kg bw/day	ECETOC TRA worker v2.0	0.376
inhalative, systemic, long-term	0.121 mg/m ³	ECETOC TRA worker v2.0	0.122
combined routes	N/A	N/A	0.498
inhalative, local, short-term	0.243 mg/m ³	ECETOC TRA worker v2.0	< 0.001

2.3. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.14 mg/kg bw/day	ECETOC TRA worker v2.0	0.248
inhalative, systemic, long-term	0.76 mg/m ³	ECETOC TRA worker v2.0	0.076
combined routes	N/A	N/A	0.324
inhalative, local, short-term	1.52 mg/m ³	ECETOC TRA worker v2.0	< 0.001

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario

Cashew, nutshell liq.

Exposure Scenario, 08/06/2021

Substance identity	Cashew, nutshell liq.
CAS No.	8007-24-7
EINECS No.	232-355-4
Registration number	01-2119502450-57

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9b, PC9a, PC1)

1. ES 1

Widespread use by professional workers; Various products (PC9b, PC9a, PC1)

1.1 TITLE SECTION

Exposure Scenario name	Dye - Professional application of coatings and inks by brush or roller - Use in rigid foams, coatings, adhesives and sealants
Date - Version	21/05/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Fillers, putties, plasters, modelling clay (PC9b) - Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1)
Article Category(ies)	Stone, plaster, cement, glass and ceramic articles: Large surface area articles (AC4a) - Other articles made of stone, plaster, cement, glass or ceramic (AC4g)

Environment Contributing Scenario

CS1	ERC8c - ERC8f
-----	---------------

Worker Contributing Scenario

CS2 Mixing operations	PROC19
CS3 Equipment cleaning and maintenance - (aqueous) - Material transfers	PROC8b
CS4 Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous)	PROC10

1.2 Conditions of use affecting exposure**1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)**

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)
----------------------------------	---

Product (article) characteristics**Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 1 %.

Amount used, frequency and duration of use (or from service life)**Amounts used:**

< 50 t(tonnes)/year
< 167 kg/day

Release type: Intermittent release**Emission days:** 365 days per year**Conditions and measures related to sewage treatment plant****STP type:**

Municipal Sewage Treatment Plant
Water - minimum efficiency of: = 93.2 %

Conditions and measures related to treatment of waste (including article waste)**Waste treatment**

Residues which cannot be recycled are disposed off as chemical waste

Other conditions affecting environmental exposure**Local marine water dilution factor:** 100**Local freshwater dilution factor:** 10

Receiving surface water flow: 18000 m³/day

Covers indoor and outdoor use

1.2. CS2: Worker Contributing Scenario: Mixing operations (PROC19)

Process Categories Manual activities involving hand contact (PROC19)

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 1 %.

Amount used, frequency and duration of use/exposure

Amounts used:

< 50 t(tonnes)/year

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Ensure operatives are trained to minimise exposures.

Avoid direct eye contact with product, also via contamination on hands.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Wear suitable coveralls to prevent exposure to the skin.

Use eye protection according to EN 166.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Covers indoor and outdoor use

Professional use

Temperature: Covers use at ambient temperatures.

1.2. CS3: Worker Contributing Scenario: Equipment cleaning and maintenance - (aqueous) - Material transfers (PROC8b)

Process Categories Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Avoid using product more than = 4 h/event

Technical and organisational conditions and measures

Technical and organisational measures

Ensure operatives are trained to minimise exposures.

Avoid direct eye contact with product, also via contamination on hands.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Covers use at ambient temperatures.

1.2. CS4: Worker Contributing Scenario: Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous) (PROC10)

Process Categories	Roller application or brushing (PROC10)
--------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Avoid using product more than = 4 h/event

Technical and organisational conditions and measures

Technical and organisational measures

Ensure operatives are trained to minimise exposures.

Provide extract ventilation to points where emissions occur.

Avoid direct eye contact with product, also via contamination on hands.

Use long handled brushes and rollers.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Covers use at ambient temperatures.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
N/A	N/A	N/A	< 1

1.3. CS2: Worker Contributing Scenario: Mixing operations (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative	N/A	ECETOC TRA worker v2.0	< 1
dermal	N/A	ECETOC TRA worker v2.0	< 1

1.3. CS3: Worker Contributing Scenario: Equipment cleaning and maintenance - (aqueous) - Material transfers (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 7.75 mg/m ³	ECETOC TRA worker v2.0	= 0.562

dermal, systemic, long-term	= 0.014 mg/m ³	ECETOC TRA worker v2.0	= 0.004
-----------------------------	---------------------------	------------------------	---------

1.3. CS4: Worker Contributing Scenario: Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous) (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, local, short-term	= 2.325 mg/m ³	ECETOC TRA worker v2.0	= 0.168
dermal, systemic, long-term	= 0.137 mg/m ³	ECETOC TRA worker v2.0	= 0.035

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario

2,4,6-tris(dimethylaminomethyl)phenol

Exposure Scenario, 05/11/2021

Substance identity	2,4,6-tris(dimethylaminomethyl)phenol
CAS No.	90-72-2
INDEX No.	603-069-00-0
EINECS No.	202-013-9
Registration number	01-2119560597-27

Table of contents

1. **ES 1** Widespread use by professional workers; Fillers, putties, plasters, modelling clay (PC9b)

1. ES 1

Widespread use by professional workers; Fillers, putties, plasters, modelling clay (PC9b)

1.1 TITLE SECTION

Exposure Scenario name	Road and construction applications - Use in rigid foams, coatings, adhesives and sealants
Date - Version	05/11/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Fillers, putties, plasters, modelling clay (PC9b)

Environment Contributing Scenario

CS1	ERC8b - ERC8e
-----	---------------

Worker Contributing Scenario

CS2 Material transfers	PROC8a
CS3 Rolling, Brushing	PROC10
CS4 Rolling, Brushing	PROC10
CS5 Roller, spreader, flow application	PROC11
CS6 Roller, spreader, flow application	PROC11

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario (ERC8b, ERC8e)

Environmental release categories	Widespread use of reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) (ERC8b, ERC8e)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.197 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use (or from service life)

Amounts used:

Amount per use <= 0.0014 tonnes/day

Release type:

Continuous release

Conditions and measures related to sewage treatment plant

STP type:

No specific measures identified.

Water - minimum efficiency of: = 0.059 %

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

This material and its container must be disposed of as hazardous.

1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
--------------------	---

Product (article) characteristics**Physical form of product:**

Liquid

Vapour pressure:

= 0.197 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Duration of contact < 30 min

Technical and organisational conditions and measures**Technical and organisational measures**

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	Inhalation - minimum efficiency of: 30 %
Local exhaust ventilation	Inhalation - minimum efficiency of: 80 %

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. Wear a full face respirator conforming to EN136.	Dermal - minimum efficiency of: 90 % Inhalation - minimum efficiency of: 95 %
Use suitable eye protection.	

Other conditions affecting worker exposure**Body parts exposed:**

Assumes that potential dermal contact is limited to hands.

1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories	Roller application or brushing (PROC10)
--------------------	---

Product (article) characteristics**Physical form of product:**

Liquid

Vapour pressure:

= 0.197 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Duration of contact < 440 min

Technical and organisational conditions and measures**Technical and organisational measures**

Provide a basic standard of general ventilation (1 to 3 air changes per hour).	Inhalation - minimum efficiency of: 44 %
--	--

Ensure that direction of application is only horizontal or downward.

Open doors and windows.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Wear a full face respirator conforming to EN136.

Wear suitable respiratory protection.

Wear an impervious suit.

Dermal - minimum efficiency of: 90 %

Inhalation - minimum efficiency of: 99 %

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

Body parts exposed:

Assumes that potential dermal contact is limited to hands.

1.2. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories Roller application or brushing (PROC10)

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

= 0.197 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Duration of contact < 440 min

Technical and organisational conditions and measures

Technical and organisational measures

Mechanical ventilation giving at least [ACH]:

Inhalation - minimum efficiency of: 44 %

Ensure that direction of application is only horizontal or downward.

Open doors and windows.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Wear a full face respirator conforming to EN136.

Wear suitable respiratory protection.

Wear an impervious suit.

Dermal - minimum efficiency of: 90 %

Inhalation - minimum efficiency of: 99 %

Use suitable eye protection.

Other conditions affecting worker exposure

Outdoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

Body parts exposed:

Assumes that potential dermal contact is limited to hands.

1.2. CS5: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
--------------------	----------------------------------

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

= 0.197 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Duration of contact < 4 h

Technical and organisational conditions and measures

Technical and organisational measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).	Inhalation - minimum efficiency of: 44 %
--	--

Ensure that direction of application is only horizontal or downward.
--

Open doors and windows.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.	Dermal - minimum efficiency of: 90 % Inhalation - minimum efficiency of: 99 %
---	--

Wear a full face respirator conforming to EN136.
--

Wear suitable respiratory protection.

Wear an impervious suit.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

Professional use

Body parts exposed:

Assumes that potential dermal contact is limited to hands.

1.2. CS6: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
--------------------	----------------------------------

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

= 0.197 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Duration of contact < 4 h

Technical and organisational conditions and measures

Technical and organisational measures

Mechanical ventilation giving at least [ACH]:	Inhalation - minimum efficiency of: 44 %
Ensure that direction of application is only horizontal or downward.	
Open doors and windows.	

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. Wear a full face respirator conforming to EN136. Wear suitable respiratory protection. Wear an impervious suit.	Dermal - minimum efficiency of: 90 % Inhalation - minimum efficiency of: 99 %
Use suitable eye protection.	

Other conditions affecting worker exposure

Outdoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

Body parts exposed:

Assumes that potential dermal contact is limited to hands.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8b, ERC8e)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.00172 mg/L	EUSES v2.1	0.037
freshwater sediment	0.00701 mg/kg dry weight	EUSES v2.1	0.027
marine water	0.00017 mg/L	EUSES v2.1	0.037
marine sediment	0.0007 mg/kg dry weight	EUSES v2.1	0.027
Sewage treatment plant	0.014 mg/L	EUSES v2.1	0.069
Agricultural soil	8E-05 mg/kg dry weight	EUSES v2.1	< 0.01
Man via environment - Inhalation	< 0.0001 mg/m³	EUSES v2.1	< 0.01

Man via environment - Oral	< 0.0001 mg/kg bw/day	EUSES v2.1	< 0.01
----------------------------	-----------------------	------------	--------

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.023 mg/m ³	EASY TRA v3.6	0.004
inhalative, systemic, short-term	0.464 mg/m ³	EASY TRA v3.6	0.211
combined routes, systemic, long-term	N/A	N/A	0.247
dermal, systemic, long-term	0.03 mg/kg bw/day	RISKOFDERM v2.1	0.203

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.31 mg/m ³	ECETOC TRA worker v3	0.584
inhalative, systemic, short-term	0.4641238 mg/m ³	EASY TRA v3.6	0.59
combined routes, systemic, long-term	N/A	N/A	0.854
dermal, systemic, long-term	0.041 mg/kg bw/day	RISKOFDERM v2.1	0.27

1.3. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.039 mg/m ³	ECETOC TRA worker v3	0.073
inhalative, systemic, short-term	0.867 mg/m ³	EASY TRA v3.6	0.413
combined routes, systemic, long-term	N/A	N/A	0.343
dermal, systemic, long-term	0.041 mg/kg bw/day	RISKOFDERM v2.1	0.27

1.3. CS5: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.367 mg/m ³	ART v1.5	0.022
inhalative, systemic, short-term	0.023 mg/m ³	ART v1.5	0.011
combined routes, systemic, long-term	N/A	N/A	0.827
dermal, systemic, long-term	0.121 mg/kg bw/day	RISKOFDERM v2.1	0.805

1.3. CS6: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.019 mg/m ³	ART v1.5	0.037
inhalative, systemic, short-term	0.039 mg/m ³	ART v1.5	0.019
combined routes, systemic, long-term	N/A	N/A	0.101
dermal, systemic, long-term	0.05 mg/kg bw/day	RISKOFDERM v2.1	0.33

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.