

## Safety Data Sheet

Conforms to – Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II,  
as amended by UK SI 2021/904

### H40 EXTREME PART B

Date of first edition: 3/20/2025

Safety Data Sheet dated 20/03/2025 version 1

**kerakoll**

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Mixture identification:

Trade name: H40 EXTREME PART B

Trade code: K46364\_UK

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: N.A.

Uses advised against: N.A.

### 1.3. Details of the supplier of the safety data sheet

Kerakoll UK Ltd

Tomlinson Road, Leyland, Lancashire, PR25 2DY,

United Kingdom

Tel. 01772 456831

safety@kerakoll.co.uk

### 1.4. Emergency telephone number

UK National Poisons Information Service.

E-mail: npis.birmingham@nhs.net; Tel: +44 (0)344 892 0111

## SECTION 2: Hazards identification



### 2.1. Classification of the substance or mixture

#### GB CLP regulation:

Skin Corr. 1B Causes severe skin burns and eye damage.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1A May cause an allergic skin reaction.

Aquatic Chronic 2 Toxic to aquatic life with long lasting effects.

GB\$DECL10 This titanium dioxide-containing product is not classified as carcinogen by inhalation because it does not meet the criteria stated in Note 10, Annex VI of GB CLP Regulation.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ .

Adverse physicochemical, human health and environmental effects:

No other hazards

### 2.2. Label elements

#### GB CLP regulation:

#### Hazard pictograms and Signal Word



Danger

#### Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P260 Do not breathe vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves and eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P33 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

8

P501 Dispose of contents/container in accordance with applicable regulations.

#### **Special Provisions:**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### **Contains**

3-aminomethyl-3,5,5-trimethylcyclohexylamine

amines, polyethylenepoly-; HEPA

2,4,6-tris(dimethylaminomethyl)phenol

#### **Special provisions according to Annex XVII of UK REACH:**

None.

#### **2.3. Other hazards**

When mixtures containing cement react with water, for instance when making concrete or mortar, or when the cement becomes wet, a strong alkaline solution is produced (high pH caused by the formation of calcium, sodium and potassium hydroxides).

Cement and mixtures containing cement may irritate the eyes, the mucous system, the throat and the respiratory system and cause coughing. Frequent inhalation of cement dust or mixtures containing cement over a long period of time increases the risk of developing lung diseases.

In case of prolonged contact with the skin, both cement and mixtures containing cement, including pastes, may cause skin sensitisation due to the presence of trace amounts of chromium VI salts. Where necessary, such an effect can be minimized by incorporating a special reducing agent to maintain the water-soluble chromium VI content to concentration rates below 0.0002% (2 ppm) on the total dry weight of cement.

No PBT or vPvB substances present in concentration >= 0.1%

Other Hazards: No other hazards

---

### **SECTION 3: Composition/information on ingredients**

#### **3.1. Substances**

N.A.

#### **3.2. Mixtures**

Mixture identification: H40 EXTREME PART B

#### **Hazardous components within the meaning of GB CLP regulation and related classification:**

Qty	Name	Ident. Numb.	Classification	Registration Number
≥10-<20 %	3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS:2855-13-2 EC:220-666-8 Index:612-067-00-9	Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1A, H317; Eye Dam. 1, H318	
≥5-<10 %	amines, polyethylenepoly-; HEPA	CAS:68131-73-7 EC:268-626-9 Index:612-121-00-1	Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Acute Tox. 4, H312	
≥3-<5 %	2,4,6-tris(dimethylaminomethyl)phenol	CAS:90-72-2 EC:202-013-9 Index:603-069-00-0	Acute Tox. 4, H302; Skin Corr. 1C, H314; Eye Dam. 1, H318	
≥1-<3 %	Titanium dioxide	CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2	Carc. 2, H351	
<0.05 %	Aluminium oxide	CAS:1344-28-1 EC:215-691-6	Substance with a workplace exposure limit in Great Britain.	
<0.01 %	Kaolin	CAS:1332-58-7 EC:310-194-1	Substance with a workplace exposure limit in Great Britain.	

This mixture contains >= 1% titanium dioxide (CAS 13463-67-7). The Annex VI classification of titanium dioxide does not apply to this mixture according to its Note 10.

---

### **SECTION 4: First aid measures**

#### **4.1. Description of first aid measures**

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAINT IMMEDIATE MEDICAL ATTENTION.
- Remove contaminated clothing immediatley and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Eye irritation

Eye damages

Skin Irritation

Erythema

#### **4.3. Indication of any immediate medical attention and special treatment needed**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

---

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO<sub>2</sub>).

Extinguishing media which must not be used for safety reasons:

- None in particular.

#### **5.2. Special hazards arising from the substance or mixture**

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.

#### **5.3. Advice for firefighters**

- Use suitable breathing apparatus .
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

---

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

**For non emergency personnel:**

- Wear personal protection equipment.
- Remove persons to safety.
- See protective measures under point 7 and 8.

**For emergency responders:**

- Wear personal protection equipment.

#### **6.2. Environmental precautions**

- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Retain contaminated washing water and dispose it.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
- Suitable material for taking up: absorbing material, organic, sand

#### **6.3. Methods and material for containment and cleaning up**

- Suitable material for taking up: absorbing material, organic, sand
- Wash with plenty of water.

#### **6.4. Reference to other sections**

See also section 8 and 13

---

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

- Avoid contact with skin and eyes, inhalation of vapours and mists.
- See also section 8 for recommended protective equipment.

**Advice on general occupational hygiene:**

- Do not eat or drink while working.

## 7.2. Conditions for safe storage, including any incompatibilities

The product must be stored in waterproof, dry, clean conditions and protected from contamination. Do not use aluminium containers due to incompatibility of the materials.

The product contains cement with an addition of a Chromium reducing agent (VI) and its effectiveness decreases with time. Consequently, packaging's of the material indicate information about the production date, storing conditions and the appropriate storage period for the maintaining of the activity of the reducing agent and for maintaining the soluble Chromium (VI) amount under 2ppm over the total dry weight referred to cement (BS EN 196-10).

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

## 7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

---

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
Titanium dioxide CAS: 13463-67-7	ACGIH		Long Term: 2.5 mg/m <sup>3</sup> (8h) Finescale particles; R ; A3 - LRT irr, pneumoconiosis
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m <sup>3</sup> Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
Aluminium oxide CAS: 1344-28-1	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m <sup>3</sup> Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m <sup>3</sup> Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
Kaolin CAS: 1332-58-7	ACGIH		Long Term: 2 mg/m <sup>3</sup> (8h) E,R, A4 - Pneumoconiosis
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 2 mg/m <sup>3</sup> Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)

#### Biological limit values

Aluminium oxide CAS: 1344-28-1	Biological Indicator: Aluminium; Sampling Period: At discretion Value: 60 µg/g; Medium: Urine
-----------------------------------	--

#### Predicted No Effect Concentration (PNEC) values

3-aminomethyl-3,5,5-trimethylcyclohexylamine  
CAS: 2855-13-2

Exposure Route: Fresh Water; PNEC Limit: 60 µg/l  
Exposure Route: Marine water; PNEC Limit: 6 µg/l  
Exposure Route: Freshwater sediments; PNEC Limit: 5.784 mg/kg  
Exposure Route: Marine water sediments; PNEC Limit: 578 µg/kg  
Exposure Route: Soil (agricultural); PNEC Limit: 1.121 mg/kg  
Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.23 mg/l

amines,  
polyethylenepoly-; HEPA  
CAS: 68131-73-7

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 3.18 mg/l  
Exposure Route: Fresh Water; PNEC Limit: 1.6 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 16 µg/l  
Exposure Route: Marine water; PNEC Limit: 1.6 µg/l  
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 3.19 mg/l  
Exposure Route: Freshwater sediments; PNEC Limit: 0.14 mg/kg  
Exposure Route: Marine water sediments; PNEC Limit: 0.14 mg/kg  
Exposure Route: Soil; PNEC Limit: 10 mg/kg  
Exposure Route: Fresh Water; PNEC Limit: 84 µg/l

2,4,6-  
tris  
(dimethylaminomethyl)  
phenol  
CAS: 90-72-2

Titanium dioxide  
CAS: 13463-67-7

Aluminium oxide  
CAS: 1344-28-1

#### Derived No Effect Level (DNEL) values

3-aminomethyl-3,5,5-  
trimethylcyclohexylamine  
CAS: 2855-13-2

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects  
Worker Professional: 20.1 mg/m<sup>3</sup>

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects  
Worker Professional: 20.1 mg/m<sup>3</sup>

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects  
Consumer: 526 µg/kg

amines,  
polyethylenepoly-; HEPA  
CAS: 68131-73-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 1.59 mg/m<sup>3</sup>; Consumer: 0.46 mg/m<sup>3</sup>

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects  
Worker Professional: 8550 mg/m<sup>3</sup>; Consumer: 2542 mg/m<sup>3</sup>

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects  
Consumer: 0.65 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects  
Consumer: 32 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 0.91 mg/m<sup>3</sup>; Consumer: 0.4 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects  
Worker Professional: 0.044 mg/cm<sup>2</sup>; Consumer: 0.68 mg/cm<sup>2</sup>

Exposure Route: Human Dermal; Exposure Frequency: Short Term (acute)  
Consumer: 1.59 mg/cm<sup>2</sup>

Titanium dioxide  
CAS: 13463-67-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects  
Worker Professional: 10 mg/m<sup>3</sup>

Aluminium oxide  
CAS: 1344-28-1

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 15.63 mg/m<sup>3</sup>

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects  
Worker Professional: 15.63 mg/m<sup>3</sup>

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

## 8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

Hygienic and Technical measures

N.A.

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical State: N.A.

Appearance and colour: N.A.

Odour: N.A.

Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: > 93°C

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: N.A.

Solubility in water: N.A.

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

Solid/gas flammability: N.A.

Volatile Organic compounds - VOCs = N.A.

### 9.2. Other information

Substance Groups relevant properties N.A.

Miscibility: N.A.

Conductivity: N.A.

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions

### 10.2. Chemical stability

Data not available.

### 10.3. Possibility of hazardous reactions

None.

### 10.4. Conditions to avoid

Stable under normal conditions.

### 10.5. Incompatible materials

None in particular.

### 10.6. Hazardous decomposition products

None.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Corr. 1B(H314)
c) serious eye damage/irritation	The product is classified: Eye Dam. 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

#### Toxicological information on main components of the mixture:

3-aminomethyl-3,5,5-trimethylcyclohexylamine

a) acute toxicity	LD50 Oral Rat = 1030 mg/kg
	LC50 Inhalation of aerosol Rat > 5.01 mg/l 4h
	LD50 Skin Rat > 2000 mg/kg
b) skin corrosion/irritation	Skin Corrosive Rabbit Positive
c) serious eye damage/irritation	Eye Irritant Rabbit Yes
d) respiratory or skin sensitisation	Skin Sensitization Guineapig Positive
f) carcinogenicity	Genotoxicity Negative
	Carcinogenicity Negative
	Mouse, oral route

amines,  
polyethylenepoly-; HEPA

a) acute toxicity	LD50 Oral Rat = 1716.2 mg/kg
	LD50 Skin Rabbit = 1465.4 mg/kg 24h
b) skin corrosion/irritation	Skin Corrosive Rabbit Positive
c) serious eye damage/irritation	Eye Irritant Rabbit Yes
d) respiratory or skin sensitisation	Skin Sensitization Guineapig Positive
f) carcinogenicity	Genotoxicity Negative
	Mouse intraperitoneal route

2,4,6-tris  
(dimethylaminomethyl)  
phenol

a) acute toxicity	LD50 Oral Rat = 2169 mg/kg
	LD50 Skin Rat > 1 ml/Kg 6h
b) skin corrosion/irritation	Skin Corrosive Rabbit Positive 4h
c) serious eye damage/irritation	Eye Irritant Rabbit Yes
d) respiratory or skin sensitisation	Skin Sensitization Guineapig Negative
g) reproductive toxicity	No Observed Effect Level Oral Rat = 15 mg/kg

Titanium dioxide	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg LC50 Inhalation > 6.82 mg/l LD50 Skin Rat > 2000 mg/kg
	c) serious eye damage/irritation	Eye Corrosive Negative
		Eye Irritant No
	d) respiratory or skin sensitisation	Skin Sensitization Negative
	i) STOT-repeated exposure	No Observed Adverse Effect Level 1000
Aluminium oxide	a) acute toxicity	LD50 Oral Rat > 15900 mg/kg
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative
	c) serious eye damage/irritation	Eye Irritant Rabbit No
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Negative
	f) carcinogenicity	Genotoxicity Rat Negative
	g) reproductive toxicity	Lowest Observed Adverse Effect Level Oral Rat = 100 mg/kg

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Toxic to aquatic life with long lasting effects.

#### List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 2(H411)

#### List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS: 2855-13-2 - EINECS: 220-666-8 - INDEX: 612-067-00-9	a) Aquatic acute toxicity : LC50 Fish Leuciscus idus = 110 mg/L 96h ,according to 84/449/EEC, C.1, 1984  a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 23 mg/L 48h OECD 202
amines, polyethylenepoly-; HEPA	CAS: 68131-73-7 - EINECS: 268-626-9 - INDEX: 612-121-00-1	a) Aquatic acute toxicity : EC50 Algae Scenedesmus subspicatus > 50 mg/L 72h b) Aquatic chronic toxicity : NOEC Daphnia = 3 mg/L 504h c) Bacteria toxicity : EC10 Pseudomonas putida = 1120 mg/L 18h  a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata = 100 mg/L 96h EU Method C.1 (Acute Toxicity for Fish)  a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 2.2 mg/L 48h EU Method C.2 (Acute Toxicity for Daphnia)
		a) Aquatic acute toxicity : EC50 Algae Selenastrum capricornutum = 0.23 mg/L 72h OECD TG 201 c) Bacteria toxicity : EC50 nitrifying bacteria = 319.3 mg/L - 2h d) Terrestrial toxicity : NOEC Worm Eisenia fetida = 1000 mg/kg OECD Guideline 222 (Earthworm Reproduction Test (Eisenia fetida/Eisenia andrei)) - 56days

2,4,6-tris(dimethylaminomethyl)phenol	CAS: 90-72-2 - EINECS: 202-013-9 - INDEX: 603-069-00-0	a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 175 mg/L 96h  a) Aquatic acute toxicity : LC50 Salmo gairdneri < 240 mg/L 96h  a) Aquatic acute toxicity : LC50 Daphnia Palemonetes vulgaris = 718 mg/L 96h
Titanium dioxide	CAS: 13463-67-7 - EINECS: 236-675-5 - INDEX: 022-006-00-2	a) Aquatic acute toxicity : EC50 Algae freshwater algae = 84 mg/L  a) Aquatic acute toxicity : LC50 Fish Pimephales promelas (Cavedano americano) > 1000 mg/L 96h  a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata (alghe cloroficee) > 100 mg/L 72h  a) Aquatic acute toxicity : NOEC Algae = 5600 mg/L a) Aquatic acute toxicity : EC50 Daphnia  Daphnia magna (Pulce d'acqua grande) > 100 mg/L 48h

## 12.2. Persistence and degradability

Component	Persistence/Degradability:	Test	Value	Notes:
3-aminomethyl-3,5,5-trimethylcyclohexylamine	Non-readily biodegradable	Dissolved organic carbon	8.000	%; EU-method C.4-A
amines, polyethylenepoly-; HEPA	Non-readily biodegradable	Oxygen consumption		OECD 301D
2,4,6-tris(dimethylaminomethyl)phenol	Non-readily biodegradable			

## 12.3. Bioaccumulative potential

N.A.

## 12.4. Mobility in soil

Component	Mobility in soil
3-aminomethyl-3,5,5-trimethylcyclohexylamine	Not mobile

## 12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration >= 0.1%

## 12.6. Other adverse effects

N.A.

---

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

---

## SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

### 14.1. UN number

N.A.

### 14.2. UN proper shipping name

N.A.

### 14.3. Transport hazard class(es)

N.A.

### 14.4. Packing group

N.A.

### 14.5. Environmental hazards

N.A.

### 14.6. Special precautions for user

N.A.

Road and Rail (ADR-RID):

N.A.

Air (IATA):

N.A.

Sea (IMDG):

N.A.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

N.A.

---

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace exposure limit within the meaning of the Control of Substances Hazardous to Health Regulations 2002 (WEL-EH40)

REACH regulation as changed by the REACH etc. (Amendment etc.) (EU Exit) Regulations (UK REACH)

CLP regulation as changed by the Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations (GB CLP)

GB PIC legislation - (Regulation (EU) No 649/2012 as changed by the Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc) (EU Exit) Regulations

Restrictions related to the product or the substances contained according to Annex XVII of UK REACH:

Restrictions related to the product: 3

Restrictions related to the substances contained: None.

Additional Regulatory Information for Great Britain

No Additional Information

Provisions related to the Control of Major Accident Hazards Regulations 2015 (GB implementation of Seveso III):

<b>Seveso III category according to Schedule I, part 1</b>	<b>Lower-tier threshold (tonnes)</b>	<b>Upper-tier threshold (tonnes)</b>
--	--------------------------------------	--------------------------------------

Product belongs to category: E2	200	500
---------------------------------	-----	-----

GB PIC Legislation:

No substances listed

SVHC Substances:

No SVHC substances present in concentration >= 0.1%

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

#### Substances for which a Chemical Safety Assessment has been carried out:

3-aminomethyl-3,5,5-trimethylcyclohexylamine

amines, polyethylenepoly-; HEPA

2,4,6-tris(dimethylaminomethyl)phenol

---

### SECTION 16: Other information

<b>Code</b>	<b>Description</b>	
H302	Harmful if swallowed.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H351	Suspected of causing cancer if inhaled.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
<b>Code</b>	<b>Hazard class and hazard category</b>	<b>Description</b>
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/1C	Skin Corr. 1C	Skin corrosion, Category 1C
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.6/2	Carc. 2	Carcinogenicity, Category 2
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1

**Classification and procedure used to derive the classification for mixtures according to GB CLP regulation:**

Classification according to GB CLP	Classification procedure
Skin Corr. 1B, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1A, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: Keep Away From Heat

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

# Exposure Scenario

## 3-aminomethyl-3,5,5-trimethylcyclohexylamine

### Exposure Scenario, 01/06/2022

Substance identity	3-aminomethyl-3,5,5-trimethylcyclohexylamine
CAS No.	2855-13-2
INDEX No.	612-067-00-9
EINECS No.	220-666-8
Registration number	01-2119514687-32

### Table of contents

1. ES 1 Widespread use by professional workers; Various products (PC9b, PC9a, PC1, PC32)

## 1. ES 1

Widespread use by professional workers; Various products (PC9b, PC9a, PC1, PC32)

### 1.1 TITLE SECTION

Exposure Scenario name	Use in rigid foams, coatings, adhesives and sealants
Date - Version	01/06/2022 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Fillers, putties, plasters, modelling clay (PC9b) - Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1) - Polymer preparations and compounds (PC32)

### Environment Contributing Scenario

CS1	ERC8c
CS2	ERC8f

### Worker Contributing Scenario

CS3 Material transfers	PROC8a
CS4 Rolling, Brushing	PROC10
CS5 Material transfers	PROC8a
CS6 Rolling, Brushing	PROC10

## 1.2 Conditions of use affecting exposure

### 1.2. CS1: Environment Contributing Scenario (ERC8c)

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) (ERC8c)
----------------------------------	--

### Product (article) characteristics

#### Physical form of product:

Liquid

#### Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

### Technical and organisational conditions and measures

#### Control measures to prevent releases

	Water - minimum efficiency of: 0.015 %
--	--

### 1.2. CS2: Environment Contributing Scenario (ERC8f)

Environmental release categories	Widespread use leading to inclusion into/onto article (outdoor) (ERC8f)
----------------------------------	---

### Product (article) characteristics

#### Physical form of product:

Liquid

#### Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

### Technical and organisational conditions and measures

#### Control measures to prevent releases

	Water - minimum efficiency of: 0.015 %
--	--

## 1.2. CS3: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
<b>Product (article) characteristics</b>	
<b>Physical form of product:</b> Liquid	
<b>Concentration of substance in product:</b> Covers percentage substance in the product up to 100 %.	
<b>Amount used, frequency and duration of use/exposure</b>	
<b>Duration:</b> Covers use up to 4 h/day	
<b>Frequency:</b> Covers use up to <= 240 days per year	
<b>Technical and organisational conditions and measures</b>	
<b>Technical and organisational measures</b>	
Local exhaust ventilation	Inhalation - minimum efficiency of: 80 %
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
<b>Personal protection</b>	
Wear suitable respiratory protection.	Inhalation - minimum efficiency of: 95 %
Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 98 %
Wear suitable coveralls to prevent exposure to the skin.	
Use suitable eye protection.	
<b>Other conditions affecting worker exposure</b>	
Indoor use	
Professional use	
<b>Body parts exposed:</b> Assumes that potential dermal contact is limited to hands.	
<b>1.2. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)</b>	
Process Categories	Roller application or brushing (PROC10)
<b>Product (article) characteristics</b>	
<b>Physical form of product:</b> Liquid	
<b>Concentration of substance in product:</b> Covers percentage substance in the product up to 100 %.	
<b>Amount used, frequency and duration of use/exposure</b>	
<b>Duration:</b> Covers use up to 4 h/day	
<b>Frequency:</b> Covers use up to <= 240 days per year	

## Technical and organisational conditions and measures

### Technical and organisational measures

Local exhaust ventilation	Inhalation - minimum efficiency of: 80 %
---------------------------	--

### Conditions and measures related to personal protection, hygiene and health evaluation

#### Personal protection

Wear suitable respiratory protection.	Inhalation - minimum efficiency of: 95 %
Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 98 %
Wear suitable coveralls to prevent exposure to the skin.	
Use suitable eye protection.	

### Other conditions affecting worker exposure

Indoor use

Professional use

#### Body parts exposed:

Assumes that potential dermal contact is limited to hands.

## 1.2. CS5: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
--------------------	--

### Product (article) characteristics

#### Physical form of product:

Liquid

#### Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

### Amount used, frequency and duration of use/exposure

#### Duration:

Covers use up to 1 h

#### Frequency:

Covers use up to <= 240 days per year

### Conditions and measures related to personal protection, hygiene and health evaluation

#### Personal protection

Wear suitable respiratory protection.	Inhalation - minimum efficiency of: 98 %
Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 98 %
Wear suitable coveralls to prevent exposure to the skin.	
Use suitable eye protection.	

### Other conditions affecting worker exposure

Outdoor use

Professional use

#### Body parts exposed:

Assumes that potential dermal contact is limited to hands.

## 1.2. CS6: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories	Roller application or brushing (PROC10)
<b>Product (article) characteristics</b>	
<b>Physical form of product:</b> Liquid	
<b>Concentration of substance in product:</b> Covers percentage substance in the product up to 100 %.	
<b>Amount used, frequency and duration of use/exposure</b>	
<b>Duration:</b> Covers use up to 1 h	
<b>Frequency:</b> Covers use up to <= 240 days per year	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
<b>Personal protection</b>	
Wear suitable respiratory protection.	Inhalation - minimum efficiency of: 98 %
Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 98 %
Wear suitable coveralls to prevent exposure to the skin.	
Use suitable eye protection.	

## Other conditions affecting worker exposure

Outdoor use

Professional use

### Body parts exposed:

Assumes that potential dermal contact is limited to hands.

## 1.3 Exposure estimation and reference to its source

### 1.3. CS1: Environment Contributing Scenario (ERC8c)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.0004855 mg/L	N/A	< 0.01
freshwater sediment	0.047 mg/kg dry weight	N/A	< 0.01
marine water	4.85E-05 mg/L	N/A	< 0.01
marine sediment	0.005 mg/kg dry weight	N/A	< 0.01
marine water	4.85E-05 mg/L	N/A	< 0.01
Sewage treatment plant	1.48E-05 mg/L	N/A	< 0.01
Agricultural soil	0.017 mg/kg dry weight	N/A	< 0.01
Man via environment - Oral	0.000188 mg/kg bw/day	N/A	< 0.01

### 1.3. CS2: Environment Contributing Scenario (ERC8f)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.000487 mg/L	N/A	< 0.01
freshwater sediment	0.047 mg/kg dry weight	N/A	< 0.01
marine water	4.815E-05 mg/L	N/A	< 0.01
marine sediment	0.005 mg/kg dry weight	N/A	< 0.01
Sewage treatment plant	2.96E-05 mg/L	N/A	< 0.01
Agricultural soil	0.017 mg/kg dry weight	N/A	= 0.015
Man via environment - Oral	0.0001193 mg/kg bw/day	N/A	< 0.01

### 1.3. CS3: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal	13.714 mg/kg bw/day	N/A	0.274
inhalative	106.438 mg/m <sup>3</sup>	N/A	N/A

### 1.3. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal	27.429 mg/kg bw/day	N/A	0.549
inhalative	106.438 mg/m <sup>3</sup>	N/A	N/A

### 1.3. CS5: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal	13.714 mg/kg bw/day	N/A	0.274
inhalative	24.835 mg/m <sup>3</sup>	N/A	0.497

### 1.3. CS6: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal	27.429 mg/kg bw/day	N/A	0.549
inhalative	24.835 mg/m <sup>3</sup>	N/A	0.497

## 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

# Exposure Scenario

## Amines, polyethylenepoly-; hepa

### Exposure Scenario, 10/08/2021

Substance identity	
	Amines, polyethylenepoly-; hepa
CAS No.	68131-73-7
INDEX No.	612-121-00-1
EINECS No.	268-626-9
Registration number	01-2119485823-28

### Table of contents

1. **ES 1** Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)
2. **ES 2** Widespread use by professional workers; Adhesives, sealants (PC1)

## 1. ES 1

Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)

### 1.1 TITLE SECTION

Exposure Scenario name	Professional application of coatings and inks
Date - Version	10/08/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Coatings and paints, thinners, paint removers (PC9a)

### Environment Contributing Scenario

CS1	ERC8c - ERC8f
-----	---------------

### Worker Contributing Scenario

CS2 Material transfers	PROC8a
CS3 Rolling, Brushing	PROC10
CS4 Roller, spreader, flow application	PROC11
CS5 Handling and dilution of concentrates	PROC19

## 1.2 Conditions of use affecting exposure

### 1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)
----------------------------------	---

#### Product (article) characteristics

##### Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

##### Concentration of substance in product:

Covers concentrations up to 25 %

#### Amount used, frequency and duration of use (or from service life)

##### Amounts used:

Daily amount per site = 2114 kg/day

##### Release type:

Continuous release

##### Emission days:

220 days per year

#### Other conditions affecting environmental exposure

##### Local freshwater dilution factor:

### 1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
--------------------	--

#### Product (article) characteristics

##### Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

##### Concentration of substance in product:

Covers concentrations up to 25 %

#### Amount used, frequency and duration of use/exposure

**Duration:**

Covers use up to > 15 min

**Conditions and measures related to personal protection, hygiene and health evaluation****Personal protection**

Wear suitable respiratory protection.

Wear suitable gloves tested to EN374.

Inhalation - minimum efficiency of: 95 %

**1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)**

**Process Categories** Roller application or brushing (PROC10)

**Product (article) characteristics****Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

**Concentration of substance in product:**

Covers concentrations up to 15 %

**Amount used, frequency and duration of use/exposure****Duration:**

Covers use up to 60 min

**Technical and organisational conditions and measures****Technical and organisational measures**

Provide extract ventilation to points where emissions occur.

Inhalation - minimum efficiency of: 90 %

**Conditions and measures related to personal protection, hygiene and health evaluation****Personal protection**

Wear suitable gloves tested to EN374.

**1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)**

**Process Categories** Non industrial spraying (PROC11)

**Product (article) characteristics****Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

**Concentration of substance in product:**

Covers concentrations up to 15 %

**Amount used, frequency and duration of use/exposure****Duration:**

Covers use up to 60 min

**Technical and organisational conditions and measures****Technical and organisational measures**

Provide extract ventilation to points where emissions occur.

Inhalation - minimum efficiency of: 90 %

**Conditions and measures related to personal protection, hygiene and health evaluation****Personal protection**

Wear suitable gloves tested to EN374.

**1.2. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)**

Process Categories	Manual activities involving hand contact (PROC19)
--------------------	---

### Product (article) characteristics

#### Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

#### Concentration of substance in product:

Covers concentrations up to 5 %

### Amount used, frequency and duration of use/exposure

#### Duration:

Covers use up to 8 h

### Conditions and measures related to personal protection, hygiene and health evaluation

#### Personal protection

Wear suitable gloves tested to EN374.

## 1.3 Exposure estimation and reference to its source

### 1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	7.92E-05 mg/L	EUSES	0.05
marine water	7.9E-06 mg/L	EUSES	0.005
freshwater sediment	0.0795 mg/kg dry weight	EUSES	0.568
marine sediment	0.00792 mg/kg dry weight	EUSES	0.057
soil	0.0118 mg/kg dry weight	EUSES	0.001

### 1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.068 mg/kg bw/day	ECETOC TRA worker v2.0	0.12
inhalative, systemic, long-term	0.456 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.457
combined routes	N/A	N/A	0.577
inhalative, local, short-term	0.913 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	< 0.001

### 1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.082 mg/kg bw/day	ECETOC TRA worker v2.0	0.144
inhalative, systemic, long-term	0.457 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.229
combined routes	N/A	N/A	0.373
inhalative, local, short-term	0.914 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	< 0.001

### 1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.214 mg/kg bw/day	ECETOC TRA worker v2.0	0.376
inhalative, systemic, long-term	0.121 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.122
combined routes	N/A	N/A	0.498
inhalative, local, short-term	0.243 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	< 0.001

### 1.3. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.14 mg/kg bw/day	ECETOC TRA worker v2.0	0.248
inhalative, systemic, long-term	0.76 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.076
combined routes	N/A	N/A	0.324
inhalative, local, short-term	1.52 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	< 0.001

## 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2

## Widespread use by professional workers; Adhesives, sealants (PC1)

### 2.1 TITLE SECTION

Exposure Scenario name	Use in rigid foams, coatings, adhesives and sealants
Date - Version	10/08/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Adhesives, sealants (PC1)

### Environment Contributing Scenario

CS1	ERC8a - ERC8d
-----	---------------

### Worker Contributing Scenario

CS2 Material transfers	PROC8a
CS3 Rolling, Brushing	PROC10
CS4 Roller, spreader, flow application	PROC11
CS5 Handling and dilution of concentrates	PROC19

### 2.2 Conditions of use affecting exposure

#### 2.2. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

### Product (article) characteristics

#### Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

#### Concentration of substance in product:

Covers concentrations up to 25 %

### Amount used, frequency and duration of use (or from service life)

#### Amounts used:

Daily amount per site = 15500 kg/day

#### Release type:

Continuous release

#### Emission days:

300 days per year

### Technical and organisational conditions and measures

#### Control measures to prevent releases

Pre-treatment of waste water by neutralization	Water - minimum efficiency of: 53.1 %
--	---------------------------------------

### Conditions and measures related to sewage treatment plant

#### STP type:

Municipal Sewage Treatment Plant

#### STP effluent (m<sup>3</sup>/day):

2000

## Other conditions affecting environmental exposure

Local freshwater dilution factor: 1000

### 2.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
--------------------	--

#### Product (article) characteristics

##### Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

##### Concentration of substance in product:

Covers concentrations up to 25 %

#### Amount used, frequency and duration of use/exposure

##### Duration:

Covers use up to > 15 min

#### Conditions and measures related to personal protection, hygiene and health evaluation

#### Personal protection

Wear suitable respiratory protection. Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 95 %
--	--------------------------------------

### 2.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories	Roller application or brushing (PROC10)
--------------------	---

#### Product (article) characteristics

##### Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

##### Concentration of substance in product:

Covers concentrations up to 15 %

#### Amount used, frequency and duration of use/exposure

##### Duration:

Covers use up to 60 min

#### Conditions and measures related to personal protection, hygiene and health evaluation

#### Personal protection

Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 95 %
---------------------------------------	--------------------------------------

### 2.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
--------------------	----------------------------------

#### Product (article) characteristics

##### Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

##### Concentration of substance in product:

Covers concentrations up to 15 %

#### Amount used, frequency and duration of use/exposure

##### Duration:

Covers use up to 60 min

## Technical and organisational conditions and measures

### Technical and organisational measures

Provide extract ventilation to points where emissions occur.	Inhalation - minimum efficiency of: 90 %
--	--

### Conditions and measures related to personal protection, hygiene and health evaluation

#### Personal protection

Wear suitable gloves tested to EN374.

### 2.2. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Process Categories	Manual activities involving hand contact (PROC19)
--------------------	---

### Product (article) characteristics

#### Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

#### Concentration of substance in product:

Covers concentrations up to 5 %

### Amount used, frequency and duration of use/exposure

#### Duration:

Covers use up to 8 h

### Conditions and measures related to personal protection, hygiene and health evaluation

#### Personal protection

Wear suitable gloves tested to EN374.

### 2.3 Exposure estimation and reference to its source

### 2.3. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	6.74E-05 mg/L	Other measured data	0.042
marine water	6.7E-06 mg/L	Other measured data	0.004
freshwater sediment	0.0677 mg/kg dry weight	Other measured data	0.483
marine sediment	0.00674 mg/kg dry weight	Other measured data	0.048
soil	0.0118 mg/kg dry weight	Other measured data	0.001

### 2.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.068 mg/kg bw/day	ECETOC TRA worker v2.0	0.12
inhalative, systemic, long-term	0.456 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.457
combined routes	N/A	N/A	0.577
inhalative, local, short-term	0.913 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	< 0.001

### 2.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.082 mg/kg bw/day	ECETOC TRA worker v2.0	0.144
inhalative, systemic, long-term	0.457 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.229
combined routes	N/A	N/A	0.373
inhalative, local, short-term	0.914 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	< 0.001

### 2.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.214 mg/kg bw/day	ECETOC TRA worker v2.0	0.376
inhalative, systemic, long-term	0.121 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.122
combined routes	N/A	N/A	0.498
inhalative, local, short-term	0.243 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	< 0.001

### 2.3. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.14 mg/kg bw/day	ECETOC TRA worker v2.0	0.248
inhalative, systemic, long-term	0.76 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	0.076
combined routes	N/A	N/A	0.324
inhalative, local, short-term	1.52 mg/m <sup>3</sup>	ECETOC TRA worker v2.0	< 0.001

## 2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

# Exposure Scenario

## 2,4,6-tris(dimethylaminomethyl)phenol

### Exposure Scenario, 05/11/2021

Substance identity	2,4,6-tris(dimethylaminomethyl)phenol
CAS No.	90-72-2
INDEX No.	603-069-00-0
EINECS No.	202-013-9
Registration number	01-2119560597-27

### Table of contents

1. **ES 1** Widespread use by professional workers; Fillers, putties, plasters, modelling clay (PC9b)

## 1. ES 1

Widespread use by professional workers; Fillers, putties, plasters, modelling clay (PC9b)

### 1.1 TITLE SECTION

Exposure Scenario name	Road and construction applications - Use in rigid foams, coatings, adhesives and sealants
Date - Version	05/11/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Fillers, putties, plasters, modelling clay (PC9b)

### Environment Contributing Scenario

CS1	ERC8b - ERC8e
-----	---------------

### Worker Contributing Scenario

CS2 Material transfers	PROC8a
CS3 Rolling, Brushing	PROC10
CS4 Rolling, Brushing	PROC10
CS5 Roller, spreader, flow application	PROC11
CS6 Roller, spreader, flow application	PROC11

## 1.2 Conditions of use affecting exposure

### 1.2. CS1: Environment Contributing Scenario (ERC8b, ERC8e)

Environmental release categories	Widespread use of reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) (ERC8b, ERC8e)
----------------------------------	---

### Product (article) characteristics

#### Physical form of product:

Liquid

#### Vapour pressure:

0.197 Pa

#### Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

### Amount used, frequency and duration of use (or from service life)

#### Amounts used:

Amount per use <= 0.0014 tonnes/day

#### Release type:

Continuous release

### Conditions and measures related to sewage treatment plant

#### STP type:

No specific measures identified.

Water - minimum efficiency of: = 0.059 %

### Conditions and measures related to treatment of waste (including article waste)

#### Waste treatment

This material and its container must be disposed of as hazardous.

### 1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
--------------------	---

**Product (article) characteristics****Physical form of product:**

Liquid

**Vapour pressure:**

= 0.197 Pa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

**Amount used, frequency and duration of use/exposure****Duration:**

Duration of contact &lt; 30 min

**Technical and organisational conditions and measures****Technical and organisational measures**

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	Inhalation - minimum efficiency of: 30 %
Local exhaust ventilation	Inhalation - minimum efficiency of: 80 %

**Conditions and measures related to personal protection, hygiene and health evaluation****Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. Wear a full face respirator conforming to EN136.	Dermal - minimum efficiency of: 90 % Inhalation - minimum efficiency of: 95 %
Use suitable eye protection.	

**Other conditions affecting worker exposure****Body parts exposed:**

Assumes that potential dermal contact is limited to hands.

**1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)**

Process Categories	Roller application or brushing (PROC10)
--------------------	---

**Product (article) characteristics****Physical form of product:**

Liquid

**Vapour pressure:**

= 0.197 Pa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

**Amount used, frequency and duration of use/exposure****Duration:**

Duration of contact &lt; 440 min

**Technical and organisational conditions and measures****Technical and organisational measures**

Provide a basic standard of general ventilation (1 to 3 air changes per hour).	Inhalation - minimum efficiency of: 44 %
--	--

Ensure that direction of application is only horizontal or downward.

Open doors and windows.

### **Conditions and measures related to personal protection, hygiene and health evaluation**

#### **Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Wear a full face respirator conforming to EN136.

Wear suitable respiratory protection.

Wear an impervious suit.

Dermal - minimum efficiency of: 90 %

Inhalation - minimum efficiency of: 99 %

Use suitable eye protection.

### **Other conditions affecting worker exposure**

Indoor use

Professional use

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

**Body parts exposed:**

Assumes that potential dermal contact is limited to hands.

### **1.2. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)**

**Process Categories**      Roller application or brushing (PROC10)

### **Product (article) characteristics**

**Physical form of product:**

Liquid

**Vapour pressure:**

= 0.197 Pa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### **Amount used, frequency and duration of use/exposure**

**Duration:**

Duration of contact < 440 min

### **Technical and organisational conditions and measures**

#### **Technical and organisational measures**

Mechanical ventilation giving at least [ACH]:

Inhalation - minimum efficiency of: 44 %

Ensure that direction of application is only horizontal or downward.

Open doors and windows.

### **Conditions and measures related to personal protection, hygiene and health evaluation**

#### **Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Wear a full face respirator conforming to EN136.

Wear suitable respiratory protection.

Wear an impervious suit.

Dermal - minimum efficiency of: 90 %

Inhalation - minimum efficiency of: 99 %

Use suitable eye protection.

### Other conditions affecting worker exposure

Outdoor use

Professional use

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

**Body parts exposed:**

Assumes that potential dermal contact is limited to hands.

### 1.2. CS5: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
--------------------	----------------------------------

#### Product (article) characteristics

**Physical form of product:**

Liquid

**Vapour pressure:**

= 0.197 Pa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

#### Amount used, frequency and duration of use/exposure

**Duration:**

Duration of contact < 4 h

#### Technical and organisational conditions and measures

##### Technical and organisational measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).	Inhalation - minimum efficiency of: 44 %
--	--

Ensure that direction of application is only horizontal or downward.
--

Open doors and windows.
-------------------------

#### Conditions and measures related to personal protection, hygiene and health evaluation

##### Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.	Dermal - minimum efficiency of: 90 % Inhalation - minimum efficiency of: 99 %
---	--

Wear a full face respirator conforming to EN136.
--

Wear suitable respiratory protection.
---------------------------------------

Wear an impervious suit.
--------------------------

Use suitable eye protection.
------------------------------

### Other conditions affecting worker exposure

Indoor use

Professional use

**Body parts exposed:**

Assumes that potential dermal contact is limited to hands.

### 1.2. CS6: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
--------------------	----------------------------------

#### Product (article) characteristics

**Physical form of product:**

Liquid

**Vapour pressure:**

= 0.197 Pa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

**Amount used, frequency and duration of use/exposure**

**Duration:**

Duration of contact < 4 h

**Technical and organisational conditions and measures**

**Technical and organisational measures**

Mechanical ventilation giving at least [ACH]:	Inhalation - minimum efficiency of: 44 %
Ensure that direction of application is only horizontal or downward.	
Open doors and windows.	

**Conditions and measures related to personal protection, hygiene and health evaluation**

**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. Wear a full face respirator conforming to EN136. Wear suitable respiratory protection. Wear an impervious suit.	Dermal - minimum efficiency of: 90 % Inhalation - minimum efficiency of: 99 %
Use suitable eye protection.	

**Other conditions affecting worker exposure**

Outdoor use

Professional use

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

**Body parts exposed:**

Assumes that potential dermal contact is limited to hands.

## 1.3 Exposure estimation and reference to its source

### 1.3. CS1: Environment Contributing Scenario (ERC8b, ERC8e)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.00172 mg/L	EUSES v2.1	0.037
freshwater sediment	0.00701 mg/kg dry weight	EUSES v2.1	0.027
marine water	0.00017 mg/L	EUSES v2.1	0.037
marine sediment	0.0007 mg/kg dry weight	EUSES v2.1	0.027
Sewage treatment plant	0.014 mg/L	EUSES v2.1	0.069
Agricultural soil	8E-05 mg/kg dry weight	EUSES v2.1	< 0.01
Man via environment - Inhalation	< 0.0001 mg/m³	EUSES v2.1	< 0.01

Man via environment - Oral	< 0.0001 mg/kg bw/day	EUSES v2.1	< 0.01
----------------------------	-----------------------	------------	--------

### 1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.023 mg/m <sup>3</sup>	EASY TRA v3.6	0.004
inhalative, systemic, short-term	0.464 mg/m <sup>3</sup>	EASY TRA v3.6	0.211
combined routes, systemic, long-term	N/A	N/A	0.247
dermal, systemic, long-term	0.03 mg/kg bw/day	RISKOFDERM v2.1	0.203

### 1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.31 mg/m <sup>3</sup>	ECETOC TRA worker v3	0.584
inhalative, systemic, short-term	0.4641238 mg/m <sup>3</sup>	EASY TRA v3.6	0.59
combined routes, systemic, long-term	N/A	N/A	0.854
dermal, systemic, long-term	0.041 mg/kg bw/day	RISKOFDERM v2.1	0.27

### 1.3. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.039 mg/m <sup>3</sup>	ECETOC TRA worker v3	0.073
inhalative, systemic, short-term	0.867 mg/m <sup>3</sup>	EASY TRA v3.6	0.413
combined routes, systemic, long-term	N/A	N/A	0.343
dermal, systemic, long-term	0.041 mg/kg bw/day	RISKOFDERM v2.1	0.27

### 1.3. CS5: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.367 mg/m <sup>3</sup>	ART v1.5	0.022
inhalative, systemic, short-term	0.023 mg/m <sup>3</sup>	ART v1.5	0.011
combined routes, systemic, long-term	N/A	N/A	0.827
dermal, systemic, long-term	0.121 mg/kg bw/day	RISKOFDERM v2.1	0.805

### 1.3. CS6: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.019 mg/m <sup>3</sup>	ART v1.5	0.037
inhalative, systemic, short-term	0.039 mg/m <sup>3</sup>	ART v1.5	0.019
combined routes, systemic, long-term	N/A	N/A	0.101
dermal, systemic, long-term	0.05 mg/kg bw/day	RISKOFDERM v2.1	0.33

## 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.