

## Safety Data Sheet

Conforms to – Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II,  
as amended by UK SI 2021/904

### L34 FLEX

Date of first edition: 1/5/2026

Safety Data Sheet dated 05/01/2026 version 1

**kerakoll**

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Mixture identification:

Trade name: L34 FLEX

Trade code: S100B0022

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Adhesives/sealants for hardwood floors

Uses advised against: All uses other than recommended ones

### 1.3. Details of the supplier of the safety data sheet

Kerakoll UK Ltd

Tomlinson Road, Leyland, Lancashire, PR25 2DY,

United Kingdom

Tel. 01772 456831

safety@kerakoll.co.uk

### 1.4. Emergency telephone number

UK National Poisons Information Service.

E-mail: npis.birmingham@nhs.net; Tel: +44 (0)344 892 0111

---

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GB CLP regulation:

The product is not classified as dangerous according to GB CLP regulation.

Adverse physicochemical, human health and environmental effects:

No other hazards

### 2.2. Label elements

The product is not classified as dangerous according to GB CLP regulation.

#### Special Provisions:

EUH210 Safety data sheet available on request.

#### Contains

3-aminopropyltriethoxysilane May produce an allergic reaction.

Trimethoxyvinilsilane May produce an allergic reaction.

#### Special provisions according to Annex XVII of UK REACH:

None.

### 2.3. Other hazards

When mixtures containing cement react with water, for instance when making concrete or mortar, or when the cement becomes wet, a strong alkaline solution is produced (high pH caused by the formation of calcium, sodium and potassium hydroxides).

Cement and mixtures containing cement may irritate the eyes, the mucous system, the throat and the respiratory system and cause coughing. Frequent inhalation of cement dust or mixtures containing cement over a long period of time increases the risk of developing lung diseases.

In case of prolonged contact with the skin, both cement and mixtures containing cement, including pastes, may cause skin sensitisation due to the presence of trace amounts of chromium VI salts. Where necessary, such an effect can be minimized by incorporating a special reducing agent to maintain the water-soluble chromium VI content to concentration rates below 0.0002% (2 ppm) on the total dry weight of cement.

No PBT or vPvB substances present in concentration >= 0.1%

Other Hazards: No other hazards

---

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

N.A.

### 3.2. Mixtures

Mixture identification: L34 FLEX

#### Hazardous components within the meaning of GB CLP regulation and related classification:

Qty	Name	Ident. Num.	Classification	Registration Number
≥10-<20 %	Limestone	CAS:1317-65-3 EC:215-279-6	Substance with a workplace exposure limit in Great Britain.	
≥0.5-<1 %	3-aminopropyltriethoxysilane	CAS:919-30-2 EC:213-048-4 Index:612-108-00-0	Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317	
≥0.5-<1 %	Trimethoxyvinilsilane	CAS:2768-02-7 EC:220-449-8 Index:014-049-00-0	Skin Sens. 1B, H317; Flam. Liq. 2, H225; Acute Tox. 4, H332	

---

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

### 4.2. Most important symptoms and effects, both acute and delayed

N.A.

### 4.3. Indication of any immediate medical attention and special treatment needed

N.A.

---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

#### For emergency responders:

Wear personal protection equipment.

### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

### 6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

## 6.4. Reference to other sections

See also section 8 and 13

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

See also section 8 for recommended protective equipment.

### Advice on general occupational hygiene:

Do not eat or drink while working.

### 7.2. Conditions for safe storage, including any incompatibilities

The product must be stored in waterproof, dry, clean conditions and protected from contamination. Do not use aluminium containers due to incompatibility of the materials.

The product contains cement with an addition of a Chromium reducing agent (VI) and its effectiveness decreases with time. Consequently, packaging's of the material indicate information about the production date, storing conditions and the appropriate storage period for the maintaining of the activity of the reducing agent and for maintaining the soluble Chromium (VI) amount under 2ppm over the total dry weight referred to cement (BS EN 196-10).

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

### 7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

---

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
Limestone CAS: 1317-65-3	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m <sup>3</sup> Inhalable fraction Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m <sup>3</sup> Respirable fraction Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
Diiron trioxide CAS: 1309-37-1	ACGIH		Long Term: 5 mg/m <sup>3</sup> (8h) R, A4 - Pneumoconiosis
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 5 mg/m <sup>3</sup> ; Short Term: 10 mg/m <sup>3</sup> Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m <sup>3</sup> Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m <sup>3</sup> Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
methanol CAS: 67-56-1	ACGIH		Long Term: 200 ppm (8h); Short Term: 250 ppm Skin, BEI - Headache, eye dam, dizziness, nausea

WEL-EH40 UNITED Long Term: 266 mg/m<sup>3</sup> - 200 ppm; Short Term: 333 mg/m<sup>3</sup> - 250 ppm  
KINGDOM OF Sk Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)  
GREAT BRITAIN AND  
NORTHERN  
IRELAND

#### **Predicted No Effect Concentration (PNEC) values**

3-aminopropyltriethoxysilane  
Exposure Route: Fresh Water; PNEC Limit: 330 µg/l  
e  
CAS: 919-30-2

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 3.3 mg/l  
Exposure Route: Marine water; PNEC Limit: 33 µg/l  
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 13 mg/l  
Exposure Route: Freshwater sediments; PNEC Limit: 1.2 mg/kg  
Exposure Route: Marine water sediments; PNEC Limit: 120 µg/kg  
Exposure Route: Soil; PNEC Limit: 50 µg/kg  
Exposure Route: Fresh Water; PNEC Limit: 400 µg/l

Trimethoxyvinilsilane  
CAS: 2768-02-7

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 2.4 mg/l  
Exposure Route: Marine water; PNEC Limit: 40 µg/l  
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 6.6 mg/l  
Exposure Route: Freshwater sediments; PNEC Limit: 1.5 mg/kg  
Exposure Route: Marine water sediments; PNEC Limit: 150 µg/kg  
Exposure Route: Soil; PNEC Limit: 60 µg/kg

#### **Derived No Effect Level (DNEL) values**

3-aminopropyltriethoxysilane  
Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 59 mg/m<sup>3</sup>; Consumer: 17.4 mg/m<sup>3</sup>  
e  
CAS: 919-30-2

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects  
Worker Professional: 59 mg/m<sup>3</sup>; Consumer: 17.4 mg/m<sup>3</sup>

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 8.3 mg/kg; Consumer: 5 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects  
Worker Professional: 8.3 mg/kg; Consumer: 5 mg/kg

Trimethoxyvinilsilane  
CAS: 2768-02-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 27.6 mg/m<sup>3</sup>; Consumer: 6.7 mg/m<sup>3</sup>

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects  
Worker Professional: 260 mg/m<sup>3</sup>; Consumer: 50 mg/m<sup>3</sup>

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects  
Worker Professional: 3.9 mg/kg; Consumer: 7.8 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects  
Consumer: 300 µg/kg

## **8.2. Exposure controls**

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing.

Protection for hands:

Nitrile rubber .

Respiratory protection:

N.A.

Thermal Hazards:

Not expected if used as intended

Environmental exposure controls:

Prevent the product from entering sewers or surface and underground water.

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical State: Liquid

Appearance and colour: Liquid Brown

Odour: Light

Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: > 93°C

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 1.64 g/cm<sup>3</sup>

Solubility in water: Insoluble

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

Solid/gas flammability: N.A.

Volatile Organic compounds - VOCs = 0.00 % ; 0.01 g/l

### 9.2. Other information

Substance Groups relevant properties N.A.

Miscibility: N.A.

Conductivity: N.A.

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions

### 10.2. Chemical stability

Data not available.

### 10.3. Possibility of hazardous reactions

None.

### 10.4. Conditions to avoid

Stable under normal conditions.

### 10.5. Incompatible materials

None in particular.

### 10.6. Hazardous decomposition products

None.

---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified
	Based on available data, the classification criteria are not met
c) serious eye damage/irritation	Not classified
	Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	Not classified
	Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified

f) carcinogenicity	Based on available data, the classification criteria are not met Not classified
g) reproductive toxicity	Based on available data, the classification criteria are not met Not classified
h) STOT-single exposure	Based on available data, the classification criteria are not met Not classified
i) STOT-repeated exposure	Based on available data, the classification criteria are not met Not classified
j) aspiration hazard	Based on available data, the classification criteria are not met Not classified

#### Toxicological information on main components of the mixture:

3-aminopropyltriethoxysilane	a) acute toxicity	LD50 Oral Rat = 1460 mg/kg	
	e	LC50 Inhalation Vapour Rat Negative 6h LD50 Skin Rabbit = 4076 mg/kg 24h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Positive	
	f) carcinogenicity	Genotoxicity Negative	Mouse intraperitoneal route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 600 mg/kg	
Trimethoxyvinilsilane	a) acute toxicity	LD50 Oral Rat = 7.34 ml/Kg LC50 Inhalation Vapour Rat = 2773 Ppm 4h LD50 Skin Rabbit = 3.36 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative 24h	
	c) serious eye damage/irritation	Eye Irritant Rabbit No 24h	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Positive	
	f) carcinogenicity	Genotoxicity Rat Negative	Inhalation route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 250 mg/kg	

---

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

#### List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

#### List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
3-aminopropyltriethoxysilane	CAS: 919-30-2 - EINECS: 213-048-4 - INDEX: 612-108-00-0	a) Aquatic acute toxicity : LC50 Fish Brachydanio rerio > 934 mg/L 96h a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 331 mg/L 48h a) Aquatic acute toxicity : EC50 Algae Scenedesmus subspicatus > 1000 mg/L 72h

a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 331 mg/L 48h  
a) Aquatic acute toxicity : EC50 Algae Scenedesmus subspicatus > 1000 mg/L 72h

Trimethoxyvinilsilane

CAS: 2768-02-7 a) Aquatic acute toxicity : LC50 Fish *Oncorhynchus mykiss* = 137 mg/L 96h  
- EINECS: 220-449-8 - INDEX: 014-049-00-0  
a) Aquatic acute toxicity : LC50 *Daphnia Daphnia magna* = 121 mg/L 48h  
b) Aquatic chronic toxicity : NOEC *Daphnia Daphnia magna* = 20 mg/L - 21days  
a) Aquatic acute toxicity : EC50 *Algae Pseudokirchneriella subcapitata* > 89 mg/L 72h  
a) Aquatic acute toxicity : EC10 microorganisms > 100 mg/L 3h OECD 209

## 12.2. Persistence and degradability

Component	Persistence/Degradability:	Test	Value	Notes:
3-aminopropyltriethoxysilane	Non-readily biodegradable	Dissolved organic carbon	67.000 %	EU method C4-A; 28days

Trimethoxyvinilsilane Readily biodegradable

## 12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value	Notes:
3-aminopropyltriethoxysilane	Bioaccumulative	BCF - Bioconcentration factor	3.400	OECD 305

## 12.4. Mobility in soil

N.A.

## 12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration >= 0.1%

## 12.6. Other adverse effects

N.A.

---

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

---

## SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

### 14.1. UN number

N/A

### 14.2. UN proper shipping name

ADR-Shipping Name: N/A

IATA-Shipping Name: N/A

IMDG-Shipping Name: N/A

### 14.3. Transport hazard class(es)

ADR-Class: N/A

IATA-Class: N/A

IMDG-Class: N/A

### 14.4. Packing group

ADR-Packing Group: N/A

IATA-Packing group: N/A

IMDG-Packing group: N/A

### 14.5. Environmental hazards

Toxic ingredients quantity: 0.00

Very toxic ingredients quantity: 0.00

Marine pollutant: No

Environmental Pollutant: No

### 14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR exempt: No

ADR-Label: N/A

ADR - Hazard identification number: N/A  
ADR-Special Provisions: N/A  
ADR-Transport category (Tunnel restriction code): N/A

Air (IATA):

IATA-Passenger Aircraft: N/A  
IATA-Cargo Aircraft: N/A  
IATA-Label: N/A  
IATA-Subsidiary hazards: N/A  
IATA-Erg: N/A  
IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage and handling: N/A  
IMDG-Segregation: N/A  
IMDG-Subsidiary hazards: N/A  
IMDG-Special Provisions: N/A  
IMDG-EMS: N/A

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

N.A.

---

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Workplace exposure limit within the meaning of the Control of Substances Hazardous to Health Regulations 2002 (WEL-EH40)

REACH regulation as changed by the REACH etc. (Amendment etc.) (EU Exit) Regulations (UK REACH)

CLP regulation as changed by the Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations (GB CLP)

GB PIC legislation - (Regulation (EU) No 649/2012 as changed by the Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc) (EU Exit) Regulations

Restrictions related to the product or the substances contained according to Annex XVII of UK REACH:

Restrictions related to the product: None.

Restrictions related to the substances contained: 40, 69

Additional Regulatory Information for Great Britain

No Additional Information

Provisions related to the Control of Major Accident Hazards Regulations 2015 (GB implementation of Seveso III):

None

GB PIC Legislation:

No substances listed

SVHC Substances:

No SVHC substances present in concentration >= 0.1%

### **UK regulations implementing Dir. 2010/75/EC (VOC directive)**

Volatile Organic compounds - VOCs = 0.00 %

Volatile Organic compounds - VOCs = 0.00 g/L

### **15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for the mixture.

#### **Substances for which a Chemical Safety Assessment has been carried out:**

3-aminopropyltriethoxysilane

Trimethoxyvinilsilane

---

## **SECTION 16: Other information**

<b>Code</b>	<b>Description</b>
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.

  

<b>Code</b>	<b>Hazard class and hazard category</b>	<b>Description</b>
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4

3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: Keep Away From Heat

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

# Exposure Scenario

## Trimethoxyvinilsilane

### Exposure Scenario, 08/06/2021

Substance identity	
	Trimethoxyvinilsilane
CAS No.	2768-02-7
INDEX No.	014-049-00-0
EINECS No.	220-449-8
Registration number	01-2119513215-52

### Table of contents

1. ES 1

# 1. ES 1

## 1.1 TITLE SECTION

Exposure Scenario name	Use in rigid foams, coatings, adhesives and sealants - Barrier (Sealant)
Date - Version	18/05/2021 - 1.0
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22) - Building and construction work (SU19)
Product Categories	Adhesives, sealants (PC1)

## Environment Contributing Scenario

CS1 Low environmental release	ERC8c - ERC8f
-------------------------------	---------------

## Worker Contributing Scenario

CS2 Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application	PROC0
CS3 Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application	PROC1

## 1.2 Conditions of use affecting exposure

### 1.2. CS1: Environment Contributing Scenario: Low environmental release (ERC8c, ERC8f)

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)
----------------------------------	---

### Product (article) characteristics

#### Physical form of product:

Liquid

#### Concentration of substance in product:

Concentration after dilution for use maximum [%]: 0.7 %

### Amount used, frequency and duration of use (or from service life)

#### Amounts used:

Daily amount per site = 0.28 kg/day

#### Release type:

Continuous release

#### Emission days:

365 days per year

### Technical and organisational conditions and measures

#### Control measures to prevent releases

Water - minimum efficiency of: 1.5 %

### Conditions and measures related to sewage treatment plant

#### STP type:

Onsite Sewage Treatment Plant

Water - minimum efficiency of: = 0.013 %

### Conditions and measures related to treatment of waste (including article waste)

#### Waste treatment

Dispose of waste product or used containers according to local regulations.

### Other conditions affecting environmental exposure

#### Local marine water dilution factor:

100

#### Local freshwater dilution factor:

10

#### Receiving surface water flow:

20000 m<sup>3</sup>/day

Covers indoor and outdoor use

## 1.2. CS2: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC0)

Process Categories	Other (PROC0)
--------------------	---------------

### Product (article) characteristics

#### Physical form of product:

Liquid

#### Concentration of substance in product:

Covers concentrations up to 0.7 %

### Amount used, frequency and duration of use/exposure

#### Duration:

Exposure duration <= 6 h

#### Frequency:

Use frequency = 250 days per year

### Technical and organisational conditions and measures

#### Technical and organisational measures

Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

For further specification, refer to section 8 of the SDS.

### Other conditions affecting worker exposure

Covers indoor and outdoor use

Professional use

**Room size:** Covers use in room size of = 20 m<sup>3</sup>

**Temperature:** Covers use at ambient temperatures. 25°C

## 1.2. CS3: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

### Product (article) characteristics

#### Physical form of product:

Liquid

#### Concentration of substance in product:

Covers concentrations up to 2 %

### Amount used, frequency and duration of use/exposure

#### Duration:

Exposure duration = 8 h

#### Frequency:

Use frequency = 1 days per year

#### Duration:

Covers use up to = 6 h

#### Frequency:

Use frequency = 1 days per year

### Other conditions affecting worker exposure

Covers indoor and outdoor use

Professional use

**Room size:** Covers use in room size of = 20 m<sup>3</sup>

**Ventilation rate:** = 0.6 ach (air changes per hour)

## 1.3 Exposure estimation and reference to its source

### 1.3. CS2: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC0)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, long-term	= 1.9 mg/m <sup>3</sup>	N/A	= 0.069
dermal, long-term	= 4.53 mg/kg bw/day	ConsExpo	= 0.038
combined routes, long-term	N/A	N/A	0.107

### 1.3. CS3: Worker Contributing Scenario: Wiping - Hand application - finger paints, pastels, adhesives - Preparation of material for application (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, long-term	= 4.57 mg/m <sup>3</sup>	N/A	= 0.682
dermal, long-term	= 0.044 mg/kg bw/day	ConsExpo	< 0.01
combined routes, short-term	N/A	N/A	0.682

### 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

#### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

# Exposure Scenario

## 3-aminopropyltriethoxysilane

### Exposure Scenario, 14/07/2021

Substance identity	
	3-aminopropyltriethoxysilane
CAS No.	919-30-2
INDEX No.	612-108-00-0
EINECS No.	213-048-4
Registration number	01-2119480479-24

### Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9a, PC1)

1. ES 1

Widespread use by professional workers; Various products (PC9a, PC1)

**1.1 TITLE SECTION**

Exposure Scenario name	Professional application of coatings and inks by spraying - Use in rigid foams, coatings, adhesives and sealants
Date - Version	14/07/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1)

**Worker Contributing Scenario**

CS1 Rolling, Brushing	PROC10
CS2 Roller, spreader, flow application	PROC11

**1.2 Conditions of use affecting exposure****1.2. CS1: Worker Contributing Scenario: Rolling, Brushing (PROC10)**

Process Categories	Roller application or brushing (PROC10)
--------------------	---

**Product (article) characteristics****Physical form of product:**

Liquid

**Concentration of substance in product:**

Covers concentrations up to 2 %

**Amount used, frequency and duration of use/exposure****Amounts used:**

Annual site tonnage = 0.2 t(onnes)/year

Daily amount per site = 0.5 kg/day

**Duration:**

Exposure duration = 4 h

**Frequency:**

Covers exposure up to = 365 days per year

**Technical and organisational conditions and measures****Technical and organisational measures**

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Use in contained systems

For further specification, refer to section 8 of the SDS.

**Conditions and measures related to personal protection, hygiene and health evaluation****Personal protection**

Wear suitable respiratory protection.

For further specification, refer to section 8 of the SDS.

**1.2. CS2: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)**

Process Categories	Non industrial spraying (PROC11)
--------------------	----------------------------------

**Product (article) characteristics****Physical form of product:**

Liquid

**Concentration of substance in product:**

Covers concentrations up to 2 %

## Amount used, frequency and duration of use/exposure

### Amounts used:

Annual site tonnage = 0.2 t(onnes)/year  
Daily amount per site = 0.5 kg/day

### Duration:

Exposure duration = 4 h

### Frequency:

Covers exposure up to = 365 days per year

## Technical and organisational conditions and measures

### Technical and organisational measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Use in contained systems

For further specification, refer to section 8 of the SDS.

## Conditions and measures related to personal protection, hygiene and health evaluation

### Personal protection

Wear suitable respiratory protection.

For further specification, refer to section 8 of the SDS.

## 1.3 Exposure estimation and reference to its source

### 1.3. CS1: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal	= 0.055 mg/kg bw/day	ECETOC TRA worker v3	N/A
inhalative	= 1.8 mg/m <sup>3</sup>	ECETOC TRA worker v3	N/A

### 1.3. CS2: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal	= 0.21 mg/kg bw/day	ECETOC TRA worker v3	N/A
inhalative	= 46 mg/m <sup>3</sup>	ECETOC TRA worker v3	N/A

## 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.