

Safety Data Sheet

Conforms to – Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by UK SI 2021/904

L34 HYBRID

Date of first edition: 1/5/2026

Safety Data Sheet dated 05/01/2026 version 1

kerakoll

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: L34 HYBRID

Trade code: S100B0283

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Adhesives, sealants

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Kerakoll UK Ltd

Tomlinson Road, Leyland, Lancashire, PR25 2DY,

United Kingdom

Tel. 01772 456831

safety@kerakoll.co.uk

1.4. Emergency telephone number

UK National Poisons Information Service.

E-mail: npis.birmingham@nhs.net; Tel: +44 (0)344 892 0111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP regulation:

No specific hazards are encountered under normal product use.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Special Provisions:

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of UK REACH:

None.

2.3. Other hazards

When mixtures containing cement react with water, for instance when making concrete or mortar, or when the cement becomes wet, a strong alkaline solution is produced (high pH caused by the formation of calcium, sodium and potassium hydroxides).

Cement and mixtures containing cement may irritate the eyes, the mucous system, the throat and the respiratory system and cause coughing. Frequent inhalation of cement dust or mixtures containing cement over a long period of time increases the risk of developing lung diseases.

In case of prolonged contact with the skin, both cement and mixtures containing cement, including pastes, may cause skin sensitisation due to the presence of trace amounts of chromium VI salts. Where necessary, such an effect can be minimized by incorporating a special reducing agent to maintain the water-soluble chromium VI content to concentration rates below 0.0002% (2 ppm) on the total dry weight of cement.

No PBT or vPvB substances present in concentration $\geq 0.1\%$

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: L34 HYBRID

Hazardous components within the meaning of GB CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
Date	07/01/2026	Production Name	L34 HYBRID	Page n. 1 of 8

≥3-<5 %	Quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372
≥1-<3 %	Trimethoxyphenylsilane	CAS:2996-92-1 EC:221-066-9	Acute Tox. 4, H302; STOT RE 2, H373

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

N.A.

4.3. Indication of any immediate medical attention and special treatment needed

N.A.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

The product must be stored in waterproof, dry, clean conditions and protected from contamination. Do not use aluminium containers due to incompatibility of the materials.

The product contains cement with an addition of a Chromium reducing agent (VI) and its effectiveness decreases with time. Consequently, packaging's of the material indicate information about the production date, storing conditions and the appropriate storage period for the maintaining of the activity of the reducing agent and for maintaining the soluble Chromium (VI) amount under 2ppm over the total dry weight referred to cement (BS EN 196-10).

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Community Occupational Exposure Limits (OEL)**

	OEL Type	Country	Occupational Exposure Limit
Quartz CAS: 14808-60-7	ACGIH		Long Term: 0.025 mg/m ³ (8h) R, A2 - Pulm fibrosis, lung cancer
Quartz CAS: 14808-60-7	ACGIH		Long Term: 0.025 mg/m ³ (8h) R, A2 - Pulm fibrosis, lung cancer
methanol CAS: 67-56-1	ACGIH		Long Term: 200 ppm (8h); Short Term: 250 ppm Skin, BEI - Headache, eye dam, dizziness, nausea
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 266 mg/m ³ - 200 ppm; Short Term: 333 mg/m ³ - 250 ppm Sk Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Predicted No Effect Concentration (PNEC) values

Trimethoxyphenylsilane CAS: 2996-92-1 Exposure Route: Fresh Water; PNEC Limit: 240 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 2.4 mg/l

Exposure Route: Marine water; PNEC Limit: 24 µg/l

Exposure Route: Intermittent releases (marine water); PNEC Limit: 2.4 mg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 74 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 1.1 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 110 µg/kg

Exposure Route: Soil; PNEC Limit: 80 µg/kg

Derived No Effect Level (DNEL) values

Trimethoxyphenylsilane CAS: 2996-92-1 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 40.2 mg/m³; Consumer: 10 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 260 mg/m³; Consumer: 50 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 260 mg/m³; Consumer: 50 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Professional: 260 mg/m³; Consumer: 50 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 2.5 mg/kg; Consumer: 1.73 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Consumer: 33.3 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 700 µg/kg

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

N.A.

Thermal Hazards:

Not expected if used as intended

Environmental exposure controls:

Prevent the product from entering sewers or surface and underground water.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State: Liquid

Appearance and colour: Pasta White

Odour: Light

Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: 224 °C (435 °F)

Flash point: > 93°C

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 1.79 g/cm³

Solubility in water: N.A.

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

Solid/gas flammability: N.A.

Volatile Organic compounds - VOCs = 0.01 % ; 0.26 g/l

9.2. Other information

Substance Groups relevant properties N.A.

Miscibility: N.A.

Conductivity: N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified
	Based on available data, the classification criteria are not met
c) serious eye damage/irritation	Not classified
	Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	Not classified
	Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

Quartz	a) acute toxicity	LD50 Oral > 2000 mg/kg	
Trimethoxyphenylsilane	a) acute toxicity	LD50 Oral Rat = 1049 mg/kg LD50 Skin Rabbit = 3014 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative 24h	
	c) serious eye damage/irritation	Eye Irritant Rabbit No	
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Negative	
	f) carcinogenicity	Genotoxicity Rat Negative	Inhalation route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 500 mg/kg	

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
Trimethoxyphenylsilane	CAS: 2996-92-1 - EINECS: 221-066-9	a) Aquatic acute toxicity : LC50 Fish <i>Oncorhynchus mykiss</i> = 1400 mg/L 96h OECD Guideline 203
		a) Aquatic acute toxicity : EC50 <i>Daphnia magna</i> = 600 mg/L 96h OECD Guideline 202

a) Aquatic acute toxicity : EC50 Algae Pseudokirchnerella subcapitata = 120 mg/L 96h OECD Guideline 201

a) Aquatic acute toxicity : NOEC Sludge activated sludge = 1000 mg/L 3h OECD 209

12.2. Persistence and degradability

Component	Persistence/Degradability:
Trimethoxyphenylsilane	Non-readily biodegradable

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration $\geq 0.1\%$

12.6. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number

N/A

14.2. UN proper shipping name

ADR-Shipping Name: N/A

IATA-Shipping Name: N/A

IMDG-Shipping Name: N/A

14.3. Transport hazard class(es)

ADR-Class: N/A

IATA-Class: N/A

IMDG-Class: N/A

14.4. Packing group

ADR-Packing Group: N/A

IATA-Packing group: N/A

IMDG-Packing group: N/A

14.5. Environmental hazards

Toxic ingredients quantity: 0.00

Very toxic ingredients quantity: 0.00

Marine pollutant: No

Environmental Pollutant: No

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR exempt: No

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code): N/A

Air (IATA):

IATA-Passenger Aircraft: N/A

IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A

IATA-Erg: N/A

IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage and handling: N/A

IMDG-Segregation: N/A
IMDG-Subsidiary hazards: N/A
IMDG-Special Provisions: N/A
IMDG-EMS: N/A

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace exposure limit within the meaning of the Control of Substances Hazardous to Health Regulations 2002 (WEL-EH40)

REACH regulation as changed by the REACH etc. (Amendment etc.) (EU Exit) Regulations (UK REACH)

CLP regulation as changed by the Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations (GB CLP)

GB PIC legislation - (Regulation (EU) No 649/2012 as changed by the Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc) (EU Exit) Regulations

Restrictions related to the product or the substances contained according to Annex XVII of UK REACH:

Restrictions related to the product: 3

Restrictions related to the substances contained: 40, 69

Additional Regulatory Information for Great Britain

No Additional Information

Provisions related to the Control of Major Accident Hazards Regulations 2015 (GB implementation of Seveso III):

None

GB PIC Legislation:

No substances listed

SVHC Substances:

No SVHC substances present in concentration $\geq 0.1\%$

UK regulations implementing Dir. 2010/75/EC (VOC directive)

Volatile Organic compounds - VOCs = 0.00 %

Volatile Organic compounds - VOCs = 0.00 g/L

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

Trimethoxyphenylsilane

SECTION 16: Other information

Code	Description
H302	Harmful if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.

Code	Hazard class and hazard category	Description
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1
3.9/2	STOT RE 2	Specific target organ toxicity — repeated exposure, Category 2

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor
BEI: Biological Exposure Index
BOD: Biochemical Oxygen Demand
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CAV: Poison Center
CE: European Community
CLP: Classification, Labeling, Packaging.
CMR: Carcinogenic, Mutagenic and Reprotoxic
COD: Chemical Oxygen Demand
COV: Volatile Organic Compound
CSA: Chemical Safety Assessment
CSR: Chemical Safety Report
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level.
DPD: Dangerous Preparations Directive
DSD: Dangerous Substances Directive
EC50: Half Maximal Effective Concentration
ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances.
ES: Exposure Scenario
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KAFH: Keep Away From Heat
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.



Exposure Scenario

Trimethoxyphenylsilane

Exposure Scenario, 15/06/2022

Substance identity	
	Trimethoxyphenylsilane
CAS No.	2996-92-1
EINECS No.	221-066-9
Registration number	01-2119964479-19

Table of contents

1. **ES 1** Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a); Building and construction work (SU19)

1. ES 1

Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a); Building and construction work (SU19)

1.1 TITLE SECTION

Exposure Scenario name	Use in rigid foams, coatings, adhesives and sealants
Date - Version	15/06/2022 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22) - Building and construction work (SU19)
Product Categories	Coatings and paints, thinners, paint removers (PC9a)

Environment Contributing Scenario

CS1	ERC8c - ERC8f
-----	---------------

Worker Contributing Scenario

CS2 Rolling, Brushing - Mixing operations	PROC10 - PROC19
CS3 Roller, spreader, flow application	PROC11

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 Pa (Standard Temperature and Pressure)

Vapour pressure:

= 18.2 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 5 %.

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage = 1 t

Emission days: 365 days per year

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant

STP effluent (m³/day): 2000*Other conditions affecting environmental exposure*

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

1.2. CS2: Worker Contributing Scenario: Rolling, Brushing - Mixing operations (PROC10, PROC19)

Process Categories	Roller application or brushing - Manual activities involving hand contact (PROC10, PROC19)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 Pa (Standard Temperature and Pressure)

Vapour pressure:

= 18.2 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 1 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to days per week

*Technical and organisational conditions and measures***Technical and organisational measures**

Open windows during application to ensure natural ventilation.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Dermal - minimum efficiency of: 80 %

1.2. CS3: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)**Process Categories**

Non industrial spraying (PROC11)

*Product (article) characteristics***Physical form of product:**

Liquid, vapour pressure > 10 Pa (Standard Temperature and Pressure)

Vapour pressure:

= 18.2 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 1 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to days per week

*Technical and organisational conditions and measures***Technical and organisational measures**

Open windows during application to ensure natural ventilation.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Dermal - minimum efficiency of: 80 %

1.3 Exposure estimation and reference to its source**1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)**

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.00056 mg/L	EUSES v2.1	0.0023

marine water	5.5E-05 mg/L	EUSES v2.1	0.0023
freshwater sediment	0.00047 mg/kg wet weight	EUSES v2.1	0.002
marine sediment	4.6E-05 mg/kg wet weight	EUSES v2.1	0.0019
soil	0.000217 mg/kg wet weight	EUSES v2.1	0.0031
Sewage treatment plant	< 1E-06 mg/L	EUSES v2.1	< 1E-06

1.3. CS2: Worker Contributing Scenario: Rolling, Brushing - Mixing operations (PROC10, PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, long-term	2.85 mg/m ³	Stoffenmanager v5.6.10	0.071
dermal, long-term	0.0274 mg/kg bw/day	ECETOC TRA worker v3	0.011

1.3. CS3: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, long-term	9.66 mg/m ³	Stoffenmanager v5.6.10	0.24
dermal, long-term	0.0429 mg/kg bw/day	ECETOC TRA worker v3	0.017

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.