

H40 Extreme

Structural, multi-purpose, extra-flexible, extra-workable Gel-Adhesive.

For ceramic, porcelain and natural stone of all types and formats.



1. Extreme flexibility
2. Extreme adhesion
3. Extreme workability
4. High strength polyurethane base adhesive

kerakoll

Areas of application

→ Use

Substrates:

- existing tiles
- cement-based screeds
- concrete
- plasterboard
- fibro-cement slabs
- gypsum and anhydrite
- cellular concrete
- brick
- lime and cement-based plasters/renders
- finished and subsequently plastered thermal insulation panelling systems
- wood – metal – sheet metal
- rubber floors – PVC
- high-thickness coatings in epoxy and polyurethane resin
- aluminium honey-comb

Materials:

- porcelain tiles
- laminated stoneware and/or stoneware featuring backing materials
- porcelain tile with resin back
- large format tiles
- low thickness slabs
- ceramic tiles
- marble - natural stone
- marble with resin back
- resin-based recomposed materials
- cement-based recomposed materials
- glass mosaics
- glass tiles
- thermal and acoustic insulation
- terracotta - klinker
- metal tiles

Uses:

- adhesive
- floors and walls
- for internal use - external
- overlaying
- terraces and balconies
- facades
- swimming pools and fountains
- saunas and SPA
- domestic
- commercial
- industrial

Instructions for use

→ Preparation of substrates

Substrates must be compact and consistent, free from dust, oil and grease, free from any rising damp, with no loose, flaky, or imperfectly anchored parts. The surface must be stable, without cracks and have already completed the curing period of hygrometric shrinkage. Uneven areas must be corrected with suitable smoothing and finishing products.

→ Preparation

H40 Extreme is prepared by mixing together parts A and B from the bottom upwards, using a low-rev ($\approx 400/\text{min.}$) helicoidal agitator, respecting the preset ratio of 3.2 : 0.8 of the packs. Pour part B into the bucket containing part A, being careful to mix the two parts uniformly until a smooth, even coloured mixture is obtained. The user must mix a quantity of

adhesive which can be consumed within 1 hour at $+23\text{ }^{\circ}\text{C}$ / 50% R.H. Packs of H40 Extreme must be stored at a temperature of $\approx +20\text{ }^{\circ}\text{C}$ for at least 2/3 days prior to use.

→ Application

H40 Extreme must be applied with a suitable, toothed trowel of the type and dimensions most appropriate for the format and type of tiles used. Using the smooth part of the trowel, apply a fine layer of product, pressing down onto the surface in order to ensure maximum adhesion. Press down each tile into the ribbed adhesive to allow for maximum coverage of the surface. In environments subjected to heavy traffic, in external applications and wherever high-elasticity fixing system is required, use the double-spread technique to ensure 100% application of the product to the rear of the tiles.

Instructions for use

→ Cleaning

Residues of H40 Extreme can be cleaned from tools and covered surfaces with water and

alcohol while the adhesive is still fresh. Once cured, the adhesive can only be removed by mechanical means.

Special notes

→ Materials and special substrates

- Marble—natural stones and recomposed materials: check for the presence of any really consistent traces of rock dust created during cutting, and remove them if found.
- Special substrates: adherent and floating polymer sheets, liquid bitumen and tar-based sheets or membranes require application of a laying screed on top.

→ Special applications

- Facades (UNI 11493 - point 7.13.7): the substrate should guarantee a cohesive tensile strength of $\geq 1.0 \text{ N/mm}^2$. Always apply a layer of adhesive on the substrate and on the back of the material (double-spread technique).

Certificates and marks



Abstract

High-performance laying of porcelain tiles, ceramic tiles, mosaic, marble, granite and natural stone on deformable substrates will be carried out using a highly deformable and workable hybrid gel adhesive that has been tested under the most extreme working conditions, compliant with standard EN 12004 – class R2 T, such as H40 Extreme by Kerakoll Spa. The substrate must be clean, free from any loose, flaky parts and adequately matured. A ____ mm toothed spreader must be used for an average coverage of $\approx$ ____ kg/m^2 . Create elastic fractionizing joints every ____ m^2 . Tiles must be laid with joints of ____ mm width.

Technical Data compliant with Kerakoll Quality Standard		
Appearance	Part A white paste / Part B white paste	
Mixing ratio	Part A : Part B = 3.2 : 0.8	
Pack	monopack 4 kg (3.2 + 0.8 kg)	
Shelf life	≈ 24 months from production in the original sealed packaging	
Thickness	from 2 to 10 mm	
Temperature range for application	from +5 °C to +35 °C	UNI 11493 - 8.3
Pot life at +25 °C	≥ 90 min.	
Open time	≥ 90 min.	EN 12004-2
Adjustability	≥ 70 min.	
Vertical slip	≤ 0.5 mm	EN 12004-2
Foot traffic	≈ 24 h	
Grouting	≈ 12 hrs on walls / ≈ 24 hrs on floors	
Interval before normal use	≈ 3 days	
Consumption per mm of thickness	≈ 1.5 kg/m²	

Rilevazione dati a +23 °C di temperatura, 50% U.R. e assenza di ventilazione. Possono variare in funzione delle specifiche condizioni di cantiere: temperatura, ventilazione, assorbenza del fondo e del materiale posato.

Performance		
HIGH-TECH		
Durability test:		
- shear adhesion after water immersion	≥ 5 N/mm ²	EN 12004-2
- shear adhesion after thermal shock	≥ 5 N/mm ²	EN 12004-2
Vertical slip	≤ 0.2 mm	EN 12004-2
Elongation at break after 7 days	≈ 30%	
Service temperature of the cured product	from -40 °C to +70 °C	
Tensile adhesion strength:		
- dry conditions	3.5 N/mm ²	IS 15477: 2019
Shear adhesion strength:		
- dry condition	6.2 N/mm ²	IS 15477: 2019
- heat ageing condition	5.17 N/mm ²	IS 15477: 2019
Deformability	≥ 50 mm	IS 15477: 2019
Slip resistance	0.2 mm	IS 15477: 2019
Initial shear adhesion strength	4.15 N/mm ²	EN 12004-2
Open time tensile adhesion strength	3.00 N/mm ²	EN 1346

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.

Warning

- Abide by any standards and national regulations

→ use at temperatures between +10 °C and +30 °C

→ use packs which have been stored for 2/3 days before use at +25 °C

→ strictly keep to the mixing ratio of 3.2 : 0.8. For partial mixing, weigh the two parts precisely

→ workability times may vary considerably, depending on environmental conditions and the temperature of the tiles
- protect against direct rain for at least 12 hrs

→ do not fix on surfaces subject to moisture rising or which are not completely dry

→ if necessary, ask for the safety data sheet

→ for any other issues, contact Kerakoll Customer Care +91-22-2839 5593 / 1800 102 4957 - info@kerakollindia.com

This information was last updated in August 2026; please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.