

Tapetex

Compressible, closed-cell expanded polyethylene tape for perimeter and desolidarisation joints.

Thanks to the practical polyethylene band with double-sided adhesive, Tapetex guarantees coupling when laying the mineral screed on polyethylene or PVC sheets.



1. Easy to apply using the lower adhesive side
2. Guarantees desolidarisation of the screed and floor
3. Adhesive coupling with the horizontal layer
4. Height 100 mm

Areas of application

→ Intended use

Creation of perimetric joints for internal and external screeds.

Desolidarisation of walls and vertical structures in general.

Do not use on loose, damp or dirty substrates.

Instructions for use

→ Before laying, make sure that the height of the tape is sufficient to guarantee that the screed is desolidarised up to the tiled level. To do this, lay the Tapetex compressible tape along the whole perimeter of the room, on the walls and on any other vertical elements protruding from the supporting layer (for example pillars, columns, installations...), so as to guarantee desolidarisation of the screeds in all points.

Make sure the tape adheres perfectly to the vertical structures, to ensure that it is laid continuously over door recesses and patio doors, if there are any, and heating manifolds, paying particular attention to corners.

Use the PE film part with adhesive to guarantee the continuity of the coupling with the horizontal layer.

Certificates and marks



* Émission dans l'air intérieur Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

Abstract

The perimetric joint of desolidarisation is made by laying Kerakoll Tapetex compressible, closed-cell expanded polyethylene tape, width 100 mm and thickness 8 mm, complete with double-sided adhesive polyethylene film as coupling with the horizontal layer.

Technical Data compliant with Kerakoll Quality Standard	
Appearance	polyethylene foam roll
Colour	anthracite grey
Roll width	≈ 100 mm
Roll length	≈ 50 m
Thickness	≈ 8 mm

Performance		
VOC Indoor Air Quality (IAQ) - Volatile organic compound emissions		
Conformity	EC 1 plus GEV-Emicode	GEV certified 6043/11.01.02

Warning

- Abide by any standards and national regulations
- the product is an item according to the definitions of the EC Regulation No. 1907/2006 and therefore does not require a Safety Data Sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com



This information was last updated in July 2026; please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.