

Fuga-Remove

Scraper for joints.

Manual tool for the removal and cleaning of joint gaps between tiles.



1. Versatile, for 1 to 5 mm joints
2. Blade coated with tungsten carbide
3. Ergonomic plastic handle

Areas of application

→ Use:

- removal of old grout prior to subsequent re-grouting using Fugalite

- cleaning of residual adhesive from ceramic tile joints before grouting

Instructions for use

→ Application

Use 1, 2 or 3 blades according to the width of the existing joints.

Slide the Fuga-Remove blade longitudinally along the joint, pressing lightly (to clean) or firmly (to remove).


High pressure or inadequate use of Fuga-Remove may damage the covering.

Before grouting again, dust must be removed from joints by cleaning them thoroughly with a vacuum cleaner.

Warning

- Abide by any standards and national regulations
- the product is an item according to the definitions of the EC Regulation No. 1907/2006 and therefore does not require a Safety Data Sheet

- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com



This information was last updated in June 2026; please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.