

Hyper Foam Clean

Cleaner for guns and PU foams.

Hyper Foam Clean ensures easy cleaning inside and outside of dispensing guns for polyurethane expanding foam. It also cleans unhardened polyurethane foam residues.



1. Ready-to-use
2. Effectively removes fresh foam residues
3. Improves durability and performance of dispensing guns for polyurethane foam

Rating 2

- × VOC Low Emission
- × Water Based
- × Solvent ≤ 80 g/kg
- ✓ Low Ecological Impact
- ✓ Health Care



kerakoll

Areas of application

→ Use.

Cleaning of dispensing guns for Hyper Foam range polyurethane foams and polyurethane foams in general.

Removal of fresh residues of Hyper Foam range polyurethane foams and polyurethane foams in general.

Do not use on substrates that are sensitive to solvents such as acetone.

Instructions for use

→ Application

- For removal of fresh PU foam residue: mount the dispensing nozzle on the canister and use Hyper Foam as if it were a standard canister. Then dry with a cloth or paper towels.

- For cleaning inside the gun: fit the dispensing nozzle and clean the gun tip and threads using Hyper Foam Clean like a standard canister. After removing the dispensing nozzle, screw Hyper Foam Clean onto the gun and pull the trigger to clean the inside until pure detergent comes out.

Special notes

→ Check on a non-visible part that the substrate is compatible with Hyper Foam Clean.

Technical Data compliant with Kerakoll Quality Standard

Appearance	transparent liquid
Base	organic solvent
Shelf life	≈ 24 months from production in the original sealed packaging, protect from humidity
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Pack	500 ml aerosol
Temperature range for application	from +5 °C to +30 °C

Warning

- Product for professional use
- abide by any standards and national regulations
- use protective gloves and goggles
- comply with the usual occupational hygiene measures

- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com



The Rating classifications refer to the GreenBuilding Rating Manual 2012. This information was last updated in January 2025 (ref. GBR Data Report – 01.25); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions of your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.