

Keradecor Sintolite

Organic mineral preparation coat.

Keradecor Sintolite is a solvent-based, high filling power undercoat suitable for wood and steel surfaces. Levels surfaces before subsequent application of the glaze coat. For internal and external use.



1. Easy to apply and sand
2. Can be easily applied with a brush or roller
3. High coverage

Areas of application

→ Use

Preparation coat for:

- seasoned soft and hardwood structures
- well dried and seasoned artificial plywood structures
- steel or metal duly prepared, as an intermediate coat

For internal and external use.

Do not use on wet surfaces.

Instructions for use

→ Preparation of substrates

On timber or metal, smooth with sandpaper and clean thoroughly before applying one or more coats of Keradecor Sintolite. For the treatment of substrates other than those mentioned and for additional information on the types of intervention to be carried out, we recommend to consult Kerakoll's Guide to decorating and preparing substrates.

→ Preparation

Always remix the product before application.

→ Application

Keradecor Sintolite must be thoroughly applied on all the surface with a brush, or roller after diluting with Keradecor Solmix thinner depending on the application.

For application with a brush or roller dilute Keradecor Sintolite to 5% with Keradecor Solmix.

24 hours after applying Keradecor Sintolite smooth the treated surface with sandpaper and clean thoroughly. Apply one or more coats to be finished with a glaze from the Kerakoll range. Conditions required for decorating are ambient and substrate temperatures between +5 °C and +30 °C and a relative ambient humidity lower than 80%.

→ Cleaning

Residual traces of Keradecor Sintolite can be removed from tools using Keradecor Solmix before the product hardens.

Special notes

→ Keradecor Sintolite is flammable.

Certificates and marks



* Émission dans l'air intérieur Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

Abstract

Preparation coat for internal and external substrates, applied using a brush, roller or a high coverage and high filling power spray, suitable for levelling timber and steel surfaces before the subsequent application of glaze, solvent-based alkyd resin product, such as Keradecor Sintolite by Kerakoll Spa.

Technical Data compliant with Kerakoll Quality Standard	
Appearance	white paste
Volumetric mass	≈ 1.7 kg/l
Chemical nature	alkyd resin
Pack	cans 0.5 – 2.5 l
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +5 °C to +30 °C
Humidity of the substrate	≤ 6%
Dilute with Keradecor Solmix	max 10% by volume
Coverage per single coat	≈ 0.1 – 0.15 l/m ²

Values taken at +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.

Warning

- Product for professional use

→ abide by any standards and national regulations

→ flammable product

→ store away from naked flames and sparks

→ make sure the substrate is not frozen
- do not add binders or additives

→ if necessary, ask for the safety data sheet

→ for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com



This information was last updated in September 2026; please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions of your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.