



kerakoll

DECLARATION OF PERFORMANCE NO. 0367

1. Unique identification code of the product-type: **GEOCALCE G ANTISISMICO**
2. Intended use/es: **General purpose masonry mortar (G) for external use in elements subject to structural requirements**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 2+
System 4 for reaction to fire
5. Harmonised standard: **EN 998-2:2016**
Notified body/ies: **LRQA Inspection Iberia n. 0094**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength Shear bond strength Flexural bond strength Contents of chloride Water absorption Water vapour permeability Thermal conductivity Durability (against freeze-thaw)	M 15 0,15 N/mm²(t.v.) NPD ≤ 0,05% 0,3 Kg/m²min^{0,5} μ 15/35 (t.v.) 0,82 W/mK (t.v.) NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 30/09/2025

kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.



kerakoll

DECLARATION OF PERFORMANCE No 0367

1. Unique identification code of the product-type: **GEOCALCE G ANTISISMICO**
2. Intended use/es: **Concrete non structural repair products, used in buildings and civil engineering works**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 2+
System 4 for reaction to fire
5. Harmonised standard: **EN 1504-3:2005**
Notified body/ies: **LRQA Inspection Iberia n. 0094**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	Class R1
Chloride ion content	≤ 0,05 %
Adhesive bond	≥ 0,8 MPa
Thermal compatibility (freeze-thaw)	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 30/09/2025

kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.