



kerakoll

DECLARATION OF PERFORMANCE No 0370

1. Unique identification code of the product-type: **GEOCALCE MULTIUSO**
2. Intended use/es: **General purpose rendering/plastering mortar (GP)**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 4
System 4 for reaction to fire
5. Harmonised standard: **EN 998-1:2016**
Notified body/ies:-
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Adhesion Water absorption Water vapour diffusion coeff. Thermal conductivity ((λ_{10}, dry)	$\geq 0,5 \text{ N/mm}^2$ - FP: B W_{c1} $\mu 13$ 0,54 W/mK (v.t.)
Durability (against freeze-thaw) : evaluation based on provisions valid in the intended place of use of the mortar	
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 07/07/2025

Kerakoll Spa
via dell'Artigianato 9
41049 Sassuolo (MO)
Italia

Società con unico socio
Fin Firel Spa.
Soggetta a direzione
e coordinamento
di Fin Firel Spa.

+39 0536816511
+39 0536816581
info@kerakoll.com
www.kerakoll.com

Rea MO n. 231812
R.I./C.F./P.I. 01174510360
Cap. soc. € 2.000.000,00 i.v.



kerakoll

DECLARATION OF PERFORMANCE No 0370

1. Unique identification code of the product-type: **GEOCALCE MULTIUSO**
2. Intended use/es: **Repair products for concrete, used in buildings and civil engineering works**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 2+
System 4 for reaction to fire
5. Harmonised standard: **EN 1504-3:2005**
Notified body/ies: **LRQA Inspection Iberia No.0094**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	Class R1
Chloride ion content	≤ 0,05 %
Adhesive bond	≥ 0,8 MPa
Thermal compatibility (freeze-thaw)	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 07/07/2025

Kerakoll Spa
via dell'Artigianato 9
41049 Sassuolo (MO)
Italia

Società con unico socio
Fin Firel Spa.
Soggetta a direzione
e coordinamento
di Fin Firel Spa.

+39 0536816511
+39 0536816581
info@kerakoll.com
www.kerakoll.com

Rea MO n. 231812
R.I./C.F./P.I. 01174510360
Cap. soc. € 2.000.000,00 i.v.