



# kerakoll

## DECLARATION OF PERFORMANCE No. 0411

1. Unique identification code of the product-type: **CHIUDI TRACCIA**
2. Intended use/es: **Designed general purpose masonry mortar (G) for internal and external use in elements subject to structural requirements**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:  
**System 2+**  
**System 4 for reaction to fire**
5. Harmonised standard: **EN 998-2:2016**  
Notified body/ies: **LRQA Iberia No.0094**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	M 2,5
Shear bond strength	0,15 N/mm <sup>2</sup> (t.v.)
Flexural bond strength	NPD
Contents of chloride	≤ 0,05%
Water absorption	1,20 Kg/m <sup>2</sup> min <sup>0,5</sup>
Water vapour permeability	μ 15/35 (t.v.)
Thermal conductivity	0,66 W/mK (t.v.)
Durability	NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 02/06/2025

**kerakoll.com**

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa  
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com  
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.