



kerakoll

DECLARATION OF PERFORMANCE No 0057

1. Unique identification code of the product-type: **ISOBUILD ECO BLOCK**
2. Intended use/es: **Designed thin layer masonry mortar (T) for external and internal use in elements subject to structural requirements**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 2+
5. Harmonised standard: **EN 998-2:2016**
Notified body/ies: **LRQA Inspection Iberia No. 0094**
6. Declared performance/s:

| Essential characteristics | Performance |
|--|---|
| Reaction to fire | Class A1 |
| Compressive strength | M5 |
| Initial shear strength | 0,3 N/mm² (v.t.) |
| Flexural bond strength | NPD |
| Contents of chloride | ≤ 0,05% |
| Water absorption | 0,7 Kg/(m² min^{0,5}) |
| Water vapour permeability | μ 5/20 (v.t.) |
| Thermal conductivity | 0,37 W/mK (v.t.) |
| Durability | NPD |
| Release of dangerous substances | See SDS |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 02/07/2025

Kerakoll Spa
via dell'Artigianato 9
41049 Sassuolo (MO)
Italia

Società con unico socio
Fin Firel Spa.
Soggetta a direzione
e coordinamento
di Fin Firel Spa.

+39 0536816511
+39 0536816581
info@kerakoll.com
www.kerakoll.com

Rea MO n. 231812
R.I./C.F./P.I. 01174510360
Cap. soc. € 2.000.000,00 i.v.