



kerakoll

DECLARATION OF PERFORMANCE No 0015

1. Unique identification code of the product-type: **BIOCALCE MURATURA FINO**
2. Intended use/es: **General purpose masonry mortar (G) for external and internal use in elements subject to structural requirements**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 2+
System 4 for reaction to fire
5. Harmonised standard: **EN 998-2**
Notified body/ies: **LRQA Inspection Iberia No. 0094**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength Initial shear strength Contents of chloride Water absorption Water vapour permeability Thermal conductivity Durability	M10 0,2 N/mm² ≤ 0,05% 0,7 Kg/(m² min^{0,5}) μ 15/35 (v.t.) 0,83 W/mK (v.t.) NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 05/05/2025

Kerakoll Spa
via dell'Artigianato 9
41049 Sassuolo (MO)
Italia

Società con unico socio
Fin Firel Spa.
Soggetta a direzione
e coordinamento
di Fin Firel Spa.

+39 0536816511
+39 0536816581
info@kerakoll.com
www.kerakoll.com

Rea MO n. 231812
R.I./C.F./P.I. 01174510360
Cap. soc. € 2.000.000,00 i.v.