



DECLARATION OF PERFORMANCE N. 0737

1. Unique identification code of the product-type: **GLASS NET A305**
2. Intended use/es: **CRM (Composite Reinforced Mortar) reinforcement of masonry and reinforced concrete structures, in flexure, in shear, under pure axial load and/or combinations of axial load and flexure**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP: **System 2+**
5. European Assessment Document: **EAD 340392-00-0104, November 2018**
European Technical Assessment: **ETA 25/0350 of 14/04/2025**
Technical Assessment Body: **ITC-CNR**
Notified body/ies: **ITC n°0970**
6. Declared performance/s:

Identification data of the article			
Mesh size (centre-to-centre distance of each bar)		38 x 38 mm \pm 5 %	
Weight	Mesh without impregnation	255 g/m ² \pm 10 %	
	Impregnated mesh	305 g/m ² \pm 10 %	
Composition	AR Alkali Resistant glass fibre (According to UNI EN 15422); Fibre density 2.68 g/cm ³	By weight approx. 84%	By volume approx. 68%
	Thermosetting Epoxy resin; Resin density 1.1 g/cm ³	By weight approx. 16%	By volume approx. 32%
Nominal cross section area of the bars	warp	3.21 mm ² \pm 5 %	
	weft	5.27 mm ² \pm 5 %	

Essential characteristics		Performance
Tensile resistance of the impregnated bar		1.85 kN
Water resistance after 1000 hours	warp/weft	Residual \geq 85 %
Saltwater resistance after 1000 hours	warp/weft	Residual \geq 85 %
Alkali resistance after 1000 hours	warp/weft	Residual \geq 85 %
Freezing and thawing resistance	warp/weft	Residual \geq 85 %
Glass Transition Temperature Tg of the mesh		59.96°C



kerakoll

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

In Sassuolo, on 06/04/2026



kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.