

## Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

### EP21 (A)

Date of first edition: 6/11/2021

Safety Data Sheet dated 03/12/2024

version 8

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Mixture identification:

Trade name: EP21 (A)

Trade code: S100B0171 .011

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: resin

Uses advised against: All uses other than recommended ones

### 1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

### 1.4. Emergency telephone number

European emergency phone number 112

Ireland Poison information centre: 01 809 2166 (Daily 8am-10pm) In case of emergency call 999 or 112

Malta In case of emergency call: +356 2395 2000 (24h)

## SECTION 2: Hazards identification



### 2.1. Classification of the substance or mixture

#### Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2 Causes serious eye irritation.

Skin Sens. 1B May cause an allergic skin reaction.

Aquatic Chronic 2 Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

### 2.2. Label elements

#### Regulation (EC) No 1272/2008 (CLP):

#### Hazard pictograms and Signal Word



Warning

#### Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves and eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with applicable regulations.

Contains

Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

Dir. 2004/42/EC (VOC directive)

Binding primers

EU limit value for this product (cat. A/h): 750 g/l

This product contains max 0 g/l VOC.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: EP21 (A)

Hazardous components within the meaning of the CLP regulation and related classification:

| Qty       | Name   | Ident. Numb.  | Classification  | Registration Number   |
|-----------|--|---|---|-----------------------|
| ≥20-<50 % | bis-[4-(2,3-epoxipropoxy)phenyl]propane  | CAS:1675-54-3<br>EC:216-823-5<br>Index:603-073-00-2 | Eye Irrit. 2, H319<br>Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>Aquatic Chronic 2, H411, M-Chronic:1 | 01-2119456619-26      |
|           |  |   | Specific Concentration Limits:<br>C ≥ 5%: Eye Irrit. 2 H319<br>C ≥ 5%: Skin Irrit. 2 H315               |                       |
| ≥20-<50 % | Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane | EC:701-263-0  | Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 2, H411, M-Chronic:1                           | 01-2119454392-40      |
| ≥20-<50 % | Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane   | EC:701-477-4  | Skin Sens. 1B, H317   | 01-2119982994-15-0000 |

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist

immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Eye irritation

Eye damages

Skin Irritation

Erythema

#### **4.3. Indication of any immediate medical attention and special treatment needed**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

---

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

Suitable extinguishing media:

Water.

Carbon dioxide (CO<sub>2</sub>).

Extinguishing media which must not be used for safety reasons:

None in particular.

#### **5.2. Special hazards arising from the substance or mixture**

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

#### **5.3. Advice for firefighters**

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

**For non emergency personnel:**

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

**For emergency responders:**

Wear personal protection equipment.

#### **6.2. Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

#### **6.3. Methods and material for containment and cleaning up**

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

#### **6.4. Reference to other sections**

See also section 8 and 13

---

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

**Advice on general occupational hygiene:**

#### **7.2. Conditions for safe storage, including any incompatibilities**

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

### 7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

---

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Predicted No Effect Concentration (PNEC) values

bis-[4-(2,3-  
epoxipropoxy)phenyl]  
propane  
CAS: 1675-54-3

Exposure Route: Fresh Water; PNEC Limit: 0.006 mg/l

Exposure Route: Marine water; PNEC Limit: 600 ng/L

Exposure Route: Freshwater sediments; PNEC Limit: 0.996 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0.099 mg/kg

Exposure Route: Soil; PNEC Limit: 0.196 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.018 mg/l

Reaction mass of 2,2'-  
[methylenebis(2,1-  
phenyleneoxymethylene)]  
bis(oxirane) and 2,2'-  
[methylenebis(4,1-  
phenyleneoxymethylene)]  
bis(oxirane) and 2-(2-  
[4-(oxiran-2-  
ylmethoxy)benzyl]  
phenoxy}methyl)oxirane

Exposure Route: Fresh Water; PNEC Limit: 3 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 25.4 µg/l

Exposure Route: Marine water; PNEC Limit: 300 ng/L

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 294 µg/kg

Exposure Route: Marine water sediments; PNEC Limit: 29.4 µg/kg

Exposure Route: Soil; PNEC Limit: 237 µg/kg

#### Derived No Effect Level (DNEL) values

bis-[4-(2,3-  
epoxipropoxy)phenyl]  
propane  
CAS: 1675-54-3

Exposure Route: Human Oral; Exposure Frequency: Long Term, local effects  
Worker Professional: 0.75 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 0.75 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 3.571 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects  
Worker Professional: 3.571 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 12.25 mg/m<sup>3</sup>

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects  
Worker Professional: 12.25 mg/m<sup>3</sup>

Reaction mass of 2,2'-  
[methylenebis(2,1-  
phenyleneoxymethylene)]  
bis(oxirane) and 2,2'-  
[methylenebis(4,1-  
phenyleneoxymethylene)]  
bis(oxirane) and 2-(2-  
[4-(oxiran-2-  
ylmethoxy)benzyl]  
phenoxy}methyl)oxirane

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 29.39 mg/m<sup>3</sup>; Consumer: 8.7 mg/m<sup>3</sup>

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 104.15 mg/kg; Consumer: 62.5 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects  
Consumer: 6.25 mg/kg

## 8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing. Safety shoes.

Protection for hands:

Protection for hands:

Suitable materials for safety gloves; EN 374:

Nitrile rubber - NBR: thickness  $\geq 0,35\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: Colourless

Odour: Odourless

Odour threshold: N.A.

pH: Not Relevant Notes: non determinabile

Kinematic viscosity: N.A.

Melting point/freezing point: N.A. Notes: non determinabile

Boiling point or initial boiling point and boiling range:  $> 200\text{ }^{\circ}\text{C}$  (392  $^{\circ}\text{F}$ )

Flash point:  $> 100\text{ }^{\circ}\text{C}$  (212  $^{\circ}\text{F}$ )

Lower and upper explosion limit: N.A.

Relative vapour density: N.A.

Vapour pressure: N.A.

Density and/or relative density: 1.10 g/cm<sup>3</sup>

Solubility in water: Insoluble

Solubility in oil: N.A.

Partition coefficient n-octanol/water (log value): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: N.A.

Volatile Organic compounds - VOCs = 0 % ; 0 g/l

#### Particle characteristics:

Particle size: N.A.

### 9.2. Other information

Viscosity: 0.55 PA-s

No other relevant information

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions

### 10.2. Chemical stability

Data not available.

### 10.3. Possibility of hazardous reactions

None.

### 10.4. Conditions to avoid

Stable under normal conditions.

### 10.5. Incompatible materials

None in particular.

### 10.6. Hazardous decomposition products

None.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicological Information of the Preparation

|                                      |  |
|--------------------------------------|--|
| a) acute toxicity                    | Not classified   |
|                                      | Based on available data, the classification criteria are not met |
| b) skin corrosion/irritation         | The product is classified: Skin Irrit. 2(H315)                   |
| c) serious eye damage/irritation     | The product is classified: Eye Irrit. 2(H319)                    |
| d) respiratory or skin sensitisation | The product is classified: Skin Sens. 1B(H317)                   |
| e) germ cell mutagenicity            | Not classified   |
|                                      | Based on available data, the classification criteria are not met |
| f) carcinogenicity                   | Not classified   |
|                                      | Based on available data, the classification criteria are not met |
| g) reproductive toxicity             | Not classified   |
|                                      | Based on available data, the classification criteria are not met |
| h) STOT-single exposure              | Not classified   |
|                                      | Based on available data, the classification criteria are not met |
| i) STOT-repeated exposure            | Not classified   |
|                                      | Based on available data, the classification criteria are not met |
| j) aspiration hazard                 | Not classified   |
|                                      | Based on available data, the classification criteria are not met |

#### Toxicological information on main components of the mixture:

|  |                                      |   |   |
|--|--------------------------------------|---|---|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane  | a) acute toxicity                    | LD50 Oral Rabbit = 19800 mg/kg                  |   |
|  |                                      | LD50 Skin Rabbit > 20 mg/kg 24h                 |   |
|  | b) skin corrosion/irritation         | Skin Irritant Rabbit Positive                   | epoxy resin with an average molecular mass ≤ 700 d irritate skin of rabbits |
|  | c) serious eye damage/irritation     | Eye Irritant Rabbit Yes                         |   |
|  | d) respiratory or skin sensitisation | Skin Sensitization Positive                     | Mouse   |
|  | f) carcinogenicity                   | Genotoxicity Negative                           | Mouse, oral   |
|  |                                      | Carcinogenicity Oral Rat = 15 mg/kg             | NOAEL   |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane |                                      | Carcinogenicity Skin Rat = 1 mg/kg              | NOAEL   |
|  | g) reproductive toxicity             | No Observed Effect Level Oral Rat = 750 mg/kg   |   |
|  | a) acute toxicity                    | LD50 Oral Rat > 5000 mg/kg                      |   |
|  |                                      | LD50 Skin Rat > 2000 mg/kg 24h                  |   |
|  | b) skin corrosion/irritation         | Skin Irritant Rabbit Positive 4h                |   |
|  | c) serious eye damage/irritation     | Eye Irritant Rabbit No                          |   |
|  | d) respiratory or skin sensitisation | Skin Sensitization Positive                     | Mouse   |
|  | f) carcinogenicity                   | Genotoxicity Negative                           | Hamster oral route  |
|  | g) reproductive toxicity             | No Observed Adverse Effect Level Oral Rat = 750 |   |
|  |                                      |   |   |

**11.2. Information on other hazards****Endocrine disrupting properties:**

No endocrine disruptor substances present in concentration  $\geq 0.1\%$

**SECTION 12: Ecological information****12.1. Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Toxic to aquatic life with long lasting effects.

**List of Eco-Toxicological properties of the product**

The product is classified: Aquatic Chronic 2(H411)

**List of Eco-Toxicological properties of the components**

| Component   | Ident. Numb.  | Ecotox Data   |
|---|---|---|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane   | CAS: 1675-54-3<br>- EINECS: 216-823-5 - INDEX: 603-073-00-2 | a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 2 mg/L 96h<br><br>a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 1.8 mg/L 48h<br>a) Aquatic acute toxicity : EC50 Algae Scenedesmus capricornutum = 11 mg/L 72h EPA-660/3-75-009<br>c) Bacteria toxicity : EC50 Sludge activated sludge = 100 mg/L 3h   |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane | EINECS: 701-263-0   | a) Aquatic acute toxicity : LC50 Fish Leuciscus idus = 2.54 mg/L 96h<br><br>a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 2.55 mg/L 48h<br>b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 0.3 mg/L - 21days<br>a) Aquatic acute toxicity : EC50 Algae Selenastrum capricornutum = 1.8 mg/L 72h<br>a) Aquatic acute toxicity : NOEC Sludge activated sludge = 100 mg/L 3h |

**12.2. Persistence and degradability**

| Component   | Persistence/Degradability: | Test               | Value  | Notes:  |
|---|----------------------------|--------------------|--------|---|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane   | Non-readily biodegradable  | Oxygen consumption |        | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane | Non-readily biodegradable  |                    | 16.000 | 28days  |

**12.3. Bioaccumulative potential**

| Component  | Bioaccumulation | Test                          | Value   |
|--|-----------------|-------------------------------|---------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane                            | Bioaccumulative | BCF - Bioconcentration factor | 31.000  |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis | Bioaccumulative | BCF - Bioconcentration factor | 150.000 |

(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

#### 12.4. Mobility in soil

Data not available.

#### 12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration  $\geq 0.1\%$

#### 12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration  $\geq 0.1\%$

#### 12.7. Other adverse effects

Data not available.

---

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as hazardous waste

---

### SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

#### 14.1. UN number or ID number

3082

#### 14.2. UN proper shipping name

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane - Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane)

IATA-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane - Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane)

IMDG-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane - Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane)

#### 14.3. Transport hazard class(es)

IATA-Class: 9

IMDG-Class: 9

#### 14.4. Packing group

IATA-Packing group: III

IMDG-Packing group: III

#### 14.5. Environmental hazards

Most important toxic component: bis-[4-(2,3-epoxipropoxy)phenyl]propane

IMDG-EMS: F-A, S-F

#### 14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 9

ADR - Hazard identification number: 90

ADR-Special Provisions: 274 335 375 601

ADR-Transport category (Tunnel restriction code): 3 (-)

ADR Limited Quantities: 5 L

ADR Excepted Quantities: E1

Air (IATA):

IATA-Passenger Aircraft: 964

IATA-Cargo Aircraft: 964

IATA-Label: 9

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisions: A97 A158 A197 A215

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 274 335 969

#### 14.7. Maritime transport in bulk according to IMO instruments

N.A.

---

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

| Seveso III category according to Annex 1, part 1 | Lower-tier threshold (tonnes) | Upper-tier threshold (tonnes) |
|--|-------------------------------|-------------------------------|
|--|-------------------------------|-------------------------------|

|                                 |     |     |
|---------------------------------|-----|-----|
| Product belongs to category: E2 | 200 | 500 |
|---------------------------------|-----|-----|

#### Explosives precursors – Regulation 2019/1148

No substances listed

#### Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

#### German Water Hazard Class.

3: Severe hazard to waters

#### German Lagerklasse according to TRGS 510:

LGK 10

SVHC Substances:

No SVHC substances present in concentration  $\geq 0.1\%$

#### Dir. 2004/42/EC (VOC directive)

(ready to use)

Volatile Organic compounds - VOCs = 0.00 %

Volatile Organic compounds - VOCs = 0.00 g/L

EP21 (A) (not ready to use)

Volatile Organic compounds - VOCs = 0.00 %  
Volatile Organic compounds - VOCs = 0.00 g/L

## 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

### Substances for which a Chemical Safety Assessment has been carried out:

bis-[4-(2,3-epoxipropoxy)phenyl]propane

---

## SECTION 16: Other information

| Code | Description                                      |
|------|--|
| H315 | Causes skin irritation.                          |
| H317 | May cause an allergic skin reaction.             |
| H319 | Causes serious eye irritation.                   |
| H411 | Toxic to aquatic life with long lasting effects. |

| Code     | Hazard class and hazard category | Description                                    |
|----------|----------------------------------|--|
| 3.2/2    | Skin Irrit. 2                    | Skin irritation, Category 2                    |
| 3.3/2    | Eye Irrit. 2                     | Eye irritation, Category 2                     |
| 3.4.2/1  | Skin Sens. 1                     | Skin Sensitisation, Category 1                 |
| 3.4.2/1B | Skin Sens. 1B                    | Skin Sensitisation, Category 1B                |
| 4.1/C2   | Aquatic Chronic 2                | Chronic (long term) aquatic hazard, category 2 |

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

| Classification according to Regulation (EC) Nr. 1272/2008 | Classification procedure |
|---|--------------------------|
| Skin Irrit. 2, H315                                       | Calculation method       |
| Eye Irrit. 2, H319  | Calculation method       |
| Skin Sens. 1B, H317                                       | Calculation method       |
| Aquatic Chronic 2, H411                                   | Calculation method       |

This document was prepared by a competent person who has received appropriate training.

#### Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

#### Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency  
 EINECS: European Inventory of Existing Commercial Chemical Substances.  
 ES: Exposure Scenario  
 GefStoffVO: Ordinance on Hazardous Substances, Germany.  
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.  
 IARC: International Agency for Research on Cancer  
 IATA: International Air Transport Association.  
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
 IC50: half maximal inhibitory concentration  
 ICAO: International Civil Aviation Organization.  
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).  
 IMDG: International Maritime Code for Dangerous Goods.  
 INCI: International Nomenclature of Cosmetic Ingredients.  
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care  
 KAFH: Keep Away From Heat  
 KSt: Explosion coefficient.  
 LC50: Lethal concentration, for 50 percent of test population.  
 LD50: Lethal dose, for 50 percent of test population.  
 LDLo: Leathal Dose Low  
 N.A.: Not Applicable  
 N/A: Not Applicable  
 N/D: Not defined/ Not available  
 NA: Not available  
 NIOSH: National Institute for Occupational Safety and Health  
 NOAEL: No Observed Adverse Effect Level  
 OSHA: Occupational Safety and Health Administration  
 PBT: Persistent, Bioaccumulative and Toxic  
 PGK: Packaging Instruction  
 PNEC: Predicted No Effect Concentration.  
 PSG: Passengers  
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.  
 STEL: Short Term Exposure limit.  
 STOT: Specific Target Organ Toxicity.  
 TLV: Threshold Limiting Value.  
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).  
 vPvB: Very Persistent, Very Bioaccumulative.  
 WGK: German Water Hazard Class.

**Paragraphs modified from the previous revision:**

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 8: Exposure controls/personal protection
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information

# Exposure Scenario

## bis-[4-(2,3-epoxipropoxy)phenyl]propane

### Exposure Scenario, 07/06/2021

| Substance identity  |   |
|---------------------|---|
|                     | bis-[4-(2,3-epoxipropoxy)phenyl]propane |
| CAS No.             | 1675-54-3                               |
| INDEX No.           | 603-073-00-2                            |
| EINECS No.          | 216-823-5                               |
| Registration number | 01-2119456619-26                        |

### Table of contents

1. **ES 1** Widespread use by professional workers; ESC2\_0000001

|  |   |  |  |
|--|---|--|--|
| 1. ES 1  |   | Widespread use by professional workers; ESC2_0000001 |  |
| <b>1.1 TITLE SECTION</b>   |   |  |  |
| Exposure Scenario name   | Professional application of coatings and inks - Etching agent - Resins (prepolymers) - Adhesion promotor  |  |  |
| Date - Version   | 27/05/2021 - 1.0  |  |  |
| Life Cycle Stage   | Widespread use by professional workers  |  |  |
| Main user group  | Professional uses   |  |  |
| Sector(s) of use   | Professional uses (SU22)  |  |  |
| Product Categories   | ESC2_0000001  |  |  |
| Article Category(ies)  | Other articles made of stone, plaster, cement, glass or ceramic (AC4g)  |  |  |
| <b>Environment Contributing Scenario</b>   |   |  |  |
| CS1  | ERC8c - ERC8f   |  |  |
| <b>Worker Contributing Scenario</b>  |   |  |  |
| CS2 Material transfers   | PROC8a  |  |  |
| CS3 Rolling, Brushing  | PROC10  |  |  |
| CS4 Roller, spreader, flow application   | PROC11  |  |  |
| CS5 Mixing operations - Manual   | PROC19  |  |  |
| <b>1.2 Conditions of use affecting exposure</b>  |   |  |  |
| <b>1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)</b>  |   |  |  |
| Environmental release categories   | Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f) |  |  |
| <i>Product (article) characteristics</i>   |   |  |  |
| <b>Physical form of product:</b><br>Liquid, vapour pressure < 0,5 kPa at STP                                     |   |  |  |
| <b>Concentration of substance in product:</b><br>Covers percentage substance in the product up to 100 %.         |   |  |  |
| <i>Amount used, frequency and duration of use (or from service life)</i>   |   |  |  |
| <b>Amounts used:</b><br>Daily amount per site = 175 kg/day   |   |  |  |
| <b>Release type:</b> Continuous release  |   |  |  |
| <b>Emission days:</b> 365 days per year  |   |  |  |
| <i>Technical and organisational conditions and measures</i>  |   |  |  |
| <b>Control measures to prevent releases</b><br>Provide onsite wastewater removal efficiency of <sup>3</sup> (%): |   |  |  |
| <i>Conditions and measures related to sewage treatment plant</i>   |   |  |  |
| <b>STP type:</b><br>Municipal Sewage Treatment Plant   |   |  |  |
| <b>STP effluent (m<sup>3</sup>/day):</b> 2   |   |  |  |
| <i>Conditions and measures related to treatment of waste (including article waste)</i>                           |   |  |  |
| <b>Waste treatment</b><br>Dispose of waste cans and containers according to local regulations.                   |   |  |  |
| <i>Other conditions affecting environmental exposure</i>   |   |  |  |

**Local marine water dilution factor:** 100  
**Local freshwater dilution factor:** 10  
**Receiving surface water flow:** 18000 m<sup>3</sup>/day  
Covers indoor and outdoor use

## 1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

|                           |  |
|---------------------------|--|
| <b>Process Categories</b> | Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a) |
|---------------------------|--|

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Covers daily exposures up to 8 hours

### *Technical and organisational conditions and measures*

#### **Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 4 hours per day.

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

#### *Other conditions affecting worker exposure*

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

## 1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

|                           |   |
|---------------------------|---|
| <b>Process Categories</b> | Roller application or brushing (PROC10) |
|---------------------------|---|

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Covers daily exposures up to 8 hours

### *Technical and organisational conditions and measures*

#### **Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 4 hours per day.

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

#### *Other conditions affecting worker exposure*

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

## 1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

|                           |                                  |
|---------------------------|----------------------------------|
| <b>Process Categories</b> | Non industrial spraying (PROC11) |
|---------------------------|----------------------------------|

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

***Amount used, frequency and duration of use/exposure*****Duration:**

Covers daily exposures up to 8 hours

***Technical and organisational conditions and measures*****Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 4 hours per day.

***Conditions and measures related to personal protection, hygiene and health evaluation*****Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Wear suitable face shield.

Wear an impervious suit.

Wear a respirator conforming to EN140.

***Other conditions affecting worker exposure***

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

**1.2. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)****Process Categories**

Manual activities involving hand contact (PROC19)

***Product (article) characteristics*****Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

***Amount used, frequency and duration of use/exposure*****Duration:**

Covers daily exposures up to 8 hours

***Technical and organisational conditions and measures*****Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 1 hour per day.

***Conditions and measures related to personal protection, hygiene and health evaluation*****Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

***Other conditions affecting worker exposure***

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

**1.3 Exposure estimation and reference to its source****1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)**

| protection target   | Exposure level             | Calculation method | Risk Characterization Ratio (RCR) |
|---------------------|----------------------------|--------------------|-----------------------------------|
| freshwater          | = 0.0022 mg/L              | EUSES              | = 0.00022                         |
| marine sediment     | = 0.00127 mg/L             | EUSES              | = 0.0128                          |
| freshwater sediment | = 0.012 mg/L               | EUSES              | = 0.0369                          |
| marine water        | = 2.34E-05 mg/L            | EUSES              | = 0.029                           |
| soil                | = 0.00142 mg/kg dry weight | EUSES              | = 0.00722                         |

### 1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

| Exposure route, Health effect, Exposure indicator | Exposure level           | Calculation method     | Risk Characterization Ratio (RCR) |
|---|--------------------------|------------------------|-----------------------------------|
| inhalative, systemic, long-term                   | = 0.84 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | 0.07                              |
| dermal, systemic, long-term                       | = 0.2742 mg/kg bw/day    | ECETOC TRA worker v2.0 | = 0.03                            |

### 1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

| Exposure route, Health effect, Exposure indicator | Exposure level            | Calculation method     | Risk Characterization Ratio (RCR) |
|---|---------------------------|------------------------|-----------------------------------|
| inhalative, systemic, long-term                   | = 5E-07 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | < 0.001                           |
| dermal, systemic, long-term                       | = 2.743 mg/kg bw/day      | ECETOC TRA worker v2.0 | = 0.33                            |

### 1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

| Exposure route, Health effect, Exposure indicator | Exposure level           | Calculation method     | Risk Characterization Ratio (RCR) |
|---|--------------------------|------------------------|-----------------------------------|
| inhalative, systemic, long-term                   | = 0.36 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | 0.03                              |
| dermal, systemic, long-term                       | = 2.68 mg/kg bw/day      | ECETOC TRA worker v2.0 | = 0.32                            |

### 1.3. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)

| Exposure route, Health effect, Exposure indicator | Exposure level            | Calculation method     | Risk Characterization Ratio (RCR) |
|---|---------------------------|------------------------|-----------------------------------|
| inhalative, systemic, long-term                   | = 2E-07 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | < 0.001                           |
| dermal, systemic, long-term                       | = 1.414 mg/kg bw/day      | ECETOC TRA worker v3   | < 0.42                            |
| combined routes, systemic, long-term              | N/A                       | ECETOC TRA worker v3   | = 0.42                            |

## 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

### EP21 (B)

Date of first edition: 6/14/2021

Safety Data Sheet dated 06/10/2025

version 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Mixture identification:

Trade name: EP21 (B)

Trade code: S100B0172 42

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: hardener

Uses advised against: All uses other than recommended ones

### 1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

### 1.4. Emergency telephone number

European emergency phone number 112

Ireland Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Members of the public Number (8 am-10 pm): +353 (0)1 809 2166

Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

Malta In case of emergency call: +356 2395 2000 (24h)

## SECTION 2: Hazards identification



### 2.1. Classification of the substance or mixture

#### Regulation (EC) n. 1272/2008 (CLP)

|                   |  |
|-------------------|--|
| Acute Tox. 4      | Harmful if swallowed.  |
| Skin Corr. 1B     | Causes severe skin burns and eye damage.                           |
| Eye Dam. 1        | Causes serious eye damage.   |
| Skin Sens. 1A     | May cause an allergic skin reaction.                               |
| STOT RE 2         | May cause damage to organs through prolonged or repeated exposure. |
| Aquatic Acute 1   | Very toxic to aquatic life.  |
| Aquatic Chronic 2 | Toxic to aquatic life with long lasting effects.                   |

Adverse physicochemical, human health and environmental effects:

No other hazards

### 2.2. Label elements

#### Regulation (EC) No 1272/2008 (CLP):

#### Hazard pictograms and Signal Word



Danger

#### Hazard statements

|      |  |
|------|--|
| H302 | Harmful if swallowed.                    |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction.     |

H373 May cause damage to organs through prolonged or repeated exposure.  
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe vapours.  
P273 Avoid release to the environment.  
P280 Wear protective gloves and eye protection.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Contains

Cashew, nutshell liq.  
1,3-benzenedimethanamine, n-(2-phenylethyl) derivs.  
2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated  
M-phenylenebis(methylamine)  
FATTY ACIDS, C18 UNSAT., REACTION PRODUCTS WITH TETRAETHYLENEPENTAMINE  
3-aminopropyldiethylamine  
Ammine,polietilenpoli, frazionetetraetilenpentamminica  
amines, polyethylenepoly-; HEPA

Dir. 2004/42/EC (VOC directive)

Binding primers  
EU limit value for this product (cat. A/h): 750 g/l  
This product contains max 0 g/l VOC.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: EP21 (B)

Hazardous components within the meaning of the CLP regulation and related classification:

| Qty       | Name   | Ident. Numb.                     | Classification   | Registration Number |
|-----------|--|----------------------------------|--|---------------------|
| ≥20-<50 % | 2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated | CAS:1173092-74-4<br>EC:630-554-4 | Acute Tox. 4, H302; Skin Corr. 1C, H314; Eye Dam. 1, H318; Skin Sens. 1, H317; STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 2, H411 |                     |
| ≥10-<20 % | M-phenylenebis(methylamine)  | CAS:1477-55-0<br>EC:216-032-5    | Acute Tox. 4, H302; Acute Tox. 4, H332; Aquatic Chronic 3, H412; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1B, H314, EUH071             | 01-2119480150-50    |
| ≥10-<20 % | Cashew, nutshell liq.  | CAS:8007-24-7<br>EC:700-991-6    | Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1A,  | 01-2119502450-57    |

|           |   |  |  |                  |
|-----------|---|--|--|------------------|
| ≥10-<20 % | FATTY ACIDS, C18 UNSAT., REACTION PRODUCTS WITH TETRAETHYLENEMPENTAMINE | CAS:1226892-45-0<br>EC:629-725-6                     | Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317; Skin Corr. 1C, H314; Eye Dam. 1, H318, M-Chronic:1, M-Acute:10                     | 01-2119487006-38 |
| ≥3-<5 %   | 1,3-benzenedimethanamine, n-(2-phenylethyl) derivs.                     | CAS:404362-22-7<br>EC:445-790-1                      | Acute Tox. 4, H302; Skin Corr. 1B, H314; Eye Dam. 1, H318; Skin Sens. 1A, H317; STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410        | 01-0000018826-60 |
| ≥1-<3 %   | 2,4,6-tris(dimethylaminomethyl)phenol                                   | CAS:90-72-2<br>EC:202-013-9<br>Index:603-069-00-0    | Acute Tox. 4, H302; Skin Corr. 1C, H314; Eye Dam. 1, H318  | 01-2119560597-27 |
| ≥1-<3 %   | 3-aminopropyldiethylamine   | CAS:104-78-9<br>EC:203-236-4<br>Index:612-062-00-1   | Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 3, H311; Skin Corr. 1B, H314; Eye Dam. 1, H318; Skin Sens. 1, H317; Repr. 2, H361d; STOT SE 3, H335 |                  |
| ≥1-<3 %   | Ammine, polietilenpoli, frazionetetraetilenpentamminica                 | CAS:90640-66-7<br>EC:292-587-7                       | Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410      | 01-2119487290-37 |
| ≥1-<3 %   | amines, polyethylenepoly-; HEPA   | CAS:68131-73-7<br>EC:268-626-9<br>Index:612-121-00-1 | Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Acute Tox. 4, H312, M-Chronic:1                                  | 01-2119485823-28 |

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Remove contaminated clothing immediately and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Give nothing to eat or drink.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

### 4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO<sub>2</sub>).

Extinguishing media which must not be used for safety reasons:

- None in particular.

### 5.2. Special hazards arising from the substance or mixture

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.

### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

#### For emergency responders:

Wear personal protection equipment.

### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

### 6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

### 6.4. Reference to other sections

See also section 8 and 13

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

#### Advice on general occupational hygiene:

### 7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

### 7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

---

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Community Occupational Exposure Limits (OEL)

|   | OEL Type | Country | Occupational Exposure Limit   |
|---|----------|---------|---|
| M-phenylenebis(methylamine)<br>CAS: 1477-55-0 | ACGIH    |         | Short Term: Ceiling - 0.018 ppm<br>Skin - Eye, skin, and GI irr   |
|   | NATIONAL | BELGIUM | Short Term: 0.1 mg/m3<br>D, M<br>Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1 |
|   | NATIONAL | IRELAND | Long Term: 0.1 mg/m3<br>Source: 2021 Code of Practice   |
|   | NATIONAL | AUSTRIA | Long Term: 0.1 mg/m3; Short Term: Ceiling - 0.1 mg/m3<br>Mow, MAK<br>Source: GKV, BGBl. II Nr. 156/2021   |

|          |             |  |
|----------|-------------|--|
| NATIONAL | DENMARK     | Short Term: Ceiling - 0.1 mg/m <sup>3</sup> - 0.02 ppm<br>LH<br>Source: BEK nr 2203 af 29/11/2021            |
| NATIONAL | FINLAND     | Short Term: Ceiling - 0.1 mg/m <sup>3</sup><br>kattoarvo, iho<br>Source: HTP-ARVOT 2020                      |
| NATIONAL | FRANCE      | Short Term: 0.1 mg/m <sup>3</sup><br>Source: INRS outil65  |
| NATIONAL | NORWAY      | Short Term: Ceiling - 0.1 mg/m <sup>3</sup><br>T<br>Source: FOR-2021-06-28-2248                              |
| SUVA     | SWITZERLAND | Long Term: 0.1 mg/m <sup>3</sup><br>R/H, S, TGI Peau Yeux / GIT Haut Auge<br>Source: suva.ch/valeurs-limites |

#### Predicted No Effect Concentration (PNEC) values

M-phenylenebis  
(methylamine)  
CAS: 1477-55-0

Exposure Route: Fresh Water; PNEC Limit: 94 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 152 µg/l

Exposure Route: Marine water; PNEC Limit: 9.4 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 430 µg/kg

Exposure Route: Marine water sediments; PNEC Limit: 43 µg/kg

Exposure Route: Soil; PNEC Limit: 45 µg/kg

Cashew, nutshell liq.  
CAS: 8007-24-7

Exposure Route: Fresh Water; PNEC Limit: 0.003 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 0.088 mg/kg

Exposure Route: Freshwater sediments; PNEC Limit: 0.97 mg/kg

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.03 mg/l

Exposure Route: Soil; PNEC Limit: 6.71 mg/kg

1,3-benzenedimethanamine,  
n-(2-phenylethyl) derivs.  
CAS: 404362-22-7

Exposure Route: Fresh Water; PNEC Limit: 800 ng/L

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 1.5 µg/l

Exposure Route: Marine water; PNEC Limit: 80 ng/L

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 1 ng/L

Exposure Route: Freshwater sediments; PNEC Limit: 140 µg/kg

Exposure Route: Marine water sediments; PNEC Limit: 14 µg/kg

Exposure Route: Soil; PNEC Limit: 28 µg/kg

Exposure Route: Secondary poisoning; PNEC Limit: 167 µg/kg

2,4,6-tris  
(dimethylaminomethyl)  
phenol  
CAS: 90-72-2

Exposure Route: Fresh Water; PNEC Limit: 84 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 840 µg/l

Exposure Route: Marine water; PNEC Limit: 8.4 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 200 µg/l

3-aminopropyldiethylamine  
CAS: 104-78-9

Exposure Route: Fresh Water; PNEC Limit: 30 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 300 µg/l

Exposure Route: Marine water; PNEC Limit: 3 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 418.2 µg/kg

Exposure Route: Marine water sediments; PNEC Limit: 41.8 µg/kg

Exposure Route: Soil; PNEC Limit: 66 µg/kg

Exposure Route: Fresh Water; PNEC Limit: 1.6 µg/l

amines,  
polyethylenepoly-; HEPA  
CAS: 68131-73-7

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 16 µg/l

Exposure Route: Marine water; PNEC Limit: 1.6 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 3.19 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0.14 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0.14 mg/kg

Exposure Route: Soil; PNEC Limit: 10 mg/kg

#### Derived No Effect Level (DNEL) values

M-  
phenylenebis  
(methylamine)  
CAS: 1477-55-0

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 1.2 mg/m<sup>3</sup>

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects  
Worker Professional: 200 µg/m<sup>3</sup>

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 330 µg/kg

Cashew, nutshell liq.  
CAS: 8007-24-7

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects  
Worker Professional: 0.5 mg/kg; Consumer: 0.25 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects  
Worker Professional: 0.88 mg/m<sup>3</sup>; Consumer: 0.2 mg/m<sup>3</sup>

Exposure Route: Human Oral; Exposure Frequency: Long Term, local effects  
Consumer: 0.25 mg/kg

1,3-  
benzenedimethanamine,  
n-(2-phenylethyl) derivs.  
CAS: 404362-22-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 180 µg/m<sup>3</sup>; Consumer: 40 µg/m<sup>3</sup>

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects  
Worker Professional: 4 µg/m<sup>3</sup>; Consumer: 2 µg/m<sup>3</sup>

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 50 µg/kg; Consumer: 30 µg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects  
Consumer: 30 µg/kg

3-  
aminopropyldiethylamine  
CAS: 104-78-9

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 24.7 mg/m<sup>3</sup>; Consumer: 1.8 mg/m<sup>3</sup>

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 3.5 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects  
Consumer: 500 µg/l

amines,  
polyethylenepoly-; HEPA  
CAS: 68131-73-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 1.59 mg/m<sup>3</sup>; Consumer: 0.46 mg/m<sup>3</sup>

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects  
Worker Professional: 8550 mg/m<sup>3</sup>; Consumer: 2542 mg/m<sup>3</sup>

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects  
Consumer: 0.65 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects  
Consumer: 32 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects  
Worker Professional: 0.91 mg/m<sup>3</sup>; Consumer: 0.4 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects  
Worker Professional: 0.044 mg/cm<sup>2</sup>; Consumer: 0.68 mg/cm<sup>2</sup>

## 8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing. Safety shoes.

Protection for hands:

Protection for hands:

Suitable materials for safety gloves; EN 374:

Nitrile rubber - NBR: thickness  $\geq 0,35\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

Not expected if used as intended

Environmental exposure controls:

Prevent the product from entering sewers or surface and underground water.

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: Brown

Odour: Odourless

Odour threshold: N.A.

pH: Not Relevant Notes: non determinabile

Kinematic viscosity: N.A.

Melting point/freezing point: N.A. Notes: non determinabile

Boiling point or initial boiling point and boiling range:  $> 200\text{ }^{\circ}\text{C}$  (392  $^{\circ}\text{F}$ )

Flash point:  $93\text{ }^{\circ}\text{C}$  (199  $^{\circ}\text{F}$ )

Lower and upper explosion limit: N.A.

Relative vapour density: N.A.

Vapour pressure: N.A.

Density and/or relative density:  $1.00\text{ g/cm}^3$

Solubility in water: Insoluble

Solubility in oil: N.A.

Partition coefficient n-octanol/water (log value): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: N.A.

Volatile Organic compounds - VOCs = 0 % ; 0 g/l

#### Particle characteristics:

Particle size: N.A.

### 9.2. Other information

Viscosity: 0.46 PA-s

No other relevant information

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions

### 10.2. Chemical stability

Data not available.

### 10.3. Possibility of hazardous reactions

None.

### 10.4. Conditions to avoid

Stable under normal conditions.

### 10.5. Incompatible materials

None in particular.

### 10.6. Hazardous decomposition products

None.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicological Information of the Preparation

|                                      |  |
|--------------------------------------|--|
| a) acute toxicity                    | The product is classified: Acute Tox. 4(H302)                    |
| b) skin corrosion/irritation         | The product is classified: Skin Corr. 1B(H314)                   |
| c) serious eye damage/irritation     | The product is classified: Eye Dam. 1(H318)                      |
| d) respiratory or skin sensitisation | The product is classified: Skin Sens. 1A(H317)                   |
| e) germ cell mutagenicity            | Not classified   |
|                                      | Based on available data, the classification criteria are not met |
| f) carcinogenicity                   | Not classified   |
|                                      | Based on available data, the classification criteria are not met |
| g) reproductive toxicity             | Not classified   |
|                                      | Based on available data, the classification criteria are not met |
| h) STOT-single exposure              | Not classified   |
|                                      | Based on available data, the classification criteria are not met |
| i) STOT-repeated exposure            | The product is classified: STOT RE 2(H373)                       |
| j) aspiration hazard                 | Not classified   |
|                                      | Based on available data, the classification criteria are not met |

#### Toxicological information on main components of the mixture:

|  |                                      |   |                    |
|--|--------------------------------------|---|--------------------|
| 2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated | a) acute toxicity                    | LD50 Oral = 500 mg/kg                         |                    |
| M-phenylenebis (methyamine)  | a) acute toxicity                    | LD50 Oral Rat = 1001 mg/kg                    |                    |
|  |                                      | LC50 Inhalation Mist Rat = 1.34 mg/l 4h       |                    |
|  |                                      | LD50 Skin Rat > 3100 mg/kg                    |                    |
|  | b) skin corrosion/irritation         | Skin Irritant Rat Positive 4h                 |                    |
|  | d) respiratory or skin sensitisation | Skin Sensitization Positive                   | Mouse              |
|  | f) carcinogenicity                   | Genotoxicity Negative                         | Mouse              |
|  | g) reproductive toxicity             | No Observed Effect Level Oral Rat = 450 mg/kg |                    |
| Cashew, nutshell liq.  | a) acute toxicity                    | LD50 Oral Rat = 2000 mg/kg                    |                    |
|  |                                      | LD50 Skin Rat > 2000 mg/kg 24h                |                    |
|  | b) skin corrosion/irritation         | Skin Irritant Rabbit Positive                 |                    |
|  | c) serious eye damage/irritation     | Eye Irritant Rabbit Yes                       |                    |
|  | d) respiratory or skin sensitisation | Skin Sensitization Positive                   | Mouse              |
| FATTY ACIDS, C18 UNSAT., REACTION PRODUCTS WITH TETRAETHYLENEPENTAMINE   | a) acute toxicity                    | LD50 Oral Rat > 2000 mg/kg bw                 |                    |
| 1,3-benzenedimethanamine, n-(2-phenylethyl) derivs.  | a) acute toxicity                    | LD50 Oral Rat > 500 mg/kg                     | 500 and 2000 mg/kg |
|  | b) skin corrosion/irritation         | Skin Corrosive Rabbit Positive                |                    |

|   |                                      |  |                            |
|---|--------------------------------------|--|----------------------------|
| 2,4,6-tris<br>(dimethylaminomethyl)<br>phenol | d) respiratory or skin sensitisation | Skin Sensitization Positive                  | Mouse                      |
|   | g) reproductive toxicity             | No Observed Effect Level Oral Rat = 15 mg/kg |                            |
|   | a) acute toxicity                    | LD50 Oral Rat = 2169 mg/kg                   |                            |
|   |                                      | LD50 Skin Rat > 1 ml/Kg 6h                   |                            |
|   | b) skin corrosion/irritation         | Skin Corrosive Rabbit Positive 4h            |                            |
|   | c) serious eye damage/irritation     | Eye Irritant Rabbit Yes                      |                            |
| 3-aminopropyldiethylamine                     | d) respiratory or skin sensitisation | Skin Sensitization Guineapig Negative        |                            |
|   | g) reproductive toxicity             | No Observed Effect Level Oral Rat = 15 mg/kg |                            |
|   | a) acute toxicity                    | LD50 Oral Rat = 830 mg/kg                    |                            |
|   |                                      | LC50 Inhalation Vapour Rat Negative 4h       | No mortality               |
|   |                                      | LD50 Skin Rabbit = 524 mg/kg 24h             |                            |
|   | b) skin corrosion/irritation         | Skin Corrosive Rabbit Positive               |                            |
| amines,<br>polyethylenepoly-; HEPA            | d) respiratory or skin sensitisation | Skin Sensitization Guineapig Negative        |                            |
|   | a) acute toxicity                    | LD50 Oral Rat = 1716.2 mg/kg                 |                            |
|   |                                      | LD50 Skin Rabbit = 1465.4 mg/kg 24h          |                            |
|   | b) skin corrosion/irritation         | Skin Corrosive Rabbit Positive               |                            |
|   | c) serious eye damage/irritation     | Eye Irritant Rabbit Yes                      |                            |
|   | d) respiratory or skin sensitisation | Skin Sensitization Guineapig Positive        |                            |
|   | f) carcinogenicity                   | Genotoxicity Negative                        | Mouse intraperitoneal rout |

## 11.2. Information on other hazards

### Endocrine disrupting properties:

No endocrine disruptor substances present in concentration  $\geq 0.1\%$

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Very toxic to aquatic organisms.

Toxic to aquatic life with long lasting effects.

#### List of Eco-Toxicological properties of the product

The product is classified: Aquatic Acute 1(H400), Aquatic Chronic 2(H411)

#### List of Eco-Toxicological properties of the components

| Component                   | Ident. Numb.                          | Ecotox Data   |
|-----------------------------|---------------------------------------|---|
| M-phenylenebis(methylamine) | CAS: 1477-55-0<br>- EINECS: 216-032-5 | a) Aquatic acute toxicity : LC50 Fish <i>Oryzias latipes</i> = 87.6 mg/L 96h OECD 203 |
|                             |                                       | a) Aquatic acute toxicity : EC50 <i>Daphnia magna</i> = 15.2 mg/L 48h OECD 202        |
|                             |                                       | b) Aquatic chronic toxicity : NOEC <i>Daphnia magna</i> = 4.7 mg/L OECD 211 - 21days  |

|   |   |  |
|---|---|--|
|   |   | a) Aquatic acute toxicity : EC50 Algae <i>Selenastrum capricornutum</i> = 32.1 mg/L 72h OECD 201   |
|   |   | a) Aquatic acute toxicity : EC50 Sludge activated sludge > 1000 mg/L OECD 209  |
| Cashew, nutshell liq.                               | CAS: 8007-24-7<br>- EINECS: 700-991-6                     | a) Aquatic acute toxicity : LC50 Fish <i>Cyprinodon variegatus</i> = 1000 mg/L 96h „OECD Guideline 203 (Fish, Acute Toxicity Test)   |
|   |   | a) Aquatic acute toxicity : LC50 Daphnia <i>Daphnia magna</i> = 40.46 mg/L 48h „EPA OPPTS 850.1010 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)                 |
|   |   | a) Aquatic acute toxicity : EC50 Algae <i>Pseudokirchneriella subcapitata</i> = 1300 mg/L 72h „OECD Guideline 201 (Alga, Growth Inhibition Test)                                   |
|   |   | a) Aquatic acute toxicity : NOEC Sludge activated sludge = 100 mg/L  |
| 1,3-benzenedimethanamine, n-(2-phenylethyl) derivs. | CAS: 404362-22-7 - EINECS: 445-790-1                      | a) Aquatic acute toxicity : LL50 Fish <i>Oncorhynchus mykiss</i> = 4 mg/L 96h OECD TG 203  |
|   |   | a) Aquatic acute toxicity : EL50 Daphnia <i>Daphnia magna</i> = 3.4 mg/L 48h OECD TG 202   |
|   |   | b) Aquatic chronic toxicity : NOEC Daphnia <i>Daphnia magna</i> = 0.14 mg/L OECD TG 211 - 21days   |
|   |   | a) Aquatic acute toxicity : NOELR Algae <i>Scenedesmus subspicatus</i> = 0.04 mg/L 72h OECD TG 201   |
|   |   | a) Aquatic acute toxicity : NOEC Sludge activated sewage sludge = 10 mg/L 3h OECD TG 209   |
| 2,4,6-tris(dimethylaminomethyl)phenol               | CAS: 90-72-2 - EINECS: 202-013-9 - INDEX: 603-069-00-0    | a) Aquatic acute toxicity : LC50 Fish <i>Cyprinus carpio</i> = 175 mg/L 96h  |
|   |   | a) Aquatic acute toxicity : LC50 <i>Salmo gairdneri</i> < 240 mg/L 96h   |
|   |   | a) Aquatic acute toxicity : LC50 Daphnia <i>Palemonetes vulgaris</i> = 718 mg/L 96h  |
|   |   | a) Aquatic acute toxicity : EC50 Algae freshwater algae = 84 mg/L  |
| 3-aminopropyldiethylamine                           | CAS: 104-78-9 - EINECS: 203-236-4 - INDEX: 612-062-00-1   | a) Aquatic acute toxicity : LC50 Fish <i>Leuciscus idus</i> = 146.6 mg/L 96h DIN 38412 part 15   |
|   |   | a) Aquatic acute toxicity : LC50 Daphnia <i>Daphnia magna</i> = 30.16 mg/L 48h „EU Directive 79/831/EEC, Annex V, part C   |
|   |   | a) Aquatic acute toxicity : EC50 Algae <i>Pseudokirchneriella subcapitata</i> = 34 mg/L 72h  |
|   |   | c) Bacteria toxicity : EC50 <i>Pseudomonas putida</i> = 100.5 mg/L „DIN 38412, part 8  |
| amines, polyethylenepoly-; HEPA                     | CAS: 68131-73-7 - EINECS: 268-626-9 - INDEX: 612-121-00-1 | a) Aquatic acute toxicity : LC50 Fish <i>Poecilia reticulata</i> = 100 mg/L 96h EU Method C.1 (Acute Toxicity for Fish)  |
|   |   | a) Aquatic acute toxicity : EC50 Daphnia <i>Daphnia magna</i> = 2.2 mg/L 48h EU Method C.2 (Acute Toxicity for Daphnia)  |
|   |   | a) Aquatic acute toxicity : EC50 Algae <i>Selenastrum capricornutum</i> = 0.23 mg/L 72h OECD TG 201  |
|   |   | c) Bacteria toxicity : EC50 nitrifying bacteria = 319.3 mg/L - 2h  |
|   |   | d) Terrestrial toxicity : NOEC Worm <i>Eisenia fetida</i> = 1000 mg/kg OECD Guideline 222 (Earthworm Reproduction Test ( <i>Eisenia fetida</i> / <i>Eisenia andrei</i> )) - 56days |

## 12.2. Persistence and degradability

| Component | Persistence/Degradability: | Test            | Value    | Notes:           |
|-----------|----------------------------|-----------------|----------|------------------|
| Date      | 06/10/2025                 | Production Name | EP21 (B) | Page n. 10 of 15 |

|   |                           |                    |                           |
|---|---------------------------|--------------------|---------------------------|
| M-phenylenebis(methylamine)                         | Non-readily biodegradable | Oxygen consumption | OECD 301B                 |
| Cashew, nutshell liq.                               | Readily biodegradable     | Oxygen consumption | 83.800 %; EU Method C.4-D |
| 1,3-benzenedimethanamine, n-(2-phenylethyl) derivs. | Non-readily biodegradable | Oxygen consumption | OECD TG 301C              |
| 2,4,6-tris(dimethylaminomethyl)phenol               | Non-readily biodegradable |                    |                           |
| 3-aminopropyl-diethylamine                          | Readily biodegradable     |                    | OECD Guideline 301A       |
| amines, polyethylenepoly-; HEPA                     | Non-readily biodegradable | Oxygen consumption | OECD 301D                 |

### 12.3. Bioaccumulative potential

| Component                   | Bioaccumulation     | Test                          | Notes:  |
|-----------------------------|---------------------|-------------------------------|---|
| M-phenylenebis(methylamine) | Not bioaccumulative | BCF - Bioconcentration factor | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |

### 12.4. Mobility in soil

N.A.

### 12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration  $\geq 0.1\%$

### 12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration  $\geq 0.1\%$

### 12.7. Other adverse effects

N.A.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as hazardous waste

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

### Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

N.A.

## SECTION 14: Transport information

### 14.1. UN number or ID number

2735

### 14.2. UN proper shipping name

ADR-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated - M-phenylenebis(methylamine))

IATA-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated - M-phenylenebis(methylamine))

IMDG-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (2-propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated - M-phenylenebis(methylamine))

### 14.3. Transport hazard class(es)

ADR-Class: 8

IATA-Class: 8

IMDG-Class: 8

### 14.4. Packing group

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

### 14.5. Environmental hazards

Most important toxic component: FATTY ACIDS, C18 UNSAT., REACTION PRODUCTS WITH TETRAETHYLENEPENTAMINE

Marine pollutant: Yes

Environmental Pollutant: Yes

IMDG-EMS: F-A, S-B

14.6. Special precautions for user

Road and Rail (ADR-RID):

- ADR-Label: 8
- ADR - Hazard identification number: 80
- ADR-Special Provisions: 274
- ADR-Transport category (Tunnel restriction code): 2 (E)
- ADR Limited Quantities: 1 L
- ADR Excepted Quantities: E2

Air (IATA):

- IATA-Passenger Aircraft: 851
- IATA-Cargo Aircraft: 855
- IATA-Label: 8
- IATA-Subsidiary hazards: -
- IATA-Erg: 8L
- IATA-Special Provisions: A3 A803

Sea (IMDG):

- IMDG-Stowage and handling: Category A
- IMDG-Segregation: SG35 SGG18
- IMDG-Subsidiary hazards: -
- IMDG-Special Provisions: 274

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2023/707

Regulation (EU) n. 2023/1434 (ATP 19 CLP)

Regulation (EU) n. 2023/1435 (ATP 20 CLP)

Regulation (EU) n. 2024/197 (ATP 21 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 40, 75

Provisions related to directive EU 2012/18 (Seveso III):

| Seveso III category according to Annex 1, part 1 | Lower-tier threshold (tonnes) | Upper-tier threshold (tonnes) |
|--|-------------------------------|-------------------------------|
| Product belongs to category: E1                  | 100                           | 200                           |

**Explosives precursors – Regulation 2019/1148**

No substances listed

**Regulation (EU) No 649/2012 (PIC regulation)**

No substances listed

**German Water Hazard Class.**

3: Severe hazard to waters

**German Lagerklasse according to TRGS 510:**

LGK 8A

SVHC Substances:

No SVHC substances present in concentration  $\geq 0.1\%$ **Dir. 2004/42/EC (VOC directive)**

(ready to use)

Volatile Organic compounds - VOCs = 0.00 %

Volatile Organic compounds - VOCs = 0.00 g/L

EP21 (B) (not ready to use)

Volatile Organic compounds - VOCs = 0.00 %

Volatile Organic compounds - VOCs = 0.00 g/L

**15.2. Chemical safety assessment**

A Chemical Safety Assessment has been carried out for the mixture.

**Substances for which a Chemical Safety Assessment has been carried out:**

Cashew, nutshell liq.

2,4,6-tris(dimethylaminomethyl)phenol

amines, polyethylenepoly-; HEPA

**SECTION 16: Other information**

| Code   | Description  |
|--------|--|
| EUH071 | Corrosive to the respiratory tract.                                |
| H226   | Flammable liquid and vapour.                                       |
| H302   | Harmful if swallowed.  |
| H311   | Toxic in contact with skin.  |
| H312   | Harmful in contact with skin.                                      |
| H314   | Causes severe skin burns and eye damage.                           |
| H315   | Causes skin irritation.  |
| H317   | May cause an allergic skin reaction.                               |
| H318   | Causes serious eye damage.   |
| H332   | Harmful if inhaled.  |
| H335   | May cause respiratory irritation.                                  |
| H361d  | Suspected of damaging the unborn child.                            |
| H373   | May cause damage to organs through prolonged or repeated exposure. |
| H400   | Very toxic to aquatic life.  |
| H410   | Very toxic to aquatic life with long lasting effects.              |
| H411   | Toxic to aquatic life with long lasting effects.                   |
| H412   | Harmful to aquatic life with long lasting effects.                 |

| Code         | Hazard class and hazard category | Description                             |
|--------------|----------------------------------|---|
| 2.6/3        | Flam. Liq. 3                     | Flammable liquid, Category 3            |
| 3.1/3/Dermal | Acute Tox. 3                     | Acute toxicity (dermal), Category 3     |
| 3.1/4/Dermal | Acute Tox. 4                     | Acute toxicity (dermal), Category 4     |
| 3.1/4/Inhal  | Acute Tox. 4                     | Acute toxicity (inhalation), Category 4 |
| 3.1/4/Oral   | Acute Tox. 4                     | Acute toxicity (oral), Category 4       |
| 3.2/1B       | Skin Corr. 1B                    | Skin corrosion, Category 1B             |
| 3.2/1C       | Skin Corr. 1C                    | Skin corrosion, Category 1C             |
| 3.2/2        | Skin Irrit. 2                    | Skin irritation, Category 2             |
| 3.3/1        | Eye Dam. 1                       | Serious eye damage, Category 1          |

|          |                   |  |
|----------|-------------------|--|
| 3.4.2/1  | Skin Sens. 1      | Skin Sensitisation, Category 1                                 |
| 3.4.2/1A | Skin Sens. 1A     | Skin Sensitisation, Category 1A                                |
| 3.7/2    | Repr. 2           | Reproductive toxicity, Category 2                              |
| 3.8/3    | STOT SE 3         | Specific target organ toxicity — single exposure, Category 3   |
| 3.9/2    | STOT RE 2         | Specific target organ toxicity — repeated exposure, Category 2 |
| 4.1/A1   | Aquatic Acute 1   | Acute aquatic hazard, category 1                               |
| 4.1/C1   | Aquatic Chronic 1 | Chronic (long term) aquatic hazard, category 1                 |
| 4.1/C2   | Aquatic Chronic 2 | Chronic (long term) aquatic hazard, category 2                 |
| 4.1/C3   | Aquatic Chronic 3 | Chronic (long term) aquatic hazard, category 3                 |

**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:**

**Classification according to Regulation (EC) Nr. 1272/2008      Classification procedure**

|                         |                    |
|-------------------------|--------------------|
| Acute Tox. 4, H302      | Calculation method |
| Skin Corr. 1B, H314     | Calculation method |
| Eye Dam. 1, H318        | Calculation method |
| Skin Sens. 1A, H317     | Calculation method |
| STOT RE 2, H373         | Calculation method |
| Aquatic Acute 1, H400   | Calculation method |
| Aquatic Chronic 2, H411 | Calculation method |

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration  
ICAO: International Civil Aviation Organization.  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).  
IMDG: International Maritime Code for Dangerous Goods.  
INCI: International Nomenclature of Cosmetic Ingredients.  
IRCCS: Scientific Institute for Research, Hospitalization and Health Care  
KAFH: Keep Away From Heat  
KSt: Explosion coefficient.  
LC50: Lethal concentration, for 50 percent of test population.  
LD50: Lethal dose, for 50 percent of test population.  
LDLo: Leathal Dose Low  
N.A.: Not Applicable  
N/A: Not Applicable  
N/D: Not defined/ Not available  
NA: Not available  
NIOSH: National Institute for Occupational Safety and Health  
NOAEL: No Observed Adverse Effect Level  
OSHA: Occupational Safety and Health Administration  
PBT: Persistent, Bioaccumulative and Toxic  
PGK: Packaging Instruction  
PNEC: Predicted No Effect Concentration.  
PSG: Passengers  
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.  
STEL: Short Term Exposure limit.  
STOT: Specific Target Organ Toxicity.  
TLV: Threshold Limiting Value.  
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).  
vPvB: Very Persistent, Very Bioaccumulative.  
WGK: German Water Hazard Class.

**Paragraphs modified from the previous revision:**

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 14: Transport information
- SECTION 16: Other information

# Exposure Scenario

## Amines, polyethylenepoly-; hepa

### Exposure Scenario, 10/08/2021

| Substance identity  |                                 |
|---------------------|---------------------------------|
|                     | Amines, polyethylenepoly-; hepa |
| CAS No.             | 68131-73-7                      |
| INDEX No.           | 612-121-00-1                    |
| EINECS No.          | 268-626-9                       |
| Registration number | 01-2119485823-28                |

### Table of contents

1. **ES 1** Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a)
2. **ES 2** Widespread use by professional workers; Adhesives, sealants (PC1)

|   |   |  |  |
|---|---|--|--|
| 1. ES 1   |   | Widespread use by professional workers; Coatings and paints, thinners, paint removers (PC9a) |  |
| <b>1.1 TITLE SECTION</b>  |   |  |  |
| Exposure Scenario name  | Professional application of coatings and inks   |  |  |
| Date - Version  | 10/08/2021 - 1.0  |  |  |
| Life Cycle Stage  | Widespread use by professional workers  |  |  |
| Main user group   | Professional uses   |  |  |
| Sector(s) of use  | Professional uses (SU22)  |  |  |
| Product Categories  | Coatings and paints, thinners, paint removers (PC9a)  |  |  |
| <b>Environment Contributing Scenario</b>  |   |  |  |
| CS1   | ERC8c - ERC8f   |  |  |
| <b>Worker Contributing Scenario</b>   |   |  |  |
| CS2 Material transfers  | PROC8a  |  |  |
| CS3 Rolling, Brushing   | PROC10  |  |  |
| CS4 Roller, spreader, flow application  | PROC11  |  |  |
| CS5 Handling and dilution of concentrates   | PROC19  |  |  |
| <b>1.2 Conditions of use affecting exposure</b>                                   |   |  |  |
| <b>1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)</b>                 |   |  |  |
| Environmental release categories  | Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f) |  |  |
| <i>Product (article) characteristics</i>  |   |  |  |
| <b>Physical form of product:</b><br>Liquid, vapour pressure < 0,5 kPa at STP      |   |  |  |
| <b>Concentration of substance in product:</b><br>Covers concentrations up to 25 % |   |  |  |
| <i>Amount used, frequency and duration of use (or from service life)</i>          |   |  |  |
| <b>Amounts used:</b><br>Daily amount per site = 2114 kg/day                       |   |  |  |
| <b>Release type:</b> Continuous release   |   |  |  |
| <b>Emission days:</b> 220 days per year   |   |  |  |
| <i>Other conditions affecting environmental exposure</i>                          |   |  |  |
| <b>Local freshwater dilution factor:</b> 10                                       |   |  |  |
| <b>1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)</b>        |   |  |  |
| Process Categories  | Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)  |  |  |
| <i>Product (article) characteristics</i>  |   |  |  |
| <b>Physical form of product:</b><br>Liquid, vapour pressure < 0,5 kPa at STP      |   |  |  |
| <b>Concentration of substance in product:</b><br>Covers concentrations up to 25 % |   |  |  |
| <i>Amount used, frequency and duration of use/exposure</i>                        |   |  |  |

**Duration:**

Covers use up to &gt; 15 min

***Conditions and measures related to personal protection, hygiene and health evaluation*****Personal protection**

Wear suitable respiratory protection.  
Wear suitable gloves tested to EN374.

Inhalation - minimum efficiency of: 95 %

**1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)****Process Categories**

Roller application or brushing (PROC10)

***Product (article) characteristics*****Physical form of product:**

Liquid, vapour pressure &lt; 0,5 kPa at STP

**Concentration of substance in product:**

Covers concentrations up to 15 %

***Amount used, frequency and duration of use/exposure*****Duration:**

Covers use up to 60 min

***Technical and organisational conditions and measures*****Technical and organisational measures**

Provide extract ventilation to points where emissions occur.

Inhalation - minimum efficiency of: 90 %

***Conditions and measures related to personal protection, hygiene and health evaluation*****Personal protection**

Wear suitable gloves tested to EN374.

**1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)****Process Categories**

Non industrial spraying (PROC11)

***Product (article) characteristics*****Physical form of product:**

Liquid, vapour pressure &lt; 0,5 kPa at STP

**Concentration of substance in product:**

Covers concentrations up to 15 %

***Amount used, frequency and duration of use/exposure*****Duration:**

Covers use up to 60 min

***Technical and organisational conditions and measures*****Technical and organisational measures**

Provide extract ventilation to points where emissions occur.

Inhalation - minimum efficiency of: 90 %

***Conditions and measures related to personal protection, hygiene and health evaluation*****Personal protection**

Wear suitable gloves tested to EN374.

**1.2. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)**

|   |   |
|---|---|
| <b>Process Categories</b>   | Manual activities involving hand contact (PROC19) |
| <b><i>Product (article) characteristics</i></b>   |   |
| <b>Physical form of product:</b><br>Liquid, vapour pressure < 0,5 kPa at STP                        |   |
| <b>Concentration of substance in product:</b><br>Covers concentrations up to 5 %                    |   |
| <b><i>Amount used, frequency and duration of use/exposure</i></b>                                   |   |
| <b>Duration:</b><br>Covers use up to 8 h  |   |
| <b><i>Conditions and measures related to personal protection, hygiene and health evaluation</i></b> |   |
| <b>Personal protection</b><br>Wear suitable gloves tested to EN374.                                 |   |

## 1.3 Exposure estimation and reference to its source

### 1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

| protection target   | Exposure level           | Calculation method | Risk Characterization Ratio (RCR) |
|---------------------|--------------------------|--------------------|-----------------------------------|
| freshwater          | 7.92E-05 mg/L            | EUSES              | 0.05                              |
| marine water        | 7.9E-06 mg/L             | EUSES              | 0.005                             |
| freshwater sediment | 0.0795 mg/kg dry weight  | EUSES              | 0.568                             |
| marine sediment     | 0.00792 mg/kg dry weight | EUSES              | 0.057                             |
| soil                | 0.0118 mg/kg dry weight  | EUSES              | 0.001                             |

### 1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

| Exposure route, Health effect, Exposure indicator | Exposure level          | Calculation method     | Risk Characterization Ratio (RCR) |
|---|-------------------------|------------------------|-----------------------------------|
| dermal, systemic, long-term                       | 0.068 mg/kg bw/day      | ECETOC TRA worker v2.0 | 0.12                              |
| inhalative, systemic, long-term                   | 0.456 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | 0.457                             |
| combined routes                                   | N/A                     | N/A                    | 0.577                             |
| inhalative, local, short-term                     | 0.913 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | < 0.001                           |

### 1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

| Exposure route, Health effect, Exposure indicator | Exposure level          | Calculation method     | Risk Characterization Ratio (RCR) |
|---|-------------------------|------------------------|-----------------------------------|
| dermal, systemic, long-term                       | 0.082 mg/kg bw/day      | ECETOC TRA worker v2.0 | 0.144                             |
| inhalative, systemic, long-term                   | 0.457 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | 0.229                             |
| combined routes                                   | N/A                     | N/A                    | 0.373                             |
| inhalative, local, short-term                     | 0.914 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | < 0.001                           |

### 1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

| Exposure route, Health effect, Exposure indicator | Exposure level          | Calculation method     | Risk Characterization Ratio (RCR) |
|---|-------------------------|------------------------|-----------------------------------|
| dermal, systemic, long-term                       | 0.214 mg/kg bw/day      | ECETOC TRA worker v2.0 | 0.376                             |
| inhalative, systemic, long-term                   | 0.121 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | 0.122                             |
| combined routes                                   | N/A                     | N/A                    | 0.498                             |
| inhalative, local, short-term                     | 0.243 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | < 0.001                           |

### 1.3. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

| Exposure route, Health effect, Exposure indicator | Exposure level         | Calculation method     | Risk Characterization Ratio (RCR) |
|---|------------------------|------------------------|-----------------------------------|
| dermal, systemic, long-term                       | 0.14 mg/kg bw/day      | ECETOC TRA worker v2.0 | 0.248                             |
| inhalative, systemic, long-term                   | 0.76 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | 0.076                             |
| combined routes                                   | N/A                    | N/A                    | 0.324                             |
| inhalative, local, short-term                     | 1.52 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | < 0.001                           |

## 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 2. ES 2

## Widespread use by professional workers; Adhesives, sealants (PC1)

## 2.1 TITLE SECTION

|                        |  |
|------------------------|--|
| Exposure Scenario name | Use in rigid foams, coatings, adhesives and sealants |
| Date - Version         | 10/08/2021 - 1.0                                     |
| Life Cycle Stage       | Widespread use by professional workers               |
| Main user group        | Professional uses                                    |
| Sector(s) of use       | Professional uses (SU22)                             |
| Product Categories     | Adhesives, sealants (PC1)                            |

## Environment Contributing Scenario

|     |               |
|-----|---------------|
| CS1 | ERC8a - ERC8d |
|-----|---------------|

## Worker Contributing Scenario

|   |        |
|---|--------|
| CS2 Material transfers                    | PROC8a |
| CS3 Rolling, Brushing                     | PROC10 |
| CS4 Roller, spreader, flow application    | PROC11 |
| CS5 Handling and dilution of concentrates | PROC19 |

## 2.2 Conditions of use affecting exposure

## 2.2. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

|                                  |  |
|----------------------------------|--|
| Environmental release categories | Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) -<br>Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d) |
|----------------------------------|--|

*Product (article) characteristics***Physical form of product:**

Liquid, vapour pressure &lt; 0,5 kPa at STP

**Concentration of substance in product:**

Covers concentrations up to 25 %

*Amount used, frequency and duration of use (or from service life)***Amounts used:**

Daily amount per site = 15500 kg/day

**Release type:** Continuous release**Emission days:** 300 days per year*Technical and organisational conditions and measures***Control measures to prevent releases**

|  |                                       |
|--|---------------------------------------|
| Pre-treatment of waste water by neutralization | Water - minimum efficiency of: 53.1 % |
|--|---------------------------------------|

*Conditions and measures related to sewage treatment plant***STP type:**

Municipal Sewage Treatment Plant

**STP effluent (m<sup>3</sup>/day):** 2000

|  |  |
|--|--|
| <i>Other conditions affecting environmental exposure</i>                                     |  |
| Local freshwater dilution factor: 1000   |  |
| <b>2.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)</b>                   |  |
| Process Categories   | Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a) |
| <i>Product (article) characteristics</i>   |  |
| <b>Physical form of product:</b><br>Liquid, vapour pressure < 0,5 kPa at STP                 |  |
| <b>Concentration of substance in product:</b><br>Covers concentrations up to 25 %            |  |
| <i>Amount used, frequency and duration of use/exposure</i>                                   |  |
| <b>Duration:</b><br>Covers use up to > 15 min  |  |
| <i>Conditions and measures related to personal protection, hygiene and health evaluation</i> |  |
| <b>Personal protection</b>   |  |
| Wear suitable respiratory protection.<br>Wear suitable gloves tested to EN374.               | Dermal - minimum efficiency of: 95 %   |
| <b>2.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)</b>                    |  |
| Process Categories   | Roller application or brushing (PROC10)  |
| <i>Product (article) characteristics</i>   |  |
| <b>Physical form of product:</b><br>Liquid, vapour pressure < 0,5 kPa at STP                 |  |
| <b>Concentration of substance in product:</b><br>Covers concentrations up to 15 %            |  |
| <i>Amount used, frequency and duration of use/exposure</i>                                   |  |
| <b>Duration:</b><br>Covers use up to 60 min  |  |
| <i>Conditions and measures related to personal protection, hygiene and health evaluation</i> |  |
| <b>Personal protection</b>   |  |
| Wear suitable gloves tested to EN374.  | Dermal - minimum efficiency of: 95 %   |
| <b>2.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)</b>   |  |
| Process Categories   | Non industrial spraying (PROC11)   |
| <i>Product (article) characteristics</i>   |  |
| <b>Physical form of product:</b><br>Liquid, vapour pressure < 0,5 kPa at STP                 |  |
| <b>Concentration of substance in product:</b><br>Covers concentrations up to 15 %            |  |
| <i>Amount used, frequency and duration of use/exposure</i>                                   |  |
| <b>Duration:</b><br>Covers use up to 60 min  |  |

## Technical and organisational conditions and measures

### Technical and organisational measures

|  |  |
|--|--|
| Provide extract ventilation to points where emissions occur. | Inhalation - minimum efficiency of: 90 % |
|--|--|

## Conditions and measures related to personal protection, hygiene and health evaluation

### Personal protection

Wear suitable gloves tested to EN374.

## 2.2. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

|                    |   |
|--------------------|---|
| Process Categories | Manual activities involving hand contact (PROC19) |
|--------------------|---|

## Product (article) characteristics

### Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

### Concentration of substance in product:

Covers concentrations up to 5 %

## Amount used, frequency and duration of use/exposure

### Duration:

Covers use up to 8 h

## Conditions and measures related to personal protection, hygiene and health evaluation

### Personal protection

Wear suitable gloves tested to EN374.

## 2.3 Exposure estimation and reference to its source

### 2.3. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

| protection target   | Exposure level           | Calculation method  | Risk Characterization Ratio (RCR) |
|---------------------|--------------------------|---------------------|-----------------------------------|
| freshwater          | 6.74E-05 mg/L            | Other measured data | 0.042                             |
| marine water        | 6.7E-06 mg/L             | Other measured data | 0.004                             |
| freshwater sediment | 0.0677 mg/kg dry weight  | Other measured data | 0.483                             |
| marine sediment     | 0.00674 mg/kg dry weight | Other measured data | 0.048                             |
| soil                | 0.0118 mg/kg dry weight  | Other measured data | 0.001                             |

### 2.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

| Exposure route, Health effect, Exposure indicator | Exposure level          | Calculation method     | Risk Characterization Ratio (RCR) |
|---|-------------------------|------------------------|-----------------------------------|
| dermal, systemic, long-term                       | 0.068 mg/kg bw/day      | ECETOC TRA worker v2.0 | 0.12                              |
| inhalative, systemic, long-term                   | 0.456 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | 0.457                             |
| combined routes                                   | N/A                     | N/A                    | 0.577                             |
| inhalative, local, short-term                     | 0.913 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | < 0.001                           |

### 2.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

| Exposure route, Health effect, Exposure indicator | Exposure level          | Calculation method     | Risk Characterization Ratio (RCR) |
|---|-------------------------|------------------------|-----------------------------------|
| dermal, systemic, long-term                       | 0.082 mg/kg bw/day      | ECETOC TRA worker v2.0 | 0.144                             |
| inhalative, systemic, long-term                   | 0.457 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | 0.229                             |
| combined routes                                   | N/A                     | N/A                    | 0.373                             |
| inhalative, local, short-term                     | 0.914 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | < 0.001                           |

### 2.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

| Exposure route, Health effect, Exposure indicator | Exposure level          | Calculation method     | Risk Characterization Ratio (RCR) |
|---|-------------------------|------------------------|-----------------------------------|
| dermal, systemic, long-term                       | 0.214 mg/kg bw/day      | ECETOC TRA worker v2.0 | 0.376                             |
| inhalative, systemic, long-term                   | 0.121 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | 0.122                             |
| combined routes                                   | N/A                     | N/A                    | 0.498                             |
| inhalative, local, short-term                     | 0.243 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | < 0.001                           |

### 2.3. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

| Exposure route, Health effect, Exposure indicator | Exposure level         | Calculation method     | Risk Characterization Ratio (RCR) |
|---|------------------------|------------------------|-----------------------------------|
| dermal, systemic, long-term                       | 0.14 mg/kg bw/day      | ECETOC TRA worker v2.0 | 0.248                             |
| inhalative, systemic, long-term                   | 0.76 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | 0.076                             |
| combined routes                                   | N/A                    | N/A                    | 0.324                             |
| inhalative, local, short-term                     | 1.52 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | < 0.001                           |

## 2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



## Exposure Scenario

### Cashew, nutshell liq.

## Exposure Scenario, 08/06/2021

| Substance identity  |                       |
|---------------------|-----------------------|
|                     | Cashew, nutshell liq. |
| CAS No.             | 8007-24-7             |
| EINECS No.          | 232-355-4             |
| Registration number | 01-2119502450-57      |

## Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9b, PC9a, PC1)

|   |   |  |  |
|---|---|--|--|
| 1. ES 1   |   | Widespread use by professional workers; Various products (PC9b, PC9a, PC1) |  |
| <b>1.1 TITLE SECTION</b>  |   |  |  |
| Exposure Scenario name  | Dye - Professional application of coatings and inks by brush or roller - Use in rigid foams, coatings, adhesives and sealants                                   |  |  |
| Date - Version  | 21/05/2021 - 1.0  |  |  |
| Life Cycle Stage  | Widespread use by professional workers  |  |  |
| Main user group   | Professional uses   |  |  |
| Sector(s) of use  | Professional uses (SU22)  |  |  |
| Product Categories  | Fillers, putties, plasters, modelling clay (PC9b) - Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1)                            |  |  |
| Article Category(ies)   | Stone, plaster, cement, glass and ceramic articles: Large surface area articles (AC4a) - Other articles made of stone, plaster, cement, glass or ceramic (AC4g) |  |  |
| <b>Environment Contributing Scenario</b>  |   |  |  |
| CS1   | ERC8c - ERC8f   |  |  |
| <b>Worker Contributing Scenario</b>   |   |  |  |
| CS2 Mixing operations   | PROC19  |  |  |
| CS3 Equipment cleaning and maintenance - (aqueous) - Material transfers   | PROC8b  |  |  |
| CS4 Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous) | PROC10  |  |  |
| <b>1.2 Conditions of use affecting exposure</b>   |   |  |  |
| <b>1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)</b>   |   |  |  |
| Environmental release categories  | Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)                 |  |  |
| <i>Product (article) characteristics</i>  |   |  |  |
| <b>Physical form of product:</b><br>Liquid  |   |  |  |
| <b>Concentration of substance in product:</b><br>Covers percentage substance in the product up to 1 %.                    |   |  |  |
| <i>Amount used, frequency and duration of use (or from service life)</i>  |   |  |  |
| <b>Amounts used:</b><br>< 50 t(tonnes)/year<br>< 167 kg/day   |   |  |  |
| <b>Release type:</b> Intermittent release   |   |  |  |
| <b>Emission days:</b> 365 days per year   |   |  |  |
| <i>Conditions and measures related to sewage treatment plant</i>  |   |  |  |
| <b>STP type:</b><br>Municipal Sewage Treatment Plant<br>Water - minimum efficiency of: = 93.2 %                           |   |  |  |
| <i>Conditions and measures related to treatment of waste (including article waste)</i>                                    |   |  |  |
| <b>Waste treatment</b><br>Residues which cannot be recycled are disposed off as chemical waste                            |   |  |  |
| <i>Other conditions affecting environmental exposure</i>  |   |  |  |
| <b>Local marine water dilution factor:</b> 100<br><b>Local freshwater dilution factor:</b> 10                             |   |  |  |

|  |  |
|--|--|
| <b>Receiving surface water flow:</b> 18000 m <sup>3</sup> /day<br>Covers indoor and outdoor use  |  |
| <b>1.2. CS2: Worker Contributing Scenario: Mixing operations (PROC19)</b>  |  |
| <b>Process Categories</b>  | Manual activities involving hand contact (PROC19)  |
| <i>Product (article) characteristics</i>   |  |
| <b>Physical form of product:</b><br>Liquid   |  |
| <b>Concentration of substance in product:</b><br>Covers percentage substance in the product up to 1 %.   |  |
| <i>Amount used, frequency and duration of use/exposure</i>   |  |
| <b>Amounts used:</b><br>< 50 t(tonnes)/year  |  |
| <b>Duration:</b><br>Covers daily exposures up to 8 hours   |  |
| <i>Technical and organisational conditions and measures</i>  |  |
| <b>Technical and organisational measures</b><br>Ensure operatives are trained to minimise exposures.<br>Avoid direct eye contact with product, also via contamination on hands.                                      |  |
| <i>Conditions and measures related to personal protection, hygiene and health evaluation</i>   |  |
| <b>Personal protection</b><br>Wear suitable gloves tested to EN374.<br>Wear suitable coveralls to prevent exposure to the skin.<br>Use eye protection according to EN 166.<br>Wear a respirator conforming to EN140. |  |
| <i>Other conditions affecting worker exposure</i>  |  |
| Covers indoor and outdoor use<br>Professional use<br><b>Temperature:</b> Covers use at ambient temperatures.   |  |
| <b>1.2. CS3: Worker Contributing Scenario: Equipment cleaning and maintenance - (aqueous) - Material transfers (PROC8b)</b>  |  |
| <b>Process Categories</b>  | Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b) |
| <i>Product (article) characteristics</i>   |  |
| <b>Physical form of product:</b><br>Liquid, vapour pressure < 0,5 kPa at STP   |  |
| <b>Concentration of substance in product:</b><br>Covers percentage substance in the product up to 25 %.  |  |
| <i>Amount used, frequency and duration of use/exposure</i>   |  |
| <b>Duration:</b><br>Covers daily exposures up to 8 hours   |  |
| <b>Frequency:</b><br>Avoid using product more than .... = 4 h/event  |  |
| <i>Technical and organisational conditions and measures</i>  |  |
| <b>Technical and organisational measures</b><br>Ensure operatives are trained to minimise exposures.<br>Avoid direct eye contact with product, also via contamination on hands.                                      |  |
| <i>Conditions and measures related to personal protection, hygiene and health evaluation</i>   |  |
| <b>Personal protection</b><br>Wear suitable gloves tested to EN374.  |  |
| <i>Other conditions affecting worker exposure</i>  |  |

Indoor use

Professional use

**Temperature:** Covers use at ambient temperatures.

## 1.2. CS4: Worker Contributing Scenario: Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous) (PROC10)

**Process Categories** Roller application or brushing (PROC10)

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 25 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Covers daily exposures up to 8 hours

#### **Frequency:**

Avoid using product more than .... = 4 h/event

### *Technical and organisational conditions and measures*

#### **Technical and organisational measures**

Ensure operatives are trained to minimise exposures.

Provide extract ventilation to points where emissions occur.

Avoid direct eye contact with product, also via contamination on hands.

Use long handled brushes and rollers.

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

Wear suitable gloves tested to EN374.

Wear a respirator conforming to EN140.

### *Other conditions affecting worker exposure*

Indoor use

Professional use

**Temperature:** Covers use at ambient temperatures.

## 1.3 Exposure estimation and reference to its source

### 1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

| protection target | Exposure level | Calculation method | Risk Characterization Ratio (RCR) |
|-------------------|----------------|--------------------|-----------------------------------|
| N/A               | N/A            | N/A                | < 1                               |

### 1.3. CS2: Worker Contributing Scenario: Mixing operations (PROC19)

| Exposure route, Health effect, Exposure indicator | Exposure level | Calculation method     | Risk Characterization Ratio (RCR) |
|---|----------------|------------------------|-----------------------------------|
| inhalative  | N/A            | ECETOC TRA worker v2.0 | < 1                               |
| dermal  | N/A            | ECETOC TRA worker v2.0 | < 1                               |

### 1.3. CS3: Worker Contributing Scenario: Equipment cleaning and maintenance - (aqueous) - Material transfers (PROC8b)

| Exposure route, Health effect, Exposure indicator | Exposure level           | Calculation method     | Risk Characterization Ratio (RCR) |
|---|--------------------------|------------------------|-----------------------------------|
| inhalative, systemic, long-term                   | = 7.75 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | = 0.562                           |

|                             |                           |                        |         |
|-----------------------------|---------------------------|------------------------|---------|
| dermal, systemic, long-term | = 0.014 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | = 0.004 |
|-----------------------------|---------------------------|------------------------|---------|

### 1.3. CS4: Worker Contributing Scenario: Equipment cleaning and maintenance - Large surfaces - Surfaces - Rolling, Brushing - Finishing operations - (aqueous) (PROC10)

| Exposure route, Health effect, Exposure indicator | Exposure level            | Calculation method     | Risk Characterization Ratio (RCR) |
|---|---------------------------|------------------------|-----------------------------------|
| inhalative, local, short-term                     | = 2.325 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | = 0.168                           |
| dermal, systemic, long-term                       | = 0.137 mg/m <sup>3</sup> | ECETOC TRA worker v2.0 | = 0.035                           |

## 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



# Exposure Scenario

## 2,4,6-tris(dimethylaminomethyl)phenol

### Exposure Scenario, 05/11/2021

| Substance identity  |                                       |
|---------------------|---------------------------------------|
|                     | 2,4,6-tris(dimethylaminomethyl)phenol |
| CAS No.             | 90-72-2                               |
| INDEX No.           | 603-069-00-0                          |
| EINECS No.          | 202-013-9                             |
| Registration number | 01-2119560597-27                      |

### Table of contents

1. **ES 1** Widespread use by professional workers; Fillers, putties, plasters, modelling clay (PC9b)

|   |  |   |  |
|---|--|---|--|
| 1. ES 1   |  | Widespread use by professional workers; Fillers, putties, plasters, modelling clay (PC9b) |  |
| 1.1 TITLE SECTION   |  |   |  |
| Exposure Scenario name  | Road and construction applications - Use in rigid foams, coatings, adhesives and sealants  |   |  |
| Date - Version  | 05/11/2021 - 1.0   |   |  |
| Life Cycle Stage  | Widespread use by professional workers   |   |  |
| Main user group   | Professional uses  |   |  |
| Sector(s) of use  | Professional uses (SU22)   |   |  |
| Product Categories  | Fillers, putties, plasters, modelling clay (PC9b)  |   |  |
| Environment Contributing Scenario   |  |   |  |
| CS1   |  | ERC8b - ERC8e   |  |
| Worker Contributing Scenario  |  |   |  |
| CS2 Material transfers  |  | PROC8a  |  |
| CS3 Rolling, Brushing   |  | PROC10  |  |
| CS4 Rolling, Brushing   |  | PROC10  |  |
| CS5 Roller, spreader, flow application  |  | PROC11  |  |
| CS6 Roller, spreader, flow application  |  | PROC11  |  |
| 1.2 Conditions of use affecting exposure  |  |   |  |
| 1.2. CS1: Environment Contributing Scenario (ERC8b, ERC8e)  |  |   |  |
| Environmental release categories  | Widespread use of reactive processing aid (no inclusion into or onto article, indoor) -<br>Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) (ERC8b, ERC8e) |   |  |
| Product (article) characteristics   |  |   |  |
| Physical form of product:<br>Liquid   |  |   |  |
| Vapour pressure:<br>0.197 Pa  |  |   |  |
| Concentration of substance in product:<br>Covers percentage substance in the product up to 100 %. |  |   |  |
| Amount used, frequency and duration of use (or from service life)                                 |  |   |  |
| Amounts used:<br>Amount per use <= 0.0014 tonnes/day  |  |   |  |
| Release type: Continuous release  |  |   |  |
| Conditions and measures related to sewage treatment plant   |  |   |  |
| STP type:<br>No specific measures identified.<br>Water - minimum efficiency of: = 0.059 %         |  |   |  |
| Conditions and measures related to treatment of waste (including article waste)                   |  |   |  |
| Waste treatment<br>This material and its container must be disposed of as hazardous.              |  |   |  |
| 1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)                               |  |   |  |
| Process Categories  | Transfer of substance or mixture (charging and discharging) at non-dedicated facilities  |   |  |

|   |  |
|---|--|
| (PROC8a)  |  |
| <b>Product (article) characteristics</b>  |  |
| <b>Physical form of product:</b><br>Liquid  |  |
| <b>Vapour pressure:</b><br>= 0.197 Pa   |  |
| <b>Concentration of substance in product:</b><br>Covers percentage substance in the product up to 100 %.  |  |
| <b>Amount used, frequency and duration of use/exposure</b>  |  |
| <b>Duration:</b><br>Duration of contact < 30 min  |  |
| <b>Technical and organisational conditions and measures</b>   |  |
| <b>Technical and organisational measures</b>  |  |
| Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).   | Inhalation - minimum efficiency of: 30 %   |
| Local exhaust ventilation   | Inhalation - minimum efficiency of: 80 %   |
| <b>Conditions and measures related to personal protection, hygiene and health evaluation</b>  |  |
| <b>Personal protection</b>  |  |
| Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.<br>Wear a full face respirator conforming to EN136. | Dermal - minimum efficiency of: 90 %<br>Inhalation - minimum efficiency of: 95 % |
| Use suitable eye protection.  |  |
| <b>Other conditions affecting worker exposure</b>   |  |
| <b>Body parts exposed:</b><br>Assumes that potential dermal contact is limited to hands.  |  |
| <b>1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)</b>   |  |
| <b>Process Categories</b>   | Roller application or brushing (PROC10)  |
| <b>Product (article) characteristics</b>  |  |
| <b>Physical form of product:</b><br>Liquid  |  |
| <b>Vapour pressure:</b><br>= 0.197 Pa   |  |
| <b>Concentration of substance in product:</b><br>Covers percentage substance in the product up to 100 %.  |  |
| <b>Amount used, frequency and duration of use/exposure</b>  |  |
| <b>Duration:</b><br>Duration of contact < 440 min   |  |
| <b>Technical and organisational conditions and measures</b>   |  |
| <b>Technical and organisational measures</b>  |  |
| Provide a basic standard of general ventilation (1 to 3 air changes per hour).  | Inhalation - minimum efficiency of: 44 %   |

|  |
|--|
| Ensure that direction of application is only horizontal or downward. |
| Open doors and windows.  |

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

|  |  |
|--|--|
| Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.<br>Wear a full face respirator conforming to EN136.<br>Wear suitable respiratory protection.<br>Wear an impervious suit. | Dermal - minimum efficiency of: 90 %<br>Inhalation - minimum efficiency of: 99 % |
| Use suitable eye protection.   |  |

### *Other conditions affecting worker exposure*

Indoor use

Professional use

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

#### **Body parts exposed:**

Assumes that potential dermal contact is limited to hands.

### **1.2. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)**

|                           |   |
|---------------------------|---|
| <b>Process Categories</b> | Roller application or brushing (PROC10) |
|---------------------------|---|

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid

#### **Vapour pressure:**

= 0.197 Pa

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Duration of contact < 440 min

### *Technical and organisational conditions and measures*

#### **Technical and organisational measures**

|  |  |
|--|--|
| Mechanical ventilation giving at least [ACH]:                        | Inhalation - minimum efficiency of: 44 % |
| Ensure that direction of application is only horizontal or downward. |  |
| Open doors and windows.  |  |

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

|  |  |
|--|--|
| Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.<br>Wear a full face respirator conforming to EN136.<br>Wear suitable respiratory protection.<br>Wear an impervious suit. | Dermal - minimum efficiency of: 90 %<br>Inhalation - minimum efficiency of: 99 % |
|--|--|

Use suitable eye protection.

### *Other conditions affecting worker exposure*

Outdoor use

Professional use

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

**Body parts exposed:**

Assumes that potential dermal contact is limited to hands.

### **1.2. CS5: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)**

|                           |                                  |
|---------------------------|----------------------------------|
| <b>Process Categories</b> | Non industrial spraying (PROC11) |
|---------------------------|----------------------------------|

### *Product (article) characteristics*

**Physical form of product:**

Liquid

**Vapour pressure:**

= 0.197 Pa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

**Duration:**

Duration of contact < 4 h

### *Technical and organisational conditions and measures*

**Technical and organisational measures**

|  |  |
|--|--|
| Provide a basic standard of general ventilation (1 to 3 air changes per hour). | Inhalation - minimum efficiency of: 44 % |
| Ensure that direction of application is only horizontal or downward.           |  |
| Open doors and windows.  |  |

### *Conditions and measures related to personal protection, hygiene and health evaluation*

**Personal protection**

|   |  |
|---|--|
| Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. | Dermal - minimum efficiency of: 90 %<br>Inhalation - minimum efficiency of: 99 % |
| Wear a full face respirator conforming to EN136.  |  |
| Wear suitable respiratory protection.   |  |
| Wear an impervious suit.  |  |
| Use suitable eye protection.  |  |

### *Other conditions affecting worker exposure*

Indoor use

Professional use

**Body parts exposed:**

Assumes that potential dermal contact is limited to hands.

### **1.2. CS6: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)**

|                           |                                  |
|---------------------------|----------------------------------|
| <b>Process Categories</b> | Non industrial spraying (PROC11) |
|---------------------------|----------------------------------|

### *Product (article) characteristics*

**Physical form of product:**

Liquid

**Vapour pressure:**

= 0.197 Pa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure*

**Duration:**

Duration of contact < 4 h

*Technical and organisational conditions and measures*

**Technical and organisational measures**

|  |  |
|--|--|
| Mechanical ventilation giving at least [ACH]:                        | Inhalation - minimum efficiency of: 44 % |
| Ensure that direction of application is only horizontal or downward. |  |
| Open doors and windows.  |  |

*Conditions and measures related to personal protection, hygiene and health evaluation*

**Personal protection**

|  |  |
|--|--|
| Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.<br>Wear a full face respirator conforming to EN136.<br>Wear suitable respiratory protection.<br>Wear an impervious suit. | Dermal - minimum efficiency of: 90 %<br>Inhalation - minimum efficiency of: 99 % |
| Use suitable eye protection.   |  |

*Other conditions affecting worker exposure*

Outdoor use

Professional use

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

**Body parts exposed:**

Assumes that potential dermal contact is limited to hands.

## 1.3 Exposure estimation and reference to its source

### 1.3. CS1: Environment Contributing Scenario (ERC8b, ERC8e)

| protection target                | Exposure level             | Calculation method | Risk Characterization Ratio (RCR) |
|----------------------------------|----------------------------|--------------------|-----------------------------------|
| freshwater                       | 0.00172 mg/L               | EUSES v2.1         | 0.037                             |
| freshwater sediment              | 0.00701 mg/kg dry weight   | EUSES v2.1         | 0.027                             |
| marine water                     | 0.00017 mg/L               | EUSES v2.1         | 0.037                             |
| marine sediment                  | 0.0007 mg/kg dry weight    | EUSES v2.1         | 0.027                             |
| Sewage treatment plant           | 0.014 mg/L                 | EUSES v2.1         | 0.069                             |
| Agricultural soil                | 8E-05 mg/kg dry weight     | EUSES v2.1         | < 0.01                            |
| Man via environment - Inhalation | < 0.0001 mg/m <sup>3</sup> | EUSES v2.1         | < 0.01                            |

|                            |                       |            |        |
|----------------------------|-----------------------|------------|--------|
| Man via environment - Oral | < 0.0001 mg/kg bw/day | EUSES v2.1 | < 0.01 |
|----------------------------|-----------------------|------------|--------|

### 1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

| Exposure route, Health effect, Exposure indicator | Exposure level          | Calculation method | Risk Characterization Ratio (RCR) |
|---|-------------------------|--------------------|-----------------------------------|
| inhalative, systemic, long-term                   | 0.023 mg/m <sup>3</sup> | EASY TRA v3.6      | 0.004                             |
| inhalative, systemic, short-term                  | 0.464 mg/m <sup>3</sup> | EASY TRA v3.6      | 0.211                             |
| combined routes, systemic, long-term              | N/A                     | N/A                | 0.247                             |
| dermal, systemic, long-term                       | 0.03 mg/kg bw/day       | RISKOFDERM v2.1    | 0.203                             |

### 1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

| Exposure route, Health effect, Exposure indicator | Exposure level              | Calculation method   | Risk Characterization Ratio (RCR) |
|---|-----------------------------|----------------------|-----------------------------------|
| inhalative, systemic, long-term                   | 0.31 mg/m <sup>3</sup>      | ECETOC TRA worker v3 | 0.584                             |
| inhalative, systemic, short-term                  | 0.4641238 mg/m <sup>3</sup> | EASY TRA v3.6        | 0.59                              |
| combined routes, systemic, long-term              | N/A                         | N/A                  | 0.854                             |
| dermal, systemic, long-term                       | 0.041 mg/kg bw/day          | RISKOFDERM v2.1      | 0.27                              |

### 1.3. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)

| Exposure route, Health effect, Exposure indicator | Exposure level          | Calculation method   | Risk Characterization Ratio (RCR) |
|---|-------------------------|----------------------|-----------------------------------|
| inhalative, systemic, long-term                   | 0.039 mg/m <sup>3</sup> | ECETOC TRA worker v3 | 0.073                             |
| inhalative, systemic, short-term                  | 0.867 mg/m <sup>3</sup> | EASY TRA v3.6        | 0.413                             |
| combined routes, systemic, long-term              | N/A                     | N/A                  | 0.343                             |
| dermal, systemic, long-term                       | 0.041 mg/kg bw/day      | RISKOFDERM v2.1      | 0.27                              |

### 1.3. CS5: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

| Exposure route, Health effect, Exposure indicator | Exposure level          | Calculation method | Risk Characterization Ratio (RCR) |
|---|-------------------------|--------------------|-----------------------------------|
| inhalative, systemic, long-term                   | 0.367 mg/m <sup>3</sup> | ART v1.5           | 0.022                             |
| inhalative, systemic, short-term                  | 0.023 mg/m <sup>3</sup> | ART v1.5           | 0.011                             |
| combined routes, systemic, long-term              | N/A                     | N/A                | 0.827                             |
| dermal, systemic, long-term                       | 0.121 mg/kg bw/day      | RISKOFDERM v2.1    | 0.805                             |

### 1.3. CS6: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

| Exposure route, Health effect, Exposure indicator | Exposure level          | Calculation method | Risk Characterization Ratio (RCR) |
|---|-------------------------|--------------------|-----------------------------------|
| inhalative, systemic, long-term                   | 0.019 mg/m <sup>3</sup> | ART v1.5           | 0.037                             |
| inhalative, systemic, short-term                  | 0.039 mg/m <sup>3</sup> | ART v1.5           | 0.019                             |
| combined routes, systemic, long-term              | N/A                     | N/A                | 0.101                             |
| dermal, systemic, long-term                       | 0.05 mg/kg bw/day       | RISKOFDERM v2.1    | 0.33                              |

## 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.