

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

BIOSCUUD BT FIX

Date of first edition: 12/20/2022

Safety Data Sheet dated 06/10/2026 version 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: BIOSCUUD BT FIX

Trade code: 30072020

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Adhesives, sealants

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel. +39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Ireland Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Members of the public Number (8 am-10 pm): +353 (0)1 809 2166

Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

Malta In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 3	Flammable liquid and vapour.
Skin Irrit. 2	Causes skin irritation.
Eye Irrit. 2	Causes serious eye irritation.
STOT SE 3	May cause respiratory irritation.
STOT RE 2	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	May be fatal if swallowed and enters airways.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Danger

Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P280 Wear protective gloves/clothing and eye/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331 Do NOT induce vomiting.
P501 Dispose of contents/container in accordance with applicable regulations.

Contains

xylene

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: BIOSCUD BT FIX

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥ 20 -<50 %	xylene	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; STOT SE 3, H335; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 3, H412; Eye Irrit. 2, H319, M-Chronic:1	01-2119488216-32

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

Water.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Store in closed containers and in a well-ventilated place. Store the product at a temperature between +5°C and +35°C.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

xylene

CAS: 1330-20-7	ACGIH	Long Term: 20 ppm (8h) Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair
	EU	Long Term: 221 mg/m ³ - 50 ppm (8h); Short Term: 442 mg/m ³ - 100 ppm Notes: Skin
	NATION AUSTRIA AL	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: 15(Miw), 4x, MAK Source: BGBl. II Nr. 156/2021
	NATION BELGIUM AL	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: D Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATION BULGARIA AL	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: Кожа Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATION CYPRUS AL	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: δέρμα Source: Οι περί Ασφάλειας και Υγείας στην Εργασία (Χημικοί Παράγοντες) Κανονισμοί του 2001 έως 2021
	NATION CZECHIA AL	Long Term: 200 mg/m ³ ; Short Term: Ceiling - 400 mg/m ³ Notes: B, D, I Source: Nařízení vlády č. 361-2007 Sb
	NATION GERMANY AL	Long Term: 220 mg/m ³ - 50 ppm Notes: DFG, EU, H, 2(II) Source: TRGS 900
	NATION DENMARK AL	Long Term: 109 mg/m ³ - 25 ppm Notes: EH Source: BEK nr 2203 af 29/11/2021
	NATION SPAIN AL	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: vía dérmica, VLB®, VLI Source: LEP 2022
	NATION ESTONIA AL	Long Term: 200 mg/m ³ - 50 ppm; Short Term: 450 mg/m ³ - 100 ppm Notes: A Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATION FINLAND AL	Long Term: 220 mg/m ³ - 50 ppm; Short Term: 440 mg/m ³ - 100 ppm Notes: iho Source: HTP-ARVOT 2020
	NATION FRANCE AL	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: Risque de pénétration percutanée Source: INRS outil65, article R. 4412-149 du Code du travail
	NATION GREECE AL	Long Term: 435 mg/m ³ - 100 ppm; Short Term: 650 mg/m ³ - 150 ppm Notes: Δ Source: ΦΕΚ 94/Α` 13.5.1999
	NATION CROATIA AL	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: koža Source: 2000/39/EZ
	NATION HUNGARY AL	Long Term: 221 mg/m ³ ; Short Term: 442 mg/m ³ Notes: b, BEM, EU1, R Source: 5/2020. (II. 6.) ITM rendelet
	NATION IRELAND AL	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: Sk, IOELV Source: 2021 Code of Practice
	NATION ITALY AL	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: Cute Source: D.lgs. 81/2008, Allegato XXXVIII
	NATION LITHUANIA AL	Long Term: 200 mg/m ³ - 50 ppm; Short Term: 450 mg/m ³ - 100 ppm Notes: O Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
	NATION LUXEMBOUR G	Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: Peau

NATION LATVIA AL		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: Āda Source: KN325P1
NATION MALTA AL		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: skin Source: S.L.424.24
NATION NETHERLAND AL S		Long Term: 210 mg/m ³ ; Short Term: 442 mg/m ³ Notes: H Source: Arbeidsomstandighedenregeling - Lijst A
NATION NORWAY AL		Long Term: 108 mg/m ³ - 25 ppm Notes: H E Source: FOR-2021-06-28-2248
NATION POLAND AL		Long Term: 100 mg/m ³ ; Short Term: 200 mg/m ³ Notes: skóra Source: Dz.U. 2018 poz. 1286
NATION PORTUGAL AL		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: Cutânea Source: Decreto-Lei n.º 1/2021
NATION ROMANIA AL		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: P, Dir. 2000/39 Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATION SLOVAKIA AL		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: K, 7) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATION SLOVENIA AL		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: K, BAT, EU1 Source: UL št. 72, 11. 5. 2021
NATION SWEDEN AL		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Notes: H Source: AFS 2021:3
WEL- EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 220 mg/m ³ - 50 ppm; Short Term: 441 mg/m ³ - 100 ppm Notes: Sk, BMGV Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
SUVA	SWITZERLAND	Long Term: 220 mg/m ³ - 50 ppm; Short Term: 440 mg/m ³ - 100 ppm Notes: R/H, B, SNC / ZNS, NIOSH INRS Source: suva.ch/valeurs-limites

Biological limit values

xylene

CAS: 1330-20-7 Biological Indicator: Methyl hippuric acid in urine; Sampling Period: End of turn
Value: 2000 mg/L; Medium: Urine

Predicted No Effect Concentration (PNEC) values

xylene

CAS: 1330-20-7 Exposure Route: Fresh Water; PNEC Limit: 327 mg/m³
Exposure Route: Intermittent releases (fresh water); PNEC Limit: 327 mg/m³
Exposure Route: Marine water; PNEC Limit: 327 mg/m³
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 6.58 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 12.46 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 12.46 mg/kg
Exposure Route: Soil; PNEC Limit: 2.31 mg/kg

Derived No Effect Level (DNEL) values

xylene

CAS: 1330-20-7 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 221 mg/kg/day; Consumer: 65.3 mg/kg/day

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 442 mg/kg/day; Consumer: 260 mg/kg/day

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 221 mg/kg/day; Consumer: 65.3 mg/kg/day

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Professional: 442 mg/kg/day; Consumer: 260 mg/kg/day

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 212 mg/kg; Consumer: 125 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 12.5 mg/kg

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing. Safety shoes.

Protection for hands:

Protection for hands:

Suitable materials for safety gloves; EN 374:

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Respiratory protection:

Gas filter type A .

Thermal Hazards:

Not expected if used as intended

Environmental exposure controls:

Prevent the product from entering sewers or surface and underground water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Black
Odour:	Like: Xylene
Odour threshold:	Not Relevant Notes: Data not available
pH:	Not Relevant Notes: Not applicable, non-aqueous mixture
Kinematic viscosity:	$\leq 20,5 \text{ mm}^2/\text{s}$ (40 °C)
Melting point/freezing point:	-54 °C (-65 °F)
Boiling point or initial boiling point and boiling range:	137 °C (279 °F)
Flash point:	30 °C (86 °F)
Lower and upper explosion limit:	7.00 % (UEL). 1.10 % (LEL).
Relative vapour density:	Not Relevant Notes: Some data is not known
Vapour pressure:	Not Relevant Notes: Some data is not known
Density and/or relative density:	1.03 g/cm ³
Solubility in water:	Insoluble
Solubility in oil:	Not Relevant Notes: Not determined, as it is not required for CLP classification
Partition coefficient n-octanol/water (log value):	Not Relevant Notes: Not applicable to mixtures

Auto-ignition temperature:	450.00 °C
Decomposition temperature:	250.00 °C
Flammability:	The product is classified Flam. Liq. 3
Volatile Organic compounds - VOCs =	23.00%; 236.90g/L
Particle characteristics:	
Particle size:	N.A.

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

Vapors may form explosive mixture with air

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with oxidizing materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	Not classified Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	The product is classified: STOT SE 3(H335)
i) STOT-repeated exposure	The product is classified: STOT RE 2(H373)
j) aspiration hazard	The product is classified: Asp. Tox. 1(H304)

Toxicological information on main components of the mixture:

xylene

CAS: 1330-20-7	a) acute toxicity	LD50 Oral Rat = 3523 ml/Kg LC50 Inhalation Vapour Rat = 29000 mg/m3 4h LD50 Skin Rabbit = 12126 mg/kg 24h
	b) skin corrosion/irritation	Skin Corrosive Rabbit Negative 4h
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes 1h
	f) carcinogenicity	Genotoxicity Negative
	g) reproductive toxicity	No Observed Adverse Effect Level Inhalation Rat = 2171 mg/kg

11.2. Information on other hazards

Endocrine disrupting properties:

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

xylene

- CAS: 1330-20-7
- a) Aquatic acute toxicity: LC50 Fish freshwater fish = 2.6 mg/L 96h
 - b) Aquatic chronic toxicity: NOEC Fish freshwater fish = 1.3 mg/L
 - a) Aquatic acute toxicity: LC50 Daphnia Daphnia magna = 1 mg/L 24h
 - b) Aquatic chronic toxicity: NOEC Daphnia Ceriodaphnia dubia = 0.96 mg/L
 - a) Aquatic acute toxicity: EC50 Algae freshwater algae = 1.3 mg/L 48h
 - a) Aquatic acute toxicity: EC50 microorganisms = 96 mg/L
 - d) Terrestrial toxicity: NOEC Worm earthworms = 16 mg/kg
 - e) Plant toxicity: LC50 terrestrial plants = 1 mg/kg

12.2. Persistence and degradability

xylene

CAS: 1330-20-7 Readily biodegradable

12.3. Bioaccumulative potential

xylene

CAS: 1330-20-7 Bioaccumulative Test: BCF - Bioconcentration factor; Value: 25.9

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration $\geq 0.1\%$

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as hazardous waste

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

N.A.

SECTION 14: Transport information

14.1. UN number or ID number

1307

14.2. UN proper shipping name

ADR-Shipping Name: XYLENES

IATA-Shipping Name: XYLENES

IMDG-Shipping Name: XYLENES

14.3. Transport hazard class(es)

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

14.4. Packing group
ADR-Packing Group: III
IATA-Packing group: III
IMDG-Packing group: III

14.5. Environmental hazards
Marine pollutant: No
Environmental Pollutant: No
IMDG-EMS: F-E, S-D

14.6. Special precautions for user
Road and Rail (ADR-RID):
ADR-Label: 3
ADR - Hazard identification number: 30
ADR-Special Provisions: -
ADR-Transport category (Tunnel restriction code): 3 (D/E)
ADR Limited Quantities: 5 L
ADR Excepted Quantities: E1

Air (IATA):
IATA-Passenger Aircraft: 355
IATA-Cargo Aircraft: 366
IATA-Label: 3
IATA-Subsidiary hazards: -
IATA-Erg: 3L
IATA-Special Provisions: A3

Sea (IMDG):
IMDG-Stowage and handling: Category A
IMDG-Segregation: -
IMDG-Subsidiary hazards: -
IMDG-Special Provisions: 223

14.7. Maritime transport in bulk according to IMO instruments
N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EU) n. 2020/878
Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP) Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP) Regulation (EU) n. 2021/849 (ATP 17 CLP)
Regulation (EU) n. 2022/692 (ATP 18 CLP) Regulation (EU) n. 2023/707
Regulation (EU) n. 2023/1434 (ATP 19 CLP) Regulation (EU) n. 2023/1435 (ATP 20 CLP)
Regulation (EU) n. 2024/197 (ATP 21 CLP) Regulation (EU) n. 2024/2564 (ATP 22 CLP)
Regulation (EU) n. 2024/2865 Regulation (EU) n. 2025/1222 (ATP 23 CLP)
Regulation (EC) nr 648/2004 (Detergents).
Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
Restrictions related to the product: 3, 40
Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
Product belongs to category: P5c	5000	50000

Explosives precursors – Regulation 2019/1148

No substances listed

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

Class 2: hazardous for water.

German Lagerklasse according to TRGS 510:

LGK 3

SVHC Substances:

No SVHC substances present in concentration $\geq 0.1\%$

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
------	-------------

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/2	STOT RE 2	Specific target organ toxicity — repeated exposure, Category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373	Calculation method
Asp. Tox. 1, H304	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ATE: Acute Toxicity Estimate
 ATEmix: Acute toxicity Estimate (Mixtures)
 BCF: Biological Concentration Factor
 BEI: Biological Exposure Index
 BOD: Biochemical Oxygen Demand
 CAS: Chemical Abstracts Service (division of the American Chemical Society).
 CAV: Poison Center
 CE: European Community
 CLP: Classification, Labeling, Packaging.
 CMR: Carcinogenic, Mutagenic and Reprotoxic
 COD: Chemical Oxygen Demand
 COV: Volatile Organic Compound
 CSA: Chemical Safety Assessment
 CSR: Chemical Safety Report
 DMEL: Derived Minimal Effect Level
 DNEL: Derived No Effect Level.
 DPD: Dangerous Preparations Directive
 DSD: Dangerous Substances Directive
 EC50: Half Maximal Effective Concentration
 ECHA: European Chemicals Agency
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 ES: Exposure Scenario
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 IC50: half maximal inhibitory concentration
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 IMDG: International Maritime Code for Dangerous Goods.
 INCI: International Nomenclature of Cosmetic Ingredients.
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care
 KAFH: Keep Away From Heat
 KSt: Explosion coefficient.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 LDLo: Leathal Dose Low
 N.A.: Not Applicable
 N/A: Not Applicable
 N/D: Not defined/ Not available
 NA: Not available
 NIOSH: National Institute for Occupational Safety and Health
 NOAEL: No Observed Adverse Effect Level
 OSHA: Occupational Safety and Health Administration
 PBT: Persistent, Bioaccumulative and Toxic
 PGK: Packaging Instruction
 PNEC: Predicted No Effect Concentration.
 PSG: Passengers
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 vPvB: Very Persistent, Very Bioaccumulative.
 WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- Safety Data Sheet
- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification

- SECTION 3: Composition/information on ingredients
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information