

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

KERAGRIP ECO PULEP

Date of first edition: 3/26/2021

Safety Data Sheet dated 13/12/2024

version 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: KERAGRIP ECO PULEP

Trade code: 27102020 -2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: primer

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel. +39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Ireland Poison information centre: 01 809 2166 (Daily 8am-10pm) In case of emergency call 999 or 112

Malta In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 2 Highly flammable liquid and vapour.

Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2 Causes serious eye irritation.

Skin Sens. 1 May cause an allergic skin reaction.

STOT SE 3 May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves and eye protection.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

PACK2 The packing must have tactile indications of danger for blind people.

Contains

propan-2-ol; isopropyl alcohol; isopropanol
3-aminopropyltriethoxysilane

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: KERAGRIP ECO PULEP

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥ 50 -<70 %	ethanol; ethyl alcohol	CAS:64-17-5 EC:200-578-6 Index:603-002-00-5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Specific Concentration Limits: C $\geq 50\%$: Eye Irrit. 2 H319	01-2119457610-43
≥ 20 -<50 %	propan-2-ol; isopropyl alcohol; isopropanol	CAS:67-63-0 EC:200-661-7 Index:603-117-00-0	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	01-2119457558-25
≥ 1 -<3 %	3-aminopropyltriethoxysilane	CAS:919-30-2 EC:213-048-4 Index:612-108-00-0	Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317	01-2119480479-24

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.
- Wash thoroughly the body (shower or bath).
- Remove contaminated clothing immediately and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation
Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
ethanol; ethyl alcohol CAS: 64-17-5	ACGIH		Short Term: 1000 ppm A3 - URT irr
	NATIONAL	AUSTRIA	Long Term: 1900 mg/m ³ - 1000 ppm; Short Term: Ceiling - 3800 mg/m ³ - 2000 ppm 60(Mow), 3x, MAK Source: GKV, BGBl. II Nr. 156/2021
	NATIONAL	BULGARIA	Long Term: 1000 mg/m ³ Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATIONAL	CZECHIA	Long Term: 1000 mg/m ³ ; Short Term: Ceiling - 3000 mg/m ³ Source: Nařízení vlády č. 361-2007 Sb
	NATIONAL	DENMARK	Long Term: 1900 mg/m ³ - 1000 ppm Source: BEK nr 2203 af 29/11/2021
	NATIONAL	ESTONIA	Long Term: 1000 mg/m ³ - 500 ppm; Short Term: 1900 mg/m ³ - 1000 ppm Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	FINLAND	Long Term: 1900 mg/m ³ - 1000 ppm; Short Term: 2500 mg/m ³ - 1300 ppm Source: HTP-ARVOT 2020
	NATIONAL	FRANCE	Long Term: 1900 mg/m ³ - 1000 ppm; Short Term: 9500 mg/m ³ - 5000 ppm Source: INRS outil65
	NATIONAL	GREECE	Long Term: 1900 mg/m ³ - 1000 ppm Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL	HUNGARY	Long Term: 1900 mg/m ³ ; Short Term: 3800 mg/m ³ N Source: 5/2020. (II. 6.) ITM rendelet
	NATIONAL	LATVIA	Long Term: 1000 mg/m ³ Source: KN325P1
	NATIONAL	LITHUANIA	Long Term: 1000 mg/m ³ - 500 ppm; Short Term: 1900 mg/m ³ - 1000 ppm Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
	NATIONAL	NETHERLAND S	Long Term: 260 mg/m ³ ; Short Term: 1900 mg/m ³ H Source: Arbeidsomstandighedenregeling - Lijst B2
	NATIONAL	NORWAY	Long Term: 950 mg/m ³ - 500 ppm Source: FOR-2021-06-28-2248
	NATIONAL	POLAND	Long Term: 1900 mg/m ³ Source: Dz.U. 2018 poz. 1286
	NATIONAL	SLOVAKIA	Long Term: 960 mg/m ³ - 500 ppm; Short Term: 1920 mg/m ³ - 1000 ppm Source: 355 NARIADENIE VLÁDY z 10. mája 2006
	NATIONAL	SWEDEN	Long Term: 1000 mg/m ³ - 500 ppm; Short Term: 1900 mg/m ³ - 1000 ppm V Source: AFS 2021:3
	SUVA	SWITZERLAND	Long Term: 960 mg/m ³ - 500 ppm; Short Term: 1920 mg/m ³ - 1000 ppm SSC, Formel / Formal, INRS NIOSH Source: suva.ch/valeurs-limites
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 1920 mg/m ³ - 1000 ppm Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	NATIONAL	BELGIUM	Long Term: 1907 mg/m ³ - 1000 ppm Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	CROATIA	Long Term: 1900 mg/m ³ - 1000 ppm Source: NN 1/2021
	NATIONAL	GERMANY	Long Term: 380 mg/m ³ - 200 ppm

propan-2-ol; isopropyl
alcohol; isopropanol
CAS: 67-63-0

		DFG, Y, 4(II) Source: TRGS 900
NATIONAL	IRELAND	Short Term: 1000 ppm Source: 2021 Code of Practice
NATIONAL	ROMANIA	Long Term: 1900 mg/m ³ - 1000 ppm; Short Term: 9500 mg/m ³ - 5000 ppm Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATIONAL	SLOVENIA	Long Term: 960 mg/m ³ - 500 ppm; Short Term: 1920 mg/m ³ - 1000 ppm Y Source: UL št. 72, 11. 5. 2021
NATIONAL	SPAIN	Short Term: 1910 mg/m ³ - 1000 ppm S Source: LEP 2022
NATIONAL	AUSTRALIA	Long Term: 983 mg/m ³ - 400 ppm (8h); Short Term: 1230 mg/m ³ - 500 ppm
ACGIH		Long Term: 200 ppm (8h); Short Term: 400 ppm A4, BEI - Eye and URT irr, CNS impair
NATIONAL	AUSTRIA	Long Term: 500 mg/m ³ - 200 ppm; Short Term: 2000 mg/m ³ - 800 ppm 15(Miw), 4x, MAK Source: BGBl. II Nr. 156/2021
NATIONAL	BULGARIA	Long Term: 980 mg/m ³ ; Short Term: 1225 mg/m ³ Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
NATIONAL	CZECHIA	Long Term: 500 mg/m ³ ; Short Term: Ceiling - 1000 mg/m ³ I Source: Nařízení vlády č. 361-2007 Sb
NATIONAL	DENMARK	Long Term: 490 mg/m ³ - 200 ppm Source: BEK nr 2203 af 29/11/2021
NATIONAL	ESTONIA	Long Term: 350 mg/m ³ - 150 ppm; Short Term: 600 mg/m ³ - 250 ppm Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	FINLAND	Long Term: 500 mg/m ³ - 200 ppm; Short Term: 620 mg/m ³ - 250 ppm Source: HTP-ARVOT 2020
NATIONAL	FRANCE	Short Term: 980 mg/m ³ - 400 ppm Source: INRS outil65
NATIONAL	GREECE	Long Term: 980 mg/m ³ - 400 ppm; Short Term: 1225 mg/m ³ - 500 ppm Source: ΦΕΚ 94/Α` 13.5.1999
NATIONAL	HUNGARY	Long Term: 500 mg/m ³ ; Short Term: 1000 mg/m ³ b, i, R Source: 5/2020. (II. 6.) ITM rendelet
NATIONAL	LATVIA	Long Term: 350 mg/m ³ ; Short Term: 600 mg/m ³ Source: KN325P1
NATIONAL	LITHUANIA	Long Term: 350 mg/m ³ - 150 ppm; Short Term: 600 mg/m ³ - 250 ppm Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	NORWAY	Long Term: 245 mg/m ³ - 100 ppm Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 900 mg/m ³ ; Short Term: 1200 mg/m ³ skóra Source: Dz.U. 2018 poz. 1286
NATIONAL	SLOVAKIA	Long Term: 500 mg/m ³ - 200 ppm; Short Term: 1000 mg/m ³ - 400 ppm Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATIONAL	SWEDEN	Long Term: 350 mg/m ³ - 150 ppm; Short Term: 600 mg/m ³ - 250 ppm V Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 500 mg/m ³ - 200 ppm; Short Term: 1000 mg/m ³ - 400 ppm SSC, B, VRS Foie SNC Yeux / OAW Laber ZNS Auge, INRS NIOSH Source: suva.ch/valeurs-limites
WEL-EH40	UNITED KINGDOM OF GREAT	Long Term: 999 mg/m ³ - 400 ppm; Short Term: 1250 mg/m ³ - 500 ppm Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)

BRITAIN AND
NORTHERN
IRELAND

NATIONAL	BELGIUM	Long Term: 500 mg/m ³ - 200 ppm; Short Term: 1000 mg/m ³ - 400 ppm Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATIONAL	CROATIA	Long Term: 999 mg/m ³ - 400 ppm; Short Term: 1250 mg/m ³ - 500 ppm Source: NN 1/2021
NATIONAL	GERMANY	Long Term: 500 mg/m ³ - 200 ppm DFG, Y, 2(II) Source: TRGS 900
NATIONAL	IRELAND	Long Term: 200 ppm; Short Term: 400 ppm Sk Source: 2021 Code of Practice
NATIONAL	ROMANIA	Long Term: 200 mg/m ³ - 81 ppm; Short Term: 500 mg/m ³ - 203 ppm Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATIONAL	SLOVENIA	Long Term: 500 mg/m ³ - 200 ppm; Short Term: 1000 mg/m ³ - 400 ppm Y, BAT Source: UL št. 72, 11. 5. 2021
NATIONAL	SPAIN	Long Term: 500 mg/m ³ - 200 ppm; Short Term: 1000 mg/m ³ - 400 ppm VLB®, s Source: LEP 2022
3-aminopropyltriethoxysilane CAS: 919-30-2	NATIONAL FINLAND	Long Term: 28 mg/m ³ - 3 ppm; Short Term: 55 mg/m ³ - 6 ppm Source: HTP-ARVOT 2020

Biological limit values

propan-2-ol; isopropyl alcohol; isopropanol
CAS: 67-63-0

Biological Indicator: Acetone; Sampling Period: End of turn
Value: 25 mg/L; Medium: Urine

Biological Indicator: Acetone; Sampling Period: End of turn
Value: 25 mg/L; Medium: Blood

Predicted No Effect Concentration (PNEC) values

ethanol; ethyl alcohol
CAS: 64-17-5

Exposure Route: Fresh Water; PNEC Limit: 960 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 2.75 mg/l

Exposure Route: Marine water; PNEC Limit: 790 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 580 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 3.6 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 2.9 mg/kg

Exposure Route: Soil; PNEC Limit: 630 µg/kg

Exposure Route: Secondary poisoning; PNEC Limit: 550 mg/kg

propan-2-ol; isopropyl alcohol; isopropanol
CAS: 67-63-0

Exposure Route: Fresh Water; PNEC Limit: 140.9 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 140.9 mg/l

Exposure Route: Marine water; PNEC Limit: 140.9 mg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 2251 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 552 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 552 mg/kg

Exposure Route: Soil; PNEC Limit: 28 mg/kg

Exposure Route: Secondary poisoning; PNEC Limit: 160 mg/kg

3-aminopropyltriethoxysilane
CAS: 919-30-2

Exposure Route: Fresh Water; PNEC Limit: 330 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 3.3 mg/l

Exposure Route: Marine water; PNEC Limit: 33 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 13 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 1.2 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 120 µg/kg
Exposure Route: Soil; PNEC Limit: 50 µg/kg

Derived No Effect Level (DNEL) values

ethanol; ethyl alcohol
CAS: 64-17-5 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 950 mg/m³; Consumer: 114 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Professional: 1900 mg/m³; Consumer: 950 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 343 mg/kg; Consumer: 206 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 87 mg/kg

propan-2-ol; isopropyl alcohol; isopropanol
CAS: 67-63-0 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 89 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Consumer: 319 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 26 mg/kg

3-aminopropyltriethoxysilane
CAS: 919-30-2 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 59 mg/m³; Consumer: 17.4 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 59 mg/m³; Consumer: 17.4 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 8.3 mg/kg; Consumer: 5 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Professional: 8.3 mg/kg; Consumer: 5 mg/kg

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing. Safety shoes.

Protection for hands:

Suitable materials for safety gloves (EN 374, EN 16523-1:2015+A1:2018: Level 6):

Nitrile rubber - NBR: thickness ≥0,4mm; breakthrough time ≥480min.

Butyl rubber - IIR: thickness ≥0,4mm; breakthrough time ≥480min.

Respiratory protection:

Gas filter type A .

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: Transparent

Odour: Like: Hydrocarbons, aliphatic

Odour threshold: N.A.

pH: Not Relevant

Kinematic viscosity: N.A.

Melting point/freezing point: > 120 °C (248 °F)

Boiling point or initial boiling point and boiling range: N.A.

Flash point: 13 °C (55 °F)

Lower and upper explosion limit: N.A.

Relative vapour density: N.A.

Vapour pressure: N.A.
Density and/or relative density: 0.80 g/cm³
Solubility in water: Immiscible
Solubility in oil: N.A.
Partition coefficient n-octanol/water (log value): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Flammability: The product is classified Flam. Liq. 2 H225
Volatile Organic compounds - VOCs = 98 % ; 744.8 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

Not Relevant

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Heat and open flames. Heating

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	The product is classified: STOT SE 3(H336)
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

ethanol; ethyl alcohol	a) acute toxicity	LD50 Oral Rat = 10470 mg/kg LC50 Inhalation Vapour Rat = 117 mg/l 4h LD50 Skin Rabbit = 17100 mg/kg
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative
	c) serious eye damage/irritation	Eye Irritant Rabbit No
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Negative

	f) carcinogenicity	Genotoxicity Negative	Mouse oral route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral = 20700 mg/kg	Mouse
propan-2-ol; isopropyl alcohol; isopropanol	a) acute toxicity	LD50 Oral Rat = 5840 mg/kg	
		LC50 Inhalation Vapour Rat > 10000 Ppm 6h	
		LD50 Skin Rabbit = 16.4 ml/Kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative 4h	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Negative	
3-aminopropyltriethoxysilane	f) carcinogenicity	Genotoxicity Negative Carcinogenicity = 5000 Ppm	Mouse intraperitoneal route NOEC for mouse
	a) acute toxicity	LD50 Oral Rat = 1460 mg/kg	
		LC50 Inhalation Vapour Rat Negative 6h	
		LD50 Skin Rabbit = 4076 mg/kg 24h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Positive	
	f) carcinogenicity	Genotoxicity Negative	Mouse intraperitoneal route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 600 mg/kg	

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
ethanol; ethyl alcohol	CAS: 64-17-5 - EINECS: 200-578-6 - INDEX: 603-002-00-5	a) Aquatic acute toxicity : LC50 Fish <i>S. gairdneri</i> > 11.2 g/L 96h
		b) Aquatic chronic toxicity : NOEC Fish <i>Oryzias latipes</i> = 250 mg/L OECD212
		a) Aquatic acute toxicity : LC50 <i>Daphnia magna</i> = 5012 mg/L 48h
		a) Aquatic acute toxicity : NOEC <i>Daphnia Ceriodaphnia dubia</i> = 9.6 mg/L - 10days
		a) Aquatic acute toxicity : EC50 Algae <i>Chlorella vulgaris</i> = 275 mg/L 72h
		a) Aquatic acute toxicity : LC50 <i>Paramecium caudatum</i> = 5800 mg/L - 16hr
		d) Terrestrial toxicity : LC50 Worm <i>Eisenia foetida</i> = 0.1 mg/cm ²
		e) Plant toxicity : EC50 = 633 mg/kg

propan-2-ol; isopropyl alcohol; isopropanol	CAS: 67-63-0 - EINECS: 200- 661-7 - INDEX: 603-117-00-0	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 9640 mg/L 96h a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 10000 mg/L 24h OECD guideline 202 d) Terrestrial toxicity : LC50 Drosophila melanogaster = 25.1 g/L 24h e) Plant toxicity : IC50 Lactuca sativa = 2104 mg/kg 72h
3-aminopropyltriethoxysilane	CAS: 919-30-2 - EINECS: 213- 048-4 - INDEX: 612-108-00-0	a) Aquatic acute toxicity : LC50 Fish Brachydanio rerio > 934 mg/L 96h a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 331 mg/L 48h a) Aquatic acute toxicity : EC50 Algae Scenedesmus subspicatus > 1000 mg/L 72h c) Bacteria toxicity : EC50 Pseudomonas putida = 43 mg/L

12.2. Persistence and degradability

Component	Persitence/Degradability:	Test	Value	Notes:
ethanol; ethyl alcohol	Readily biodegradable	CO2 production	75.000	
propan-2-ol; isopropyl alcohol; isopropanol	Readily biodegradable	Biochemical oxygen demand		
3-aminopropyltriethoxysilane	Non-readily biodegradable	Dissolved organic carbon	67.000	%; EU method C4-A; 28days

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value	Notes:
ethanol; ethyl alcohol	Bioaccumulative	BCF - Bioconcentration factor	4.500	
3-aminopropyltriethoxysilane	Bioaccumulative	BCF - Bioconcentration factor	3.400	OECD 305

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration $\geq 0.1\%$

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT RELATED MATERIAL
IATA-Technical name: PAINT RELATED MATERIAL
IMDG-Technical name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR-Class: 3
IATA-Class: 3

IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: F-E, S-E

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 3

ADR - Hazard identification number: 33

ADR-Special Provisions: 163 367 640C 650

ADR-Transport category (Tunnel restriction code): 2 (D/E)

ADR Limited Quantities: 5 L

ADR Excepted Quantities: E2

Air (IATA):

IATA-Passenger Aircraft: 353

IATA-Cargo Aircraft: 364

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisions: A3 A72 A192

Sea (IMDG):

IMDG-Stowage Code: Category B

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 163 367

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and

subsequent modifications:

Restrictions related to the product: 3, 40

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c 5000

50000

Explosives precursors – Regulation 2019/1148

No substances listed

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

1: Low hazard to waters

German Lagerklasse according to TRGS 510:

LGK 3

SVHC Substances:

No SVHC substances present in concentration $\geq 0.1\%$

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

ethanol; ethyl alcohol

propan-2-ol; isopropyl alcohol; isopropanol

3-aminopropyltriethoxysilane

SECTION 16: Other information

Code	Description
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Code	Hazard class and hazard category	Description
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ATE: Acute Toxicity Estimate
ATEmix: Acute toxicity Estimate (Mixtures)
BCF: Biological Concentration Factor
BEI: Biological Exposure Index
BOD: Biochemical Oxygen Demand
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CAV: Poison Center
CE: European Community
CLP: Classification, Labeling, Packaging.
CMR: Carcinogenic, Mutagenic and Reprotoxic
COD: Chemical Oxygen Demand
COV: Volatile Organic Compound
CSA: Chemical Safety Assessment
CSR: Chemical Safety Report
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level.
DPD: Dangerous Preparations Directive
DSD: Dangerous Substances Directive
EC50: Half Maximal Effective Concentration
ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances.
ES: Exposure Scenario
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KAHF: Keep Away From Heat
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 13: Disposal considerations
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information



Exposure Scenario

Ethanol

Exposure Scenario, 29/07/2021

Substance identity	
	Ethanol
CAS No.	64-17-5
INDEX No.	603-002-00-5
EINECS No.	200-578-6
Registration number	01-2119457610-43

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9a, PC1)

1. ES 1		Widespread use by professional workers; Various products (PC9a, PC1)	
1.1 TITLE SECTION			
Exposure Scenario name	Professional application of coatings and inks		
Date - Version	29/07/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1)		
Environment Contributing Scenario			
CS1	ERC8a - ERC8d		
Worker Contributing Scenario			
CS2 Rolling, Brushing	PROC10		
CS3 Roller, spreader, flow application	PROC11		
CS4 Handling and dilution of concentrates	PROC19		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8a, ERC8d)			
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid			
Concentration of substance in product: Covers concentrations up to 80 %			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Amounts used: Annual site tonnage = 10000 t			
Release type: Continuous release			
Emission days: 300 days per year			
<i>Technical and organisational conditions and measures</i>			
Control measures to prevent releases			
Prevent discharge of undissolved substance to or recover from onsite wastewater.		Air - minimum efficiency of: 100 % Soil - minimum efficiency of: 20 % Water - minimum efficiency of: 100 %	
<i>Conditions and measures related to sewage treatment plant</i>			
STP type: Municipal Sewage Treatment Plant Water - minimum efficiency of: = 90 %			
STP effluent (m ³ /day): 2000			

<i>Conditions and measures related to treatment of waste (including article waste)</i>	
Waste treatment Contain and dispose of waste according to local regulations.	
<i>Other conditions affecting environmental exposure</i>	
Local marine water dilution factor: 100 Local freshwater dilution factor: 10 Receiving surface water flow: 18000 m ³ /day	
1.2. CS2: Worker Contributing Scenario: Rolling, Brushing (PROC10)	
Process Categories	Roller application or brushing (PROC10)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Concentration of substance in product: Covers concentrations up to 80 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers use up to > 4 h Frequency: Use frequency 5 days per week	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection For further specification, refer to section 8 of the SDS.	
<i>Other conditions affecting worker exposure</i>	
Indoor use Professional use	
1.2. CS3: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)	
Process Categories	Non industrial spraying (PROC11)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Concentration of substance in product: Covers percentage substance in the product up to 25 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers use up to < 4 h Frequency: Use frequency 5 days per week	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection	

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training. For further specification, refer to section 8 of the SDS.		Dermal - minimum efficiency of: = 80 %	
--	--	--	--

Other conditions affecting worker exposure

Indoor use
Professional use

1.2. CS4: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Process Categories	Manual activities involving hand contact (PROC19)		
--------------------	---	--	--

Product (article) characteristics

Physical form of product:
Liquid

Concentration of substance in product:
Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure

Duration:
Covers use up to > 4 h

Frequency:
Use frequency 5 days per week

Technical and organisational conditions and measures

Technical and organisational measures
Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection
For further specification, refer to section 8 of the SDS.

Other conditions affecting worker exposure

Indoor use
Professional use

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	= 0.045 mg/L	EUSES v2.1	= 0.0469
freshwater sediment	= 0.045 mg/kg dry weight	EUSES v2.1	= 0.0469
marine water	= 0.0044 mg/L	EUSES v2.1	= 0.00557
marine sediment	= 0.0044 mg/kg dry weight	EUSES v2.1	= 0.00557
soil	= 0.0003 mg/kg dry weight	EUSES v2.1	= 0.00476
wastewater treatment plant microbes	= 0.34 mg/L	EUSES v2.1	= 0.000586

1.3. CS2: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)

inhalative, systemic, long-term	= 198.08 mg/m ³	ECETOC TRA worker v2.0	= 0.202
dermal, systemic, long-term	= 27.42 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.177

1.3. CS3: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 345.75 mg/m ³	ECETOC TRA worker v2.0	= 0.364
dermal, systemic, long-term	= 21.42 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.138

1.3. CS4: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 115.25 mg/m ³	ECETOC TRA worker v2.0	= 0.1213
dermal, systemic, long-term	= 84.86 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.547

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

Propan-2-ol

Exposure Scenario, 29/07/2021

Substance identity	
	Propan-2-ol
CAS No.	67-63-0
INDEX No.	603-117-00-0
EINECS No.	200-661-7
Registration number	01-2119457558-25

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9a, PC1)

1. ES 1		Widespread use by professional workers; Various products (PC9a, PC1)	
1.1 TITLE SECTION			
Exposure Scenario name	Professional application of coatings and inks		
Date - Version	29/07/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1)		
Environment Contributing Scenario			
CS1	ERC8a - ERC8d		
Worker Contributing Scenario			
CS2 Material transfers	PROC8a		
CS3 Rolling, Brushing	PROC10		
CS4 Roller, spreader, flow application	PROC11		
CS5 Handling and dilution of concentrates	PROC19		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8a, ERC8d)			
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)		
Product (article) characteristics			
Physical form of product: Liquid			
Concentration of substance in product: Covers concentrations up to 35 %			
1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)			
Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)		
Product (article) characteristics			
Physical form of product: Liquid			
Vapour pressure: < 100000 Pa			
Concentration of substance in product: Covers concentrations up to 35 %			
Amount used, frequency and duration of use/exposure			
Duration: Covers daily exposures up to 8 hours			
Conditions and measures related to personal protection, hygiene and health evaluation			
Personal protection			
For further specification, refer to section 8 of the SDS.			

Other conditions affecting worker exposure	
Covers indoor and outdoor use Professional use Temperature: Assumes use at not more than 20 °C above ambient temperature.	
1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)	
Process Categories	Roller application or brushing (PROC10)
Product (article) characteristics	
Physical form of product: Liquid	
Vapour pressure: < 100000 Pa	
Concentration of substance in product: Covers concentrations up to 35 %	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection For further specification, refer to section 8 of the SDS.	
Other conditions affecting worker exposure	
Covers indoor and outdoor use Professional use Temperature: Assumes use at not more than 20 °C above ambient temperature.	
1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)	
Process Categories	Non industrial spraying (PROC11)
Product (article) characteristics	
Physical form of product: Liquid	
Vapour pressure: < 100000 Pa	
Concentration of substance in product: Covers concentrations up to 35 %	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures	
Technical and organisational measures Carry out in a vented booth or extracted enclosure.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection For further specification, refer to section 8 of the SDS.	
Other conditions affecting worker exposure	
Covers indoor and outdoor use Professional use Temperature: Assumes use at not more than 20 °C above ambient temperature.	
1.2. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)	
Process Categories	Manual activities involving hand contact (PROC19)

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 100000 Pa

Concentration of substance in product:

Covers concentrations up to 35 %

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

For further specification, refer to section 8 of the SDS.

Other conditions affecting worker exposure

Covers indoor and outdoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

Additional information on exposure estimation:

As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative	= 100 ppm	ECETOC TRA worker v2.0	= 0.5
dermal	= 13.71 mg/kg bw/day	ECETOC TRA worker v2.0	= 0

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative	= 100 ppm	ECETOC TRA worker v2.0	= 0.5
dermal	= 27.43 mg/kg bw/day	ECETOC TRA worker v2.0	= 0

1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
---	----------------	--------------------	-----------------------------------

inhalative	= 150 ppm	ECETOC TRA worker v2.0	= 0.7
dermal	= 107.14 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.1

1.3. CS5: Worker Contributing Scenario: Handling and dilution of concentrates (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative	= 150 ppm	ECETOC TRA worker v2.0	= 0.5
dermal	= 141.43 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.2

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

3-aminopropyltriethoxysilane

Exposure Scenario, 14/07/2021

Substance identity	
	3-aminopropyltriethoxysilane
CAS No.	919-30-2
INDEX No.	612-108-00-0
EINECS No.	213-048-4
Registration number	01-2119480479-24

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9a, PC1)

1. ES 1		Widespread use by professional workers; Various products (PC9a, PC1)	
1.1 TITLE SECTION			
Exposure Scenario name	Professional application of coatings and inks by spraying - Use in rigid foams, coatings, adhesives and sealants		
Date - Version	14/07/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1)		
Worker Contributing Scenario			
CS1 Rolling, Brushing		PROC10	
CS2 Roller, spreader, flow application		PROC11	
1.2 Conditions of use affecting exposure			
1.2. CS1: Worker Contributing Scenario: Rolling, Brushing (PROC10)			
Process Categories	Roller application or brushing (PROC10)		
Product (article) characteristics			
Physical form of product: Liquid			
Concentration of substance in product: Covers concentrations up to 2 %			
Amount used, frequency and duration of use/exposure			
Amounts used: Annual site tonnage = 0.2 t(tonnes)/year Daily amount per site = 0.5 kg/day			
Duration: Exposure duration = 4 h			
Frequency: Covers exposure up to = 365 days per year			
Technical and organisational conditions and measures			
Technical and organisational measures Provide a basic standard of general ventilation (1 to 3 air changes per hour). Use in contained systems For further specification, refer to section 8 of the SDS.			
Conditions and measures related to personal protection, hygiene and health evaluation			
Personal protection Wear suitable respiratory protection. For further specification, refer to section 8 of the SDS.			
1.2. CS2: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)			
Process Categories	Non industrial spraying (PROC11)		
Product (article) characteristics			
Physical form of product: Liquid			
Concentration of substance in product: Covers concentrations up to 2 %			

Amount used, frequency and duration of use/exposure

Amounts used:

Annual site tonnage = 0.2 t(tonnes)/year
Daily amount per site = 0.5 kg/day

Duration:

Exposure duration = 4 h

Frequency:

Covers exposure up to = 365 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).
Use in contained systems
For further specification, refer to section 8 of the SDS.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable respiratory protection.
For further specification, refer to section 8 of the SDS.

1.3 Exposure estimation and reference to its source

1.3. CS1: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal	= 0.055 mg/kg bw/day	ECETOC TRA worker v3	N/A
inhalative	= 1.8 mg/m ³	ECETOC TRA worker v3	N/A

1.3. CS2: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal	= 0.21 mg/kg bw/day	ECETOC TRA worker v3	N/A
inhalative	= 46 mg/m ³	ECETOC TRA worker v3	N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.