

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

DELTA PLUS ECO

Date of first edition: 3/11/2021

Safety Data Sheet dated 24/02/2026

version 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: DELTA PLUS ECO

Trade code: 19022021 11

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: detergent

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Ireland Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

Members of the public Number (8 am-10 pm): +353 (0)1 809 2166

Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

Malta In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Corr. 1A Causes severe skin burns and eye damage.

Eye Dam. 1 Causes serious eye damage.

STOT SE 3 May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Danger

Hazard statements

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe dust.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves and eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with applicable regulations.

Contains

hydrogen chloride

Regulation (EC) nr 648/2004 (Detergents).

Product contents:

non-ionic surfactants < 5%

Perfumes

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: DELTA PLUS ECO

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥ 10 -<20 %	hydrogen chloride	CAS:7647-01-0 EC:231-595-7 Index:017-002-00-2	Met. Corr. 1, H290; Eye Dam. 1, H318; Skin Corr. 1B, H314; STOT SE 3, H335	
			Specific Concentration Limits: $10\% \leq C < 25\%$: Eye Irrit. 2 H319 $C \geq 10\%$: STOT SE 3 H335 $C \geq 25\%$: Skin Corr. 1B H314 $10\% \leq C < 25\%$: Skin Irrit. 2 H315	
<0.01 %	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	CAS:111-76-2 EC:203-905-0 Index:603-014-00-0	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Acute Tox. 3, H331	01-2119475108-36
			Acute Toxicity Estimate : ATE - Oral : 1200 mg/kg bw ATE - Inhalation (Vapours) : 3 mg/l	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.
Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Use appropriate respiratory protection.
See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular
Industrial sector specific solutions:
None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
hydrogen chloride CAS: 7647-01-0	ACGIH		Short Term: Ceiling - 2 ppm A4 - URT irr
	NATIONAL	AUSTRIA	Long Term: 8 mg/m ³ - 5 ppm; Short Term: Ceiling - 15 mg/m ³ - 10 ppm 5(Mow), 8x, MAK Source: GKV, BGBl. II Nr. 156/2021
	NATIONAL	BULGARIA	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATIONAL	CZECHIA	Long Term: 8 mg/m ³ ; Short Term: Ceiling - 15 mg/m ³ I Source: Nařízení vlády č. 361-2007 Sb
	NATIONAL	DENMARK	Short Term: Ceiling - 8 mg/m ³ - 5 ppm EL Source: BEK nr 2203 af 29/11/2021
	NATIONAL	ESTONIA	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	FINLAND	Short Term: 7.6 mg/m ³ - 5 ppm Source: HTP-ARVOT 2020
	NATIONAL	FRANCE	Short Term: 7.6 mg/m ³ - 5 ppm Source: INRS outil65, article R. 4412-149 du Code du travail
	NATIONAL	GREECE	Long Term: 7 mg/m ³ - 5 ppm; Short Term: 7 mg/m ³ - 5 ppm Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL	HUNGARY	Long Term: 8 mg/m ³ ; Short Term: 16 mg/m ³ i, m, EU1, N Source: 5/2020. (II. 6.) ITM rendelet
	NATIONAL	LITHUANIA	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
	NATIONAL	NETHERLANDS	Long Term: 8 mg/m ³ ; Short Term: 15 mg/m ³ Source: Arbeidsomstandighedenregeling - Lijst A
	NATIONAL	NORWAY	Short Term: Ceiling - 7 mg/m ³ - 5 ppm T E Source: FOR-2021-06-28-2248
	NATIONAL	POLAND	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ Source: Dz.U. 2018 poz. 1286
	NATIONAL	SLOVAKIA	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Source: 355 NARIADENIE VLÁDY z 10. mája 2006
	NATIONAL	SWEDEN	Long Term: 3 mg/m ³ - 2 ppm; Short Term: 6 mg/m ³ - 4 ppm Source: AFS 2021:3
	SUVA	SWITZERLAND	Long Term: 3 mg/m ³ - 2 ppm; Short Term: 6 mg/m ³ - 4 ppm SSC, VRS / OAW, NIOSH DFG OSHA Source: suva.ch/valeurs-limites
	WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 2 mg/m ³ - 1 ppm; Short Term: 8 mg/m ³ - 5 ppm Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	NATIONAL	BELGIUM	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	CROATIA	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm

		Source: 2000/39/EZ
2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve CAS: 111-76-2	NATIONAL CYPRUS	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Source: Οι περί Ασφάλειας και Υγείας στην Εργασία (Χημικοί Παράγοντες) Κανονισμοί του 2001 έως 2021
	NATIONAL GERMANY	Long Term: 3 mg/m ³ - 2 ppm DFG, EU, Y, 2(I) Source: TRGS 900
	NATIONAL IRELAND	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm IOELV Source: 2021 Code of Practice
	NATIONAL ITALY	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Source: D.lgs. 81/2008, Allegato XXXVIII
	NATIONAL LATVIA	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Source: KN325P1
	NATIONAL LUXEMBOURG	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Source: Mémorial A n.226 du 22 mars 2021
	NATIONAL MALTA	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Source: S.L.424.24
	NATIONAL PORTUGAL	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Source: Decreto-Lei n.º 1/2021
	NATIONAL ROMANIA	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Dir. 2000/39 Source: Republicarea 1 - nr. 743 din 29 iulie 2021
	NATIONAL SLOVENIA	Long Term: 8 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm Y, EU1 Source: UL št. 72, 11. 5. 2021
	NATIONAL SPAIN	Long Term: 7.6 mg/m ³ - 5 ppm; Short Term: 15 mg/m ³ - 10 ppm VLI Source: LEP 2022
	EU	Long Term: 8 mg/m ³ - 5 ppm (8h); Short Term: 15 mg/m ³ - 10 ppm
	ACGIH	Long Term: 20 ppm (8h) A3, BEI - Eye and URT irr
	NATIONAL AUSTRIA	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 200 mg/m ³ - 40 ppm 30(Miw), 4x, MAK, H Source: GKV, BGBl. II Nr. 156/2021
	NATIONAL BULGARIA	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm Кожа Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
	NATIONAL CZECHIA	Long Term: 100 mg/m ³ ; Short Term: Ceiling - 200 mg/m ³ D, I, B Source: Nařízení vlády č. 361-2007 Sb
	NATIONAL DENMARK	Long Term: 98 mg/m ³ - 20 ppm EH Source: BEK nr 2203 af 29/11/2021
	NATIONAL ESTONIA	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm A, S Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL FINLAND	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 250 mg/m ³ - 50 ppm iho Source: HTP-ARVOT 2020
	NATIONAL FRANCE	Long Term: 49 mg/m ³ - 10 ppm; Short Term: 246 mg/m ³ - 50 ppm Risque de pénétration percutanée Source: INRS outil65, article R. 4412-149 du Code du travail
	NATIONAL GREECE	Long Term: 120 mg/m ³ Δ Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL HUNGARY	Long Term: 98 mg/m ³ ; Short Term: 246 mg/m ³

		b, i, EU1, T Source: 5/2020. (II. 6.) ITM rendelet
NATIONAL	LITHUANIA	Long Term: 50 mg/m ³ - 10 ppm; Short Term: 100 mg/m ³ - 20 ppm O Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	NETHERLANDS	Long Term: 100 mg/m ³ ; Short Term: 246 mg/m ³ H Source: Arbeidsomstandighedenregeling - Lijst A
NATIONAL	NORWAY	Long Term: 50 mg/m ³ - 10 ppm H E Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 98 mg/m ³ ; Short Term: 200 mg/m ³ skóra Source: Dz.U. 2018 poz. 1286
NATIONAL	SLOVAKIA	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm K Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATIONAL	SWEDEN	Long Term: 50 mg/m ³ - 10 ppm; Short Term: 246 mg/m ³ - 50 ppm H Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 49 mg/m ³ - 10 ppm; Short Term: 98 mg/m ³ - 20 ppm R/H, SSC, B, VRS Yeux / OAW Auge, INRS HSE NIOSH Source: suva.ch/valeurs-limites
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 123 mg/m ³ - 25 ppm; Short Term: 246 mg/m ³ - 50 ppm Sk, BMGV Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
NATIONAL	BELGIUM	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm D Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATIONAL	CROATIA	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm koža Source: 2000/39/EZ
NATIONAL	CYPRUS	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm δέρμα Source: Οι περί Ασφάλειας και Υγείας στην Εργασία (Χημικοί Παράγοντες) Κανονισμοί του 2001 έως 2021
NATIONAL	GERMANY	Long Term: 49 mg/m ³ - 10 ppm EU, DFG; H, Y, 2(I) Source: TRGS 900
NATIONAL	IRELAND	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm Sk, IOELV Source: 2021 Code of Practice
NATIONAL	ITALY	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm Cute Source: D.lgs. 81/2008, Allegato XXXVIII
NATIONAL	LATVIA	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm Āda Source: KN325P1
NATIONAL	LUXEMBOURG	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm Peau Source: Mémorial A n.226 du 22 mars 2021
NATIONAL	MALTA	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm skin Source: S.L.424.24
NATIONAL	PORTUGAL	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm Cutânea Source: Decreto-Lei n.º 1/2021
NATIONAL	ROMANIA	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm

		P, Dir. 2000/39 Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATIONAL	SLOVENIA	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 246 mg/m ³ - 50 ppm K, Y, BAT, EU1 Source: UL št. 72, 11. 5. 2021
NATIONAL	SPAIN	Long Term: 98 mg/m ³ - 20 ppm; Short Term: 245 mg/m ³ - 50 ppm vía dérmica VLI, VLB® Source: LEP 2022
EU		Long Term: 98 mg/m ³ - 20 ppm (8h); Short Term: 246 mg/m ³ - 50 ppm Skin

Biological limit values

2-butoxyethanol;
ethyleneglycol monobutyl
ether; butyl cellosolve
CAS: 111-76-2

Biological Indicator: 2-Butoxyethylacetat; Sampling Period: End of turn; End of working week
Value: 150 mg/g; Medium: Urine

Predicted No Effect Concentration (PNEC) values

2-butoxyethanol;
ethyleneglycol monobutyl
ether; butyl cellosolve
CAS: 111-76-2

Exposure Route: Fresh Water; PNEC Limit: 8.8 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 26.4 mg/l

Exposure Route: Marine water; PNEC Limit: 880 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 463 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 34.6 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 3.46 mg/kg

Exposure Route: Soil; PNEC Limit: 2.33 mg/kg

Exposure Route: Secondary poisoning; PNEC Limit: 20 mg/kg

Derived No Effect Level (DNEL) values

hydrogen chloride
CAS: 7647-01-0

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 8 mg/m³; Consumer: 8 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Professional: 15 mg/m³; Consumer: 15 mg/m³

2-butoxyethanol;
ethyleneglycol monobutyl
ether; butyl cellosolve
CAS: 111-76-2

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 98 mg/m³; Consumer: 59 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 1091 mg/m³; Consumer: 426 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Professional: 246 mg/m³; Consumer: 147 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 125 mg/kg; Consumer: 75 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Professional: 89 mg/kg; Consumer: 89 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 6.3 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 26.7 mg/kg

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing.

Protection for hands:

Butyl rubber .

Respiratory protection:

Gas filter type B

Thermal Hazards:

Not expected if used as intended

Environmental exposure controls:

Prevent the product from entering sewers or surface and underground water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: Blue

Odour: Acidic

Odour threshold: N.A. (Data not available)

pH: =1.00 (ISO 2811)

Kinematic viscosity: N.A. (Not determined, as it is not required for CLP classification)

Melting point/freezing point: N.A.

Boiling point or initial boiling point and boiling range: > 100 °C (212 °F)

Flash point: > 60°C / 93°C

Lower and upper explosion limit: N.A. (Not applicable as the mixture is not flammable)

Relative vapour density: N.A. (Some data is not known)

Vapour pressure: N.A. (Some data is not known)

Density and/or relative density: 1.00 REL

Solubility in water: Soluble

Solubility in oil: N.A. (Not determined, as it is not required for CLP classification)

Partition coefficient n-octanol/water (log value): N.A. (Not applicable to mixtures)

Auto-ignition temperature: N.A. (Not applicable as the mixture is not flammable)

Decomposition temperature: N.A. (Not applicable, as the mixture is not self-reactive)

Flammability: ; Not applicable as the mixture is not flammable

Volatile Organic compounds - VOCs = 0.00 % ; 0.00 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Corr. 1A(H314)
c) serious eye damage/irritation	The product is classified: Eye Dam. 1(H318)
d) respiratory or skin sensitisation	Not classified Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met

g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	The product is classified: STOT SE 3(H335)
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

hydrogen chloride	a) acute toxicity	LC50 Inhalation of aerosol Rat = 8.3 mg/l 30min	
	b) skin corrosion/irritation	Skin Corrosive Human Positive	human skin model
	c) serious eye damage/irritation	Eye Corrosive Positive	Excised Bovine Cornea
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Negative	
	f) carcinogenicity	Carcinogenicity Inhalation Rat Negative	
2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	a) acute toxicity	ATE - Oral : 1200 mg/kg bw	
		ATE - Inhalation (Vapours) : 3 mg/l	
		LD50 Oral Guinea pig = 1414 mg/kg	
		LC50 Inhalation Vapour Rat = 2.56 mg/l 4h	
		LD50 Skin Guinea pig > 2000 mg/kg	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive 4h	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes 24h	
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Negative	
	f) carcinogenicity	Genotoxicity Negative	Mouse intraperitoneal route
		Carcinogenicity Inhalation Rat = 125 mg/m ³	NOAEC
	g) reproductive toxicity	No Observed Adverse Effect Level Oral = 720 mg/kg	Mouse

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
hydrogen chloride	CAS: 7647-01-0 - EINECS: 231-595-7 - INDEX: 017-002-00-2	a) Aquatic acute toxicity : LC50 Fish = 20.5 mg/L
		a) Aquatic acute toxicity : LC50 Daphnia = 0.45 mg/L
		a) Aquatic acute toxicity : EC50 Algae = 0.73 mg/L
		c) Bacteria toxicity : EC50 = 0.23 mg/L
2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	CAS: 111-76-2 - EINECS: 203-905-0 - INDEX: 603-014-00-0	a) Aquatic acute toxicity : LC50 Fish <i>Oncorhynchus mykiss</i> = 1474 mg/L 96h

b) Aquatic chronic toxicity : NOEC Fish Brachydanio rerio = 100 mg/L
OECD204 - 21days

a) Aquatic acute toxicity : EC50 freshwater invertebrates = 690 mg/L

b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 100 mg/L

a) Aquatic acute toxicity : EC50 Algae pseudokirchneriella subcapitata = 623 mg/L 72h

c) Bacteria toxicity : NOEC Uronema parduczi = 463 mg/L 48h

12.2. Persistence and degradability

Component	Persistence/Degradability:	Test	Value	Notes:
2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	Readily biodegradable	Biochemical oxygen demand	98.000	28days

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration $\geq 0.1\%$

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as hazardous waste

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

N.A.

SECTION 14: Transport information

14.1. UN number or ID number

1789

14.2. UN proper shipping name

ADR-Shipping Name: HYDROCHLORIC ACID

IATA-Shipping Name: HYDROCHLORIC ACID

IMDG-Shipping Name: HYDROCHLORIC ACID

14.3. Transport hazard class(es)

ADR-Class: 8

IATA-Class: 8

IMDG-Class: 8

14.4. Packing group

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: F-A, S-B

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 8

ADR - Hazard identification number: 80
ADR-Special Provisions: 520
ADR-Transport category (Tunnel restriction code): 2 (E)
ADR Limited Quantities: 1 L
ADR Excepted Quantities: E2

Air (IATA):

IATA-Passenger Aircraft: 851
IATA-Cargo Aircraft: 855
IATA-Label: 8
IATA-Subsidiary hazards: -
IATA-Erg: 8L
IATA-Special Provisions: A3 A803

Sea (IMDG):

IMDG-Stowage and handling: Category C
IMDG-Segregation: SGG1 SG36 SG49
IMDG-Subsidiary hazards: -
IMDG-Special Provisions: -

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2023/707

Regulation (EU) n. 2023/1434 (ATP 19 CLP)

Regulation (EU) n. 2023/1435 (ATP 20 CLP)

Regulation (EU) n. 2024/197 (ATP 21 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

None

Explosives precursors – Regulation 2019/1148

No substances listed

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

3: Severe hazard to waters

German Lagerklasse according to TRGS 510:

LGK 8A

SVHC Substances:No SVHC substances present in concentration $\geq 0.1\%$ **15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

hydrogen chloride

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve

SECTION 16: Other information**Code Description**

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.

Code	Hazard class and hazard category	Description
2.16/1	Met. Corr. 1	Substance or mixture corrosive to metals, Category 1
3.1/3/Inhal	Acute Tox. 3	Acute toxicity (inhalation), Category 3
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1A	Skin Corr. 1A	Skin corrosion, Category 1A
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Skin Corr. 1A, H314	On basis of test data (pH)
Eye Dam. 1, H318	On basis of test data (pH)
STOT SE 3, H335	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).
 CAV: Poison Center
 CE: European Community
 CLP: Classification, Labeling, Packaging.
 CMR: Carcinogenic, Mutagenic and Reprotoxic
 COD: Chemical Oxygen Demand
 COV: Volatile Organic Compound
 CSA: Chemical Safety Assessment
 CSR: Chemical Safety Report
 DMEL: Derived Minimal Effect Level
 DNEL: Derived No Effect Level.
 DPD: Dangerous Preparations Directive
 DSD: Dangerous Substances Directive
 EC50: Half Maximal Effective Concentration
 ECHA: European Chemicals Agency
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 ES: Exposure Scenario
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 IC50: half maximal inhibitory concentration
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 IMDG: International Maritime Code for Dangerous Goods.
 INCI: International Nomenclature of Cosmetic Ingredients.
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care
 KAFH: Keep Away From Heat
 KSt: Explosion coefficient.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 LDLo: Leathal Dose Low
 N.A.: Not Applicable
 N/A: Not Applicable
 N/D: Not defined/ Not available
 NA: Not available
 NIOSH: National Institute for Occupational Safety and Health
 NOAEL: No Observed Adverse Effect Level
 OSHA: Occupational Safety and Health Administration
 PBT: Persistent, Bioaccumulative and Toxic
 PGK: Packaging Instruction
 PNEC: Predicted No Effect Concentration.
 PSG: Passengers
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 vPvB: Very Persistent, Very Bioaccumulative.
 WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 13: Disposal considerations
- SECTION 14: Transport information

- SECTION 15: Regulatory information
- SECTION 16: Other information



Exposure Scenario

2-butoxyethanol

Exposure Scenario, 17/03/2023

Substance identity	
	2-butoxyethanol
CAS No.	111-76-2
INDEX No.	603-014-00-0
EINECS No.	203-905-0
Registration number	01-2119475108-36

Table of contents

1. ES 1

1. ES 1

1.1 TITLE SECTION

Exposure Scenario name	Professional application of coatings and inks
Date - Version	17/03/2023 - 1.0
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Coatings and paints, thinners, paint removers (PC9a)

Environment Contributing Scenario

CS1	ERC8a - ERC8d
-----	---------------

Worker Contributing Scenario

CS2 Material transfers	PROC8a
CS3 Rolling, Brushing	PROC10
CS4 Rolling, Brushing	PROC10
CS5 Roller, spreader, flow application	PROC11
CS6 Roller, spreader, flow application	PROC11

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 Pa (Standard Temperature and Pressure)

Vapour pressure:

= 117 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use (or from service life)

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

	Air - minimum efficiency of: 98 % Soil - minimum efficiency of: 1 % Water - minimum efficiency of: 1 %
--	--

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant

STP effluent (m³/day): 2000

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 18000 m³/day

Covers indoor and outdoor use

1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 Pa (Standard Temperature and Pressure)

Vapour pressure:

= 117 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to = 480 min

Frequency:

Covers use up to 5 days per week

Technical and organisational conditions and measures

Technical and organisational measures

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).	Inhalation - minimum efficiency of: = 70 %
---	--

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: = 80 %
Wear suitable face shield.	

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories	Roller application or brushing (PROC10)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 Pa (Standard Temperature and Pressure)

Vapour pressure:

= 117 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to = 480 min

Frequency:

Covers use up to 5 days per week

Technical and organisational conditions and measures

Technical and organisational measures

Provide a good standard of controlled ventilation (5 to 10 air changes per hour).

Inhalation - minimum efficiency of: = 70 %

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of: = 80 %

Wear suitable face shield.

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories

Roller application or brushing (PROC10)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 Pa (Standard Temperature and Pressure)

Vapour pressure:

= 117 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers use up to = 480 min

Frequency:

Covers use up to 5 days per week

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of: = 80 %

Wear suitable face shield.

Other conditions affecting worker exposure

Outdoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS5: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories

Non industrial spraying (PROC11)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 Pa (Standard Temperature and Pressure)

Vapour pressure:

= 117 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Amounts used:**

Amount per use < 3 L/min

Duration:

Covers use up to = 240 min

Frequency:

Covers use up to 5 days per week

Technical and organisational conditions and measures**Technical and organisational measures**

Ensure operatives are trained to minimise exposures.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: = 80 %
Wear suitable respiratory protection.	Inhalation - minimum efficiency of: = 95 %
Wear suitable face shield.	

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.**1.2. CS6: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)**

Process Categories	Non industrial spraying (PROC11)
---------------------------	----------------------------------

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure > 10 Pa (Standard Temperature and Pressure)

Vapour pressure:

= 117 Pa

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure**Amounts used:**

Amount per use < 3 L/min

Duration:

Covers use up to = 480 min

Frequency:

Covers use up to 5 days per week

Technical and organisational conditions and measures**Technical and organisational measures**

Ensure operatives are trained to minimise exposures.

Ensure that a spraying booth is used.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable respiratory protection.

Wear suitable face shield.

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8a, ERC8d)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
soil	N/A	ECETOC TRA environment v3	= 0.018688

Additional information on exposure estimation:

Risk from environmental exposure is driven by soil.

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 2.7429 mg/kg bw/day	ECETOC TRA worker v3	= 0.021943
inhalative, systemic, long-term	= 36.9294 mg/m ³	ECETOC TRA worker v3	= 0.376831

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 5.4857 mg/kg bw/day	ECETOC TRA worker v3	= 0.043886
inhalative, systemic, long-term	= 36.9294 mg/m ³	ECETOC TRA worker v3	= 0.376831

1.3. CS4: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 3.2914 mg/kg bw/day	ECETOC TRA worker v3	= 0.026331
inhalative, systemic, long-term	= 57.7012 mg/m ³	ECETOC TRA worker v3	= 0.527563

1.3. CS5: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 21.4286 mg/kg bw/day	ECETOC TRA worker v3	= 0.171429

inhalative, systemic, long-term	= 55 mg/m ³	ECETOC TRA worker v3	= 0.561224
---------------------------------	------------------------	-------------------------	------------

1.3. CS6: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 12.8571 mg/kg bw/day	ECETOC TRA worker v3	= 0.102857
inhalative, systemic, long-term	= 62 mg/m ³	ECETOC TRA worker v3	= 0.632653

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



Exposure Scenario

Hydrogen chloride

Exposure Scenario, 16/02/2022

Substance identity	
	Hydrogen chloride
CAS No.	7647-01-0
INDEX No.	017-002-00-2
EINECS No.	231-595-7

Table of contents

1. **ES 1** Widespread use by professional workers

1. ES 1		Widespread use by professional workers	
1.1 TITLE SECTION			
Exposure Scenario name	Professional use of facade/surface cleaning products		
Date - Version	16/02/2022 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Environment Contributing Scenario			
CS1	ERC8a - ERC8b - ERC8e		
Worker Contributing Scenario			
CS2 Equipment cleaning and maintenance	PROC8a		
CS3 Rolling, Brushing	PROC10		
CS4 Mixing operations	PROC19		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8a, ERC8b, ERC8e)			
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8b, ERC8e)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid, vapour pressure 0,5 - 10 kPa at STP			
Concentration of substance in product: Covers concentrations up to 40 %			
1.2. CS2: Worker Contributing Scenario: Equipment cleaning and maintenance (PROC8a)			
Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid, vapour pressure 0,5 - 10 kPa at STP			
Concentration of substance in product: Covers concentrations up to 40 %			
<i>Amount used, frequency and duration of use/exposure</i>			
Duration: Covers use up to > 4 h			
<i>Technical and organisational conditions and measures</i>			
Technical and organisational measures			
Handle substance within a predominantly closed system provided with extract ventilation. Ensure operatives are trained to minimise exposures.			Dermal - minimum efficiency of: 90 %
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>			
Personal protection			
Wear suitable gloves tested to EN374.			

Other conditions affecting worker exposure	
Professional use Temperature: Assumes use at not more than 20 °C above ambient temperature.	
1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)	
Process Categories	Roller application or brushing (PROC10)
Product (article) characteristics	
Physical form of product: Liquid, vapour pressure 0,5 - 10 kPa at STP	
Concentration of substance in product: Covers concentrations up to 40 %	
Amount used, frequency and duration of use/exposure	
Duration: Covers use up to > 4 h	
Technical and organisational conditions and measures	
Technical and organisational measures	
Ensure operatives are trained to minimise exposures. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	Inhalation - minimum efficiency of: 90 %
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection Wear suitable gloves tested to EN374.	
Other conditions affecting worker exposure	
Professional use Temperature: Assumes use at not more than 20 °C above ambient temperature.	
1.2. CS4: Worker Contributing Scenario: Mixing operations (PROC19)	
Process Categories	Manual activities involving hand contact (PROC19)
Product (article) characteristics	
Physical form of product: Liquid, vapour pressure 0,5 - 10 kPa at STP	
Concentration of substance in product: Covers concentrations up to 40 %	
Amount used, frequency and duration of use/exposure	
Duration: Covers use up to > 4 h	
Technical and organisational conditions and measures	
Technical and organisational measures	
Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection Wear suitable gloves tested to EN374. Wear a full face respirator conforming to EN136.	
Other conditions affecting worker exposure	
Professional use Temperature: Assumes use at not more than 20 °C above ambient temperature.	
1.3 Exposure estimation and reference to its source	
N/A	

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.