

Decor

Water-based decorative resin-paint with washable and wipeable matt-finish and high chromatic intensity.

Ideal for decorating walls requiring more cleaning (kitchen, bathroom, kid bedrooms) and high traffic areas (hallways, staircases). Decor's fine finish is perfect for all environments in which you want to create an exclusive and refined atmosphere. Furthermore, thanks to its high resin and pigment content, it is ideal for stronger colours. Available in the 150 Color Collection colours and in the 1.500 Kerakoll Colors colours.



1. Washable
2. Minimal dirt collection
3. Resistant to detergents and disinfectants
4. Excellent resistance to wear
5. Anti-drip
6. Resistant to mould According to UNI EN 15457
7. Suitable for overlaying after 30 minutes
8. Free from heavy metals according to EN 71-3 standard, ideal for children's bedrooms
9. Compliant to HACCP protocol for the decoration of environments for food use

kerakoll

Areas of application

- Decorative and protective paint for internal walls for application on:
- cement-, gypsum- or lime-based traditional and ready-mixed finishing products
 - plasterboard
 - prefabricated cement elements
 - old paint layers and coatings in good condition and well anchored to the substrate
 - timber
 - Wallcrete for the creation of the Wallcrete and Wallcrete Living surfaces

- Wallpaper Living for the creation of the Wallpaper Living surface
- Stripe for the creation of the Stripe Living surface
- repainting ceramic tile joints on floors and coverings

Do not use in the presence of rising damp; on substrates which are dirty, non-cohesive, powdery.

Instructions for use

→ Preparation of substrates

Carefully clean the substrates using suitable equipment to remove all traces of dirt, dust or efflorescences.

Completely remove any loose debris or parts that do not fully adhere to the substrate from deteriorated paint coatings and coverings.

New render patch layers must be left to cure until the bonding agent has set and primed with Universal Wall Primer; wait for 6 hours before the subsequent paint cycle. On plasters or inconsistent and loose finishing coats, apply Universal Wall Primer. On smooth and compact finishing coats, apply Exence Primer or Universal Wall Primer depending on the consistency of the substrate. Exence Primer is a fixative primer, Universal Wall Primer is a fixative and consolidating primer.

mould or biodeteriorating agents, repair first with Skil Remove.

→ Preparation

Mix the product before application.

→ Application

Using a brush, roller or spray, carefully apply across the entire surface two coats of Decor either pure or diluted using water by up to 15% of the total volume depending on requirements and the tools used. Apply on well-dried substrates or with moisture content not exceeding 6%.

For optimal application of the resin-paint, use a suitable roller according to the type of substrate to be covered:

- on plasterboard and smooth finishings, it is recommended to use a short-bristle roller (5-8 mm);

- on finishings with a grain size between 0.3 mm and 1 mm, it is recommended to use a medium-bristle roller (8-12 mm);
- on finishings with a grain size of more than 1 mm it is recommended to use a long-bristle roller (> 12 mm).

Conditions required for decorating are ambient and substrate temperatures between +5 °C and +30 °C and relative ambient moisture lower than 80%.

Leave at least 30 minutes between the first and second coats at +23 °C and R.H. of ≤ 80%.

If different batches of product are used, it is suggested to mix different buckets together in order to avoid slight differences in tone.

Before applying Decor to repaint joints, thoroughly clean the existing grout; apply the resin-paint with a roller or brush to the joints and onto the adjacent ceramic surface. Wait until the product on the ceramic surface is dry. Dampen the excess product and remove it by gently rubbing with a soft (white) Scotch-Brite pad. Finally, rinse and let dry. Before repainting joints, check the cleanability of the covering, as porous or highly micro-porous surfaces may make cleaning difficult. It is recommended to perform a preliminary test in a small, concealed area.

→ Cleaning

Product residues can be removed with running water before the product has hardened.

Special notes

- Evaluate seasonal application conditions: different temperature and humidity conditions result in significant differences in paint drying and/or reaction times.
- The product has very good resistance to rubbing; however, in more intense colours a blackboard effect may occur.
- The photographic images in the catalogue and on the website, as well as the colours shown in the samples are to be considered purely indicative. We therefore recommend testing the product onsite to check the exact colour and coverage that will be obtained.
- Use material from a single production batch for each project.
- Materials from different batches may have slight colour and sheen variations.
- On some bright colours, prior application of one or two smooth finish coats of Exence Base Flat in the same matching colour improves coverage and evenness. An additional finishing coat may also be required.
- On intense shades, it is recommended to apply the product without interruption, wet on wet, in order to avoid signs of recoating.
- In the presence of gypsum surfaces or grouting, always apply Universal Wall Primer first.
- Touch-ups may vary depending on various factors and may be visible even after the product has dried.

Certificates and marks



* Émission dans l'air intérieur Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

Abstract

Protection and decoration of internal surfaces will be carried out by applying by brush, roller or spray two coats of an easy-to-sanitize, decorative resin-paint, resistant to mould according to standard EN 15457, free from heavy metals according to standard EN 71-3, such as Decor by Kerakoll Spa, with a coverage of approx. 0.15 – 0.2 l/m².

Permeability to water vapour class V2 (average) according to standard EN ISO 7783, with permeability to liquid water class W3 (low) according to standard ISO 1062-3, resistance to wet scrubbing (standard ISO 11998) > class 1 according to standard EN 13300.

Technical Data compliant with Kerakoll Quality Standard	
Appearance	white or coloured paint
Volumetric mass	≈ 1.3 kg/l
Chemical nature	blend of acrylic resins
Pack	100 ml* tins / 0.75 – 1.5 – 4 – 10 l buckets
Shelf life:	≈ 12 months from production in the original sealed packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +5 °C to +30 °C
Humidity of the substrate	≤ 6%
Reaction to fire	B-s1-d0
Waiting time between 1 st and 2 nd coat	≥ 30 minutes
Dilution with water	max 15% by volume
Coverage when applying two coats for a fine-texture, two-coat finish	≈ 0.15 – 0.20 l/m ²

Average values taken on Kerakoll Color Collection colours at a temperature of +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate.
 * Only in the Color Collection colours.

Performance

HIGH-TECH

Resistance to wet scrubbing (ISO 11998)	Class 1	EN 13300
Permeability to water vapour (ISO 7783)	Sd 0.40 m; class V2 (average)	ISO1062-1
Permeability to liquid water (ISO 1062-3)	class W3 (low)	ISO1062-1
Coverage (referred to white colour) (ISO 6504-3)	class 1, 99.5% coverage with 4.5 m ² /l consumption	EN 13300
Gloss (matt) (ISO 2813)	< 9 gloss at 85°	EN 13300
Mould and fungi resistance	no proliferation	EN 15457

Average values taken on Kerakoll Color Collection colours at a temperature of +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.

Warning

- Abide by any standards and national regulations
- keep the tin tightly closed before and after use, and out of reach from frost, direct sunlight, heat: the low concentration of preservative additives could compromise the storage of paint over time
- once opened, the product must be stored undiluted.
- clean the tools after use, pressing them several times on the inner edge of the tin in order to recover most of the product.
- do not use running water for washing; tools must be dipped in a minimum quantity of water
- do not apply at temperatures below +5 °C and above +30 °C
- any dry drops can be easily removed from the surfaces with a damp sponge.
- empty containers or containers presenting slight traces of dried residual product must be disposed of according to local regulations
- if necessary, ask for the safety data sheet
- for unstable wooden types, particular substrates and for any other issues, contact the Technical Customer Service Kerakoll:
+ 39 0536.811.516
www.kerakoll.com/contatti



This information was last updated in April 2026; please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions of your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.