

Aquastop Flangia

Elastic, waterproof NBR flange.

Ideal for sealing pipes and drains to be used in Kerakoll's Laminati No Crack systems prior to laying of ceramic tiles, porcelain tiles and natural stones. Applied by cold bonding.



1. High elasticity
2. For internal and external use
3. Ideal for bonding with Nanoflex No Limits gel-membrane, Nanodefense Eco and all Aquastop waterproofing products in Kerakoll's Laminati systems
4. Central core in breathable NBR and resistant to basic environments

Areas of application

- Intended use:
Waterproof sealing of water/electrical systems, through elements and drains on external surfaces (balconies, terraces, flat roofs) and in damp environments (kitchens, shower cubicles, bathrooms, saunas).
- Do not use for exposed applications.

Instructions for use

- Preparation of substrates
See the technical data sheets of the waterproofing products used for bonding.
- Preparation
The seal is ready for use. Directly bond overlapping sections on-site using Nanoflex No Limits, Nanodefense Eco or Kerakoll waterproofing products from the Aquastop range. For Aquastop Flangia 350x350 make an opening according to the diameter of the drainage outlet to be waterproofed prior to laying.
- Application
Aquastop Flangia is applied on the floor (350x350) to create a waterproof joint with floor drains and on the wall (120x120) to create a waterproof joint for passage of water/electrical pipes. To bond Aquastop Flangia apply the waterproofing product on the previously prepared substrate using a spreader, insert Aquastop Flangia into the drain or pipe to be waterproofed with the mesh side facing down, then press firmly onto the waterproofing layer while still wet. When laying the second coat of the waterproofing product, completely cover Aquastop Flangia so that it is entirely embedded in the waterproofing layer.

Technical Data compliant with Kerakoll Quality Standard	
Appearance	green tape
Shelf life	unlimited
Nature of material	thermoplastic NBR
Working temperature	from -40 °C to +100 °C
Aquastop Flangia 120x120:	
- Pack	20 pcs boxes
- Dimensions	≈ 120x120 mm
- Thickness	≈ 0.6 mm
Aquastop Flangia 350x350:	
- Pack	10 pcs boxes
- Dimensions	≈ 350x350 mm
- Thickness	≈ 0.8 mm

Warning

- Product for professional use
 - abide by any standards and national regulations
 - protect the flange once laid from being damaged at the building site
 - the product is an item according to the definitions of the EC Regulation No. 1907/2006 and therefore does not require a Safety Data Sheet
- for any other issues, contact Kerakoll Technical Customer Service:
+ 39 0536.811.516
www.kerakoll.com/contatti



This information was last updated in January 2025; please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions of your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.